

Question: Change directories, check the current directory, return to the previous directory, and test an invalid path

```
teja@LAPTOP-FGDPB110: ~/sl X + v
teja@LAPTOP-FGDPB110:~$ mkdir -p ~/shell_practice/folder1
cd ~/shell_practice
pwd
cd folder1
pwd
cd ..
pwd
cd -
pwd
type cd
type pwd
echo "Hello from the shell"
/home/teja/shell_practice
/home/teja/shell_practice/folder1
/home/teja/shell_practice
/home/teja/shell_practice/folder1
/home/teja/shell_practice/folder1
cd is a shell builtin
pwd is a shell builtin
Hello from the shell
teja@LAPTOP-FGDPB110:~/shell_practice/folder1$ type cd
type pwd
```

The `cd` command changes the current working directory. The `pwd` command shows the path of the current directory. We use `cd ..` to move to the parent directory and `cd -` to return to the previous directory.

Before changing directories, the shell checks whether the given path exists. If it does not exist, the shell displays “No such file or directory” and stays in the current directory.

Session 9 — Question 2

Question: Identify shell built-in commands, run them in the current shell, and check how the shell handles an invalid command.

```
pwd is a shell builtin
Hello from the shell
teja@LAPTOP-FGDPB110:~/shell_practice/folder1$ type cd
type pwd
type echo
pwd
echo "Hello from the shell"
cd ..
pwd
invalidcommand
cd is a shell builtin
pwd is a shell builtin
echo is a shell builtin
/home/teja/shell_practice/folder1
Hello from the shell
/home/teja/shell_practice
invalidcommand: command not found
teja@LAPTOP-FGDPB110:~/shell_practice$ |
```

A shell built-in is a command that runs inside the shell itself. For example, `cd` is a built-in because it changes the current shell's working directory. The shell identifies the command and runs the correct built-in function. If the command name is invalid, it displays **"command not found"** and waits for the next command.