

Docker Cheat Sheet

Table of Contents

1. Installation
2. Basic Commands
3. Container Lifecycle
4. Image Management
5. Networking
6. Volumes
7. Docker Compose
8. Docker Scout
9. Security
10. Dockerfile Instruction

1. Installation

Install Docker:

Update package list and install prerequisites:

```
sudo apt-get update

sudo apt-get install \

ca-certificates \

curl \

gnupg \

Lsb-release
```

Add Docker's official GPG key:

```
sudo apt-get update
```

```
sudo apt-get install ca-certificates curl
sudo install -m 0755 -d /etc/apt/keyrings
sudo curl -fsSL
https://download.docker.com/linux/ubuntu/gpg -o
/etc/apt/keyrings/docker.asc
sudo chmod a+r /etc/apt/keyrings/docker.asc
```

Set up the stable repository:

```
echo \ "deb [arch=$(dpkg --print-architecture)
signed-by=/etc/apt/keyrings/docker.asc]
https://download.docker.com/linux/ubuntu \ $(.
/etc/os-release && echo "$VERSION_CODENAME") stable" | \
sudo tee /etc/apt/sources.list.d/docker.list > /dev/null
sudo apt-get update
```

Install Docker Engine:

```
sudo apt-get install docker-ce docker-ce-cli
containerd.io docker-buildx-plugin docker-compose-plugin
```

Verify Docker Installation:

```
docker --version
```

Install Docker Compose:

Download the current stable release of Docker Compose:

```
sudo curl -L
"https://github.com/docker/compose/releases/download/
$(curl -s
https://api.github.com/repos/docker/compose/releases/
latest | grep -Po '(?<="tag_name":
```

```
" ) [ ^ " ] * ' ) / docker-compose - $(uname -s) - $(uname -m) " -o /usr/local/bin/docker-compose
```

Apply executable permissions to the binary:

```
sudo chmod +x /usr/local/bin/docker-compose
```

Verify Docker Compose Installation:

```
docker-compose --version
```

2. Basic Commands

Version Info:

```
docker --version
```

```
docker info
```

3. Container Lifecycle

Run a Container:

```
docker run -d -p <host_port>:<container_port> --name <container_name> <image>
```

List Containers:

```
docker ps
```

```
docker ps -a
```

Stop, Start, Restart, Remove a Container:

```
docker stop <container_id>
```

```
docker start <container_id>
```

```
docker restart <container_id>
```

```
docker rm <container_id>
```

View Logs:

```
docker logs <container_id>
```

Execute Command in Running Container:

```
docker exec -it <container_id> <command>
```

```
docker exec -it <container_id> bash
```

4. Image Management

Build an Image:

```
docker build -t <image_name>:<tag> .
```

List Images:

```
docker images
```

Remove an Image:

```
docker rmi <image_id>
```

Pull an Image:

```
docker pull <image>
```

Push an Image:

```
docker push <image>
```

Tag an Image:

```
docker tag <existing_image>:<tag> <new_image>:<tag>
```

5. Networking

List Networks:

```
docker network ls
```

Create a Network:

```
docker network create <network_name>
```

Connect a Container to a Network:

```
docker network connect <network_name> <container_id>
```

Disconnect a Container from a Network:

```
docker network disconnect <network_name>  
<container_id>
```

6. Volumes

List Volumes:

```
docker volume ls
```

Create a Volume:

```
docker volume create <volume_name>
```

Attach a Volume to a Container:

```
docker run -v <volume_name>:/path/in/container  
<image>
```

Remove a Volume:

```
docker volume rm <volume_name>
```

7. Docker Compose

Start Services:

```
docker-compose up
```

Start Services in Detached Mode:

```
docker-compose up -d
```

Stop Services:

```
docker-compose down
```

View Logs:

```
docker-compose logs
```

Execute Command in a Service:

```
docker-compose exec <service_name> <command>
```

8. Docker Scout

Install Docker Scout:

```
curl -fsSL
```

```
https://raw.githubusercontent.com/docker/scout-cli/main/install.sh -o install-scout.sh
```

```
sh install-scout.sh
```

Check Version:

```
docker scout version
```

Analyze Image for CVEs:

```
docker scout cves <image>
```

9. Security

Scan an Image for Vulnerabilities:

```
docker scan <image>
```

Login to Docker Hub:

```
docker login
```

Logout from Docker Hub:

```
docker logout
```

10. Dockerfile Instructions

Basic Dockerfile Example:

```
# Use an official OpenJDK runtime as a parent image
```

```
FROM openjdk:8-jre-alpine
```

```
# Set the working directory

WORKDIR /app

# Copy the local file into the container

COPY . .

# Make port 8080 available to the world outside this
container

EXPOSE 8080

# Run the application

ENTRYPOINT ["java", "-jar", "app.jar"]
```

Common Instructions:

- **FROM:** Specifies the base image.
 - **WORKDIR:** Sets the working directory.
 - **COPY:** Copies files from the host to the container.
 - **RUN:** Executes commands in the container.
 - **CMD:** Specifies the command to run within the container.
 - **ENTRYPOINT:** Configures a container that will run as an executable.
-