

CHANDIGARH UNIVERSITY APEX INSTITUTE OF TECHNOLOGY



EXPERIMENT 11

**Subject: Advanced Database Management
System**


Submitted By:
Name: Akshra Ahuja
UID: 24BAI70523
Class: 24AIT_KRG_1B

Submitted To:
Mr. Alok Sir

Question 1:


**DEPARTMENT OF CAREER
PLANNING & DEVELOPMENT**
Discover. Learn. Empower.

**NAAC
GRADE A+**
ACCREDITED UNIVERSITY

**CS WORLD
UNIVERSITY**
AMONG ALL PRIVATE
UNIVERSITIES OF INDIA

**nirf**
RANKED #20
AMONGST TOP
UNIVERSITIES
IN INDIA

Solution:



The screenshot shows a PostgreSQL IDE interface with a query editor and a results pane. The query editor contains the following SQL code:

```
331 (3, 101, 'Alok', '2026-03-01', 55000),
332
333 (4, 102, 'Priya', '2026-01-01', 60000),
334 (5, 102, 'Priya', '2026-02-01', 58000),
335 (6, 102, 'Priya', '2026-03-01', 62000),
336
337 (7, 103, 'Raj', '2026-01-01', 45000),
338 (8, 103, 'Raj', '2026-02-01', 47000),
339 (9, 103, 'Raj', '2026-03-01', 49000),
340
341 (10, 104, 'Sneha', '2026-01-01', 70000),
342 (11, 104, 'Sneha', '2026-02-01', 70000),
343 (12, 104, 'Sneha', '2026-03-01', 72000);
344
345 SELECT distinct employee_id, employee_name
346 FROM (
347     SELECT
348         e1.*,
349         LAG(salary) OVER (
350             PARTITION BY employee_id
351             ORDER BY salary_month
352         ) AS previous_salary
353     FROM EmployeeSalaryHistory e1
354 ) AS E
355 group by employee_id, employee_name
356 having count(*) filter(where salary <= previous_salary)=0;
```

The results pane shows the output of the query, displaying two rows of data:

employee_id	employee_name
101	Alok
103	Raj

The status bar at the bottom indicates "Total rows: 2" and "Query complete 00:00:00.060".

Question 2:

Problem Statement

[Hard]

- A company maintains employee details in an Employee table and department information in a Department table.
- Write an SQL query to find the employees whose salaries belong to the **top three distinct salary levels within their respective departments**.
- If multiple employees have the same salary, they should receive the same salary rank and all of them should be included in the result.
- The output should display:
 - Department Name
 - Employee Name
 - Salary

Solution:

```
397
398 --Solution:
399 SELECT D.name AS Department,
400        E.name AS Employee,
401        E.salary
402 FROM (
403     SELECT *,
404            DENSE_RANK() OVER (
405                PARTITION BY departmentId
406                ORDER BY salary DESC
407            ) AS rnk
408     FROM Employee
409 ) E
410 JOIN Department D
411 ON E.departmentId = D.id
412 WHERE rnk <= 3;
413
414
```

Data Output Messages Notifications

Showing rows: 1 to 10 Page No: 1 of 1

	department character varying (50)	employee character varying (50)	salary integer
1	IT	Max	90000
2	IT	Jim	85000
3	IT	John	85000
4	IT	Alex	75000
5	Sales	Henry	80000
6	Sales	Susan	75000
7	Sales	David	70000
8	HR	Tina	60000
9	HR	Rita	55000