

**CYK Algorithm**

*and*

**Probabilistic**

**Context Free Grammar**

**Aashraya Sachdeva**

Automata Theory and Computability


Dept. of Computer Science and Automation

18<sup>th</sup> Nov, 2016

$$\begin{aligned} S &\rightarrow XY \\ X &\rightarrow XA|a|b \\ Y &\rightarrow AY|a \\ A &\rightarrow a \end{aligned}$$

How can you tell if ***baaaaa***  $\in L(G)$ ?

$S \rightarrow XY$   
 $X \rightarrow XA|a|b$   
 $Y \rightarrow AY|a$   
 $A \rightarrow a$



Can you make parse tree for

***bbbbaaabaabaabbbbaaabaabaabaabbaaaaa ?***

**C:** Cocke, J  
**Y:** Younger, D  
**K:** Kasami, T.

# Algorithm

1. Works with Chomsky Normal Form.
2. Bottom-up parsing.
3. Dynamic Programming.
4. Polynomial time in length of input sentence.

$n \times n$  matrix

Different length  
Substrings

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	ba	aa	aa	aa	
1	b	a	a	a	a

Input Sentence

b	a	a	a	a
---	---	---	---	---

$S \rightarrow XY$   
 $X \rightarrow XA|a|b$   
 $Y \rightarrow AY|a$   
 $A \rightarrow a$

Substrings of length 1

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	ba	aa	aa	aa	
1	X	X,Y,A	X,Y,A	X,Y,A	X,Y,A

Input Sentence

b	a	a	a	a
---	---	---	---	---


$$S \rightarrow XY$$

$$X \rightarrow XA|a|b$$

$$Y \rightarrow AY|a$$

$$A \rightarrow a$$

Substrings of length 2



Input Sentence

b	a	a	a	a
---	---	---	---	---



$S \rightarrow XY$   
 $X \rightarrow XA|a|b$   
 $Y \rightarrow AY|a$   
 $A \rightarrow a$

$$X.(X,Y,A) = \{XX \cup XY \cup XA\}$$

Substrings of length 2

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	S,X	aa	aa	aa	
1	X	X,Y,A	X,Y,A	X,Y,A	X,Y,A

Input Sentence

b	a	a	a	a
---	---	---	---	---

$$(X, Y, A). (X, Y, A) = \{XX \cup XY \cup XA \cup YX \cup YY \cup YA \cup AX \cup AY \cup AA\}$$

$S \rightarrow XY$   
 $X \rightarrow XA|a|b$   
 $Y \rightarrow AY|a$   
 $A \rightarrow a$

Substrings of length 2

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	S,X	S,X,Y	aa	aa	
1	X	X,Y,A	X,Y,A	X,Y,A	X,Y,A

Input Sentence

b	a	a	a	a
---	---	---	---	---

$$S \rightarrow XY$$

$$X \rightarrow XA|a|b$$

$$Y \rightarrow AY|a$$

$$A \rightarrow a$$

Substrings of length 2

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	<b>S,X</b>	<b>S,X,Y</b>	<b>S,X,Y</b>	<b>S,X,Y</b>	
1	<b>X</b>	<b>X,Y,A</b>	<b>X,Y,A</b>	<b>X,Y,A</b>	<b>X,Y,A</b>

Input Sentence

b	a	a	a	a
---	---	---	---	---


$$S \rightarrow XY$$

$$X \rightarrow XA|a|b$$

$$Y \rightarrow AY|a$$

$$A \rightarrow a$$

Substrings of length 3



$$S \rightarrow XY$$


$$X \rightarrow XA|a|b$$

$$Y \rightarrow AY|a$$

$$A \rightarrow a$$

Substrings of length 3

5	baaaa				
4	baaa	aaaa			
3	S	aaa	aaa		
2	S,X	S,X,Y	S,X,Y	S,X,Y	
1	X	X,Y,A	X,Y,A	X,Y,A	X,Y,A



Input Sentence

b	a	a	a	a
---	---	---	---	---

$S \rightarrow XY$   
 $X \rightarrow XA|a|b$   
 $Y \rightarrow AY|a$   
 $A \rightarrow a$

Substrings of length 3

5	baaaa				
4	baaa	aaaa			
3	S,X	aaa	aaa		
2	S,X	S,X,Y	S,X,Y	S,X,Y	
1	X	X,Y,A	X,Y,A	X,Y,A	X,Y,A

Input Sentence

b	a	a	a	a
---	---	---	---	---


$$S \rightarrow XY$$

$$X \rightarrow XA|a|b$$

$$Y \rightarrow AY|a$$

$$A \rightarrow a$$

Substrings of length 3



$$S \rightarrow XY$$

$$X \rightarrow XA|a|b$$

$$Y \rightarrow AY|a$$

$$A \rightarrow a$$

Substrings of length 3

5	baaaa				
4	baaa	aaaa			
3	S,X	aaa	aaa		
2	S,X	S,X,Y	S,X,Y	S,X,Y	
1	X	X,Y,A	X,Y,A	X,Y,A	X,Y,A

Input Sentence

b	a	a	a	a
---	---	---	---	---



$$S \rightarrow XY$$

$$X \rightarrow XA|a|b$$

$$Y \rightarrow AY|a$$

$$A \rightarrow a$$

Substrings of length 3

5	baaaa				
4	baaa	aaaa			
3	S,X	S,X,Y	aaa		
2	S,X	S,X,Y	S,X,Y	S,X,Y	
1	X	X,Y,A	X,Y,A	X,Y,A	X,Y,A

Input Sentence

b	a	a	a	a
---	---	---	---	---

$$S \rightarrow XY$$

$$X \rightarrow XA|a|b$$

$$Y \rightarrow AY|a$$

$$A \rightarrow a$$

Substrings of length 3

5	baaaa				
4	baaa	aaaa			
3	S,X	S,X,Y	S,X,Y		
2	S,X	S,X,Y	S,X,Y	S,X,Y	
1	X	X,Y,A	X,Y,A	X,Y,A	X,Y,A

The diagram illustrates a sequence of states in a grid. The grid has 5 rows and 6 columns. The states are as follows:

- Row 5: baaaa
- Row 4: baaa, aaaa
- Row 3: S,X, S,X,Y, S,X,Y
- Row 2: S,X, S,X,Y, S,X,Y, S,X,Y
- Row 1: X, X,Y,A, X,Y,A, X,Y,A, X,Y,A

Arrows indicate transitions between states:

- A blue arrow points from the state **S,X,Y** in Row 2, Column 4 to the state **S,X,Y** in Row 3, Column 3.
- A blue arrow points from the state **S,X,Y** in Row 2, Column 5 to the state **S,X,Y** in Row 3, Column 4.
- A blue arrow points from the state **S,X,Y** in Row 2, Column 6 to the state **S,X,Y** in Row 3, Column 5.
- A blue arrow points from the state **S,X,Y** in Row 2, Column 4 to the state **S,X,Y** in Row 3, Column 4.


Input Sentence

b	a	a	a	a
---	---	---	---	---

Substrings of length 4

$S \rightarrow XY$   
 $X \rightarrow XA|a|b$   
 $Y \rightarrow AY|a$   
 $A \rightarrow a$


Input Sentence



Substrings of length 4


$S \rightarrow XY$   
 $X \rightarrow XA|a|b$   
 $Y \rightarrow AY|a$   
 $A \rightarrow a$

Input Sentence



Substrings of length 5

$S \rightarrow XY$   
 $X \rightarrow XA|a|b$   
 $Y \rightarrow AY|a$   
 $A \rightarrow a$



Sentence can  
be generated  
from S as well  
as from X.

5	S,X				
4	S,X,Y	S,X,Y			
3	S,X	S,X,Y	S,X,Y		
2	S,X	S,X,Y	S,X,Y	S,X,Y	
1	X	X,Y,A	X,Y,A	X,Y,A	X,Y,A

b	a	a	a	a
---	---	---	---	---

Complexity...?

Can You generate  
a parse tree...?


$$S \rightarrow XY$$

$$X \rightarrow XA|a|b$$


$$Y \rightarrow AY|a$$

$$A \rightarrow a$$

**Maintain Back  
pointers!!!**



Wait, did we get a different parse tree....?





# Ambiguity

Context Free Grammar,  $G$

$T_G$ : set of all possible left-most derivations (parse trees) under the grammar  $G$ .

$s$ : a given sentence

Define,

$$T_G(s) = \{t: t \in T_G, \text{yield}(t) = s\}$$

$$s \in L(G) \Leftrightarrow |T_G(s)| > 0$$

$$s \text{ is ambiguous} \Leftrightarrow |T_G(s)| > 1$$

# Natural Language Grammar

## Non-terminals

S = sentence

VP = verb phrase

NP = noun phrase

PP = prepositional phrase

DT = determiner

Vi = intransitive verb



Vt = transitive verb

NN = noun

IN = preposition.

S	→	NP	VP
VP	→	Vi	
VP	→	Vt	NP
VP	→	VP	PP
NP	→	DT	NN
NP	→	NP	PP
PP	→	IN	NP


Vi	→	sleeps
Vt	→	saw
NN	→	man
NN	→	woman
NN	→	telescope
NN	→	dog
DT	→	the
IN	→	with
IN	→	in



*the man saw the dog with the telescope*

**Which one is preferred over the other ...?**

# Probabilistic Context Free Grammar



## Something New

$$\forall \alpha \rightarrow \beta \in R$$

$$q(\alpha \rightarrow \beta) = P(\alpha \rightarrow \beta | \alpha):$$

*Probability of choosing rule  $\alpha \rightarrow \beta$  in a left-most derivation, given that the non-terminal being expanded is  $\alpha$ .*

Let's add probability constraints:

$$q(\alpha \rightarrow \beta) \geq 0$$

$$\sum_{\alpha \rightarrow \beta \in R, \alpha = X} q(\alpha \rightarrow \beta) = 1$$

## Coming back to Natural language


S	→	NP	VP	1.0	= 1
VP	→	Vi		0.3	
VP	→	Vt	NP	0.5	
VP	→	VP	PP	0.2	
NP	→	DT	NN	0.8	
NP	→	NP	PP	0.2	
PP	→	IN	NP	1.0	

Vi	→	sleeps	1.0	= 1
Vt	→	saw	1.0	
NN	→	man	0.1	
NN	→	woman	0.1	
NN	→	telescope	0.3	
NN	→	dog	0.5	
DT	→	the	1.0	
IN	→	with	0.6	
IN	→	in	0.4	

Lets come back to *which parse tree is better...?*

We need something to measure to compare two different parse trees.  
Let's define that measure,

$$p(t) = \prod_{i=1}^n q(\alpha_i \rightarrow \beta_i)$$



$$\begin{aligned} p(t) = & q(S \rightarrow NP \ VP) \times q(NP \rightarrow DT \ NN) \\ & \times q(DT \rightarrow \text{the}) \times q(NN \rightarrow \text{dog}) \times \\ & q(VP \rightarrow Vi) \times q(Vi \rightarrow \text{sleeps}) \end{aligned}$$

## Let's make a parse tree probabilistically....!

- Define  $s_1 = S, i = 1$ .
- While  $s_i$  contains at least one non-terminal:
  - Find the left-most non-terminal in  $s_i$ , call this  $X$ .
  - Choose one of the rules of the form  $X \rightarrow \beta$  from the distribution  $q(X \rightarrow \beta)$ .
  - Create  $s_{i+1}$  by replacing the left-most  $X$  in  $s_i$  by  $\beta$ .
  - Set  $i = i + 1$ .

In the end we reach a tree,  $t$  with score  $p(t)$ .



- Define  $s_1 = S, i = 1$ .
- While  $s_i$  contains at least one non-terminal:
  - Find the left-most non-terminal in  $s_i$ , call this  $X$ .
  - Choose one of the rules of the form  $X \rightarrow \beta$  from the distribution  $q(X \rightarrow \beta)$ .
  - Create  $s_{i+1}$  by replacing the left-most  $X$  in  $s_i$  by  $\beta$ .
  - Set  $i = i + 1$ .

How do we choose a rule?

$$t = \arg \max_{t' \in T_G(\text{sentence})} p(t')$$

***valid parse tree***

# Can we do it using CYK algorithm?


Obviously we can, that's why I asked...!!!

$S \rightarrow XY$	1.0
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	0.2
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0

Can you find **score** of most probable parse tree of ***baaaaa***?

$$\max_{t' \in T_G(\text{sentence})} p(t')$$

$S \rightarrow XY$	1.0
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	0.2
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0



$S \rightarrow XY$	1.0
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	0.2
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	ba	aa	aa	aa	
1	X: 0.3	X:0.2 Y:0.8 A:1.0	X:0.2 Y:0.8 A:1.0	X:0.2 Y:0.8 A:1.0	X:0.2 Y:0.8 A:1.0

Input Sentence	b	a	a	a	a
----------------	---	---	---	---	---

<b><math>S \rightarrow XY</math></b>	<b>1.0</b>
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	0.2
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0

$$p(t|S) = q(S \rightarrow XY) * p(t_1|X) * p(t_2|Y)$$

$$= 1.0 * 0.3 * 0.8$$

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	<b><math>S \rightarrow XY:.24</math></b> <b><math>X \rightarrow XA:.15</math></b>	aa	aa	aa	
1	<b><math>X \rightarrow b:0.3</math></b>	<b><math>X \rightarrow a:0.2</math></b> <b><math>Y \rightarrow a:0.8</math></b> <b><math>A \rightarrow a:1.0</math></b>	<b><math>X \rightarrow a:0.2</math></b> <b><math>Y \rightarrow a:0.8</math></b> <b><math>A \rightarrow a:1.0</math></b>	<b><math>X \rightarrow a:0.2</math></b> <b><math>Y \rightarrow a:0.8</math></b> <b><math>A \rightarrow a:1.0</math></b>	<b><math>X \rightarrow a:0.2</math></b> <b><math>Y \rightarrow a:0.8</math></b> <b><math>A \rightarrow a:1.0</math></b>

Input Sentence	b	a	a	a	a
----------------	---	---	---	---	---

$S \rightarrow XY$	1.0
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	0.2
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0

$$\begin{aligned}
 p(t|X) &= q(X \rightarrow XA) * p(t_1|X) * p(t_2|A) \\
 &= 0.5 * 0.3 * 1.0
 \end{aligned}$$

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	S->XY:0.24 X->XA:0.15	aa	aa	aa	
1	X->b:0.3	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0

Input Sentence	b	a	a	a	a
----------------	---	---	---	---	---

$S \rightarrow XY$	1.0
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	<b>0.2</b>
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	S->XY:0.24 X->XA:0.15	S->XY:0.16 X->XA:0.1 Y->AY:?	aa	aa	
1	X->b:0.3	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0

Input Sentence	b	a	a	a	a
----------------	---	---	---	---	---



$S \rightarrow XY$	1.0
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	0.2
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	S->XY:0.24 X->XA:0.15	S->XY:0.16 X->XA:0.1 Y->AY:0.16	aa	aa	
1	X->b:0.3	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0

Input Sentence	b	a	a	a	a
----------------	---	---	---	---	---

$S \rightarrow XY$	1.0
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	0.2
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0

5	baaaa				
4	baaa	aaaa			
3	baa	aaa	aaa		
2	S->XY:0.24 X->XA:0.15	S->XY:0.16 X->XA:0.1 Y->AY:0.16	S->XY:0.16 X->XA:0.1 Y->AY:0.16	S->XY:0.16 X->XA:0.1 Y->AY:0.16	
1	X->b:0.3	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0

Input Sentence	b	a	a	a	a
----------------	---	---	---	---	---

**A bit tricky...!**

$S \rightarrow XY$	1.0
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	0.2
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0

5	baaaa				
4	baaa	aaaa			
3	<b>S</b> <b>X</b>	aaa	aaa		
2	S->XY:0.24 X->XA:0.15	S->XY:0.16 X->XA:0.1 Y->AY:0.16	S->XY:0.16 X->XA:0.1 Y->AY:0.16	S->XY:0.16 X->XA:0.1 Y->AY:0.16	
1	X->b:0.3	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0




Input Sentence

b	a	a	a	a
---	---	---	---	---

**A bit tricky...!**

$S \rightarrow XY$	1.0
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	0.2
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0



$S \rightarrow XY$	1.0	5	baaaa							
$X \rightarrow XA$	0.5									
$X \rightarrow a$	0.2	4	baaa		aaaa					
$X \rightarrow b$	0.3									
$Y \rightarrow AY$	0.2	3	<b>S-&gt;XY:0.12</b> <b>X-&gt;XA:.075</b>		aaa		aaa			
$Y \rightarrow a$	0.8									
$A \rightarrow a$	1.0	2	<b>S-&gt;XY:0.24</b> <b>X-&gt;XA:0.15</b>		<b>S-&gt;XY:0.16</b> <b>X-&gt;XA:0.1</b> <b>Y-&gt;AY:0.16</b>		<b>S-&gt;XY:0.16</b> <b>X-&gt;XA:0.1</b> <b>Y-&gt;AY:0.16</b>		<b>S-&gt;XY:0.16</b> <b>X-&gt;XA:0.1</b> <b>Y-&gt;AY:0.16</b>	
		1	<b>X-&gt;b:0.3</b>		<b>X-&gt;a:0.2</b> <b>Y-&gt;a:0.8</b> <b>A-&gt;a:1.0</b>		<b>X-&gt;a:0.2</b> <b>Y-&gt;a:0.8</b> <b>A-&gt;a:1.0</b>		<b>X-&gt;a:0.2</b> <b>Y-&gt;a:0.8</b> <b>A-&gt;a:1.0</b>	
Input Sentence			b		a		a		a	

$S \rightarrow XY$	1.0	5	baaaa							
$X \rightarrow XA$	0.5									
$X \rightarrow a$	0.2	4	baaa		aaaa					
$X \rightarrow b$	0.3									
$Y \rightarrow AY$	0.2	3	<b>S-&gt;XY:0.12</b> <b>X-&gt;XA:0.075</b>		<b>S-&gt;XY:.08</b> <b>X-&gt;XA:0.05</b> <b>Y-&gt;AY:.032</b>		<b>S-&gt;XY:.08</b> <b>X-&gt;XA:0.05</b> <b>Y-&gt;AY:.032</b>			
$Y \rightarrow a$	0.8									
$A \rightarrow a$	1.0	2	<b>S-&gt;XY:0.24</b> <b>X-&gt;XA:0.15</b>		<b>S-&gt;XY:0.16</b> <b>X-&gt;XA:0.1</b> <b>Y-&gt;AY:0.16</b>		<b>S-&gt;XY:0.16</b> <b>X-&gt;XA:0.1</b> <b>Y-&gt;AY:0.16</b>		<b>S-&gt;XY:0.16</b> <b>X-&gt;XA:0.1</b> <b>Y-&gt;AY:0.16</b>	
		1	<b>X-&gt;b:0.3</b>		<b>X-&gt;a:0.2</b> <b>Y-&gt;a:0.8</b> <b>A-&gt;a:1.0</b>		<b>X-&gt;a:0.2</b> <b>Y-&gt;a:0.8</b> <b>A-&gt;a:1.0</b>		<b>X-&gt;a:0.2</b> <b>Y-&gt;a:0.8</b> <b>A-&gt;a:1.0</b>	
Input Sentence			b		a		a		a	

$S \rightarrow XY$	1.0	5	baaaa				
$X \rightarrow XA$	0.5						
$X \rightarrow a$	0.2	4	<b>S-&gt;XY:0.06</b>	<b>S-&gt;XY:0.04</b>			
$X \rightarrow b$	0.3		<b>X-&gt;XA: 0.0375</b>	<b>X-&gt;AX:? Y-&gt;AY:?</b>			
$Y \rightarrow AY$	0.2	3	<b>S-&gt;XY:0.12</b>	<b>S-&gt;XY:.08</b>	<b>S-&gt;XY:.08</b>		
$Y \rightarrow a$	0.8		<b>X-&gt;XA:.075</b>	<b>X-&gt;XA:0.05</b>	<b>X-&gt;XA:0.05</b>	<b>Y-&gt;AY:.032</b>	
$A \rightarrow a$	1.0	2	<b>S-&gt;XY:0.24</b>	<b>S-&gt;XY:0.16</b>	<b>S-&gt;XY:0.16</b>	<b>S-&gt;XY:0.16</b>	
			<b>X-&gt;XA:0.15</b>	<b>X-&gt;XA:0.1</b>	<b>X-&gt;XA:0.1</b>	<b>X-&gt;XA:0.1</b>	
				<b>Y-&gt;AY:0.16</b>	<b>Y-&gt;AY:0.16</b>	<b>Y-&gt;AY:0.16</b>	
		1	<b>X-&gt;b:0.3</b>	<b>X-&gt;a:0.2</b>	<b>X-&gt;a:0.2</b>	<b>X-&gt;a:0.2</b>	<b>X-&gt;a:0.2</b>
				<b>Y-&gt;a:0.8</b>	<b>Y-&gt;a:0.8</b>	<b>Y-&gt;a:0.8</b>	<b>Y-&gt;a:0.8</b>
				<b>A-&gt;a:1.0</b>	<b>A-&gt;a:1.0</b>	<b>A-&gt;a:1.0</b>	<b>A-&gt;a:1.0</b>
Input Sentence			b	a	a	a	a

$S \rightarrow XY$	1.0	5	S->XY:0.03				
$X \rightarrow XA$	0.5						
$X \rightarrow a$	0.2	4	S->XY:0.06 X->XA: 0.0375	S->XY:0.04 X->AX:? Y->AY:?			
$X \rightarrow b$	0.3						
$Y \rightarrow AY$	0.2	3	S->XY:0.12 X->XA:.075	S->XY:.08 X->XA:0.05 Y->AY:.032	S->XY:.08 X->XA:0.05 Y->AY:.032		
$Y \rightarrow a$	0.8						
$A \rightarrow a$	1.0	2	S->XY:0.24 X->XA:0.15	S->XY:0.16 X->XA:0.1 Y->AY:0.16	S->XY:0.16 X->XA:0.1 Y->AY:0.16	S->XY:0.16 X->XA:0.1 Y->AY:0.16	
		1	X->b:0.3	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0	X->a:0.2 Y->a:0.8 A->a:1.0
Input Sentence			b	a	a	a	a




$$\max_{t' \in T_G(\textit{sentence})} p(t') = 0.03$$

Can we infer most probable parse tree?

$$\mathit{arg} \max_{t' \in T_G(\textit{sentence})} p(t')$$

$S \rightarrow XY$	1.0
$X \rightarrow XA$	0.5
$X \rightarrow a$	0.2
$X \rightarrow b$	0.3
$Y \rightarrow AY$	0.2
$Y \rightarrow a$	0.8
$A \rightarrow a$	1.0



## Proof of correctness

$$p(t) = q(X \rightarrow YZ) * p(t_1) * p(t_2)$$

At each step, we take  $\max p(t)$


It is enough to show that:

1. Tree  $t_1$ , rooted at **Y**, has max probability over the words it spans.
2. Tree  $t_2$  rooted at **Z**, has maximum probability over the words its spans.

$$S = \{w_1, \dots w_i, \dots w_s, \dots w_j, \dots w_n\}$$

Recursive definition of probability build up!

$$\pi(i, j, X) = \max_{\substack{X \rightarrow YZ \in R \\ s \in (i, j)}} q(X \rightarrow YZ) * \pi(i, s, Y) * \pi(s + 1, j, Z)$$



Highest scoring tree  
rooted at X.

How do you get  $q$ ...?

Treebank: text corpus that annotates syntactic sentence structure. E.g., Penn Tree Bank<sup>1</sup>.

$$q = \frac{\textit{Count}(\alpha \rightarrow \beta)}{\textit{Count}(\alpha)}$$

<sup>1</sup><http://www.cis.upenn.edu/~treebank/>