ANGELES UNIVERSITY FOUNDATION
COLLEGE OF COMPUTER STUDIES
PTF60 – Professional Track 6

Student Name: **Paul Andrei S. Calma**	Date Submitted: Nov. 6, 2026
Program: BS Computer Science	Professor: Sir Andrew Ramos

Final Project

How AssistAnt's Orchestrator Routes Work to its Agents and Models

Summary

AssistAnt is a personal agent that wraps up the day in Notion and plans tomorrow, and every user request is sent to the Orchestrator [1]. The Orchestrator matches the request against markdown routines or, if none match, runs an unplanned flow and drafts a new routine for user approval [2]. Work is then dispatched to eleven sub-agents, each of which requests a model tier (fast, smart, or best) from the router [1, 3].

Key findings

- All requests enter the Orchestrator, which selects the first routine whose trigger regex matches or falls back to the unplanned flow [1, 2].
- Eleven sub-agents (Reader, Summarizer, Matcher, Notes Scout, Chore Keeper, Planner, Writer, Checker, Grocery Clerk, Briefer, Portfolio Clerk) operate on specific tiers that determine their model chain [1].
- The router checks each provider's health before use and selects the first provider in the tier's chain that is marked "ok" [3].
- Provider usage is counted per day and resets at midnight in the configured time zone; providers that hit their daily caps are skipped [3].

How it works

- Incoming request – The request is received by the Orchestrator [1].
- Routine matching – The Orchestrator scans the `routines` folder, testing each routine's case-insensitive regex trigger; the first match runs its flow [2]. If none match, the unplanned flow runs and a new routine is drafted [2].
- Agent dispatch – The Orchestrator hands work to the eleven sub-agents, each assigned a tier (code, smart, fast, best) [1].
- Router tier request – Each agent asks the router for its tier [3].

Risks and limitations

- Daily usage caps may force the router to skip providers, increasing reliance on plain-rule execution [3].
- When the router falls back to plain rules, the output lacks model-generated nuance, potentially reducing result quality [3].

References

[1] architecture.md

[2] routines.md

[3] model-router.md

Review

- Reader opened 3 documents through the MCP server (architecture.md, model-router.md, routines.md).
- Notes Scout checked the Reader's 12 notes against the retrieved passages: 12 supported.
- Checker, round 1: sent the draft back to the Writer (2 missing citations, 2 unsupported claims, over the word limit).
- Checker, round 2: approved, 22/24 statements supported by the sources; still open: 2 unsupported claims, over the word limit.
- Writer revised the draft once to address the Checker's notes.
- Publisher combined the approved draft with 3 source documents and removed 2 unsupported claims and shortened it to the word limit.