

Variables in C

CMSC 104 Section 02
Feb 21, 2024

Administrative Notes

- We'll go over quiz 1 in class today; if you have any questions see me after class


A quick reset - the program from Monday

```
//This is a c program that prompts the user for two integers,  
/* reads them in,  
   adds them,  
   and then prints out the result  
*/  
  
#include <stdio.h>  
int main ()  
{  
    int first_integer; // the first integer the user will type in  
    int second_integer; // the second integer the user will type in  
    printf("This program will read in two integers, add them and print the result\n");  
  
    printf("Please enter the first integer \n"); //prompt for the first integer  
    scanf("%d", &first_integer); // read the first integer  
  
    printf("Please enter the second integer \n"); //prompt for the second integer  
    scanf("%d", &second_integer); //read the second integer  
  
    int sum; //the variable where we will store the sum  
    sum = first_integer + second_integer;  
  
    printf("The sum of your numbers is %d\n", sum); //print the sum  
}
```

How memory works in a computer

Memory (“RAM”) can be thought of as a long, one-dimensional array of cells that store strings of 1’s and 0’s - “bits”.

Each location in memory has an address



A symbol table

C, like many languages, creates a “symbol table” for each part of a program


- It contains all variables defined for the program, the type of the variable, and a pointer to the address in memory where the value of that variable is defined

Symbol table

Variable Name	Type	Address
first_integer	int	1047892
second_integer	int	1047897
sum	int	1047900

Memory

	1047891
6	1047892
	1047893
	1047895
5	1047897
11	1047900



How Variables work in C

This stuff is pretty standard in all high-level computer languages; let's look at how C is unique

Rules for variable names

- Can contain letters, digits & underscore
- Can't start with a digit
- Can't be an existing "reserved word"
- Are case sensitive - "Grade" is not the same variable as "grade"
- Can be as long as you want but only the first 31 characters in the variable name are important.
 - "abcdefghijklmnopqrstuvwxyz0123456789" and "abcdefghijklmnopqrstuvwxyz0123456777" are the same variable

C reserved words (“keywords”)

These words cannot be used as variable names in C

auto	break	int	long
case	char	register	return
const	continue	short	signed
default	do	sizeof	static
double	else	struct	switch
enum	extern	typedef	union
float	for	unsigned	void
goto	if	volatile	while

CMSC104 Naming Conventions

These are not rules enforced by C, but they are conventions used in our class to make your code easier to read:

- Begin variable names with lowercase letters.
- Use meaningful identifiers (name)
- Separate “words” within identifiers with underscores or mixed upper and lower case.
 - Example: `surfaceArea`, `surface_area`, `surface_Area`
 - Be consistent!

To emphasize:

Legal identifiers refer to the restrictions C places on naming identifiers, such as not beginning with a number.

Naming conventions refer to the standards you must follow for this course, such as all variable names must be lowercase. But this isn't technically required by the compiler.

A quick check

Which of the following variable names are legal for C:

AREA

3D

lucky***

num45

Last-Chance

#values

x

yt3

pi

num\$

%done

area_under_the_curve

Another check:

Which of the following are legal C variable names, but do not follow CMSC104 Naming Conventions?

Area

person1

Last_Chance

values

x

yt3

pi

finaltotal

numChildren

area_under_the_curve

Basic types: int, float, char

(we'll add more types later on in the semester)

C has three basic predefined data types:

- Integers (whole numbers)
 - int, long int (or just long), short int (or just short)
 - Always positive: unsigned (unsigned int, unsigned long, unsigned short)
- Floating point (real numbers)
 - float, double
- Characters
 - char

But they're all bits

It's just a string of 1's and 0's

- you can do things with a variable that you might not have originally intended

Examples

What if the variable was an int, and you entered a character?

What if the variable was a float, and you entered an integer?

What if the variable was a char, and you entered a float?

Another example

```
#include <stdio.h>

int main() {
    float fathoms;// the depth in fathoms
    float feet;// the depth in feet
    float inches; //the depth in inches

    /* Ask the user for the depth in fathoms */
    printf("Enter the depth in fathoms: ")
    scanf("%f", &fathoms);
    /* Convert depth from fathoms to inches */
    feet = 6.0 * fathoms
    inches = 12.0 * feet

    /* Display The Results */
    printf ( "Its depth at sea:\n" );
    printf( "\t%1.2f fathoms\n" , fathoms);
    printf( "\t%1.2f feet\n", feet);
    printf ( "\t%1.2f inches\n", inches);
    return 0 ; }
```