

While Loops

September 30, 2020

Today's topics

While loops in general

Sentinel Loops

Boolean Flags

while loops

“while” loops are the most general type of iteration in Python - anything you can solve with a “for” loop can also be solved with a “while” loop, but not everything that can be solved with a “while” loop can be solved with a “for” loop

- “for” loops are used when you know how many times you want to iterate through some code
 - You know the specific number of times
 - You know you want to iterate a number of times that is the value of a specific variable, such as the length of a list
- “while” loops are the only loop used when you don’t know how many times you will iterate through code

Syntax of a while loop

```
while boolean-condition-is-true:
```

```
    Code to be executed
```

Remember indentation. All the code that is indented underneath the “while” statement is executed as part of the loop. When you unindent, that code is no longer part of the loop.

Set the value of your boolean condition. Unlike with “for” loops, Python does not automatically set a value for a new variable used in the boolean condition of a “while.”

Examples:

```
age = 0;
while (age < 18):
    age = input("enter your age in years: ")
    print ("If you're 18 or older you should vote")
print ("that's the end of our story")
```

What happens if we leave out the initial `age = 0` statement? The loop fails because `age` has no value.

How many times will this loop be executed? We don't know - until the user cooperates

'Priming read'

```
age = int(input("enter your age in years: "))
while (age < 18):
    age = int(input("enter your age in years: "))
    print ("If you're 18 or older you should vote")
print ("that's the end of our story")
```

"Priming" - refers to getting an initial value before executing the loop

- If the user enters 35 - the loop never executes

Example: factorial

compute 10! Using a while loop

product = 1

factor = 1

while factor <= 10:

 product *= factor #or product = product * factor

 factor += 1

Common programming errors 1: Loop is never executed

Suppose we want to print out all of the even numbers between 2 and 100 inclusive. Why won't this loop work?

```
num = 1
```

```
while num % 2 == 0:
```

```
    print(num)
```

```
    num += 2
```

It is perfectly acceptable to write a loop that may never be executed, due to other conditions in your code.

But be sure that that's really what you want

A loop that never executes:

```
age = int(input("please enter your age in  
years: "))  
while (age < 0) or (age > 100):  
    print("Age must be between 0 and 100  
inclusive ")  
    age = int(input("please enter your age  
in years: "))
```

If the user enters, say, 21 at the first prompt, the boolean condition is false at the start, and the code under the while is never executed.

That's perfectly fine. Just make sure that it's really what you wanted.

Common programming errors II: infinite loops

An infinite loop is one that never stops executing, because the boolean condition never becomes false.

Common causes:

- You never change a variable used in the boolean condition
- You plan to stop when a variable takes on a value that it will never take on

The code will never stop on its own. The program is only stopped by external action - you shut off the program or run out of resources. On gl.umbc.edu and similar machines, you can hit “Control” and “c”.

Note: infinite loops can occur with “for” loops, but you have to really work hard to make that happen. They’re rare.

Infinite loop examples

```
grade = ""
name = ""
while name != "Hrabowski":
    # get the user's grade
    grade = input("What is your
grade? ")
print("You passed!")
```

```
cookiesLeft = 50
```

```
while cookiesLeft > 0:
    # eat a cookie
    cookiesLeft = cookiesLeft + 1
```

```
#print all the positive odd numbers
#less than 100
```

```
num = 1
while num != 100:
    print(num)
    num = num + 2
```

Sentinel Loops

A loop that runs until a specific value is encountered

A 'sentinel' is a value that denotes the end of a data set.

Simple example: letting the user input data. The user inputs "Q" to indicate that it is time to quit. "Q" is the sentinel value

Code - see next slide

Sentinel loop - example

```
birthdate = input("Enter your month and day of birth as mm/dd. Enter 'Q' to quit.")
while birthdate != "Q":
    month_and_day = birthdate.split('/')
    for i in range(2):
        month_and_day[i] = int(month_and_day[i])
    day_of_year = 30 * month_and_day[0] + month_and_day[1]
    print(f"Your birthday is the {day_of_year:5d} day of the year")
    birthdate = input("Enter your month and day of birth as mm/dd. Enter 'Q' to quit.")
```

:

Boolean flags

You have to have a boolean condition in your while loop, so what's a "Boolean flag?"

- It's a boolean variable that you explicitly set to true or false and use that to end a while loop

Boolean Flag

```
prompt = "Tell me something cool: "  
prompt += "\nEnter 'quit' to end the program"  
active = True  
while active:  
    message = input(prompt)  
    if message == 'quit':  
        active = False  
    else:  
        print(message)
```

NOT a Boolean Flag

```
prompt = "Tell me something cool: "  
prompt += "\nEnter 'quit' to end the program"  
message = input(prompt)  
while message != "quit":  
    print(message)  
    message = input(prompt)
```