

# Complexity and Analysis of Algorithms

May 5, 2021

# Administrative Notes

Please complete the course evaluation for this course!! The deadline is May 12.

The final is Monday, May 17, on Blackboard - scheduled for 3:30 - 5:30 pm

- IF you'd rather take it that day from 8:30 - 10:30 am, please let me know by next Wednesday, the 12th
  - I have some students who need to take the exam that morning, so I'll be online anyway.
  - I do need to set it up in Blackboard - this is completely optional, but you do need to let me know

Project 3 - due in one week - you should have major parts of it working by now

- We'll talk about graphing later today

Homework 6 is due next Monday - it's pretty easy; just get it done

# Analysis of Algorithms: Sorting and Searching

We covered two ways to search through a list for a specific value: linear search, which always works because we search every element of a list until we find what we want; and binary search, which works if the list is already sorted

We covered three algorithms for sorting a list into order:

- Bubble sort
- Selection sort
- Quick sort

I said during that lecture that quick sort is the fastest of those algorithms. What does that mean?

# Linear Search:

We have the following 120-element list:

[22, 75, 67, 24, 49, 65, 96, 81, 96, 36, 66, 100, 73, 30, 23, 32, 89, 5, 8, 70, 71, 9, 71, 77, 48, 45, 6, 73, 42, 71, 55, 98, 19, 47, 71, 21, 43, 75, 5, 72, 78, 53, 72, 89, 60, 79, 43, 89, 84, 81, 14, 31, 44, 54, 41, 91, 78, 71, 24, 24, 42, 30, 57, 55, 26, 26, 48, 65, 28, 95, 74, 93, 89, 49, 92, 86, 14, 62, 36, 15, 51, 27, 36, 6, 24, 41, 69, 54, 14, 24, 50, 6, 27, 58, 100, 45, 35, 9, 91, 57, 22, 3, 50, 72, 89, 13, 64, 0, 68, 52, 20, 16, 52, 40, 6, 74, 34, 34, 15, 71]

How many comparisons does it take to see if the number 83 is in the list, using linear search? 120, because it's not there and we have to check each element to confirm that.

How many comparisons does it take to see if the number 22 is in the list? 1, because we find it on the first comparison

# Notation:

“Big O” notation: use a capital “O” to describe how long it takes for an algorithm to execute in the worst case. E.g., how many comparisons it takes.

We usually express this in terms of “n” because we assume a list of size n.

In the previous example: linear search is  $O(n)$ . Because in the worst case - like with 83 - you have to check every element in the list. All n of them

Big Omega -  $\Omega(n)$  - describes how long the algorithm takes to run in the best case. Linear search is  $\Omega(1)$  because in the best case - like with 22 - it only takes one comparison

# Binary search

Worst case -  $O(\log_2 n)$  - you might not find it

Best case -  $\Omega(1)$  - you might find it on the first value

Explanation:

$\log_2 n$  is the power that you have to raise 2 to in order to get n. Also, the number of times you can successively divide n in half.

# Now, the sorting algorithms

## Bubble sort:

- List is  $n$  elements long
- You have to go through all remaining unsorted elements of the list each time:
  - $n$  elements the first time;  $n-1$  the second time; and so on.
  - This equals  $n * (n-1) / 2$  from your calculus classes. Or,  $(n^2 - n) / 2$
- We round this off to  $n^2$ .
- Bubble sort is  $O(n^2)$
- Bubble sort is  $\Omega(n)$  - if the list is already sorted and you stop when you don't swap anything, you only have to go through the list once

# Don't sweat the small stuff

Bubble sort is  $O((n^2 - n)/2)$ . How come we rounded that off to  $O(n^2)$ ?

Think if  $n$  is really, really large. Say 1 million.

1 million squared is 1 trillion - 10 to the 12th power.

When  $n = 1$  million,  $(n^2 - n)/2 = (1 \text{ trillion} - 1 \text{ million})/2$ . Or 999 billion, 999 million /2. We just round that off to 1 trillion - it's close enough.



# Selection sort

Selection sort is almost like bubble sort

- List is  $n$  elements long
- You have to go through all remaining unsorted elements of the list each time:
  - $n$  elements the first time;  $n-1$  the second time; and so on.
  - This equals  $n * (n-1) / 2$  from your calculus classes. Or,  $(n^2 - n) / 2$
- We round this off to  $n^2$ .
- Selection sort is  $O(n^2)$
- Selection sort is  $\Omega(n^2)$
- So we say that selection sort is  $\Theta(n^2)$  - if  $O$  and  $\Omega$  are equal,  $\Theta$  is the same value

# What about quicksort? It's different

There's an area of risk. When we pick the pivot, we have no idea whether the pivot is somewhere in the middle of the values to be sorted.

If we get really, really unlucky, each time we pick a pivot it's the smallest number left, or the largest. All remaining values go to one side, and we just make the list one element smaller.

In that case, quicksort is  $O(n^2)$  just like the other two algorithms.

And the best case is  $\Omega(n)$

## But realistically...

On the average, you're not going to randomly pick the worst possible value for the pivot every time. Sometimes you're going to have good luck.

In that case, you'll divide the list to be sorted into halves, and this becomes like binary search.

So you'll often see that quicksort is  $O(n * \log n)$