4-40 Mounting Screw - 2 places - 0.125" PIN 3.3 mm 15.2 mm 21.8 mm

BOARD CHARACTERISTICS

Copper Layer Count: Board Thickness: 62.99 mils

Board overall dimensions: 860.00 mils x 1250.00 mils

10.00 mils / 9.50 mils Min track/spacing: Min hole diameter: 10.00 mils Copper Finish: HAL SnPb Impedance Control: No Castellated pads: Plated Board Edge: No

Edge card connectors:

Layer Name	Туре	Material	Thickness (mils)	Color	Epsilon R	Loss Tangent
F.Silkscreen	Top Silk Screen	Not specified	0 mils	Not specified	1	0
F.Paste	Top Solder Paste		0 mils		1	0
F.Mask	Top Solder Mask	Not specified	0.3937 mils	Green	3.3	0
F.Cu	copper		1.37795 mils		1	0
Dielectric 1	prepreg	FR4	3.93701 mils	Not specified	4.5	0.02
In1.Cu	copper		1.37795 mils		1	0
Dielectric 2	core	FR4	48.8189 mils	Not specified	4.5	0.02
In2.Cu	copper		1.37795 mils		1	0
Dielectric 3	prepreg	FR4	3.93701 mils	Not specified	4.5	0.02
B.Cu	copper		1.37795 mils		1	0
B.Mask	Bottom Solder Mask	Not specified	0.3937 mils	Green	3.3	0
B.Paste	Bottom Solder Paste		0 mils		1	0
B.Silkscreen	Bottom Silk Screen	Not specified	0 mils	Not specified	1	0

Drill Map:

· 0.305mm / 0.0120" (27 holes) ∘ 1.000mm / 0.0394" (6 holes) + 3.175mm / 0.1250" (3 holes + 1 slot) □ 3.400mm / 0.1339" (2 holes) (not plated)

NOTES:

1. LAYERS: 4
2. PCB THICKNESS: 1.6mm
3. PCB COLOR: GREEN
4. SILKSCREEN: WHITE
5. MATERIAL TYPE: FR4 TG-155
6. SURFACE FINISH: HASL (Pb)
7. OUTER COPPER WEIGHT: 1oz
8. INNER COPPER WEIGHT: 0.5oz
9. IMPEDANCE CONTROL: NO
10. VIA COVERING: PLUGGED
11. MIN VIA HOLE DIA: 0.3mm
12. BOARD OUTLINE TOLERANCE: +/-0.2mm



971 Spartan Robotics

File: mag-encoder.kicad_pcb

Title: Mag Encoder

Size: B Date: 2024-08-25 KiCad E.D.A. 8.0.4 Rev: 1 Page: 1/1