

```

#include<stdio.h>

int main()
{
    int count,j,n,time,remain,flag=0,time_quantum;
    int wait_time=0,turnaround_time=0,at[10],bt[10],rt[10];
    printf("Enter Total Process:\t ");
    scanf("%d",&n);
    remain=n;
    for(count=0;count<n;count++)
    {
        printf("Enter Arrival Time and Burst Time for Process Process Number %d :",count+1);
        scanf("%d",&at[count]);
        scanf("%d",&bt[count]);
        rt[count]=bt[count];
    }
    printf("Enter Time Quantum:\t");
    scanf("%d",&time_quantum);
    printf("\n\nProcess\t|Turnaround Time|Waiting Time\n\n");
    for(time=0,count=0;remain!=0;)
    {
        if(rt[count]<=time_quantum && rt[count]>0)
        {
            time+=rt[count];
            rt[count]=0;
            flag=1;
        }
        else if(rt[count]>0)
        {
            rt[count]-=time_quantum;
            time+=time_quantum;
        }
        if(rt[count]==0 && flag==1)
        {
            remain--;
            printf("P[%d]\t|\t%d\t|\t%d\n",count+1,time-at[count],time-at[count]-bt[count]);
            wait_time+=time-at[count]-bt[count];
            turnaround_time+=time-at[count];
            flag=0;
        }
        if(count==n-1)
            count=0;
        else if(at[count+1]<=time)
            count++;
        else
            count=0;
    }
    printf("\nAverage Waiting Time= %f\n",wait_time*1.0/n);
    printf("Avg Turnaround Time = %f",turnaround_time*1.0/n);

    return 0;
}

```