

Disclaimer

In order to use this library, users must have a local installation of the *R* programming language and the libraries noted in the **Depends** and **Imports** sections below.

R is open source software, and the creation of this library is neither a statement of affiliation with the developers of, nor the endorsement of the use of, *R* by the U.S. Bureau of Economic Analysis.

Use of this library will result in data being stored on users' local machines. Specifically, local copies of BEA API metadata will be stored and updated in the `.libPaths() "/beaR/data"` directory in order to improve performance of `beaSearch`.

Package ‘beaR’

August 30, 2016

Title R interface to the Bureau of Economic Analysis API

Version 1.0.0

Author Andrea Julca [aut, cre],
Jeff Chen [ctb],
Jonathan Auerbach [ctb],
Walter Kampas [ctb],
Bryan Vengelen [ctb],
James Kim [ctb],
Adjai-Fatou Diagne [ctb],
Gerardo Bonilla [ctb],
Stephen Devine [ctb]

Maintainer Andrea Julca <Developers@bea.gov>

Depends R (>= 3.2.1),
data.table

Imports httr,
DT,
shiny,
jsonlite,
googleVis,
shinydashboard,
ggplot2,
stringr

Description The beaR package is an R interface for the Bureau of Economic Analysis (BEA) API that serves two core purposes -

1. To Extract/Transform/Load data [`beaGet`] from the BEA API as R-friendly formats in the user's workspace [transformation done by default in `beaGet` can be modified using optional params; see, too, `bea2List`, `bea2Tab`].
2. To enable the search of descriptive metadata [`beaSearch`].

Other features of the library exist mainly as intermediate methods or are in early stages of development.

Important Note - You must have an API Key to use this library. Register for a key at <http://www.bea.gov/API/signup/index.cfm> .

URL http://www.bea.gov/API/bea_web_service_api_user_guide.htm

License file LICENSE

LazyData no

RoxygenNote 5.0.1

R topics documented:

bea2List	2
bea2Tab	3
beaGet	3
beaParams	4
beaParamVals	5
beaSearch	5
beaSets	6
beaUpdateMetadata	6
beaViz	7

Index	8
--------------	----------

bea2List	<i>Convert BEA API httr response payload to list</i>
----------	--

Description

Convert BEA API httr response payload to list

Usage

```
bea2List(beaPayload, isMeta = FALSE)
```

Arguments

beaPayload	An object with httr class 'response' from call to BEA API
isMeta	Special parameter meant to interact with metadata functions (default: FALSE)

Value

An object of class 'list' of several dimensions. View list structure using 'str(yourList)'.

Examples

```
userSpecList <- list('UserID' = 'yourKey' ,
  'Method' = 'GetData',
  'datasetname' = 'NIPA',
  'Frequency' = 'A',
  'TableID' = '68',
  'Year' = 'X')
resp <- beaGet(userSpecList, asTable = FALSE)
BL <- bea2List(resp)
```

bea2Tab	<i>Convert BEA API http response or list payload to data.table</i>
---------	--

Description

Convert BEA API http response or list payload to data.table. Also, converts LONG data frame (default API format - see bea2List results) to WIDE data (with years as columns) by default

Usage

```
bea2Tab(beaPayload, asWide = TRUE, iTableStyle = TRUE)
```

Arguments

beaPayload	An object of class 'list' or http 'response' returned from beaGet() call to BEA API
asWide	Return data.table in wide format (default: TRUE)
iTableStyle	If "asWide = TRUE", setting "iTableStyle = TRUE" will return data.table in same format as shown on BEA website, with dates and attributes as column headers and series as rows; otherwise, results have series codes as column headers (default: TRUE)

Value

An object of class 'data.table' containing data from beaGet(...) with custom attributes(BDT)\$params.

Examples

```
userSpecList <- list('UserID' = 'yourKey' ,
  'Method' = 'GetData',
  'datasetname' = 'NIPA',
  'Frequency' = 'A',
  'TableID' = '68',
  'Year' = 'X')
resp <- beaGet(userSpecList)
BDT <- bea2Tab(resp)
```

beaGet	<i>Pass list of user specifications (including API key) to return data from BEA API.</i>
--------	--

Description

Pass list of user specifications (including API key) to return data from BEA API.

Usage

```
beaGet(beaSpec, asString = FALSE, asList = FALSE, asTable = TRUE,
  asWide = TRUE, isMeta = FALSE, iTableStyle = TRUE)
```

Arguments

beaSpec	A list of user specifications (required)
asString	Return result body as a string (default: FALSE)
asList	Return result body as a list (default: FALSE)
asTable	Return result body as a data.table (default: TRUE)
asWide	Return data.table in wide format (default: TRUE)
isMeta	Special parameter meant to interact with metadata functions (default: FALSE)
iTableStyle	If "asWide = TRUE", setting "iTableStyle = TRUE" will return data.table in same format as shown on BEA website, with dates and attributes as column headers and series as rows; otherwise, results have series codes as column headers (default: TRUE)

Value

By default, an object of class 'list' of several dimensions. View list structure using 'str(yourList)'.

Examples

```
userSpecList <- list('UserID' = 'yourAPIKey' ,
  'Method' = 'GetData',
  'datasetname' = 'NIPA',
  'Frequency' = 'A',
  'TableID' = '68',
  'Year' = 'X')
BDT <- beaGet(userSpecList, asTable = TRUE)
```

beaParams

Gives list of parameters possible for a given dataset

Description

Gives list of parameters possible for a given dataset

Usage

```
beaParams(beaKey, setName)
```

Arguments

beaKey	Your API key
setName	Name of BEA dataset (e.g., 'NIPA')

Value

A metadata object of class 'list' of several dimensions. View list structure using 'str(yourList)'.

Examples

```
beaParams('yourAPIkey', 'RegionalData')
```

beaParamVals	<i>Gives list of values possible for a given dataset's parameters</i>
--------------	---

Description

Gives list of values possible for a given dataset's parameters

Usage

```
beaParamVals(beaKey, setName, paramName)
```

Arguments

beaKey	Your API key
setName	Name of BEA dataset (e.g., NIPA)
paramName	Name of BEA dataset parameter (e.g., TableID)

Value

A metadata object of class 'list' of several dimensions. View list structure using 'str(yourList)'.

Examples

```
beaParamVals('yourAPIkey', 'RegionalData', 'keycode')
```

beaSearch	<i>Search a selection of indexed BEA data table names, series labels, and series codes.</i>
-----------	---

Description

Searches indexed dataset table name, label, and series codes. CAUTION: Currently only works with NATIONAL datasets (NIPA, NIUnderlyingDetail, FixedAssets) and REGIONAL datasets (RegionalData, RegionalProduct, RegionalIncome)

Usage

```
beaSearch(searchTerm, beaKey = NULL, asHtml = FALSE)
```

Arguments

searchTerm	A word or phrase of class 'character' to be found in BEA datasets
beaKey	Character string representation of user API key. Necessary for first time use and updates; recommended for anything beyond one-off searches from the console.
asHtml	Option to return results as DT markup, viewable in browser. Allows search WITHIN YOUR ALREADY-FILTERED RESULTS ONLY. Requires package 'DT' to be installed.

Value

An object of class 'data.table' with information about all indexed sets in which the search term was found.

Examples

```
beaSearch('gross domestic product', asHtml = TRUE)
```

beaSets	<i>Returns a list of all datasets</i>
---------	---------------------------------------

Description

Returns a list of all datasets

Usage

```
beaSets(beaKey)
```

Arguments

beaKey	Your API key
--------	--------------

Value

A metadata object of class 'list' of several dimensions. View list structure using 'str(yourList)'.

Examples

```
beaSets('yourAPIkey')
```

beaUpdateMetadata	<i>Download BEA metadata into library/data folder if needed</i>
-------------------	---

Description

Download BEA metadata into library/data folder if needed

Usage

```
beaUpdateMetadata(datasetList, beaKey)
```

Arguments

datasetList	list of BEA datasets to update local metadata file for (e.g., list('NIPA', 'FixedAssets'))
beaKey	Your API key

Value

Nothing. This updates local .RData files to be used in beaSearch.

Examples

```
beaUpdateMetadata(list('RegionalData', 'NIPA'), beaKey = 'yourAPIkey')
```

beaViz*Visualize BEA API response payload*

Description

CAUTION: Currently only works with NATIONAL datasets (NIPA, NIUnderlyingDetail, FixedAssets)

Usage

```
beaViz(beaPayload)
```

Arguments

beaPayload An http response from call to BEA API

Examples

```
userSpecList <- list('UserID' = 'yourKey' ,  
  'Method' = 'GetData',  
  'datasetname' = 'NIPA',  
  'Frequency' = 'A',  
  'TableID' = '68',  
  'Year' = 'X')  
resp <- beaGet(userSpecList)  
BDF <- beaViz(resp)  
userSpecList <- list('UserID' = 'yourKey' ,  
  'Method' = 'GetData',  
  'datasetname' = 'NIPA',  
  'Frequency' = 'A',  
  'TableID' = '68',  
  'Year' = 'X')
```

Index

*Topic **metadata**

- beaParams, [4](#)
- beaParamVals, [5](#)
- beaSets, [6](#)
- beaUpdateMetadata, [6](#)

*Topic **search**

- beaSearch, [5](#)
- beaUpdateMetadata, [6](#)

- bea2List, [2](#)
- bea2Tab, [3](#)
- beaGet, [3](#)
- beaParams, [4](#)
- beaParamVals, [5](#)
- beaSearch, [5](#)
- beaSets, [6](#)
- beaUpdateMetadata, [6](#)
- beaViz, [7](#)