

PyPalEx

1.3.0

Generated by Doxygen 1.9.5

1 PyPalEx: The Python Palette Extractor	1
1.1 Description	1
2 Namespace Index	1
2.1 Package List	1
3 Class Index	2
3.1 Class List	2
4 File Index	2
4.1 File List	2
5 Namespace Documentation	2
5.1 pypalex Namespace Reference	2
5.1.1 Detailed Description	3
5.2 pypalex.__main__ Namespace Reference	3
5.2.1 Function Documentation	4
5.2.2 Variable Documentation	6
5.3 pypalex.arg_messages Namespace Reference	7
5.3.1 Function Documentation	7
5.4 pypalex.constants Namespace Reference	8
5.4.1 Variable Documentation	9
5.5 pypalex.conversion_utils Namespace Reference	12
5.5.1 Function Documentation	12
5.6 pypalex.extraction_utils Namespace Reference	15
5.6.1 Function Documentation	15
5.7 pypalex.Extractor Namespace Reference	21
5.8 pypalex.image_utils Namespace Reference	22
5.8.1 Function Documentation	22
6 Class Documentation	23
6.1 Extractor Class Reference	23
6.1.1 Detailed Description	24
6.1.2 Constructor & Destructor Documentation	24
6.1.3 Member Function Documentation	26
6.1.4 Member Data Documentation	28
7 File Documentation	29
7.1 __main__.py File Reference	29
7.1.1 Detailed Description	30
7.1.2 Author(s)	30
7.2 arg_messages.py File Reference	30
7.2.1 Detailed Description	31
7.2.2 Author(s)	31

7.3 constants.py File Reference	31
7.3.1 Detailed Description	32
7.3.2 Author(s)	32
7.4 conversion_utils.py File Reference	32
7.4.1 Detailed Description	33
7.4.2 Author(s)	33
7.5 extraction_utils.py File Reference	33
7.5.1 Detailed Description	34
7.5.2 Author(s)	34
7.6 Extractor.py File Reference	34
7.6.1 Detailed Description	34
7.6.2 Author(s)	34
7.7 image_utils.py File Reference	35
7.7.1 Detailed Description	35
7.7.2 Author(s)	35
Index	37

1 PayPalEx: The Python Palette Extractor

1.1 Description

PayPalEx is a tool for extracting color palettes from images and generating a JSON format file with light and dark color themes. This tool is intended to be OS independent, for use by the tech community for developing their own custom theme managers or by artists who want to extract color palettes for their art from images, pictures or wallpapers they adore.

2 Namespace Index

2.1 Package List

Here are the packages with brief descriptions (if available):

pypalex	
Python Palette Extractor: extracts color palettes from images	2
pypalex.__main__	3
pypalex.arg_messages	7
pypalex.constants	8
pypalex.conversion_utils	12
pypalex.extraction_utils	15
pypalex.Extractor	21

[pypalex.image_utils](#)

22

3 Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

[Extractor](#)

Extracts colors given a matrix of HSV values extracted from an image

23

4 File Index

4.1 File List

Here is a list of all files with brief descriptions:

[__main__.py](#)

Main script for PyPalEx

29

[arg_messages.py](#)

Archive of messages to display for arguments supplied by user

30

[constants.py](#)

A collection of constants for PyPalEx

31

[conversion_utils.py](#)

Utilities for converting between RGB, HSV, HEX

32

[extraction_utils.py](#)

Utilities for extracting colors from the image

33

[Extractor.py](#)

Extraction utility class for extracting colors from the image

34

[image_utils.py](#)

Utilities for processing image and file handling

35

5 Namespace Documentation

5.1 pypalex Namespace Reference

Python Palette [Extractor](#): extracts color palettes from images.

Namespaces

- namespace [__main__](#)
- namespace [arg_messages](#)
- namespace [constants](#)
- namespace [conversion_utils](#)
- namespace [extraction_utils](#)
- namespace [Extractor](#)
- namespace [image_utils](#)

5.1.1 Detailed Description

Python Palette [Extractor](#): extracts color palettes from images.

PyPalEx is a tool for extracting color palettes from images and generating a JSON format file with light and dark color themes. This tool is intended to be OS independent, for use by the tech community for developing their own custom theme managers or by artists who want to extract color palettes for their art from images, pictures or wallpapers they adore.

5.2 pypalex.__main__ Namespace Reference

Functions

- def [main](#) ()
Main script function.
- def [handle_args](#) ()
Handles the arguments passed to PyPalEx.
- def [extract_color_palettes](#) ()
Handles color extraction from image(s).
- def [setup_argument_parser](#) ()
Sets up the argument parser for command line arguments.
- def [check_sources](#) (filepaths, path=None)
Checks each of the sources provided and removes any bad sources.
- def [check_path](#) (path)
Check the path to make sure it exists.
- def [set_global_args](#) (args)
Sets the global variables using the arguments.
- def [check_source](#) (filepath)
Checks to make sure the path leads to a file.

Variables

- list `EXTRACTORS` = []
List of `Extractor` class objects for each individual image.
- list `PROPER_IMAGES` = []
List of real/existing image file path(s).
- list `FILENAMES` = []
List of image filenames.
- list `OUTPUT_FILEPATHS` = []
List of output file path(s) for each image.
- string `OUTPUT_PATH` = "
The path to the output directory where all JSON files will be saved.
- string `OUTPUT_TAIL` = "-color_palette.json"
The tail to append to each output filepath.
- bool `PASTEL` = False
Flag for pastel option.
- bool `PASTEL_L` = False
Flag for light pastel option.
- bool `PASTEL_N` = False
Flag for normal pastel option.
- bool `PASTEL_D` = False
Flag for dark pastel option.

5.2.1 Function Documentation

5.2.1.1 `check_path()` `def check_path (`
`path)`

Check the path to make sure it exists.

Parameters

<code>path</code>	The path to a directory.
-------------------	--------------------------

Returns

True if the path exists and is not a file, False otherwise.

5.2.1.2 `check_source()` `def check_source (`
`filepath)`

Checks to make sure the path leads to a file.

Parameters

<i>filepath</i>	Path to file with filename and file extension.
-----------------	--

Returns

True if file exists, False otherwise.

5.2.1.3 check_sources() `def check_sources (`
 filepaths,
 path = None)

Checks each of the sources provided and removes any bad sources.

Any filepaths or source files that are not images or do not exist get removed.

Parameters

<i>filepaths</i>	List of file paths.
<i>path</i>	A path to the images, if it is provided.

Returns

True if all/some sources are good, False if all sources are bad.

5.2.1.4 extract_color_palettes() `def extract_color_palettes ()`

Handles color extraction from image(s).

5.2.1.5 handle_args() `def handle_args ()`

Handles the arguments passed to PyPalEx.

5.2.1.6 main() `def main ()`

Main script function.

5.2.1.7 set_global_args() `def set_global_args (`
 args)

Sets the global variables using the arguments.

Parameters

<i>args</i>	User-supplied arguments.
-------------	--------------------------

5.2.1.8 setup_argument_parser() `def setup_argument_parser ()`

Sets up the argument parser for command line arguments.

Returns

A command line argument parsing object.

5.2.2 Variable Documentation**5.2.2.1 EXTRACTORS** `list EXTRACTORS = []`

List of [Extractor](#) class objects for each individual image.

5.2.2.2 FILENAMES `list FILENAMES = []`

List of image filenames.

5.2.2.3 OUTPUT_FILEPATHS `list OUTPUT_FILEPATHS = []`

List of output file path(s) for each image.

5.2.2.4 OUTPUT_PATH `string OUTPUT_PATH = ''`

The path to the output directory where all JSON files will be saved.

5.2.2.5 OUTPUT_TAIL `string OUTPUT_TAIL = "-color_palette.json"`

The tail to append to each output filepath.

5.2.2.6 PASTEL `bool PASTEL = False`

Flag for pastel option.

5.2.2.7 PASTEL_D `bool PASTEL_D = False`

Flag for dark pastel option.

5.2.2.8 PASTEL_L `bool PASTEL_L = False`

Flag for light pastel option.

5.2.2.9 PASTEL_N `bool PASTEL_N = False`

Flag for normal pastel option.

5.2.2.10 PROPER_IMAGES `list PROPER_IMAGES = []`

List of real/existing image file path(s).

5.3 pypalex.arg_messages Namespace Reference

Functions

- def `bad_source_message()`
Generates an error message if the sources provided were not images.
- def `bad_path_message()`
Generates an error message if the directory provided is not a valid directory.
- def `no_args_help_message()`
Generates a help message if no arguments were presented.

5.3.1 Function Documentation

5.3.1.1 **bad_path_message()** `def bad_path_message ()`

Generates an error message if the directory provided is not a valid directory.

Returns

The "bad directory" message.

5.3.1.2 **bad_source_message()** `def bad_source_message ()`

Generates an error message if the sources provided were not images.

Returns

The "bad sources" message.

5.3.1.3 **no_args_help_message()** `def no_args_help_message ()`

Generates a help message if no arguments were presented.

Returns

The "no arguments" help message.

5.4 **pypalex.constants Namespace Reference**

Variables

- list **BLACK_RGB** = [0, 0, 0]
- list **WHITE_RGB** = [255, 255, 255]
- list **RED_RGB** = [255, 0, 0]
- list **YELLOW_RGB** = [255, 234, 0]
- list **GREEN_RGB** = [0, 255, 0]
- list **CYAN_RGB** = [0, 255, 255]
- list **BLUE_RGB** = [0, 0, 255]
- list **MAGENTA_RGB** = [255, 0, 255]
- int **BLACK_HEX** = 0x000000
- int **WHITE_HEX** = 0xFFFFFF
- int **RED_HEX** = 0xFF0000
- int **YELLOW_HEX** = 0xFFEA00
- int **GREEN_HEX** = 0x00FF00
- int **CYAN_HEX** = 0x00FFFF
- int **BLUE_HEX** = 0x0000FF
- int **MAGENTA_HEX** = 0xFF00FF
- int **RED_HUE** = 0
- int **YELLOW_HUE** = 55
- int **GREEN_HUE** = 120

- int [CYAN_HUE](#) = 180
- int [BLUE_HUE](#) = 240
- int [MAGENTA_HUE](#) = 300
- list [RED_HUE_RANGE_MAX](#) = [330, 360]
- list [RED_HUE_RANGE_MIN](#) = [0, 25]
- list [YELLOW_HUE_RANGE](#) = [25, 64]
- list [GREEN_HUE_RANGE](#) = [64, 170]
- list [CYAN_HUE_RANGE](#) = [170, 210]
- list [BLUE_HUE_RANGE](#) = [210, 260]
- list [MAGENTA_HUE_RANGE](#) = [260, 330]
- list [BLACK_BRIGHTNESS_RANGE](#) = [0.0, 45.0]
- list [GRAY_BRIGHTNESS_RANGE](#) = [45.0, 75.0]
- list [WHITE_BRIGHTNESS_RANGE](#) = [75.0, 100.0]
- list [SATURATION_RANGE](#) = [5.0, 100.0]
- list [BRIGHTNESS_RANGE](#) = [25.0, 100.0]
- list [PASTEL_SATURATION_RANGE](#) = [10.0, 75.0]
- list [PASTEL_BRIGHTNESS_RANGE](#) = [50.0, 100.0]

5.4.1 Variable Documentation

5.4.1.1 BLACK_BRIGHTNESS_RANGE `list BLACK_BRIGHTNESS_RANGE = [0.0, 45.0]`

5.4.1.2 BLACK_HEX `int BLACK_HEX = 0x000000`

5.4.1.3 BLACK_RGB `list BLACK_RGB = [0, 0, 0]`

5.4.1.4 BLUE_HEX `int BLUE_HEX = 0x0000FF`

5.4.1.5 BLUE_HUE `int BLUE_HUE = 240`

5.4.1.6 BLUE_HUE_RANGE `list BLUE_HUE_RANGE = [210, 260]`

5.4.1.7 BLUE_RGB `list BLUE_RGB = [0, 0, 255]`

5.4.1.8 BRIGHTNESS_RANGE `list BRIGHTNESS_RANGE = [25.0, 100.0]`

5.4.1.9 CYAN_HEX `int CYAN_HEX = 0x00FFFF`

5.4.1.10 CYAN_HUE `int CYAN_HUE = 180`

5.4.1.11 CYAN_HUE_RANGE `list CYAN_HUE_RANGE = [170, 210]`

5.4.1.12 CYAN_RGB `list CYAN_RGB = [0, 255, 255]`

5.4.1.13 GRAY_BRIGHTNESS_RANGE `list GRAY_BRIGHTNESS_RANGE = [45.0, 75.0]`

5.4.1.14 GREEN_HEX `int GREEN_HEX = 0x00FF00`

5.4.1.15 GREEN_HUE `int GREEN_HUE = 120`

5.4.1.16 GREEN_HUE_RANGE `list GREEN_HUE_RANGE = [64, 170]`

5.4.1.17 GREEN_RGB `list GREEN_RGB = [0, 255, 0]`

5.4.1.18 MAGENTA_HEX `int MAGENTA_HEX = 0xFF00FF`

5.4.1.19 MAGENTA_HUE `int MAGENTA_HUE = 300`

5.4.1.20 MAGENTA_HUE_RANGE `list MAGENTA_HUE_RANGE = [260, 330]`

5.4.1.21 MAGENTA_RGB `list MAGENTA_RGB = [255, 0, 255]`

5.4.1.22 PASTEL_BRIGHTNESS_RANGE `list PASTEL_BRIGHTNESS_RANGE = [50.0, 100.0]`

5.4.1.23 PASTEL_SATURATION_RANGE `list PASTEL_SATURATION_RANGE = [10.0, 75.0]`

5.4.1.24 RED_HEX `int RED_HEX = 0xFF0000`

5.4.1.25 RED_HUE `int RED_HUE = 0`

5.4.1.26 RED_HUE_RANGE_MAX `list RED_HUE_RANGE_MAX = [330, 360]`

5.4.1.27 RED_HUE_RANGE_MIN `list RED_HUE_RANGE_MIN = [0, 25]`

5.4.1.28 RED_RGB `list RED_RGB = [255, 0, 0]`

5.4.1.29 SATURATION_RANGE `list SATURATION_RANGE = [5.0, 100.0]`

5.4.1.30 WHITE_BRIGHTNESS_RANGE `list WHITE_BRIGHTNESS_RANGE = [75.0, 100.0]`

5.4.1.31 WHITE_HEX `int WHITE_HEX = 0xFFFFFF`

5.4.1.32 WHITE_RGB `list WHITE_RGB = [255, 255, 255]`

5.4.1.33 YELLOW_HEX `int YELLOW_HEX = 0xFFEA00`

5.4.1.34 YELLOW_HUE `int YELLOW_HUE = 55`

5.4.1.35 YELLOW_HUE_RANGE `list YELLOW_HUE_RANGE = [25, 64]`

5.4.1.36 YELLOW_RGB `list YELLOW_RGB = [255, 234, 0]`

5.5 pypalex.conversion_utils Namespace Reference

Functions

- `def rgb_to_hsv (rgb_array)`
Converts RGB array [r,g,b] to HSV array [h,s,v].
- `def hsv_to_hex (hsv_array)`
Convert HSV array [h,s,v] to HEX string 'ffffff'.
- `def hsv_to_rgb (hsv_array)`
Convert HSV array [h,s,v] to RGB array [r,g,b].
- `def rgb_to_hex (rgb_array)`
Convert RGB array [r,g,b] to HEX string 'ffffff'.

5.5.1 Function Documentation

5.5.1.1 [hsv_to_hex\(\)](#) `def hsv_to_hex (
 hsv_array)`

Convert HSV array [h,s,v] to HEX string 'ffffff'.

HSV where h is in the set [0, 359] and s, v are in the set [0.0, 100.0]. HEX string is in the set ["000000", "ffffff"].

Parameters

<i>hsv_array</i>	HSV array [h,s,v].
------------------	--------------------

Returns

A HEX string.

5.5.1.2 hsv_to_rgb() `def hsv_to_rgb (`
`hsv_array)`

Convert HSV array [h,s,v] to RGB array [r,g,b].

HSV where h is in the set [0, 359] and s, v are in the set [0.0, 100.0]. RGB where [r,g,b] are in the set [0, 255].
Formula adapted from <https://www.rapidtables.com/convert/color/hsv-to-rgb.html>

Parameters

<i>hsv_array</i>	HSV array [h,s,v].
------------------	--------------------

Returns

RGB array [r,g,b].

5.5.1.3 rgb_to_hex() `def rgb_to_hex (`
`rgb_array)`

Convert RGB array [r,g,b] to HEX string 'ffffff'.

RGB where [r,g,b] are in the set [0, 255]. HEX string is in the set ["000000", "ffffff"].

Parameters

<i>rgb_array</i>	RGB array [r,g,b].
------------------	--------------------

Returns

A HEX string.

5.5.1.4 rgb_to_hsv() `def rgb_to_hsv (`
`rgb_array)`

Converts RGB array [r,g,b] to HSV array [h,s,v].

RGB where [r,g,b] are in the set [0, 255]. HSV where h is in the set [0, 359] and s, v are in the set [0.0, 100.0].
Formula adapted from <https://www.rapidtables.com/convert/color/rgb-to-hsv.html>

Parameters

<code>rgb_array</code>	RGB array [r,g,b].
------------------------	--------------------

Returns

HSV array [h,s,v].

5.6 pypalex.extraction_utils Namespace Reference

Functions

- def [extract_ratios](#) (hsv_img_matrix_2d)
Extracts the ratios of hues per pixel.
- def [construct_base_color_dictionary](#) (hsv_img_matrix_2d)
Constructs dictionary of base colors from an array of HSV pixel values.
- def [extract_colors](#) (base_color_dict)
Extracts dominant light, normal, dark colors types from each of the base colors.
- def [check_missing_colors](#) (base_color_dict, extracted_colors_dict)
Checks for any missing colors in the base color dictionary and borrows them from the surrounding colors.
- def [generate_remaining_colors](#) (extracted_colors_dict, ratios)
Generate the remaining black and white, and background and foreground colors.
- def [extract_color_types](#) (hsv_base_color_matrix)
Extracts the dominant color types from a base color.
- def [get_left_and_right_colors](#) (origin_color_name)
Gets the color names of the colors that are to the left and right of the originating color.
- def [borrow_color](#) (extracted_colors_dict, origin, borrow_left, borrow_right)
Borrows a color from one of the extracted color types of the base colors.
- def [get_dominant_hue](#) (extracted_colors_dict, ratios)
Calculates the dominant hue.
- def [generate_black_and_white](#) (dominant_hue)
Generates black and white color types using the dominant hue.
- def [generate_background_and_foreground](#) (dominant_hue, complementary_hue)
Generates the background and foreground colors.
- def [sort_by_bright_value](#) (hsv_base_color_matrix)
Sorts the colors by the brightness value.
- def [extract_dominant_color](#) (hsv_color_type_matrix)
Extracts the dominant color from a color type.
- def [check_missing_color_types](#) (light_color, norm_color, dark_color)
Checks to make sure all the color types have been properly set by.
- def [check_sat_and_bright](#) (hsv_color)
Normalize saturation and brightness value.
- def [calculate_centroid](#) (hsv_color_type_matrix)
Calculates the centroid for a color type.
- def [find_closest_to_centroid](#) (hsv_color_type_matrix, centroid)
Finds a color from a color type that is closest to the centroid.

5.6.1 Function Documentation

5.6.1.1 borrow_color() `def borrow_color (`
 extracted_colors_dict,
 origin,
 borrow_left,
 borrow_right)

Borrows a color from one of the extracted color types of the base colors.

Parameters

<i>extracted_colors_dict</i>	A Dictionary of extracted colors.
<i>origin</i>	The name of the originating color.
<i>borrow_left</i>	The name of the color to borrow from, to the left of origin.
<i>borrow_right</i>	The name of the color to borrow from, to the right of origin.

Returns

A numpy array of a borrowed color.

5.6.1.2 calculate_centroid() `def calculate_centroid (`
 hsv_color_type_matrix)

Calculates the centroid for a color type.

The centroid is basically the average color of a set of colors in [h,s,v] format. The centroid is a point in 3-dimensional space. The following sources were used to make this algorithm: <http://mkweb.bcgsc.ca/color-summarizer/?faq#averagehue> and <https://stackoverflow.com/a/8170595/17047816>

Parameters

<i>hsv_color_type_matrix</i>	A 2D numpy array of a color type in [h,s,v] format.
------------------------------	---

Returns

List of centroid color values in [h,s,l] format.

5.6.1.3 check_missing_color_types() `def check_missing_color_types (`
 light_color,
 norm_color,
 dark_color)

Checks to make sure all the color types have been properly set by.

If a color type is missing, then it will be derived from the existing color types.

Parameters

<i>light_color</i>	A numpy array of a light color type in [h,s,v] format.
<i>norm_color</i>	A numpy array of a normal color type in [h,s,v] format.
<i>dark_color</i>	A numpy array of a dark color type in [h,s,v] format.

5.6.1.4 check_missing_colors() `def check_missing_colors (`
 base_color_dict,
 extracted_colors_dict)

Checks for any missing colors in the base color dictionary and borrows them from the surrounding colors.

Parameters

<i>base_color_dict</i>	A dictionary of 2D numpy arrays for each of the base colors.
<i>extracted_colors_dict</i>	A Dictionary of extracted colors.

5.6.1.5 check_sat_and_bright() `def check_sat_and_bright (`
 hsv_color)

Normalize saturation and brightness value.

The normalization process is to make sure that colors are visible, distinguishable and tolerable to look at. These ranges for saturation and brightness values are defined in [constants.py](#). This step can be removed if it is not needed as it does not impact the extraction process.

Parameters

<i>hsv_color</i>	A numpy array of a color type in [h,s,v] format.
------------------	--

5.6.1.6 construct_base_color_dictionary() `def construct_base_color_dictionary (`
 hsv_img_matrix_2d)

Constructs dictionary of base colors from an array of HSV pixel values.

Base colors are classified as [red, yellow, green, cyan, blue, magenta].

Parameters

<i>hsv_img_matrix_2d</i>	A 2D numpy array of pixels from an image, in [h,s,v] format.
--------------------------	--

Returns

Dictionary of base colors.

5.6.1.7 extract_color_types() `def extract_color_types (`
`hsv_base_color_matrix)`

Extracts the dominant color types from a base color.

A color type is either a light, normal, or dark version of one of the base colors.

Parameters

<i>hsv_base_color_matrix</i>	A 2D numpy array of a base color in [h,s,v] format.
------------------------------	---

Returns

List of dominant numpy array color types in [h,s,v] format.

5.6.1.8 extract_colors() `def extract_colors (`
`base_color_dict)`

Extracts dominant light, normal, dark colors types from each of the base colors.

Parameters

<i>base_color_dict</i>	A dictionary of 2D numpy arrays for each of the base colors.
------------------------	--

Returns

Dictionary of light, normal, dark color types for each of the base colors.

5.6.1.9 extract_dominant_color() `def extract_dominant_color (`
`hsv_color_type_matrix)`

Extracts the dominant color from a color type.

A color type is either a light, normal, or dark version of one of the base colors.

Parameters

<i>hsv_color_type_matrix</i>	A 2D numpy array of a color type in [h,s,v] format.
------------------------------	---

Returns

A numpy array of a dominant color from a color type in [h,s,v] format.

5.6.1.10 extract_ratios() `def extract_ratios (`
 hsv_img_matrix_2d `)`

Extracts the ratios of hues per pixel.

Parameters

<i>hsv_img_matrix_2d</i>	A 2D numpy array of pixels from an image in [h,s,v] format.
--------------------------	---

Returns

Dictionary of hue ratios (percentage) in set [0.0, 100.0]

5.6.1.11 find_closest_to_centroid() `def find_closest_to_centroid (`
 hsv_color_type_matrix,
 centroid `)`

Finds a color from a color type that is closest to the centroid.

The distance between the centroid color and the other colors of the color type are calculated in 3-dimensional space using formulas from the following sources: <https://stackoverflow.com/a/35114586/17047816> and <https://byjus.com/maths/distance-between-two-points-3d/>

Parameters

<i>hsv_color_type_matrix</i>	A 2D numpy array of a color type in [h,s,v] format.
<i>centroid</i>	List of centroid color values in [h,s,l] format.

Returns

List of all the colors in [h,s,v] format that are the shortest distance away from the centroid.

5.6.1.12 generate_background_and_foreground() `def generate_background_and_foreground (`
 dominant_hue,
 complementary_hue `)`

Generates the background and foreground colors.

The background and foreground colors are based on the dominant hue in an image and it's complimentary hue. The saturation and brightness values for the background and foreground colors need to be hardcoded to be easier to look at.

Parameters

<i>dominant_hue</i>	The dominant hue of an image.
<i>complementary_hue</i>	The complimentary hue to the dominant hue.

Returns

Numpy array of light and dark background and foreground colors in [h,s,v] format.

5.6.1.13 generate_black_and_white() `def generate_black_and_white (`
`dominant_hue)`

Generates black and white color types using the dominant hue.

The saturation and brightness values, for the black and white color types, needs to be hardcoded in order to not interfere with the background and foreground colors.

Parameters

<i>dominant_hue</i>	The dominant hue of an image.
---------------------	-------------------------------

Returns

List of black and white color types in [h,s,v] format.

5.6.1.14 generate_remaining_colors() `def generate_remaining_colors (`
`extracted_colors_dict,`
`ratios)`

Generate the remaining black and white, and background and foreground colors.

Parameters

<i>extracted_colors_dict</i>	A Dictionary of extracted colors.
<i>ratios</i>	A Dictionary of ratios of the base colors in the image.

5.6.1.15 get_dominant_hue() `def get_dominant_hue (`
`extracted_colors_dict,`
`ratios)`

Calculates the dominant hue.

The dominant hue, also referred to as the average hue, is based on the color ratios and the colors extracted from an image.

Parameters

<i>extracted_colors_dict</i>	A Dictionary of extracted colors.
<i>ratios</i>	A Dictionary of ratios of the base colors in the image.

Returns

The dominant hue in an image.

5.6.1.16 get_left_and_right_colors() `def get_left_and_right_colors (`
 origin_color_name)

Gets the color names of the colors that are to the left and right of the originating color.

There are two ways to think about left and right on a color wheel: from the inside looking outward and from the outside looking inward. This has an effect on how we think of the linear format of the color wheel. For this package we will think about left and right colors using the latter option.

Parameters

<i>origin_color_name</i>	The name of the originating color.
--------------------------	------------------------------------

Returns

List of color names that are to the left and right of the originating color.

5.6.1.17 sort_by_bright_value() `def sort_by_bright_value (`
 hsv_base_color_matrix)

Sorts the colors by the brightness value.

A color type is either a light, normal, or dark version of one of the base colors.

Parameters

<i>hsv_base_color_matrix</i>	A 2D numpy array of a base color in [h,s,v] format.
------------------------------	---

Returns

List of numpy array color types in [h,s,v] format.

5.7 pypalex.Extractor Namespace Reference

Classes

- class [Extractor](#)

Extracts colors given a matrix of HSV values extracted from an image.

5.8 pypalex.image_utils Namespace Reference

Functions

- def `process_image` (image)
Processes PIL Image object.
- def `save_palette_to_file` (color_palette, output_filepath)
Saves color palette to json file.
- def `rescale_image` (image)
Rescales image to a smaller sampling size.
- def `process_helper` (rgb_matrix_2d)
Helper function for multiprocessing conversion operations.

5.8.1 Function Documentation

5.8.1.1 `process_helper()`

```
def process_helper (  
    rgb_matrix_2d )
```

Helper function for multiprocessing conversion operations.

Helps convert from [r,g,b] to [h,s,v].

Parameters

<code>rgb_matrix_2d</code>	A 2D matrix of rgb values.
----------------------------	----------------------------

Returns

A numpy array/2D matrix of converted [h,s,v] values.

5.8.1.2 `process_image()`

```
def process_image (  
    image )
```

Processes PIL Image object.

Multiprocessing example from: <https://stackoverflow.com/a/45555516>

Parameters

<code>image</code>	PIL Image object.
--------------------	-------------------

Returns

2D numpy array of [h,s,v] arrays (pixels) from image.

5.8.1.3 rescale_image() `def rescale_image (`
 image)

Rescales image to a smaller sampling size.

Parameters

<i>image</i>	PIL Image object.
--------------	-------------------

Returns

Tuple of the new width and height of image.

5.8.1.4 save_palette_to_file() `def save_palette_to_file (`
 color_palette,
 output_filepath)

Saves color palette to json file.

If a file with the same name already exists, it is overwritten.

Parameters

<i>color_palette</i>	Dictionary of light, normal, and dark color palettes.
<i>output_filepath</i>	Output file path with filename of where to store color palette.

6 Class Documentation

6.1 Extractor Class Reference

Extracts colors given a matrix of HSV values extracted from an image.

Public Member Functions

- `def __init__ (self, hsv_img_matrix_2d, output_filepath, pastel=False, pastel_light=False, pastel_normal=False, pastel_dark=False)`
 Extractor Constructor.
- `def run (self)`

Main method for [Extractor](#) class.

- `def check_pastel_conversion (self)`
Checks to see if any of the palettes should be converted to pastel.
- `def construct_palette_dictionary (self)`
Constructs color palette dictionary.
- `def convert_pastel_light (self)`
Converts light palette to pastel.
- `def convert_pastel_normal (self)`
Converts normal palette to pastel.
- `def convert_pastel_dark (self)`
Converts dark palette to pastel.
- `def convert_pastel (self, hsv_color)`
Converts/normalizes HSV color to pastel.

Public Attributes

- `hsv_img_matrix_2d`
A 2D numpy array of pixels from an image in [h,s,v] format.
- `output_filepath`
Output file path with filename of where to store color palette.
- `pastel`
Flag to convert all extracted color types to pastel.
- `pastel_light`
Flag to convert light colors to pastel.
- `pastel_normal`
Flag to convert normal colors to pastel.
- `pastel_dark`
Flag to convert dark colors to pastel.
- `ratio_dict`
A dictionary that holds the ratio of base colors in an image and is used to identify the dominant color in an image.
- `base_color_dict`
A dictionary of 2D numpy arrays for each of the 6 base colors.
- `extracted_colors_dict`
A Dictionary of extracted colors in [h,s,v] format.
- `color_palette_dict`
A Dictionary of dictionaries for light and dark color schemes that are in HEX string format.

6.1.1 Detailed Description

Extracts colors given a matrix of HSV values extracted from an image.

6.1.2 Constructor & Destructor Documentation

```
6.1.2.1  __init__()  def __init__ (  
                self,  
                hsv_img_matrix_2d,  
                output_filepath,  
                pastel = False,  
                pastel_light = False,  
                pastel_normal = False,  
                pastel_dark = False )
```

[Extractor](#) Constructor.

Parameters

<i>self</i>	The object pointer.
<i>hsv_img_matrix_2d</i>	A 2D numpy array of pixels from an image in [h,s,v] format.
<i>output_filepath</i>	Output file path with filename of where to store color palette.
<i>pastel</i>	Flag to convert all extracted color types to pastel.
<i>pastel_light</i>	Flag to convert light colors to pastel.
<i>pastel_normal</i>	Flag to convert normal colors to pastel.
<i>pastel_dark</i>	Flag to convert dark colors to pastel.

6.1.3 Member Function Documentation**6.1.3.1 check_pastel_conversion()**

```
def check_pastel_conversion (
    self )
```

Checks to see if any of the palettes should be converted to pastel.

Parameters

<i>self</i>	The object pointer.
-------------	---------------------

6.1.3.2 construct_palette_dictionary()

```
def construct_palette_dictionary (
    self )
```

Constructs color palette dictionary.

Parameters

<i>self</i>	The object pointer.
-------------	---------------------

6.1.3.3 convert_pastel()

```
def convert_pastel (
    self,
    hsv_color )
```

Converts/normalizes HSV color to pastel.

For values x in range $[a, b]$, values x can be converted to the new range $[y, z]$ with the following equation: $\text{new_x} = (z - y) * ((x - a) / (b - a)) + y$

Parameters

<i>self</i>	The object pointer.
<i>hsv_color</i>	List HSV color to be converted to pastel.

6.1.3.4 convert_pastel_dark() `def convert_pastel_dark (`
`self)`

Converts dark palette to pastel.

Parameters

<i>self</i>	The object pointer.
-------------	---------------------

6.1.3.5 convert_pastel_light() `def convert_pastel_light (`
`self)`

Converts light palette to pastel.

Parameters

<i>self</i>	The object pointer.
-------------	---------------------

6.1.3.6 convert_pastel_normal() `def convert_pastel_normal (`
`self)`

Converts normal palette to pastel.

Parameters

<i>self</i>	The object pointer.
-------------	---------------------

6.1.3.7 run() `def run (`
`self)`

Main method for [Extractor](#) class.

Performs extraction of colors.

Parameters

<i>self</i>	The object pointer.
-------------	---------------------

6.1.4 Member Data Documentation**6.1.4.1 base_color_dict** `base_color_dict`

A dictionary of 2D numpy arrays for each of the 6 base colors.

6.1.4.2 color_palette_dict `color_palette_dict`

A Dictionary of dictionaries for light and dark color schemes that are in HEX string format.

6.1.4.3 extracted_colors_dict `extracted_colors_dict`

A Dictionary of extracted colors in [h,s,v] format.

6.1.4.4 hsv_img_matrix_2d `hsv_img_matrix_2d`

A 2D numpy array of pixels from an image in [h,s,v] format.

6.1.4.5 output_filepath `output_filepath`

Output file path with filename of where to store color palette.

6.1.4.6 pastel `pastel`

Flag to convert all extracted color types to pastel.

6.1.4.7 pastel_dark `pastel_dark`

Flag to convert dark colors to pastel.

6.1.4.8 `pastel_light` `pastel_light`

Flag to convert light colors to pastel.

6.1.4.9 `pastel_normal` `pastel_normal`

Flag to convert normal colors to pastel.

6.1.4.10 `ratio_dict` `ratio_dict`

A dictionary that holds the ratio of base colors in an image and is used to identify the dominant color in an image.

The documentation for this class was generated from the following file:

- [Extractor.py](#)

7 File Documentation

7.1 `__main__.py` File Reference

Main script for PyPalEx.

Namespaces

- namespace `pypalex`
Python Palette [Extractor](#): extracts color palettes from images.
- namespace `pypalex.__main__`

Functions

- def `main` ()
Main script function.
- def `handle_args` ()
Handles the arguments passed to PyPalEx.
- def `extract_color_palettes` ()
Handles color extraction from image(s).
- def `setup_argument_parser` ()
Sets up the argument parser for command line arguments.
- def `check_sources` (filepaths, path=None)
Checks each of the sources provided and removes any bad sources.
- def `check_path` (path)
Check the path to make sure it exists.
- def `set_global_args` (args)
Sets the global variables using the arguments.
- def `check_source` (filepath)
Checks to make sure the path leads to a file.

Variables

- list `EXTRACTORS` = []
List of `Extractor` class objects for each individual image.
- list `PROPER_IMAGES` = []
List of real/existing image file path(s).
- list `FILENAMES` = []
List of image filenames.
- list `OUTPUT_FILEPATHS` = []
List of output file path(s) for each image.
- string `OUTPUT_PATH` = "
The path to the output directory where all JSON files will be saved.
- string `OUTPUT_TAIL` = "-color_palette.json"
The tail to append to each output filepath.
- bool `PASTEL` = False
Flag for pastel option.
- bool `PASTEL_L` = False
Flag for light pastel option.
- bool `PASTEL_N` = False
Flag for normal pastel option.
- bool `PASTEL_D` = False
Flag for dark pastel option.

7.1.1 Detailed Description

Main script for PyPalEx.

Used to run from the Command Line.

7.1.2 Author(s)

- Created by Al Timofeyev on February 2, 2022.
- Modified by Al Timofeyev on April 21, 2022.
- Modified by Al Timofeyev on March 6, 2023.

7.2 `arg_messages.py` File Reference

Archive of messages to display for arguments supplied by user.

Namespaces

- namespace `pypalex`
Python Palette `Extractor`: extracts color palettes from images.
- namespace `pypalex.arg_messages`

Functions

- def `bad_source_message ()`
Generates an error message if the sources provided were not images.
- def `bad_path_message ()`
Generates an error message if the directory provided is not a valid directory.
- def `no_args_help_message ()`
Generates a help message if no arguments were presented.

7.2.1 Detailed Description

Archive of messages to display for arguments supplied by user.

7.2.2 Author(s)

- Created by AI Timofeyev on March 3, 2022.
- Modified by AI Timofeyev on April 21, 2022.
- Modified by AI Timofeyev on March 6, 2023.

7.3 constants.py File Reference

A collection of constants for PyPalEx.

Namespaces

- namespace `pypalex`
Python Palette [Extractor](#): extracts color palettes from images.
- namespace `pypalex.constants`

Variables

- list `BLACK_RGB` = [0, 0, 0]
- list `WHITE_RGB` = [255, 255, 255]
- list `RED_RGB` = [255, 0, 0]
- list `YELLOW_RGB` = [255, 234, 0]
- list `GREEN_RGB` = [0, 255, 0]
- list `CYAN_RGB` = [0, 255, 255]
- list `BLUE_RGB` = [0, 0, 255]
- list `MAGENTA_RGB` = [255, 0, 255]
- int `BLACK_HEX` = 0x000000
- int `WHITE_HEX` = 0xFFFFFF
- int `RED_HEX` = 0xFF0000
- int `YELLOW_HEX` = 0xFFEA00
- int `GREEN_HEX` = 0x00FF00
- int `CYAN_HEX` = 0x00FFFF
- int `BLUE_HEX` = 0x0000FF
- int `MAGENTA_HEX` = 0xFF00FF

- int `RED_HUE` = 0
- int `YELLOW_HUE` = 55
- int `GREEN_HUE` = 120
- int `CYAN_HUE` = 180
- int `BLUE_HUE` = 240
- int `MAGENTA_HUE` = 300
- list `RED_HUE_RANGE_MAX` = [330, 360]
- list `RED_HUE_RANGE_MIN` = [0, 25]
- list `YELLOW_HUE_RANGE` = [25, 64]
- list `GREEN_HUE_RANGE` = [64, 170]
- list `CYAN_HUE_RANGE` = [170, 210]
- list `BLUE_HUE_RANGE` = [210, 260]
- list `MAGENTA_HUE_RANGE` = [260, 330]
- list `BLACK_BRIGHTNESS_RANGE` = [0.0, 45.0]
- list `GRAY_BRIGHTNESS_RANGE` = [45.0, 75.0]
- list `WHITE_BRIGHTNESS_RANGE` = [75.0, 100.0]
- list `SATURATION_RANGE` = [5.0, 100.0]
- list `BRIGHTNESS_RANGE` = [25.0, 100.0]
- list `PASTEL_SATURATION_RANGE` = [10.0, 75.0]
- list `PASTEL_BRIGHTNESS_RANGE` = [50.0, 100.0]

7.3.1 Detailed Description

A collection of constants for PyPalEx.

7.3.2 Author(s)

- Created by Al Timofeyev on February 2, 2022.
- Modified by Al Timofeyev on April 21, 2022.
- Modified by Al Timofeyev on March 6, 2023.

7.4 `conversion_utils.py` File Reference

Utilities for converting between RGB, HSV, HEX.

Namespaces

- namespace `pypalex`
Python Palette [Extractor](#): extracts color palettes from images.
- namespace `pypalex.conversion_utils`

Functions

- def `rgb_to_hsv` (rgb_array)
Converts RGB array [r,g,b] to HSV array [h,s,v].
- def `hsv_to_hex` (hsv_array)
Convert HSV array [h,s,v] to HEX string 'ffffff'.
- def `hsv_to_rgb` (hsv_array)
Convert HSV array [h,s,v] to RGB array [r,g,b].
- def `rgb_to_hex` (rgb_array)
Convert RGB array [r,g,b] to HEX string 'ffffff'.

7.4.1 Detailed Description

Utilities for converting between RGB, HSV, HEX.

7.4.2 Author(s)

- Created by AI Timofeyev on February 2, 2022.
- Modified by AI Timofeyev on April 21, 2022.
- Modified by AI Timofeyev on March 6, 2023.

7.5 extraction_utils.py File Reference

Utilities for extracting colors from the image.

Namespaces

- namespace [pypalex](#)
Python Palette [Extractor](#): extracts color palettes from images.
- namespace [pypalex.extraction_utils](#)

Functions

- def [extract_ratios](#) (hsv_img_matrix_2d)
Extracts the ratios of hues per pixel.
- def [construct_base_color_dictionary](#) (hsv_img_matrix_2d)
Constructs dictionary of base colors from an array of HSV pixel values.
- def [extract_colors](#) (base_color_dict)
Extracts dominant light, normal, dark colors types from each of the base colors.
- def [check_missing_colors](#) (base_color_dict, extracted_colors_dict)
Checks for any missing colors in the base color dictionary and borrows them from the surrounding colors.
- def [generate_remaining_colors](#) (extracted_colors_dict, ratios)
Generate the remaining black and white, and background and foreground colors.
- def [extract_color_types](#) (hsv_base_color_matrix)
Extracts the dominant color types from a base color.
- def [get_left_and_right_colors](#) (origin_color_name)
Gets the color names of the colors that are to the left and right of the originating color.
- def [borrow_color](#) (extracted_colors_dict, origin, borrow_left, borrow_right)
Borrows a color from one of the extracted color types of the base colors.
- def [get_dominant_hue](#) (extracted_colors_dict, ratios)
Calculates the dominant hue.
- def [generate_black_and_white](#) (dominant_hue)
Generates black and white color types using the dominant hue.
- def [generate_background_and_foreground](#) (dominant_hue, complementary_hue)
Generates the background and foreground colors.
- def [sort_by_bright_value](#) (hsv_base_color_matrix)
Sorts the colors by the brightness value.

- def [extract_dominant_color](#) (hsv_color_type_matrix)
Extracts the dominant color from a color type.
- def [check_missing_color_types](#) (light_color, norm_color, dark_color)
Checks to make sure all the color types have been properly set by.
- def [check_sat_and_bright](#) (hsv_color)
Normalize saturation and brightness value.
- def [calculate_centroid](#) (hsv_color_type_matrix)
Calculates the centroid for a color type.
- def [find_closest_to_centroid](#) (hsv_color_type_matrix, centroid)
Finds a color from a color type that is closest to the centroid.

7.5.1 Detailed Description

Utilities for extracting colors from the image.

7.5.2 Author(s)

- Created by Al Timofeyev on February 10, 2022.
- Modified by Al Timofeyev on April 21, 2022.
- Modified by Al Timofeyev on March 6, 2023.

7.6 Extractor.py File Reference

Extraction utility class for extracting colors from the image.

Classes

- class [Extractor](#)
Extracts colors given a matrix of HSV values extracted from an image.

Namespaces

- namespace [pypalex](#)
Python Palette [Extractor](#): extracts color palettes from images.
- namespace [pypalex.Extractor](#)

7.6.1 Detailed Description

Extraction utility class for extracting colors from the image.

7.6.2 Author(s)

- Created by Al Timofeyev on February 10, 2022.
- Modified by Al Timofeyev on April 21, 2022.
- Modified by Al Timofeyev on March 6, 2023.

7.7 image_utils.py File Reference

Utilities for processing image and file handling.

Namespaces

- namespace [pypalex](#)
Python Palette [Extractor](#): extracts color palettes from images.
- namespace [pypalex.image_utils](#)

Functions

- def [process_image](#) (image)
Processes PIL Image object.
- def [save_palette_to_file](#) (color_palette, output_filepath)
Saves color palette to json file.
- def [rescale_image](#) (image)
Rescales image to a smaller sampling size.
- def [process_helper](#) (rgb_matrix_2d)
Helper function for multiprocessing conversion operations.

7.7.1 Detailed Description

Utilities for processing image and file handling.

7.7.2 Author(s)

- Created by AI Timofeyev on February 27, 2022.
- Modified by AI Timofeyev on April 21, 2022.
- Modified by AI Timofeyev on March 6, 2023.

Index

- [__init__](#)
 - [Extractor](#), [24](#)
- [__main__.py](#), [29](#)
- [arg_messages.py](#), [30](#)
- [bad_path_message](#)
 - [pypalex.arg_messages](#), [7](#)
- [bad_source_message](#)
 - [pypalex.arg_messages](#), [8](#)
- [base_color_dict](#)
 - [Extractor](#), [28](#)
- [BLACK_BRIGHTNESS_RANGE](#)
 - [pypalex.constants](#), [9](#)
- [BLACK_HEX](#)
 - [pypalex.constants](#), [9](#)
- [BLACK_RGB](#)
 - [pypalex.constants](#), [9](#)
- [BLUE_HEX](#)
 - [pypalex.constants](#), [9](#)
- [BLUE_HUE](#)
 - [pypalex.constants](#), [9](#)
- [BLUE_HUE_RANGE](#)
 - [pypalex.constants](#), [9](#)
- [BLUE_RGB](#)
 - [pypalex.constants](#), [9](#)
- [borrow_color](#)
 - [pypalex.extraction_utils](#), [15](#)
- [BRIGHTNESS_RANGE](#)
 - [pypalex.constants](#), [10](#)
- [calculate_centroid](#)
 - [pypalex.extraction_utils](#), [16](#)
- [check_missing_color_types](#)
 - [pypalex.extraction_utils](#), [16](#)
- [check_missing_colors](#)
 - [pypalex.extraction_utils](#), [17](#)
- [check_pastel_conversion](#)
 - [Extractor](#), [26](#)
- [check_path](#)
 - [pypalex.__main__](#), [4](#)
- [check_sat_and_bright](#)
 - [pypalex.extraction_utils](#), [17](#)
- [check_source](#)
 - [pypalex.__main__](#), [4](#)
- [check_sources](#)
 - [pypalex.__main__](#), [5](#)
- [color_palette_dict](#)
 - [Extractor](#), [28](#)
- [constants.py](#), [31](#)
- [construct_base_color_dictionary](#)
 - [pypalex.extraction_utils](#), [17](#)
- [construct_palette_dictionary](#)
 - [Extractor](#), [26](#)
- [conversion_utils.py](#), [32](#)
- [convert_pastel](#)
 - [Extractor](#), [26](#)
- [convert_pastel_dark](#)
 - [Extractor](#), [27](#)
- [convert_pastel_light](#)
 - [Extractor](#), [27](#)
- [convert_pastel_normal](#)
 - [Extractor](#), [27](#)
- [CYAN_HEX](#)
 - [pypalex.constants](#), [10](#)
- [CYAN_HUE](#)
 - [pypalex.constants](#), [10](#)
- [CYAN_HUE_RANGE](#)
 - [pypalex.constants](#), [10](#)
- [CYAN_RGB](#)
 - [pypalex.constants](#), [10](#)
- [extract_color_palettes](#)
 - [pypalex.__main__](#), [5](#)
- [extract_color_types](#)
 - [pypalex.extraction_utils](#), [18](#)
- [extract_colors](#)
 - [pypalex.extraction_utils](#), [18](#)
- [extract_dominant_color](#)
 - [pypalex.extraction_utils](#), [18](#)
- [extract_ratios](#)
 - [pypalex.extraction_utils](#), [19](#)
- [extracted_colors_dict](#)
 - [Extractor](#), [28](#)
- [extraction_utils.py](#), [33](#)
- [Extractor](#), [23](#)
 - [__init__](#), [24](#)
 - [base_color_dict](#), [28](#)
 - [check_pastel_conversion](#), [26](#)
 - [color_palette_dict](#), [28](#)
 - [construct_palette_dictionary](#), [26](#)
 - [convert_pastel](#), [26](#)
 - [convert_pastel_dark](#), [27](#)
 - [convert_pastel_light](#), [27](#)
 - [convert_pastel_normal](#), [27](#)
 - [extracted_colors_dict](#), [28](#)
 - [hsv_img_matrix_2d](#), [28](#)
 - [output_filepath](#), [28](#)
 - [pastel](#), [28](#)
 - [pastel_dark](#), [28](#)
 - [pastel_light](#), [28](#)
 - [pastel_normal](#), [29](#)
 - [ratio_dict](#), [29](#)
 - [run](#), [27](#)
- [Extractor.py](#), [34](#)
- [EXTRACTORS](#)
 - [pypalex.__main__](#), [6](#)
- [FILENAMES](#)
 - [pypalex.__main__](#), [6](#)
- [find_closest_to_centroid](#)
 - [pypalex.extraction_utils](#), [19](#)

- generate_background_and_foreground
 - pypalex.extraction_utils, 19
- generate_black_and_white
 - pypalex.extraction_utils, 20
- generate_remaining_colors
 - pypalex.extraction_utils, 20
- get_dominant_hue
 - pypalex.extraction_utils, 20
- get_left_and_right_colors
 - pypalex.extraction_utils, 21
- GRAY_BRIGHTNESS_RANGE
 - pypalex.constants, 10
- GREEN_HEX
 - pypalex.constants, 10
- GREEN_HUE
 - pypalex.constants, 10
- GREEN_HUE_RANGE
 - pypalex.constants, 10
- GREEN_RGB
 - pypalex.constants, 10
- handle_args
 - pypalex.__main__, 5
- hsv_img_matrix_2d
 - Extractor, 28
- hsv_to_hex
 - pypalex.conversion_utils, 12
- hsv_to_rgb
 - pypalex.conversion_utils, 13
- image_utils.py, 35
- MAGENTA_HEX
 - pypalex.constants, 10
- MAGENTA_HUE
 - pypalex.constants, 11
- MAGENTA_HUE_RANGE
 - pypalex.constants, 11
- MAGENTA_RGB
 - pypalex.constants, 11
- main
 - pypalex.__main__, 5
- no_args_help_message
 - pypalex.arg_messages, 8
- output_filepath
 - Extractor, 28
- OUTPUT_FILEPATHS
 - pypalex.__main__, 6
- OUTPUT_PATH
 - pypalex.__main__, 6
- OUTPUT_TAIL
 - pypalex.__main__, 6
- PASTEL
 - pypalex.__main__, 6
- pastel
 - Extractor, 28
- PASTEL_BRIGHTNESS_RANGE
 - pypalex.constants, 11
- PASTEL_D
 - pypalex.__main__, 7
- pastel_dark
 - Extractor, 28
- PASTEL_L
 - pypalex.__main__, 7
- pastel_light
 - Extractor, 28
- PASTEL_N
 - pypalex.__main__, 7
- pastel_normal
 - Extractor, 29
- PASTEL_SATURATION_RANGE
 - pypalex.constants, 11
- process_helper
 - pypalex.image_utils, 22
- process_image
 - pypalex.image_utils, 22
- PROPER_IMAGES
 - pypalex.__main__, 7
- pypalex, 2
- pypalex.__main__, 3
 - check_path, 4
 - check_source, 4
 - check_sources, 5
 - extract_color_palettes, 5
 - EXTRACTORS, 6
 - FILENAMES, 6
 - handle_args, 5
 - main, 5
 - OUTPUT_FILEPATHS, 6
 - OUTPUT_PATH, 6
 - OUTPUT_TAIL, 6
 - PASTEL, 6
 - PASTEL_D, 7
 - PASTEL_L, 7
 - PASTEL_N, 7
 - PROPER_IMAGES, 7
 - set_global_args, 5
 - setup_argument_parser, 6
- pypalex.arg_messages, 7
 - bad_path_message, 7
 - bad_source_message, 8
 - no_args_help_message, 8
- pypalex.constants, 8
 - BLACK_BRIGHTNESS_RANGE, 9
 - BLACK_HEX, 9
 - BLACK_RGB, 9
 - BLUE_HEX, 9
 - BLUE_HUE, 9
 - BLUE_HUE_RANGE, 9
 - BLUE_RGB, 9
 - BRIGHTNESS_RANGE, 10
 - CYAN_HEX, 10
 - CYAN_HUE, 10
 - CYAN_HUE_RANGE, 10
 - CYAN_RGB, 10

- GRAY_BRIGHTNESS_RANGE, [10](#)
- GREEN_HEX, [10](#)
- GREEN_HUE, [10](#)
- GREEN_HUE_RANGE, [10](#)
- GREEN_RGB, [10](#)
- MAGENTA_HEX, [10](#)
- MAGENTA_HUE, [11](#)
- MAGENTA_HUE_RANGE, [11](#)
- MAGENTA_RGB, [11](#)
- PASTEL_BRIGHTNESS_RANGE, [11](#)
- PASTEL_SATURATION_RANGE, [11](#)
- RED_HEX, [11](#)
- RED_HUE, [11](#)
- RED_HUE_RANGE_MAX, [11](#)
- RED_HUE_RANGE_MIN, [11](#)
- RED_RGB, [11](#)
- SATURATION_RANGE, [11](#)
- WHITE_BRIGHTNESS_RANGE, [12](#)
- WHITE_HEX, [12](#)
- WHITE_RGB, [12](#)
- YELLOW_HEX, [12](#)
- YELLOW_HUE, [12](#)
- YELLOW_HUE_RANGE, [12](#)
- YELLOW_RGB, [12](#)
- pypalex.conversion_utils, [12](#)
 - hsv_to_hex, [12](#)
 - hsv_to_rgb, [13](#)
 - rgb_to_hex, [13](#)
 - rgb_to_hsv, [13](#)
- pypalex.extraction_utils, [15](#)
 - borrow_color, [15](#)
 - calculate_centroid, [16](#)
 - check_missing_color_types, [16](#)
 - check_missing_colors, [17](#)
 - check_sat_and_bright, [17](#)
 - construct_base_color_dictionary, [17](#)
 - extract_color_types, [18](#)
 - extract_colors, [18](#)
 - extract_dominant_color, [18](#)
 - extract_ratios, [19](#)
 - find_closest_to_centroid, [19](#)
 - generate_background_and_foreground, [19](#)
 - generate_black_and_white, [20](#)
 - generate_remaining_colors, [20](#)
 - get_dominant_hue, [20](#)
 - get_left_and_right_colors, [21](#)
 - sort_by_bright_value, [21](#)
- pypalex.Extractor, [21](#)
- pypalex.image_utils, [22](#)
 - process_helper, [22](#)
 - process_image, [22](#)
 - rescale_image, [23](#)
 - save_palette_to_file, [23](#)
- ratio_dict
 - Extractor, [29](#)
- RED_HEX
 - pypalex.constants, [11](#)
- RED_HUE
 - pypalex.constants, [11](#)
- RED_HUE_RANGE_MAX
 - pypalex.constants, [11](#)
- RED_HUE_RANGE_MIN
 - pypalex.constants, [11](#)
- RED_RGB
 - pypalex.constants, [11](#)
- rescale_image
 - pypalex.image_utils, [23](#)
- rgb_to_hex
 - pypalex.conversion_utils, [13](#)
- rgb_to_hsv
 - pypalex.conversion_utils, [13](#)
- run
 - Extractor, [27](#)
- SATURATION_RANGE
 - pypalex.constants, [11](#)
- save_palette_to_file
 - pypalex.image_utils, [23](#)
- set_global_args
 - pypalex.__main__, [5](#)
- setup_argument_parser
 - pypalex.__main__, [6](#)
- sort_by_bright_value
 - pypalex.extraction_utils, [21](#)
- WHITE_BRIGHTNESS_RANGE
 - pypalex.constants, [12](#)
- WHITE_HEX
 - pypalex.constants, [12](#)
- WHITE_RGB
 - pypalex.constants, [12](#)
- YELLOW_HEX
 - pypalex.constants, [12](#)
- YELLOW_HUE
 - pypalex.constants, [12](#)
- YELLOW_HUE_RANGE
 - pypalex.constants, [12](#)
- YELLOW_RGB
 - pypalex.constants, [12](#)