

Embedded Linux Task 1

Q1:

Linux Distributions:

- 1-ubuntu
- 2-Red Hat
- 3-debian

Q2:

man command:

It is a system-wide documentation system that provides short reference manuals (pages) for individual commands, API functions, concepts, configuration file syntax, file formats and is organized in sections (1 for user commands, 2 for system calls...). That's the traditional Unix documentation system.

Q3:

The difference between rm and rmdir:

rm:

rm removes each specified file. By default, it does not remove directories.

rmdir:

Remove the DIRECTORY(ies), if they are empty.

Q4:

```
alaa@alaaHP:~$ mkdir dir1
alaa@alaaHP:~$ mkdir docs Documents
mkdir: cannot create directory 'Documents': File exists
alaa@alaaHP:~$ mkdir MyDocuments
alaa@alaaHP:~$ cd /home/alaa/dir1
alaa@alaaHP:~/dir1$ mkdir dir11 dir12
alaa@alaaHP:~/dir1$ cd /home/alaa/dir1/dir11
alaa@alaaHP:~/dir1/dir11$ touch file1
alaa@alaaHP:~/dir1/dir11$ cd /home/alaa/docs
alaa@alaaHP:~/docs$ touch mycv
alaa@alaaHP:~/docs$ touch /home/alaa/MyDocuments/OldFiles
```

```

alaa@alaaHP:~$ ls
Desktop  dir1  docs  Documents  Downloads  Embedded-Linux  Music  MyDocuments  P
ictures  Public  snap  Templates  Videos
alaa@alaaHP:~$ cd /home/alaa/docs
alaa@alaaHP:~/docs$ ls
mycv
alaa@alaaHP:~/docs$ cd /home/alaa/dir1
alaa@alaaHP:~/dir1$ ls
dir11  dir12
alaa@alaaHP:~/dir1$ cd /home/alaa/dir1/dir11
alaa@alaaHP:~/dir1/dir11$ ls
file1
alaa@alaaHP:~/dir1/dir11$ cd /home/alaa/MyDocuments
alaa@alaaHP:~/MyDocuments$ ls
OldFiles
alaa@alaaHP:~/MyDocuments$ 

```

a. Couldn't remove the directory because it is not empty. To remove a non empty directory we use "rm -r" command.

```

alaa@alaaHP:~/dir1$ rmdir dir11
rmdir: failed to remove 'dir11': Directory not empty
alaa@alaaHP:~/dir1$ rm dir11
rm: cannot remove 'dir11': Is a directory
alaa@alaaHP:~/dir1$ rm -r dir11
alaa@alaaHP:~/dir1$ ls
dir12
alaa@alaaHP:~/dir1$ 

```

b. The "OldFiles" file couldn't be removed because "rmdir -p" is used for directories only.

```

alaa@alaaHP:~$ rmdir -p /home/alaa/MyDocuments/OldFiles
rmdir: failed to remove '/home/alaa/MyDocuments/OldFiles': Not a directory

```

c. The absolute path:
 /home/user/docs/mycv
 The relative path:
 docs/mycv

Q5:

```

alaa@alaaHP:~$ pwd
/home/alaa
alaa@alaaHP:~$ cp /etc/passwd mypasswd
alaa@alaaHP:~$ ls
Desktop  docs      Downloads  Music      mypasswd  Public  Templates
dir1     Documents Embedded-Linux  MyDocuments  Pictures  snap    Videos

```

Q6:

```

alaa@alaaHP:~$ mv mypasswd oldpasswd
alaa@alaaHP:~$ ls
Desktop  docs      Downloads  Music      oldpasswd  Public  Templates
dir1     Documents Embedded-Linux MyDocuments Pictures    snap     Videos
alaa@alaaHP:~$ 

```

Q7:

- cd
- cd ~
- cd \$HOME
- cd home/user

```

alaa@alaaHP:/bin$ cd
alaa@alaaHP:~$ cd /bin
alaa@alaaHP:/bin$ cd ~
alaa@alaaHP:~$ cd /bin
alaa@alaaHP:/bin$ cd $HOME
alaa@alaaHP:~$ cd /bin
alaa@alaaHP:/bin$ cd /home/alaa
alaa@alaaHP:~$ 

```

Q8:

```

alaa@alaaHP:/usr/bin$ ls w*
w      wc      whereis  who      word-list-compress
wall   wdctl   which    whoami   wpa_passphrase
watch  wget    which.debianutils whoopsie  write
watchgnupg whatis  whiptail whoopsie-preferences write.ul
alaa@alaaHP:/usr/bin$ 

```

Q9:

Command type is used to display information about command type.

Q10:

```

alaa@alaaHP:/usr/bin$ ls c*
calibrate_ppa      chfn      column
canberra-gtk-play  chgrp     comm
cancel             chmod     compose
captaininfo        chown     compose
cat                chrt      corelist
catman             chsh      cp
cautious-launcher  chvt      cpan
cd-create-profile  ciptool   cpan5.34-x86_64-linux-gnu
cd-fix-profile     ckbcomp   cpio
cd-iccdump         cksum     cpp
cd-it8            clear     cpp-11
chac1             clear_console c_rehash
chage             cmp       crontab
chardet           cmp       csplit
chardetect        codepage  ctstat
chattr           col       cupstestppd
chcon            colcrt    cut
check-language-support colormgr   cvt
cheese          colrm     cvtsudoers
alaa@alaaHP:/usr/bin$ 

```

Q11:

```
alaa@alaaHP:~/Embedded-Linux/AdminLinux_Task1$ man -k read file
00-upstream-settings (5) - dconf configuration file
FILE (3) - overview of system data types
[ (1) - check file types and compare values
aa-exec (1) - confine a program with the specified AppArmor profile
aa-remove-unknown (8) - remove unknown AppArmor profiles
aa-teardown (8) - unload all AppArmor profiles
access.conf (5) - the login access control table file
accessdb (8) - dumps the content of a man-db database in a human read...
acct (5) - process accounting file
adduser.conf (5) - configuration file for adduser(8) and addgroup(8) .
amidi (1) - read from and write to ALSA RawMIDI ports
anacrontab (5) - configuration file for anacron
aplaymidi (1) - play Standard MIDI Files
apparmor.d (5) - syntax of security profiles for AppArmor.
apparmor.vim (5) - vim syntax highlighting file for AppArmor profiles
apparmor_parser (8) - loads AppArmor profiles into the kernel
apparmor_xattrs (7) - AppArmor profile xattr(7) matching
```

Q12:

Search the manual age names and descriptions