

# CS 1678/2078 Python Instructions

## Abstract

This document describes the recommended way to setup and use Python for the course. This document also contains links to additional Python resources.

## 1 Python Setup

It is possible to have many different versions of Python and Python packages installed on one computer. To make sure the code you develop for this course will be compatible with our grading machines, we will leverage Python virtual environments. A Python virtual environment is a Python installation separate from any other Python instance on your system. These virtual environments make it possible to have multiple versions of Python on a single computer, each with its own set of packages and dependencies. To set up this functionality, we will be using the Anaconda distribution of Python and its package manager. You can download Miniconda (a smaller version of Anaconda) from this [link](#). You should download version 3.8 for 64-bit systems (unless your computer has a 32-bit CPU). Follow their [instructions](#) to install and set up your environment variables. We recommend using the default paths during the installation.

After installing Anaconda, you should open a terminal (or the Anaconda Prompt from the Start menu if you are using windows) and type `conda list`. This command will show the currently installed Anaconda packages. If you get an error saying `command 'conda' not recognized`, you probably need to reload your terminal for the path to be updated. If this error persists, your path is not set correctly, and you will need to update your path as specified in the installation instructions. Now with a terminal open and Anaconda correctly set up, we can create a new virtual environment. Execute the following command to create the virtual environment we will use for this course.

```
conda create --name cs1678 python=3.12 numpy matplotlib
```

This command creates an environment called “cs1678” that runs Python version 3.12 and installs two packages: NumPy and Matplotlib. NumPy is a powerful library for easily manipulating arrays in Python. Matplotlib is a standard plotting package that we will use throughout the course. This environment can be activated with the command

```
conda activate cs1678
```

and then deactivated with the command

```
conda deactivate
```

Once activated, any Python command will use the Python version and packages you installed in this environment. If you need to install a new package (we will tell you if you do), you can use the command

```
conda install <package_name>
```

These commands, along with other useful conda commands, can be found in the Anaconda [documentation](#). Note that you should not need to use `sudo` (on Mac or Linux) to install anything for this course, and we advise against it. You can now close the terminal/Anaconda Prompt.

## 2 IDE Setup

You may also find it helpful to use an IDE to develop and debug your programs. While there are many good IDEs, we recommend the use of PyCharm VSCode. See each IDEs own setup instructions for basic set up and integration with Conda.

## 3 Python Resources

If you are unfamiliar with Python, there are many tutorials on the internet that cover the syntax. Python.org has many tutorials covering the basics of Python, see <https://docs.python.org/3/tutorial/>. One of the most common errors in writing Python code is in handling indents. Since Python has no curly braces or end statements to enclose functions, loops,

and other code segments, indentation is the only way to signify which block a line of code belongs to. If for indentation tab characters and spaces are mixed, then the program might silently fail by running code differently than you intended. The PEP8 standard<sup>1</sup> for Python specifies that indentation should be four spaces and use the space character instead of a tab. Most editors can automatically convert tabs to spaces for a specified tab width. This error usually only occurs when switching between editors without reformatting the code.

You may have noticed that in the function definitions for homework 2, each variable has a `:` then a *type* specified. These types are really type *hints* meaning that an IDE or editor uses them to reason about the code and possibly identify errors before it is run. Python does not have typed variables, and no checks on types will be performed unless you code for them.

## 4 NumPy Arrays

Manipulating lists, arrays, vectors, and matrices, will be a common component in the programming assignments for this course. NumPy is a powerful package for manipulating arrays and performing linear algebra (e.g., dot products, matrix-vector multiplication). Most importantly, NumPy makes it easy to index and slice (select sections) arrays. In this section, we provide a small overview of using NumPy arrays. To use the NumPy package, you can add the following line to the top of the file.

```
import numpy as np
```

This command imports the NumPy package and aliases it to use the abbreviation `np`, this way anytime you want to call a function in the NumPy package, you only have to write `np.<function_name>`. There are many ways to create and interact with NumPy arrays. Here we list a few common ones.

```
### 1D Arrays ###
```

```
# creation
```

```
x = [1,2,3,4] # a normal list in Python
```

```
x = np.array(x) # x is now a numpy array.
```

```
n = 3
```

```
x = np.zeros(n) # creates an array of length n containing all zeros
```

```
x = np.ones(n) # creates an array of length n containing all ones
```

```
x = np.arange(n) # creates an array containing the integers 0,1,...,(n-1)
```

```
# typing the elements
```

```
x = np.ones(n, dtype=np.int64) # creates an array of ones that are all 64-bit integers
```

```
# dtype is an optional argument on most NumPy functions that create arrays
```

```
# default type is np.float64
```

```
# other useful types: np.int32, np.float32, np.bool
```

```
# Python types of int, float, and bool are also acceptable
```

```
# indexing
```

```
x = np.array([1,2,3,4])
```

```
x[0] # first element (returns 1)
```

```
x[3] # last element returns 4
```

```
x[-1] # also last element
```

```
x[-2] # second to last element
```

```
x[1:4] # gets an array containing the elements at indexes 1,2,3
```

```
x[1:] # gets an array containing the elements starting at index 1
```

```
x[0:-1] # all but the last element
```

```
x[:-1] # the 0 index is assumed
```

```
x[:] # all elements
```

```
### 2D Arrays ###
```

```
# creation
```

```
n,m = 4,3
```

---

<sup>1</sup><https://www.python.org/dev/peps/pep-0008/>

```

x = np.zeros((n,m)) # creates a 2D array with n rows and m columns

x.shape # returns the dimensions/shape of the array as a tuple, in this case (4,3)
x.shape[0] # gets the number of rows
x.shape[1] # gets the number of columns
x.size # gets the total number of elements in the array

x[0, 1] # selects the element in the first row and second column
x[0, :] # selects the first row
x[:, 2] # selects the third column
x[:2, :] # selects the first two rows
x[:, :2] # selects the first two columns
x[-2:, :2] # selects the last two rows and first two columns
x[:, :] # selects all rows and columns

a = np.ones(m)
x[0,:] = a # sets the first row to be equal to array a
x[:,0] = 1 # sets the first column to be equal to one

### element-wise operations ###

a = np.arange(3)
b = np.array([2,0,3])
c = a + b # creates an array where each element in a is added by the element in b
# c = [0+2, 1+2, 2+3]
a - b # element wise subtraction
a * b # element wise multiplication
a / b # element wise division
# vectors must be same size
# this also works for matrices of the same size

```