Presenter script

Three operator cases

Alaa Selim, MIT/Dartmouth

Mohamed Chehada, UT Austin

One notebook, 83 slides, 90 minutes. Use the spoken explanation in your own voice. The run cue says exactly when to open, run, edit, reset or inspect a cell. Run the complete cell identified by its L heading and stable ID.

Python calculates new numerical results. L3, L10 and L10B show separately labeled saved model records. One Llama model fills two roles in the saved five-role Python workflow. L12 is a simulated readback; equipment_dispatch stays False.

90-minute session route

Agent concepts and Colab setup: slides 1-15, 00:00-15:00.

Voltage support: slides 16-38, 15:00-39:00.

Service restoration: slides 39-55, 39:00-56:00.

Cyber response: slides 56-72, 56:00-73:00.

Agent workflow and operator review: slides 73-83, 73:00-90:00.

Open the one Classroom Labs notebook

Colab run sheet: Setup and voltage

Slide 12: setup / RUN

Connect a CPU. Run the whole setup cell once and wait for Ready.

Cells: colab-setup.

Slide 14: L0 / RUN

Run L0 with RUN_OPENDSS=False and RUN_LOCAL_LLAMA=False.

Cells: classroom-002.

Slide 15: L1 / RUN

Run the whole L1 cell after L0.

Cells: classroom-004.

Slide 21: L2 / RUN

Run the full L2 cell at LOAD_SCALE=1.0 and RATING_FRACTION=0.80.

Cells: classroom-007.

Slide 25: L2 / EDIT AND RERUN

Change only RATING_FRACTION to 0.75. Predict, then rerun all of L2. Give this exercise four minutes.

Cells: classroom-007.

Slide 28: L2 / RESET AND RERUN

Restore LOAD_SCALE=1.0 and RATING_FRACTION=0.80; rerun the complete L2 cell.

Cells: classroom-007.

Slide 30: L3 / RUN

Run L3. Keep the default test_01 case.

Cells: classroom-010.

Slide 32: L4 / RUN

Run L4 after L3 without changing the case ID.

Cells: classroom-013.

Colab run sheet: Restoration and cyber

Slide 34: L5 / RUN

Run L5 with RUN_OPENDSS still False.

Cells: classroom-016.

Slide 41: L6 / RUN

Run L6 with CAPACITIES_KW=(40.,60.,80.,100.,120.).

Cells: classroom-018.

Slide 45: L6 / EDIT AND RERUN

Append 180. to CAPACITIES_KW, keeping 40. first. Rerun all of L6. Give this exercise four minutes.

Cells: classroom-018.

Slide 48: L6, L7 / RESET, THEN RUN

Restore the original capacity list and rerun L6. Then run the whole L7 cell.

Cells: classroom-018, classroom-021.

Slide 58: L8 / RUN

Run L8 with ATTACK_SCALES=(0.,.25,.5,1.,1.5).

Cells: classroom-023.

Slide 61: L8 / EDIT AND RERUN

Add .10 to ATTACK_SCALES. Rerun all of L8 and inspect the isolated-bias row. Give this exercise four minutes.

Cells: classroom-023.

Slide 64: L8 / RESET AND RERUN

Restore ATTACK_SCALES=(0.,.25,.5,1.,1.5) and rerun all of L8.

Cells: classroom-023.

Colab run sheet: Saved agent records and operator readback

Slide 67: L9 / RUN

Run all of L9 after resetting L8.

Cells: classroom-026.

Slide 73: L10 / RUN

Run all of L10 after L9. Read the case and stage columns in the saved trace.

Cells: classroom-028.

Slide 74: L10B / REPLAY THREE TIMES

After L10, run the whole L10B cell for SCENARIO="voltage", then "restoration", then "cyber". Change only that string between runs.

Cells: classroom-llama-walkthrough.

Slide 75: L11, L12 / SKIP LIVE CALL, THEN RUN

Keep RUN_LOCAL_LLAMA=False. Run L11 and expect SKIPPED. Then run all of L12.

Cells: classroom-030, classroom-033.

Slide 1. Hands-on: Three Operator Cases

00:00-01:00 / 1 minute

Say

Help an operator compare options, check results and decide the next step. One notebook / 90 minutes / three short exercises

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Open slide 1

Slide 2. An agent chooses what to try next

01:00-02:00 / 1 minute

Say

Give the agent a goal. It requests a tool, reads the result and chooses the next step. The agent coordinates the work. The numerical tool supplies the engineering result. An error can also guide the next request.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Ask

Who calculates the electrical result?

Expected answer

The numerical tool. The agent coordinates the requests and reads the returned evidence.

Open slide 2

Slide 3. The agent asks; the tool calculates

02:00-02:30 / 0.5 minutes

Say

A tool does one job. An agent can connect several jobs using their results. A solver can answer a well-defined study request. The agent's job is deciding which permitted request should come next.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Ask

What does the agent add to one tool call?

Expected answer

It can choose and connect permitted next steps using the returned results.

Open slide 3

Slide 4. Check the evidence before answering

02:30-03:00 / 0.5 minutes

Say

Keep the tool result and its checks with the recommendation. Stanford's example checks claims before writing an answer. Our grid adaptation checks numerical evidence before presenting a recommendation.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Ask

What should support a recommendation?

Expected answer

A matching tool result, the relevant checks and a clear account of what remains unverified.

Open slide 4

Slide 5. Solar settings: which option should we try?

03:00-03:30 / 0.5 minutes

Say

Compare possible settings, then check voltage and line current. The agent can organize these trials and report the checked options. Think of several possible solar settings on the operator's desk. Each candidate needs the same limit checks before comparison.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: PREVIEW ONLY

Show the slide only. Run L2 later on slide 21; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 5

Slide 6. Give the agent a goal and clear limits

03:30-04:30 / 1 minute

Say

State the goal, allowed tools and stopping rules. Keep the operator's review step explicit. These rules belong to the application and operating process. A persuasive model response cannot change them.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Ask

Who sets the limits and allowed actions?

Expected answer

The application and operating process, with the operator's stated task and authority.

Open slide 6

Slide 7. Restoration: who should get power first?

04:30-05:00 / 0.5 minutes

Say

The operator sets the service priority. That priority changes what we ask the restoration tool to do. For example, serving more total power can differ from serving more critical demand. The operator must state the intended goal.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: PREVIEW ONLY

Show the slide only. Run L6 later on slide 41; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 7

Slide 8. Keep three jobs clear

05:00-05:30 / 0.5 minutes

Say

The agent requests a study. The tool calculates. The operator reviews the result. Keep the three responsibilities separate when reading the examples. A fluent explanation is not a substitute for the calculation.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Ask

Which job belongs to the operator?

Expected answer

Reviewing the evidence and deciding the next authorized step.

Open slide 8

Slide 9. Wrong readings can still fit a model

05:30-06:00 / 0.5 minutes

Say

A good fit alone does not prove the readings are true. The agent can organize checks and flag missing evidence. Later we will change readings in a small model and compare the alarm with the resulting estimation error.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: PREVIEW ONLY

Show the slide only. Run L8 later on slide 58; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 9

Slide 10. Ask four questions about every result

06:00-07:00 / 1 minute

Say

What was asked? What did the tool return? Did the checks pass? What must the operator decide? These questions work for all three cases. They connect an output to the task and the person who must review it.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Open slide 10

Slide 11. Use one notebook for all three cases

07:00-08:00 / 1 minute

Say

Open Classroom Labs and save your own copy. We will use it throughout the workshop. Other notebooks on the website are supporting resources. Classroom Labs is the one required notebook for this session.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

Open Classroom Labs and save a copy. Run setup on slide 12, not the later lesson cells.

Open slide 11

Slide 12. Start Colab in three steps

08:00-10:30 / 2.5 minutes

Say

Save a copy, connect a CPU and run setup. Wait for Ready, then run L0 and L1. Colab gives you a temporary computer. After a runtime reset, rerun setup and the earlier cells to recreate their variables.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: RUN

Connect a CPU. Run the whole setup cell once and wait for Ready.

Exact cells: `colab-setup`. Run the whole cell.

Expected result

Ready appears; the support files and CPU packages are available.

Open slide 12

Slide 13. Run a cell, then read its output

10:30-11:00 / 0.5 minutes

Say

Find the L heading and run the whole cell. After changing an input, run that cell again. The play button runs the cell. The output below it belongs to the last completed run, so an edit alone changes nothing.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: PREVIEW ONLY

Show the slide only. Run L2 later on slide 21; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 13

Slide 14. L0: keep both switches off

11:00-12:30 / 1.5 minutes

Say

Keep both switches False. Python runs the calculations. Llama is the language model used in the saved examples. We inspect its recorded choices here, so no live model installation or call is needed.

Show

Locate L0 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RUN

Run L0 with RUN_OPENDSS=False and RUN_LOCAL_LLAMA=False.

Exact cells: `classroom-002`. Run the whole cell.

Expected result

The data assertion passes. Both optional live-tool paths remain off.

Open slide 14

Slide 15. L1: does the old result still match?

12:30-15:00 / 2.5 minutes

Say

Expect True, False, False: only the unchanged request matches. Changed inputs or actions need a new check. Matching evidence means the returned result belongs to this request and this proposed action. A changed request needs fresh evidence.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: RUN

Run the whole L1 cell after L0.

Exact cells: `classroom-004`. Run the whole cell.

Expected result

binding_pass is True, False, False in row order.

Open slide 15

Slide 16. Case 1: which solar settings should we use?

15:00-15:30 / 0.5 minutes

Say

Imagine an operator comparing possible settings for solar units. Each choice changes power flows. The job is to find an acceptable option while respecting voltage, line-current and unit limits. An agent can organize the requests and responses, while the tool calculates the electrical effects. We first learn those tools in Colab, then inspect saved agent decisions.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: PREVIEW ONLY

Show the slide only. Run L2 later on slide 21; keep the notebook in order.

Expected result

No new notebook output on this slide.

Ask

What must a proposed solar setting respect?

Expected answer

The checked voltage, line-current and solar-unit limits for the stated model.

Open slide 16

Slide 17. Two tools suggest different settings

15:30-16:30 / 1 minute

Say

MPC plans with a model. SAC uses a previously trained controller. Treat both outputs as proposals that need the same electrical checks. MPC means model predictive control. SAC means soft actor-critic, a learned controller. You do not need their algorithms to follow this lab: both simply supply settings for the same check.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Open slide 17

Slide 18. How the agent helps with solar settings

16:30-18:00 / 1.5 minutes

Say

Follow the arrows from the operator's goal to the returned result. If a check fails, the agent can request another permitted trial. If evidence is missing, it can stop and ask. The useful behavior is the choice made after reading the tool result. The tool still performs the electrical calculation.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Ask

What can happen after a failed trial?

Expected answer

Request another permitted trial, ask for missing evidence or stop for review.

Open slide 18

Slide 19. The study changes two solar settings

18:00-19:00 / 1 minute

Say

a sets active-power output. b sets voltage-support output. The tool checks voltage, line current and the solar unit's capacity. Active power supplies energy. Reactive power supports voltage. The inverter's shared capacity means these settings cannot be chosen independently without checking.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: PREVIEW ONLY

Show the slide only. Run L2 later on slide 21; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 19

Slide 20. A Python function can be a tool

19:00-19:30 / 0.5 minutes

Say

It receives inputs, runs calculations and returns results. L2 calls this function directly. The saved agent example shows who requests it. A tool does not have to be another AI model. Here it is ordinary Python code that calls the numerical study and returns structured results.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: PREVIEW ONLY

Show the slide only. Run L2 later on slide 21; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 20

Slide 21. L2: compare two solar proposals

19:30-22:30 / 3 minutes

Say

Run L2 with the default settings. Look for pass/fail, current used and score J. Lower J is better after checks pass. Look for feasible, max_allowed_current_pct and current_step_J in the notebook. These mean the checked limits pass, current used and the comparison score.

Show

Locate L2 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RUN

Run the full L2 cell at LOAD_SCALE=1.0 and RATING_FRACTION=0.80.

Exact cells: `classroom-007`. Run the whole cell.

Expected result

Both default proposals pass; current use is about 73.62% for MPC and 51.68% for SAC.

Open slide 21

Slide 22. Read the voltage and current checks

22:30-23:30 / 1 minute

Say

Left: voltages should stay in the allowed band. Right: current should stay below 100% of the allowance. A value below the current line does not replace the voltage check. The same candidate must satisfy every required check.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 22

Slide 23. Both pass; MPC has the lower score

23:30-24:30 / 1 minute

Say

MPC: 73.62% current use; score J about 0.03110. Saved SAC: 51.68% current use; score J about 0.43643. SAC uses less current, but MPC has the lower cost score. This is why we must name the goal instead of selecting the smallest number in any column.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 23

Slide 24. A limit needs a calculated check

24:30-25:00 / 0.5 minutes

Say

A rule states the limit. The tool tests the proposed setting. Keep the rule and returned result together for review. The stated rule and the measured result have different jobs. Keep enough context to show which proposal and model produced the result.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Open slide 24

Slide 25. Exercise 1: lower the current allowance

25:00-28:00 / 3 minutes

Say

In L2, change RATING_FRACTION from 0.80 to 0.75. Predict, then rerun. Compare pass/fail, current use and score J for both methods. Does this check cover the whole medium- and low-voltage network?

Show

Show the question for three minutes: predict for one, then edit and run for two. Advance once for the worked answer.

Colab: EDIT AND RERUN

Change only RATING_FRACTION to 0.75. Predict, then rerun all of L2. Give this exercise four minutes.

Exact cells: `classroom-007`. Run the whole cell.

Expected result

MPC current use is about 78.53%; SAC about 54.85%; both pass this MV test.

Ask

In L2, change RATING_FRACTION from 0.80 to 0.75. Predict, then rerun. Compare pass/fail, current use and score J for both methods. Does this check cover the whole medium- and low-voltage network?

Expected answer

No. The default covers MV phases and currents with ideal LV aggregation.

Open slide 25

Slide 26. Exercise 1 answer: both options still pass

28:00-29:00 / 1 minute

Say

MPC has the lower score; SAC uses less current. The score considers more than current alone. This check covers the medium-voltage model. The wider network needs a wider study. At the exercise settings, MPC uses 78.53% of the allowance and SAC uses 54.85%. Both pass. Their current-step scores are about 0.03110 and 0.43246.

Show

Advance from the exercise only after learners try it. Read the verified values, explain why the outcome occurs and answer every part of the question.

Colab: INSPECT / RESET

Use the output already produced for the exercise. Restore RATING_FRACTION=0.80 and rerun all of L2 before continuing.

Expected result

MPC has the lower score J. The saved SAC actor uses less current; current use alone is not the objective. Both checks cover the default MV model. They do not establish full MV/LV or dynamic performance.

Open slide 26

Slide 27. Less current does not mean the best option

29:00-30:00 / 1 minute

Say

Here SAC also uses less solar output. The goal values generation as well as limits. Compare the score after checks pass. The active-power setting is about 0.9603 for MPC and 0.3431 for SAC in this exercise. Lower solar output can reduce current but also increase the stated cost.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 27

Slide 28. L2: restore the starting values

30:00-30:30 / 0.5 minutes

Say

Restore LOAD_SCALE=1.0 and RATING_FRACTION=0.80. Rerun L2. The next cells use a separate saved case. Resetting keeps the class together. The following saved case has its own original inputs; your changed L2 settings do not rewrite it.

Show

Locate L2 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RESET AND RERUN

Restore LOAD_SCALE=1.0 and RATING_FRACTION=0.80; rerun the complete L2 cell.

Exact cells: `classroom-007`. Run the whole cell.

Expected result

The default output returns. L3-L5 will use their separate original test_01 case.

Open slide 28

Slide 29. Separate a new calculation from a replay

30:30-31:00 / 0.5 minutes

Say

Your inputs produce new numerical results. Saved replies show past model decisions; editing L2 does not change them. A fresh calculation answers the inputs you just supplied. A replay shows what happened previously. Both are useful, but they answer different questions.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Open slide 29

Slide 30. L3: inspect saved model choices

31:00-32:00 / 1 minute

Say

Run L3 to see what the models requested for the saved case. This displays old replies; it makes no new model call. Read the request, reason and recorded time as a historical record. The model is not responding to your new L2 input.

Show

Locate L3 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RUN

Run L3. Keep the default test_01 case.

Exact cells: `classroom-010`. Run the whole cell.

Expected result

Three saved model replies and recorded times appear; no new model request occurs.

Open slide 30

Slide 31. Different replies can request the same action

32:00-32:30 / 0.5 minutes

Say

Group requests that describe the same settings. A vote chooses what to test next. The electrical check still has to run. Wording alone should not create extra votes for the same physical operation. The numerical check still determines whether the selected setting passes.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Open slide 31

Slide 32. L4: check the chosen proposal

32:30-33:30 / 1 minute

Say

Recheck the selected proposal on its original saved case. Compare the vote with a previously learned selection rule. The learned selection rule is the frozen LinUCB selector shown in the output. We compare its chosen action; we do not train a new selector here.

Show

Locate L4 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RUN

Run L4 after L3 without changing the case ID.

Exact cells: `classroom-013`. Run the whole cell.

Expected result

Both selectors choose RELAX_Q_10_PERCENT; new_check_passes is True for both.

Open slide 32

Slide 33. Both selectors choose the same proposal

33:30-34:00 / 0.5 minutes

Say

The new electrical check passes for both selections. The selection score and the electrical check have different jobs. Both selection methods happen to agree on this case. That agreement is not the reason the electrical check passes.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 33

Slide 34. L5: see which part of the grid was checked

34:00-35:30 / 1.5 minutes

Say

Run L5 with the default settings. It checks the medium-voltage (MV) part of the saved case. The wider OpenDSS study is disabled by default. This cell therefore supports a medium-voltage claim only.

Show

Locate L5 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RUN

Run L5 with RUN_OPENDSS still False.

Exact cells: `classroom-016`. Run the whole cell.

Expected result

The linear-model check is shown; the optional full-model path is disabled.

Open slide 34

Slide 35. A PASS covers only what was checked

35:30-36:00 / 0.5 minutes

Say

A limited model cannot answer a wider grid question. Request the missing study or return HOLD. A checked part of a network does not stand for every device or every operating limit. Ask for the check needed by the actual decision.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 35

Slide 36. Recorded example: the first option fails

36:00-37:00 / 1 minute

Say

This saved study is different from your L2 run. Llama asks for a SAC check. The tool reports too much current. This is a preview of a different saved study, not a continuation of the passing L2 results. The recorded tool result reports a current-limit failure. The next agent choice follows that evidence.

Show

Preview the actual saved Llama request and returned tool evidence. Do not ask learners to run ahead. L10B will replay these records after the three labs.

Colab: PREVIEW ONLY

Show the slide only. Run L10B later on slide 74; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 36

Slide 37. Recorded example: request another option

37:00-38:00 / 1 minute

Say

Llama asks the tool to check the existing MPC fallback. The returned electrical checks pass for this saved case. The agent requests a plan that already exists rather than inventing its electrical outcome. The tool calculates the check and returns the evidence.

Show

Preview the actual saved Llama request and returned tool evidence. Do not ask learners to run ahead. L10B will replay these records after the three labs.

Colab: PREVIEW ONLY

Show the slide only. Run L10B later on slide 74; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 37

Slide 38. Recorded example: return to the operator

38:00-39:00 / 1 minute

Say

The agent returns the checked proposal and its conditions. Human review is still pending. No equipment command is sent. The result is a recommendation for review. The record still shows human acknowledgement pending and equipment dispatch disabled.

Show

Preview the actual saved Llama request and returned tool evidence. Do not ask learners to run ahead. L10B will replay these records after the three labs.

Colab: PREVIEW ONLY

Show the slide only. Run L10B later on slide 74; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 38

Slide 39. Case 2: who gets power after a fault?

39:00-39:30 / 0.5 minutes

Say

A fault removes one normal supply path. Alternative paths have limited capacity, so the operator must choose what to restore. Serving critical demand first can differ from maximizing the total power served. The agent can carry that priority into a study request, collect the result and request a new study when the situation changes.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: PREVIEW ONLY

Show the slide only. Run L6 later on slide 41; keep the notebook in order.

Expected result

No new notebook output on this slide.

Ask

Could most total power and most critical service differ?

Expected answer

Yes. Limited capacity can force a trade-off, so the goal must be stated.

Open slide 39

Slide 40. How the agent helps restore service

39:30-40:30 / 1 minute

Say

The operator supplies the goal. The numerical solver chooses loads under the network rules. An agent could manage the study request and read its result, but it should not invent the service priority. L6 runs the tools directly; the recorded agent example comes later.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: PREVIEW ONLY

Show the slide only. Run L6 later on slide 41; keep the notebook in order.

Expected result

No new notebook output on this slide.

Ask

Who chooses the service priority?

Expected answer

The operator supplies the priority; the solver and agent must preserve it.

Open slide 40

Slide 41. L6: compare two restoration goals

40:30-42:30 / 2 minutes

Say

Run L6 to choose which loads receive power under each goal. MILP chooses whole loads; a separate calculation checks its result. MILP is a solver for choices such as whether an entire load is restored. The independent search checks the small teaching model's objective result.

Show

Locate L6 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RUN

Run L6 with CAPACITIES_KW=(40.,60.,80.,100.,120.).

Exact cells: `classroom-018`. Run the whole cell.

Expected result

The priority MILP agrees with exhaustive enumeration. At 40 kW, compare 130/90 with 140/30 kW total/critical.

Open slide 41

Slide 42. Read total and critical service

42:30-43:30 / 1 minute

Say

Left: all power restored. Right: power restored to critical loads. Overlapping markers mean the two goals give the same result. The plots separate total service from service to critical loads. Always say which one a number describes.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 42

Slide 43. The service goal changes who gets power

43:30-44:30 / 1 minute

Say

Critical-first goal: 130 kW total, including 90 kW critical. Most-total-power goal: 140 kW total, including 30 kW critical. At the 40 kW tie setting, prioritizing critical loads gives up 10 kW of total service but restores 60 kW more critical service.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 43

Slide 44. Check the restoration plan

44:30-45:00 / 0.5 minutes

Say

Keep the faulted branch out of service. Check supply paths, capacity and totals before accepting the plan. The result must respect the unavailable faulted branch and the model's supply and capacity rules. A field switching sequence needs additional operating work.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Open slide 44

Slide 45. Exercise 2: increase tie capacity

45:00-48:00 / 3 minutes

Say

Add 180. to CAPACITIES_KW. Keep 40. first. Predict, then rerun L6. Compare total and critical power at 40 and 180 kW. At which tested capacity do the two goals first give the same result?

Show

Show the question for three minutes: predict for one, then edit and run for two. Advance once for the worked answer.

Colab: EDIT AND RERUN

Append 180. to CAPACITIES_KW, keeping 40. first. Rerun all of L6. Give this exercise four minutes.

Exact cells: `classroom-018`. Run the whole cell.

Expected result

At 180 kW, both goals serve 250 kW total and 90 kW critical.

Ask

Add 180. to CAPACITIES_KW. Keep 40. first. Predict, then rerun L6. Compare total and critical power at 40 and 180 kW. At which tested capacity do the two goals first give the same result?

Expected answer

They agree at 180 kW in this exercise.

Open slide 45

Slide 46. Exercise 2 answer: capacity changes the trade-off

48:00-49:00 / 1 minute

Say

At 40 kW, the priority goal serves 90 kW critical instead of 30 kW, with less total service. The goals first match at the tested 80 kW. At 180 kW, both serve 250 kW total and 90 kW critical. The goals first match at 80 kW among the tested capacities. At 180 kW both restore 250 kW total, including 90 kW critical. This discrete sweep does not identify an exact continuous crossover.

Show

Advance from the exercise only after learners try it. Read the verified values, explain why the outcome occurs and answer every part of the question.

Colab: INSPECT / RESET

Use the exercise output. Keep 40 first; restore the original list and rerun L6 before L7.

Expected result

At 40 kW, priorities give more critical service: 90 kW instead of 30 kW, with less total service. The goals match from 80 kW in the tested list. At 180 kW, both serve 250 kW total, including 90 kW critical.

Open slide 46

Slide 47. More capacity can remove this trade-off

49:00-50:00 / 1 minute

Say

At 180 kW, both goals give the same result. The chosen priority matters when capacity forces a choice. The priority rule is especially visible when resources force a trade-off. More capacity can make the two stated goals agree on this model.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 47

Slide 48. L7: change the request, then check the evidence

50:00-51:30 / 1.5 minutes

Say

Restore the original capacity list and rerun L6. Run L7: the requested capacity changes from 40 kW to 20 kW. Run the complete L7 cell after restoring L6. It compares an old checked result with a request that now has a smaller capacity.

Show

Locate L7 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RESET, THEN RUN

Restore the original capacity list and rerun L6. Then run the whole L7 cell.

Exact cells: `classroom-018, classroom-021`. Run the whole cell.

Expected result

Original contract: True. Changed rating with old evidence: False. HOLD requests a fresh solve.

Open slide 48

Slide 49. The old result no longer matches

51:30-52:00 / 0.5 minutes

Say

The original request matches; the changed request does not. Put the old recommendation on HOLD and request a new calculation. HOLD here means the old evidence no longer matches. It does not prove every newly calculated plan would fail.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 49

Slide 50. A new limit needs a new study

52:00-52:30 / 0.5 minutes

Say

Old evidence does not tell us whether a new plan works. Calculate again, check again and attach the new result to the new request. An agent can notice the changed request, ask the tool to solve it again and return the new checks. Rewriting the old explanation would not update the calculation.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Open slide 50

Slide 51. The agent keeps the operator's goal

52:30-53:00 / 0.5 minutes

Say

The operator sets priorities. The solver selects loads. The agent can request the solve and explain the returned service trade-off. Keeping the goal fixed matters when many studies are requested. The agent should return the achieved total and critical service with each result.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: PREVIEW ONLY

Show the slide only. Run L6 later on slide 41; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 51

Slide 52. This model leaves some checks for later

53:00-53:30 / 0.5 minutes

Say

This small model checks which loads receive power. Voltage, protection and field switching need separate checks. The six-node exercise is an active-power service model. AC voltage, protection and the safe order of physical operations remain outside its result.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Open slide 52

Slide 53. Recorded example: try more service

53:30-54:30 / 1 minute

Say

This saved feeder study is different from L6. Llama requests another plan. The tool reports more service and passing checks. The saved feeder example is larger than the L6 exercise and has different numbers. Watch the request, returned check and next choice rather than comparing its total kW with L6.

Show

Preview the actual saved Llama request and returned tool evidence. Do not ask learners to run ahead. L10B will replay these records after the three labs.

Colab: PREVIEW ONLY

Show the slide only. Run L10B later on slide 74; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 53

Slide 54. Recorded example: the tool rejects a trial

54:30-55:00 / 0.5 minutes

Say

The next trial carries too much current. It cannot replace the previous passing option. The numerical guard excludes the overloaded trial. Restoring more load is useful only when the required checks also pass.

Show

Preview the actual saved Llama request and returned tool evidence. Do not ask learners to run ahead. L10B will replay these records after the three labs.

Colab: PREVIEW ONLY

Show the slide only. Run L10B later on slide 74; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 54

Slide 55. Recorded example: correct a wrong ranking

55:00-56:00 / 1 minute

Say

Llama puts two passing plans in the wrong order. Python keeps the lower-cost plan and checks it again. Here the lower costs are negative: about minus 6109 is lower than minus 5509. The model's order is wrong, so Python corrects it and rechecks the retained plan.

Show

Preview the actual saved Llama request and returned tool evidence. Do not ask learners to run ahead. L10B will replay these records after the three labs.

Colab: PREVIEW ONLY

Show the slide only. Run L10B later on slide 74; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 55

Slide 56. Case 3: can we trust these readings?

56:00-56:30 / 0.5 minutes

Say

The operator sees measurements, not the true system state. Several altered readings can agree with each other and still lead to a wrong estimate. An agent can request tests and organize the evidence, but it cannot create a trusted measurement source. The lab uses known simulated changes so that we can compare fit with actual estimation error.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: PREVIEW ONLY

Show the slide only. Run L8 later on slide 58; keep the notebook in order.

Expected result

No new notebook output on this slide.

Ask

Does a good fit prove a reading is true?

Expected answer

No. Coordinated wrong readings can fit the model while giving a wrong estimated state.

Open slide 56

Slide 57. Mismatch is only one check

56:30-57:30 / 1 minute

Say

Mismatch J measures how well the model fits the readings. The simulation lets us measure how wrong the estimate is (state error). In the cyber lab, J is a mismatch statistic, not the control cost used in the voltage lab. A low mismatch says the model fits the readings; it does not authenticate them.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: PREVIEW ONLY

Show the slide only. Run L8 later on slide 58; keep the notebook in order.

Expected result

No new notebook output on this slide.

Ask

What does a low mismatch tell us?

Expected answer

That the model fits the supplied readings, not that the readings are authentic.

Open slide 57

Slide 58. L8: compare two misleading-data patterns

57:30-59:30 / 2 minutes

Say

Run L8 with the default settings. Compare one biased reading with a coordinated change across several readings. The isolated pattern changes one reading. The coordinated pattern changes several together. We compare the same two questions: did the alarm trigger, and how wrong was the estimated state?

Show

Locate L8 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RUN

Run L8 with ATTACK_SCALES=(0.,.25,.5,1.,1.5).

Exact cells: `classroom-023`. Run the whole cell.

Expected result

A coordinated Hc attack preserves a small residual while offline state error grows.

Open slide 58

Slide 59. Read the alarm and the estimation error

59:30-60:30 / 1 minute

Say

Left: mismatch and its alarm threshold. Right: error against the simulation's known truth. A quiet alarm can appear alongside a growing error. The right plot uses truth known inside the simulation. A real operator usually cannot read that error directly from a live system.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 59

Slide 60. A coordinated change can escape the alarm

60:30-61:30 / 1 minute

Say

At scale 1, one biased reading gives mismatch J=277.50 and an alarm. A coordinated change gives J=3.92, no alarm, and 0.02678 rad of state error. The coordinated changes preserve a small mismatch even as the estimate moves away from the known state. This is the reason a quiet alarm is incomplete evidence.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 60

Slide 61. Exercise 3: test a small bias

61:30-64:30 / 3 minutes

Say

Add .10 to ATTACK_SCALES. Predict, then rerun L8. At scale 0.10, compare mismatch J, the alarm and state error. Does no alarm prove that the readings are correct?

Show

Show the question for three minutes: predict for one, then edit and run for two. Advance once for the worked answer.

Colab: EDIT AND RERUN

Add .10 to ATTACK_SCALES. Rerun all of L8 and inspect the isolated-bias row. Give this exercise four minutes.

Exact cells: `classroom-023`. Run the whole cell.

Expected result

At isolated scale 0.10, J is about 10.14, below the 15.09 threshold; no alarm is not proof of truth.

Ask

Add .10 to ATTACK_SCALES. Predict, then rerun L8. At scale 0.10, compare mismatch J, the alarm and state error. Does no alarm prove that the readings are correct?

Expected answer

No. The threshold can miss a small bias, and coordinated changes can preserve the fit.

Open slide 61

Slide 62. Exercise 3 answer: no alarm can hide an error

64:30-65:30 / 1 minute

Say

Both alarms are False at scale 0.10, but both estimates still have error. No alarm means the mismatch is below this threshold. It does not establish data trust. At scale 0.10, the isolated mismatch is about 10.143 and the coordinated mismatch is about 3.920. Both are below 15.086, while their state errors are nonzero.

Show

Advance from the exercise only after learners try it. Read the verified values, explain why the outcome occurs and answer every part of the question.

Colab: INSPECT / RESET

Use the output already produced for the exercise. Restore the original ATTACK_SCALES and rerun L8 before the separate fixed L9 recovery case.

Expected result

At scale 0.10, both alarms are False. Both state estimates still have error; the coordinated shift has the larger error here. No alarm means J is below this threshold. It does not prove correct data or trusted sensors.

Open slide 62

Slide 63. A small bias can stay below the threshold

65:30-66:30 / 1 minute

Say

At scale 0.10, the mismatch is 10.14, below the 15.09 threshold. The operator still needs other evidence about the readings. This example concerns the alarm threshold. It does not establish which readings should be trusted in a real event.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 63

Slide 64. L8: reset before the recovery example

66:30-67:00 / 0.5 minutes

Say

Restore the original attack scales and rerun L8. L9 uses a separate fixed recovery case. L9 is deliberately a fixed recovery example. Your L8 sweep is a separate experiment and does not select the L9 correction.

Show

Locate L8 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RESET AND RERUN

Restore ATTACK_SCALES=(0.,.25,.5,1.,1.5) and rerun all of L8.

Exact cells: `classroom-023`. Run the whole cell.

Expected result

The default sweep returns. L9 remains a separate fixed recovery fixture.

Open slide 64

Slide 65. L9: ask whether a correction can be proposed

67:00-67:30 / 0.5 minutes

Say

Compare one case with and without readings assumed to be trusted. Changing your L8 sweep does not change this fixed case. We change the availability of assumed trusted replacement readings, while keeping the recovery case fixed. This isolates the role of that assumption.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: PREVIEW ONLY

Show the slide only. Run L9 later on slide 67; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 65

Slide 66. Trusted readings must come from somewhere

67:30-68:00 / 0.5 minutes

Say

This example assumes extra trustworthy readings are available. Neither the fitting tool nor Llama proves that these readings are authentic. The lesson supplies a trust assumption so that the numerical task can be studied. The calculation is not a method for proving sensor identity or integrity.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: PREVIEW ONLY

Show the slide only. Run L9 later on slide 67; keep the notebook in order.

Expected result

No new notebook output on this slide.

Ask

Does Llama authenticate the extra readings?

Expected answer

No. Their trustworthiness is an explicit assumption of this example.

Open slide 66

Slide 67. L9: read HOLD or PROPOSE first

68:00-69:30 / 1.5 minutes

Say

Run L9 and read the status before the proposed adjustment. Then check the model's returned limits and remaining assumptions. HOLD means a required condition is absent. PROPOSE means the tool can offer a model-based correction for review, not permission to operate equipment.

Show

Locate L9 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: RUN

Run all of L9 after resetting L8.

Exact cells: `classroom-026`. Run the whole cell.

Expected result

No trusted replacement readings: HOLD. With assumed trusted readings: PROPOSE, u about 0.121694 p.u., zero offline violations.

Open slide 67

Slide 68. Missing trust means HOLD

69:30-70:30 / 1 minute

Say

Without trusted replacement readings: HOLD. With the trust assumption: PROPOSE a 0.121694 p.u. adjustment; the offline model checks pass. The passing result depends on the declared trust premise and the simplified model. Zero offline violations is a model result, not a field guarantee.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 68

Slide 69. The tool calculates a small correction

70:30-71:00 / 0.5 minutes

Say

The solver finds the smallest allowed adjustment that meets the checked branch limits. Predicted flow: 0.17000 p.u. Offline check: 0.17046 p.u. Limit: 0.18000 p.u. Per unit, written p.u., expresses a value relative to a chosen model base. Compare the predicted and offline checked flow with the same 0.18 limit.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 69

Slide 70. How the agent helps with suspicious readings

71:00-71:30 / 0.5 minutes

Say

Follow the information from the readings to the proposed correction. Without the required trusted data, the workflow returns HOLD. With that assumption, the tool can calculate a candidate. The agent can request these steps and explain missing checks; the operator must still assess the premise and decide the authorized next step.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 70

Slide 71. Recorded example: request the recovery tool

71:30-72:00 / 0.5 minutes

Say

Llama requests the supplied recovery tool. Python calculates a correction using the assumed trusted readings. The permitted tool is already supplied in this example. Llama chooses to request it; Python performs the estimation and correction calculation.

Show

Preview the actual saved Llama request and returned tool evidence. Do not ask learners to run ahead. L10B will replay these records after the three labs.

Colab: PREVIEW ONLY

Show the slide only. Run L10B later on slide 74; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 71

Slide 72. Recorded example: keep human review

72:00-73:00 / 1 minute

Say

The model checks pass; human review is still pending. Data trust and operating permission still need review. A model check, human review and permission to operate equipment are separate steps. The record has not completed the latter two.

Show

Preview the actual saved Llama request and returned tool evidence. Do not ask learners to run ahead. L10B will replay these records after the three labs.

Colab: PREVIEW ONLY

Show the slide only. Run L10B later on slide 74; keep the notebook in order.

Expected result

No new notebook output on this slide.

Open slide 72

Slide 73. L10: inspect the saved sequence of jobs

73:00-74:30 / 1.5 minutes

Say

Run L10 to see the recorded choices, calculations and checks. The next diagrams give these jobs simple names. Read the saved trace as a sequence of jobs. Identify which job chooses a request and which jobs calculate and check its result.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: RUN

Run all of L10 after L9. Read the case and stage columns in the saved trace.

Exact cells: `classroom-028`. Run the whole cell.

Expected result

Five stage names appear. Planning and optimizer rows contain actual saved Llama replies; other stages contain Python results.

Open slide 73

Slide 74. L10B: replay each saved agent example

74:30-79:00 / 4.5 minutes

Say

Set SCENARIO to voltage, restoration or cyber, then rerun this cell. Read the model's request and the tool's response. This is a saved replay. Run this full cell once for each scenario. The displayed words and tool evidence were recorded earlier; this default demonstration makes no fresh Llama call.

Show

Locate L10B in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: REPLAY THREE TIMES

After L10, run the whole L10B cell for SCENARIO="voltage", then "restoration", then "cyber". Change only that string between runs.

Exact cells: `classroom-llama-walkthrough`. Run the whole cell.

Expected result

Input, exact model choice and public reason, saved tool result and next step appear. No new LLM call or electrical solve runs.

Open slide 74

Slide 75. L12: practice checking the recommendation ID

79:00-81:00 / 2 minutes

Say

Leave L11 disabled, then run L12. Compare the wrong ID with the matching ID. Equipment control stays off. Readback means acknowledging the specific recommendation being reviewed. The wrong identifier must not acknowledge a different recommendation.

Show

Locate L12 in Classroom Labs. Show the highlighted source lines, then run the whole cell when the Colab cue says to run. Read the returned result in plain words.

Colab: SKIP LIVE CALL, THEN RUN

Keep RUN_LOCAL_LLAMA=False. Run L11 and expect SKIPPED. Then run all of L12.

Exact cells: `classroom-030, classroom-033`. Run the whole cell.

Expected result

The table shows HOLD for full MV/LV and an acknowledged MV teaching request. The assertions confirm wrong-ID rejection; equipment_dispatch remains False.

Open slide 75

Slide 76. Approval must match the checked study

81:00-82:00 / 1 minute

Say

The wider-grid request returns HOLD. The limited teaching request permits a simulated readback. A wrong ID fails. This practice sends no equipment commands. The wider request requires checks the default study does not supply. The narrower teaching packet supports only a simulated acknowledgement, with equipment dispatch remaining False.

Show

Use the actual source image. Point to the returned status or number that supports the slide's statement. State whether it is a fresh calculation or a saved example.

Colab: NO NEW RUN

Read the output from the previous run. Compare it with the reference figure; no new cell is needed.

Open slide 76

Slide 77. Five roles share the work

82:00-83:30 / 1.5 minutes

Say

The five roles are five jobs rather than five independent language models. Python reads the case, calculates and verifies. One Llama model requests initial trials and later refinements. Python also guards the final ranking and rechecks the selected option. The default notebook displays these saved stages.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Use the saved L10 trace already displayed. Map the five roles without making a new model call.

Ask

Do five roles mean five separate Llama models?

Expected answer

No. One Llama model fills two roles; Python performs the other three jobs and the final guard.

Open slide 77

Slide 78. Voltage: request, calculate, check, improve

83:30-84:30 / 1 minute

Say

Llama requests small changes to the solar settings. Python recalculates each trial and checks its limits before comparison. This is the separate saved L10 medium-voltage example. New settings return to calculation and checking. Its final recorded current use is about 50.75% of the allowance.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Use the saved L10 trace already displayed. Map the five roles without making a new model call.

Open slide 78

Slide 79. Restoration: keep priorities and reject failures

84:30-85:30 / 1 minute

Say

The goal stays fixed when new plans are tried. Python excludes failed trials and corrects a wrong cost order. In the saved feeder case, a trial at about 111.01% current use is rejected. The retained plan serves about 1843.61 kW total and 474.04 kW critical.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Use the saved L10 trace already displayed. Map the five roles without making a new model call.

Open slide 79

Slide 80. Cyber: keep the trust assumption visible

85:30-86:30 / 1 minute

Say

The agent can request another permitted study or report that evidence is missing. It cannot make a data source trustworthy by describing it confidently. The saved cyber example keeps the assumed trusted readings visible throughout the workflow. Repeating or explaining that assumption does not establish its truth.

Show

Read the visual from the input to the result. Name the operator's goal, the agent's request and the fact supplied by the tool. Explain the decision in the two slide sentences.

Colab: NO NEW RUN

Use the saved L10 trace already displayed. Map the five roles without making a new model call.

Open slide 80

Slide 81. The operator chooses the next step

86:30-87:30 / 1 minute

Say

Review the case, tool results, checked limits and missing work. Request another study, reject the proposal or take the next authorized step. Ask whether the evidence belongs to this case, whether all needed checks are present and what remains unresolved. Those questions support the next human decision.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Ask

What should happen when a required check is missing?

Expected answer

Return the unresolved condition and request the missing study or review before proceeding.

Open slide 81

Slide 82. Measure whether the agent helps

87:30-88:30 / 1 minute

Say

Compare it with a fixed script using the same tools and cases. In L10, five final costs tied; one Llama route was worse. Benefit must be measured. The recorded comparison does not establish a general performance gain. Test completed work, missed checks, time and review effort against the same tools in a fixed script.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

Explain the figure or discuss the output already produced. Do not run ahead.

Ask

What would count as useful improvement?

Expected answer

Better completed work or less total effort under comparable cases and the same required checks.

Open slide 82

Slide 83. Try one change and explain the result

88:30-90:00 / 1.5 minutes

Say

Choose one case. Change one input, rerun and save the result. Explain the problem, agent choice, tool result and operator decision. Use one case to explain the complete story. State the problem, the agent's choice, the tool's returned fact and the operator's remaining decision.

Show

Use the two short slide statements to explain the idea. Link it to the operator's next decision or to the named Colab cell.

Colab: NO NEW RUN

No required new run. Learners may repeat one case afterward and save their changed inputs and outputs.

Ask

What are the four parts of your explanation?

Expected answer

Problem, agent choice, tool result and operator decision.

Open slide 83

Agent role map: Voltage: L10 MV archive

Read the case / Python

Read the load, forecast, current allowance and MV model scope.

Choose a trial / numerical tools and Llama

Prepare MPC and saved-SAC candidates. Llama can request the declared initial studies or return review.

Calculate / Python

Calculate the effects of each candidate using the declared three-phase linear model.

Check / Python

Check case matching, voltage, current and inverter limits. Only passing candidates receive eligible scores.

Refine / Llama, with a Python guard

Request less reactive power, then more PV output. Recalculate and check every changed setting. Python selects by verified cost and performs a final recheck.

Selected final current use: about 50.75% of the allowance. This is the L10 MV archive, not the L2 experiment or P3 OpenDSS replay. The operator still reviews scope and missing checks.

Agent role map: Restoration: L10 feeder catalog

Read the case / Python

Keep the fault, available ties, critical loads, service goal and model scope in the shared case record.

Choose a trial / numerical tools and Llama

Prepare the stated restoration catalog options; request the initial evaluations or review.

Calculate / Python

Calculate total and critical service and the current used by each option.

Check / Python

Reject the SHED_065 trial at about 111.01% of allowed current. Keep the passing SHED_075 trial eligible.

Refine / Llama, with a Python guard

Request bounded catalog changes and rank passing IDs. Python corrects the wrong cost order and rechecks the chosen plan.

Selected final service: about 1,843.61 kW total and 474.04 kW critical, at 91.87% current use. This is not L6's six-node MILP. Physical switching order and operating permissions remain outside the result.

Agent role map: Cyber: L10 four-bus DC archive

Read the case / Python

Read the measurements, alarm context and declared availability of assumed trusted channels.

Choose a trial / numerical tools and Llama

Prepare the permitted response candidates. Llama can request the initial evaluations or review.

Calculate / Python

Estimate state and calculate each candidate's branch flows and correction.

Check / Python

Test the trust condition, stated branch limits, bounds, evidence match and DC model scope.

Refine / Llama, with a Python guard

Request bounded trials including TRUSTED_QP. Python ranks only passing candidates and rechecks the selected correction.

Selected correction: about 0.121694 p.u., with predicted flow 0.17000 p.u. against the 0.18000 p.u. limit. The trusted readings are assumed, not authenticated. Human review is still separate from equipment dispatch.

Full sources

[**H00**] Classroom Labs notebook. Setup: COLAB_GUIDE.md; Classroom_Labs.ipynb. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/COLAB_GUIDE.md

[**B01**] . IEEE Communications Society: official resources and network presentation template. IEEE Communications Society. Reviewed 17 October 2026.

https://www.comsoc.org/about/brand-experience/resources

[**ST01**] Monica Lam. CS224V Agentic AI, Lecture 1: Introduction. Stanford University. Fall 2026.

https://web.stanford.edu/class/cs224v/lectures_2026/l-introduction.pdf

[**DEF03**] Erik S., Barry Zhang. Building effective agents. Anthropic Engineering. 2024-12-19.

https://www.anthropic.com/research/building-effective-agents

[**LR0**] Classroom Labs notebook and Python helper. L10B: Watch how Llama chooses a tool; src/llama_walkthrough.py. Public reproducible teaching material. 24 October 2026.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/src/llama_walkthrough.py

[**ST02**] Sina J. Semnani, Violet Z. Yao, Heidi C. Zhang, Monica S. Lam. WikiChat: Stopping the Hallucination of Large Language Model Chatbots by Few-Shot Grounding on Wikipedia. Findings of the Association for Computational Linguistics: EMNLP 2023, pp.2387-2413. December 2023.

https://aclanthology.org/2023.findings-emnlp.157/

[**H02**] Classroom Labs notebook. Classroom_Labs.ipynb, L2; cell classroom-007; src/continuous_control.py. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**ST03**] Harshit Joshi, Shicheng Liu, James Chen, Larsen Weigle, Monica Lam. Controllable and Reliable Knowledge-Intensive Task-Oriented Conversational Agents with Declarative Genie Worksheets. Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics, Volume 1: Long Papers, pp.27264-27308. July 2025.

https://aclanthology.org/2025.acl-long.1323/

[**H01**] Classroom Labs notebook. Classroom_Labs.ipynb, L0-L1; cells classroom-002 and classroom-004. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**H06**] Classroom Labs notebook. Classroom_Labs.ipynb, L6; cell classroom-018; src/standard_

formulations.py. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**H09**] Classroom Labs notebook. Classroom_Labs.ipynb, L9; cell classroom-026; fixed trusted-recovery fixture. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**H08**] Classroom Labs notebook. Classroom_Labs.ipynb, L8; cell classroom-023; four-bus DC fixture. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**H12**] Classroom Labs notebook. Classroom_Labs.ipynb, L12; cell classroom-033; simulated readback only. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**COL01**] Google Colaboratory. Frequently Asked Questions: Using Colab, notebook storage and execution state. Google Research. Reviewed 24 October 2026.

https://research.google.com/colaboratory/faq.html

[**VCASE**] Existing GridGuard workshop / SMART-DS synthetic-feeder extraction. Synthetic Greensboro feeder uhs20_1247-udt8894: model map and declared study scope. . Existing teaching snapshot reviewed 18 October 2026.

https://data.openei.org/submissions/2981

[**VMPC**] James B. Rawlings; David Q. Mayne; Moritz M. Diehl. Model Predictive Control: Theory, Computation, and Design, second edition. Nob Hill Publishing. 2017.

https://sites.engineering.ucsb.edu/~jbraw/mpc/MPC-book-2nd-edition-1st-printing.pdf

[**VSAC**] Tuomas Haarnoja; Aurick Zhou; Pieter Abbeel; Sergey Levine. Soft Actor-Critic: Off-Policy Maximum Entropy Deep Reinforcement Learning with a Stochastic Actor. Proceedings of the 35th International Conference on Machine Learning, PMLR 80, pp. 1861-1870. 2018.

https://proceedings.mlr.press/v80/haarnoja18b.html

[**LRV**] Workshop recorded model replies and numerical study records. Voltage P3_current_reserve: Llama 3.1:8b planner, recovery and review calls 1-3. Public teaching archive. 27 September 2026.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/results/continuous_llama_opendss_20260927T161223523552Z.json

[**OT01**] Keith Stouffer, Michael Pease, CheeYee Tang, Timothy Zimmerman, Victoria Pillitteri, Suzanne Lightman, Adam Hahn, Stephanie Saravia, Aslam Sherule, Michael Thompson. Guide to Operational

Technology (OT) Security. National Institute of Standards and Technology, NIST SP 800-82 Revision 3. September 2023 (final).

https://doi.org/10.6028/NIST.SP.800-82r3

[**H03**] Classroom Labs notebook. Classroom_Labs.ipynb, L3; cell classroom-010; archived test_01 context. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**H04**] Classroom Labs notebook. Classroom_Labs.ipynb, L4; cell classroom-013; fresh checks of archived choices. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**H05**] Classroom Labs notebook. Classroom_Labs.ipynb, L5; cell classroom-016; MV-only default model. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**RSTL01**] Ying Wang, Yin Xu, Jiaxu Li, Jinghan He, Xiaojun Wang. On the Radiality Constraints for Distribution System Restoration and Reconfiguration Problems. Author preprint, arXiv:1912.05185v3. 15 March2020(v3); first submitted11 December2019.

https://arxiv.org/abs/1912.05185v3

[**RSTL02**] Bo Chen, Chen Chen, Jianhui Wang, Karen L. Butler-Purry. Sequential Service Restoration for Unbalanced Distribution Systems and Microgrids. IEEE Transactions on Power Systems33(2),1507-1520. March2018.

https://doi.org/10.1109/TPWRS.2017.2720122

[**H07**] Classroom Labs notebook. Classroom_Labs.ipynb, L7; cell classroom-021; request/evidence binding. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**LRR**] Workshop recorded model replies and numerical study records. Feeder-catalog restoration: Llama 3.1:8b refinement and ranking calls 14-16. Public teaching archive. 27 September 2026.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/results/proposal_run_20260927T184402Z_53e0cf/llama_calls.json

[**CY01**] Fred C. Schweppe, J. Wildes. Power System Static-State Estimation, Part I: Exact Model. IEEE Transactions on Power Apparatus and Systems, PAS-89(1), pp. 120-125. January 1970.

https://doi.org/10.1109/TPAS.1970.292678

[**CY02**] Yao Liu, Peng Ning, Michael K. Reiter. False Data Injection Attacks against State Estimation in

Electric Power Grids. ACM Transactions on Information and System Security, 14(1), Article 13, 33 pages. May 2011.

https://doi.org/10.1145/1952982.1952995

[**LRC**] Workshop recorded model replies and numerical study records. Standard four-bus cyber study: Llama 3.1:8b tool selection and REVIEW calls 7-8. Public teaching archive. 21 September 2026.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/results/standard_stage_20260921T143826Z_42d19a61/llama_calls.json

[**H10**] Classroom Labs notebook. Classroom_Labs.ipynb, L10-L11; cells classroom-028 and classroom-030. Public notebook and Python source. 24 October 2026; stable notebook cell IDs checked.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/Classroom_Labs.ipynb

[**OLL1**] Ollama documentation maintainers. Structured Outputs: generating structured JSON with a schema. Official Ollama documentation. Reviewed 24 October 2026.

https://docs.ollama.com/capabilities/structured-outputs

[**WF01**] Alaa Selim and Mohamed Chehada. Five-role operator study workflow: implementation and recorded cases. GridGuard Agentic AI Tutorials, reproducible Python source and saved study archive. Implementation inspected 25 October 2026; records dated 27 September 2026.

https://github.com/AlaaSelim-sudo/GridGuard-Agentic-AI-Tutorials/blob/main/agentic_grid_workflow_tutorial/src/proposal_workflow.py

[**EVAL01**] National Institute of Standards and Technology. Artificial Intelligence Risk Management Framework (AI RMF 1.0). NIST AI 100-1. 26 January 2023.

https://doi.org/10.6028/NIST.AI.100-1