

NOISE ABATEMENT PROCEDURES

There are noise sensitive areas West and South of the Airport. Aircraft arriving over these areas must maintain at least 1,500 feet until crossing the Bayshore Freeway (US 101).

IFR DEPARTURES

Climb to 500 feet AGL before making any turns. Please give consideration to the residents living in the flight paths at Palo Alto Airport.

HIGH PERFORMANCE AIRCRAFT

Please use reduced power settings whenever possible to reduce noise impact.

- SAFETY ALWAYS SUPERSEDES NOISE ABATEMENT -





PALO ALTO AIRPORT



www.cityofpaloalto.org

GENERAL INFORMATION

Latitude: 37°27′40.03″ (37.461111°) North
Longitude: 122°06′54.16″ (122.115056°) West

Location: 0.5 NM East of Palo Alto, CA 94303

Field Elevation: 4 ft / 1.2m MSL (Estimated)

Pattern Altitude: 1000 ft MSL

Variation: **15 E (1995)**

Sectional Chart: San Francisco

AIRPORT LIGHTING

Runways 31/13 & Taxiways Lighted, PAPI

FREQUENCIES

 Tower (0700 - 2100):
 118.60
 Ground:
 125.00

 ATIS:
 135.275
 Unicom:
 122.95

 NORCAL Appr:
 120.10
 NUQ ASOS:
 124.175

 133.95
 PAO ASOS:
 N/A

134.50 Noise Abatement: N/A

NORCAL Depart: 121.30

AREA MAP

