



# CryptoChronicles

LessPM's Quest to a Passwordless Utopian Ecosystem

T-742-CSDA

Håvard Nordlie Mathisen

Reykjavik University

havard22@ru.is

*Instructor*

Jacky Mallet

Department of Computer Science

Reykjavik University

Match, 2023

# Executive Summary

Test[lol]

## Abstract

## Introduction

Polybius' *The Histories* [5] contains the first documented use of passwords, describing how the Romans employed “*watchwords*” to verify identities within the military. This provided a transparent, simple way to allow or deny entry to restricted areas of authorized personnel only. The story of secret writing (in this context referenced as cryptography) goes back the past 3000 years [2], where the need to protect and preserve privacy between two or more individuals blossomed.

Fernando J. Corbató is widely credited as the all-father of the first computer password when he was responsible for the Compatible Time-Sharing System (CTSS) in 1961 at MIT [4]. The system had a "LOGIN" command, which, when the user followed it by typing "PASSWORD", had its printing mechanism turned off to offer the applicant privacy while typing the password [1]. Given the long history of passwords and their importance, one could argue that it was a natural and judicious step in the evolution of computer systems.

In today's digital landscape, utilizing various identifiers (such as usernames, email addresses, or phone numbers) combined with passwords has become a prevalent method for verifying an individual's identity and ensuring their authorization to access restricted materials.

In 2004, a study titled "*The Memorability and Security of Passwords*" [9] was conducted into advising users on the entropy of passwords and ways someone can use to remember a or multiple passwords. A typical standard for larger organizations with a form of password creation system is to emphasize the diversity of smaller characters, capitalized characters, length, and not be commonly referred to in a dictionary [9]. The study analyzed the effectiveness of different password-creation strategies, suggesting that acronym-based passwords offer a delicate balance between memorability and security[9].

However, as technology has advanced, the limitations of password-based authentication have become increasingly apparent, leading to the development of more sophisticated methods like Universal Authentication Framework (UAF) [3] and WebAuthn[8] through the Fast IDentity Online Alliance (FIDO) and The World Wide Web Consortium (W3C).

WebAuthn, short for Web Authentication, is an open standard for web-based authentication that enables users to securely access online web services without relying on a traditional password. Through a collaborative effort between FIDO and W3C, WebAuthn is developed

to leverage asymmetric cryptography<sup>12</sup> and biometric or hardware-based authenticators to provide a more secure and robust authentication experience.

This report delves into the implementation of LessPM, a passwordless password manager that leverages WebAuthn to provide a secure authentication experience, free from the constraints of traditional passwords, while placing a strong emphasis on security. By examining recent advancements in authentication mechanisms and the related innovative potential of WebAuthn, we hope to illuminate the prospects of a passwordless future in digital security.

## Methodology

Exploring the development and implementation of LessPM, a passwordless password manager, our focus will be on the key components, technologies, and steps that form the system's development process. This section will discuss the WebAuthn standard, its effective integration and role in LessPM, and the various security measures contributing to a robust and reliable solution.

## WebAuthn

WebAuthn, short for Web Authentication, is a collaborative project between the FIDO Alliance and W3C that aims to implement a secure, robust, key-based authentication system for the web, to strongly authenticate users [8]. The concept relies on the use of a third-party device, called an Authenticator, which leverages asymmetric cryptography. These devices employ biometric or hardware-based mechanisms to provide a secure and reliable means of authenticating a user. For each user registering a key-pair, an identifier is generated [6, 7]

## Registration

In order to register in the system, the user (i.e. client, browser, phone, etc.) issues a registration request to a WebAuthn implemented server, called a Relying Party (RP), asking to be registered. The request contains a body with the relevant user identifier (i.e. username, phone number, email, etc.). There is no requirement in the standard to check whether the user identifier already exists in a persisted storage on the server<sup>3</sup>. The server responds by initiating a registration ceremony, responding to the client with relevant options to be stored in the client's credentials registry<sup>4</sup> with the necessary signed values from the Application

---

<sup>1</sup>Asymmetric cryptography uses a key pair consisting of public and private keys. The public key encrypts data, while the private key decrypts it. The keys are mathematically related, but deriving one from the other is infeasible, ensuring secure communication and data exchange.

<sup>2</sup>**Note:** According to the library used to implement jsonwebtokens in Rust it is the private key that encrypts and the public key is responsible for decrypting. *Last Accessed: 2023-03-25.*

<sup>3</sup>There is a requirement to check whether the credential identifier, generated by the authenticator device exists on the server. For further discussions on this topic, see section Future work

<sup>4</sup>In LessPM's case, this is the *navigator.credentials* API provided by the browser.

Programming Interface (API). When calling the API, the user is prompted to use their authenticator (i.e. phone)

The process can be seen in figure 1

## Conclusion

## Future work

Through implementing LessPM, we aimed to create a barebone implementation that could serve as a reliable Minimal Viable Product (MVP). However, we recognize that more work is needed to further enhance and compliment the product. The related topics to further improve LessPM are listed below and briefly discussed as a way to highlight potential drawbacks of the current version.

- ▶ **Authorization Headers**
- ▶ **AES Key Encryption for Password**
- ▶ **Hardcoded AES for JWT**
- ▶ **Encrypted Passkey**
- ▶ **Credential ID**

In its current implementation, LessPM supports a single registered authenticator per username to maintain a focused security approach. During registration, the server checks the database for an existing username similar to the incoming one and aborts the registration ceremony if a match is found. While WebAuthn permits users to have multiple authenticators, limiting this feature in the initial iteration of LessPM helps ensure a more controlled security environment. As the system evolves, considering the addition of support for multiple authenticators can be weighed against potential security risks and benefits.

## References

- [1] *CTSS Programmers Guide*. 2nd ed. MIT Press, 1965.
- [2] John F. Dooly. *History of Cryptography and Cryptanalysis: Codes, Ciphers, and Their Algorithms*. Springer, 2018, p. 5. ISBN: 978-3-319-90442-9.
- [3] FIDO Alliance. *FIDO UAF Overview*. <https://fidoalliance.org/specs/fido-uaf-v1.1-id-20170202/fido-uaf-overview-v1.1-id-20170202.html>. Accessed: 2023-03-25. Feb. 2017.
- [4] Steven Levy. *Hackers: Heroes of the Computer Revolution*. Sebastopol, CA: O'Reilly Media, 1984, pp. 85–102. ISBN: 978-1449388393.
- [5] Polybius. *The Histories*. Accessed on: March 23, 2023. 2023. URL: <http://www.perseus.tufts.edu/hopper/text?doc=Perseus%3Atext%3A1999.01.0234%3Abook%3D6%3Achapter%3D34>.
- [6] *Web Authentication: An API for accessing Public Key Credentials Level 2 - Credential ID*. <https://www.w3.org/TR/webauthn-2/#credential-id>. Accessed: 2023-03-25. World Wide Web Consortium, 2021.
- [7] *Web Authentication: An API for accessing Public Key Credentials Level 2 - PublicKeyCredential identifier slot*. <https://www.w3.org/TR/webauthn-2/#dom-publickeycredential-identifier-slot>. Accessed: 2023-03-25. World Wide Web Consortium, 2021.
- [8] World Wide Web Consortium. *Web Authentication: An API for accessing Public Key Credentials Level 2*. <https://www.w3.org/TR/webauthn-2/>. Accessed: 2023-03-25. Apr. 2021.
- [9] Jianxin Yan et al. *The Memorability and Security of Passwords: Some Empirical Results*. Tech. rep. UCAM-CL-TR-500. University of Cambridge, Computer Laboratory, Sept. 2000. URL: <https://www.cl.cam.ac.uk/techreports/UCAM-CL-TR-500.pdf>.