

PROCEDURE -- MEASUREMENT AT CHECK-IN

1. WHEN

Measure at check-in before any moorage agreement is signed; on any vessel substitution; whenever an applicant requests a length amendment and no haul-out sheet is offered; and whenever the Deputy Harbormaster directs a re-measurement.

2. EQUIPMENT

The District's steel measuring rail, stored in the counter cabinet. Check the calibration tag (annual) before use. The spare rail lives in the operations locker. A second person witnesses and reads the transom end.

3. METHOD

1. Vessel afloat at normal load, tied at the check-in dock.
2. Rail from the bow fitting (the farthest fixed structural point, excluding pulpits, anchors on rollers, and swim steps) to the transom edge.
3. Read to the nearest tenth of a foot. Record the measured value, not the rounded one, on the measurement block.
4. Beam at the widest fixed point; draft from the builder's plate or the most recent haul-out sheet, noted as such.
5. Both people initial the block; the measurer signs the certificate where a certificate is required.

4. ROUNDING AND BILLING

The billable length is the measured length rounded UP to the nearest whole foot (31.4 bills as 32). Where the posted slip length is greater, the slip length governs the foot-month charge. The measured value, the rounded value, and the billed value are all written on the agreement's measurement block -- an auditor should be able to follow the arithmetic without asking anyone.

5. CERTIFICATES

Where the measurement supports a length amendment under Resolution 2022-06 section 4.3, issue a measurement certificate (form MC-1): vessel, HIN, measured dimensions, method, date, place, measurer's signature. The certificate is filed with the applicant record the same day the amendment is keyed, and the register entry names it.