Predicting HDB monthly rent

Gold Miner (Group 12)

November 2026

Abstract

The target is the monthly rent of a Housing and Development Board (HDB) flat, in Singapore dollars (SGD). Labelled approvals run from January 2021 through March 2025. For the multistage model they are split by approval month into a training set, the labelled months through September 2024, a validation set, October through December 2024, and a test set, January through March 2025. Only the training set fits that model's parameters. Only the validation set stops or chooses it. The test set is scored after that choice and is not used to choose. The private test set is the unlabelled competition file after the labelled period. A private-test root-mean-square error (RMSE) did not stop or choose the multistage model. Other experiments use a six-month hold-out, a one-year hold-out, rolling folds, development folds, and a 17-month assessment. Those windows keep their own names. Core rental fields are cleaned and compared with nested means and a CatBoost baseline. Auxiliary columns from blocks, stations, schools, malls, certificate-of-entitlement (COE) premiums, and equities are audited and compared under locked CatBoost configurations. The multistage model estimates a town-month mean of rent per square metre with a per-town recurrent network, estimates the within-town unit-price gap twice, once with a per-town CatBoost and once with a per-town Gaussian mixture that do not see each other, and maps the mean, both gaps, floor area, and the flat's other features to monthly rent with one shared network. Its validation RMSE is 448.24 and its test RMSE is 462.87. The best private-test RMSE is 432.50, from add_mrt. Gold Miner (Group 12) is rank 21 after eight submissions. The latest submission scored a private-test RMSE of 441.46 and did not replace that best.

1 Introduction

The prediction target is monthly rent. The labelled approvals run from January 2021 through March 2025. This report uses four names for the multistage model, and it does not reuse those names for the other experiments.

The training set is every labelled month through September 2024. It is the only set that fits the multistage parameters. The validation set is October through December 2024. It is the only set that stops or chooses the multistage model. The test set is January through March 2025. It is scored after that choice, and it is not used to choose. The private test set is the unlabelled competition file after the labelled period. A private-test RMSE did not stop or choose the multistage model. Paths quoted for that file below start in April 2025. The file, as audited, also contains March 2025, so that calendar month appears in the labelled table and in the unlabelled file. March 2025 in the unlabelled file is not the test set.

A feature for an approval month uses only information already known before that approval. The six group-mean columns use labelled rents from the previous three approval months only. No other auxiliary column reads monthly rent. The recurrent network that estimates a town's unit-price path uses the time index and the economic trend already observed before the month being predicted. It does not receive that month's true rent, a previous predicted rent, or the true town-month rents of later months. Earlier economic inputs are carried by the hidden state. The sequence is started in 2021 so that the state already exists when a later month is predicted.

The multistage prediction follows from that split of information. The recurrent network traces the movement shared by flats in the same town. A flat's own location and attributes then explain how far its unit price sits from that path. Two models estimate that gap separately. One shared network combines the path, both gaps, and the flat's other numbers into one monthly rent.

The rest of the report keeps the audit, the exploratory figures, the core cleaning, the temporal baselines, and the rebuilt auxiliary comparisons as the main record. Section 2 describes the labelled rents. Section 3 records the cleaning of the core fields and the extra ranks used by the multistage model. Section 4 records how the auxiliary columns are built. Section 5 defines every scoring window and then reports the models that were fit. Section 6 states what those scores can support. The submitted score is in Section 7.

2 EDA

The labelled table has 150,000 rows. The private test set has 50,000 rows. Each file has the same ten input fields, and the labelled table also carries the target. Neither file has a missing cell. The labelled approval months are the 51 months from January 2021 through March 2025. The unlabelled file has 17 approval months, from March 2025 through July 2026. Table 1 is that audit. The two files also spell approval dates differently: labelled dates appear as strings such as `March-25`, and the unlabelled file uses strings such as `2025-03`. Parsing is part of the core cleaning in Section 3.

Table 1: Supplied core rental files. The unlabelled file is the private test set. It is not the test set of January–March 2025.

	Labelled table	Unlabelled file
Rows	150,000	50,000
Input fields	10	10
Missing cells	0	0
Approval period	Jan 2021–Mar 2025	Mar 2025–Jul 2026
Unique approval months	51	17

Among saved town and flat-type cells with at least 200 rentals, the median runs from 2000.00 SGD for a 2-room flat in Bukit Merah (303 records) to 4650.00 SGD for a 5-room flat in Central (200 records). These are composition-specific descriptive medians. They are not adjusted location effects. Figure 1 shows the median and the sample count together.

Figure 2 contrasts the raw monthly median rent with a mean residual from a descriptive ridge fit on the labelled rentals. The ridge uses area, log area, flat type, flat model, and town, and it does not use month. The residual is observed rent minus fitted rent, in SGD. The fit uses the labelled months through March 2025, so it is not a training-set-only fit and it is not an out-of-sample error.

The geographic display uses 8,134 blocks with at least five observed rentals. Each block contributes one plotted rent-per-area summary. The middle panel of Figure 3 counts distinct observed blocks in each spatial cell.

Figure 4 is the original dwelling panel. It compares area and lease-age bands by flat type, and it places flat-model median rent beside the sample count. Cells with fewer than 50 observations are masked, and their counts remain visible. The panel uses the labelled rentals from January 2021 through March 2025. Larger area, flat type, lease cohort, and flat model have to be read together with geography and month. They are not isolated causal premiums.




Figure 1: Town by flat type: median observed rent and sample count.




Figure 2: Monthly town distributions: raw rent and composition-adjusted residuals, with sample coverage. The residual is descriptive.




Figure 3: Block-level rent, counts of distinct observed blocks per spatial cell, and area.




Figure 4: Original dwelling attributes on the labelled rentals. Cells with fewer than 50 observations are masked. The panel is descriptive.

3 Features preprocessing: core rental fields

The raw labelled table and the private test set are left unchanged. Cleaning is applied afterwards, with the same functions on both files, so that a category has one representation. No row is removed unless there is clear evidence that it is invalid. At the end of this stage, none has been removed. Duplicate transactions and unusual rents stay in the data.

3.1 Categorical fields

The fields for town, block, street, flat type, flat model, and furnished status are stripped, lower-cased, and reduced to a single internal space. Street names are the largest inconsistency. The labelled data contain 1,146 raw street labels and 576 values after case and whitespace normalization. The unlabelled file falls from 1,129 raw labels to 573 normalized street names. The change rewrites 30,781 labelled rows and 10,482 unlabelled rows. It does not change the street those rows name.

Flat type has a second inconsistency: `4 room` and `4-room` name the same flat. One- to five-room labels are standardized to the hyphenated form by a deterministic rule. That reduces the labelled categories from 11 to 6 and modifies 35,331 labelled rows. The unlabelled file already uses the standardized names, so none of its rows change. Table 2 records the two main rewrites.

Table 2: Categorical standardization of the core fields.

Feature	Labelled before	Labelled after	Labelled rows changed	Unlabelled rows changed
Street	1,146	576	30,781	10,482
Flat type	11	6	35,331	0

Furnished status and the upfront fee are constant. Furnished status is yes on every labelled row and every row of the private test set. The fee is 0 on every row. Neither field varies. Both are removed from the cleaned modelling table used for the core baselines.

3.2 Time, building, and lease age

Approval dates are parsed into a year, a calendar month, and a month index. January 2021 has month index 0:

$$\text{month index} = 12(\text{approval year} - 2021) + (\text{approval month} - 1). \tag{1}$$

Labelled values run from 0 to 50. The private test set continues to 66, which is July 2026. September 2024 is 44. The index keeps chronological order. The year and the calendar month are kept as well, because a single continuous index does not by itself represent a within-year pattern.

A building identifier concatenates the normalized block and the normalized street. Block number alone is ambiguous, because the same number occurs on different streets. The labelled data have 9,406 buildings, and the unlabelled file has 8,940.

Lease age is the approval year minus the lease commencement year, so the same commencement year is a different age in 2021 and in 2025. One labelled row has a commencement year later than its approval year. That row is kept. An indicator is set, and only the derived lease age is stored as null. The private test set has no such row. After the derived time fields exist, the original approval-date string is dropped. Table 3 lists the derived core fields.

3.3 Ranks and keys used by the multistage model

The core baselines use the cleaned categories directly. The multistage model also uses a small set of derived keys and ranks. None of them reads monthly rent in order to build the flat-type rank. The same maps are applied to the labelled rows and to the private test set.

Table 3: Fields derived from the core rental columns.

Derived field	Source	Role
Approval year	approval date	long-run level
Approval month	approval date	calendar month
Month index	year and month	chronological order
Building	block and street	street-specific block
Lease age	approval year and lease year	age at approval
Invalid lease age	the one reversed pair	keep the row, null the age

The flat-type rank turns hyphens into spaces and maps 1-room through 5-room to 1 through 5 and executive to 6. Median floor area rises along that order, from about 31 square metres for a 1-room flat to about 144 for an executive flat. The rank is that size order. The flat-model rank is a fixed order from 0 through 19, from cheaper to dearer names in the labelled table. A separate key keeps the normalized flat-model name, so a tree can split on a subset of names. The mixture and the numeric network receive only the rank. The labelled table has 20 flat-model names. The private test set has 19 of them, and it has no name that is absent from the labelled table.

Town, block, and street keys strip, lower-case, and collapse spaces. They are names, not price ranks. The stored block key is the normalized block token only, and letters inside the block token are kept. The block-and-street string used to join the block file is a separate key. It is the building identifier above, and it is not stored as the block key. Lease commencement year stays a four-digit year and is not rewritten as a month index. Floor area and the fee amount stay in the units as recorded. They are not standardized on the combined labelled and unlabelled tables.

3.4 Duplicates, anomalies, and coverage

Duplicate rows are inspected and kept. The table records transactions, so two rows can share an approval month, a building, a flat type, and an area and still be distinct leases. The same predictors can also sit beside different rents, because the files do not record every tenancy-specific fact. Every unlabelled row needs one prediction and has to stay in its original position. Deleting a duplicate unlabelled row would break that alignment.

Floor area is checked for non-positive or implausible values, lease commencement is compared with the approval year, and labelled rents are checked for non-positive values. These checks mark rows for inspection. They are not deletion rules. A large or small rent is not treated as an error merely because it falls outside a generic interquartile fence. Housing rents vary with location, flat type, age, and time. A peer-rent diagnostic, when used, is computed after a chronological split and from the fitting portion's labels only. It is not an input feature, and no row is removed on the basis of it.

After normalization, the unlabelled file introduces no new value of town, street, flat type, or flat model. Eleven block labels are new, on 36 rows, and 50 building identifiers are new, on 102 rows. That is about 0.07% of unlabelled rows for a new block label and about 0.20% for a new building. The encoder has to accept an unseen category, and the mismatch is limited. Town and street still identify the flat when the building itself is new. Table 4 is the coverage count.

3.5 What may be learned before a split

Deterministic steps may be applied before any chronological split. Those steps are text normalization, flat-type standardization, date parsing, and the construction of the building identifier and lease age. Anything estimated from the data is fit on the fitting portion of that experiment only. Table 5 is the rule. It matters most for high-cardinality fields such as building, block,

Table 4: Categorical coverage after normalization. "Unseen" means a value present in the unlabelled file and absent from the labelled table.

Feature	Labelled unique	Unlabelled unique	Unseen values	Unlabelled rows
Town	26	26	0	0
Street	576	573	0	0
Flat type	6	6	0	0
Flat model	20	19	0	0
Block	2,720	2,660	11	36
Building	9,406	8,940	50	102

and street: if a later encoding uses rents, rents from the scored months of that experiment do not enter the encoding. The windows themselves are defined in Section 5. This table does not rename them.

Table 5: Which preprocessing steps may precede a chronological split.

Operation	Before the split?	Rule
Text normalization	Yes	deterministic
Flat-type standardization	Yes	deterministic
Date parsing	Yes	deterministic
Building and lease age	Yes	deterministic
Missing-value imputation	No	fitting portion only
Feature scaling	No	fitting portion only
Target encoding	No	fitting labels only
Historical mean rent	No	earlier fitting rows only
Target-based outlier statistics	No	fitting portion only

The cleaned files keep a log of the issue, the rule, the reason, and the number of affected rows. The private-test row order is preserved. The next stage attaches block, transport, amenity, and market columns without changing that order.

4 Auxiliary features preprocessing

Stations, schools, and malls have coordinates and no block number. The block table is the hub: it has an address and coordinates, and every later spatial column starts from that join. Saved auxiliary tables contain the new columns in source-row order. The original rental fields are concatenated back when a model is fit. Labelled rows and the private test set are joined by that order, and they are not sorted.

Two ledgers appear in the work, and they are not the same column list. The multistage model reads an auxiliary table of 94 columns in that row order. The rebuilt audit is a larger candidate ledger. It is the source of the locked CatBoost comparisons in Section 5. A count from one ledger is not the width of the other.

4.1 The rebuilt candidate audit

The rebuilt audit reconstructs candidates from the original rental inputs and from every field in the six supplied auxiliary files. The source ledger has 63 input-field positions: ten original rental fields and 53 auxiliary fields. The target is recorded separately. Furnished status and the fee are ignored, including derived indicators and interactions, which leaves 61 source positions for predictors, construction, joins, or metadata. Source names, URLs, and keys receive explicit roles. They are not labelled as causal rent factors.

The audit records 1,878 conceptual candidates, including 1,595 month-panel candidates. The compact rental table stores 492 candidate columns plus row, month, target, and provenance metadata. Individual-stock and adjusted-price candidates stay in the monthly panel and are reduced with training-month preprocessing, so the same macro vector is not copied onto every rental as if it were a flat-level measurement. The family ledger is a candidate universe, not the dimension of a fitted model. Table 6 counts the families.

Table 6: Rebuilt candidate families. These counts are the audit ledger, not the 94-column auxiliary table.

Candidate family	Columns
Block structure	5
Location	11
MRT	122
Schools	123
Malls	8
COE	164
Stocks	1200
Adjusted-price sensitivity	231
Original	14

The normalized town, block, and street key is checked as a many-to-one link, with rental row identity and order preserved. Block features retain latitude, longitude, postal and geographic labels, completion year, and maximum building floor. Ages, density, and location summaries are derived. The maximum floor is not the unit floor. Mass Rapid Transit (MRT) construction distinguishes code rows from deduplicated entities, open and planned snapshot status, line-code prefixes, interchange descriptors, distances, and radius counts. Schools include the observed primary, secondary, junior-college, and mixed-stage definitions, together with type, gender, session, address, and transport-text descriptors. Malls contribute identity, nearest distances, and radius counts. COE uses the supplied categories and rounds, with premium, prevailing premium, quota, bids, and derived differences and ratios. Stocks audit all 77 symbols and the open, high, low, close, adjusted-close, and volume fields. Adjusted-price descriptors are a separately labelled retrospective sensitivity. Figure 5 shows lagged monthly-return availability for those 77 symbols. A month is missing when the symbol has no return from the preceding completed month. The property basket used below is missing on early rows because one constituent starts later.

4.2 Block attributes and age

The rental row is left-joined to the block file on the normalized block concatenated with the normalized street. Normalization strips, lower-cases, and collapses spaces, and letters inside the block token are kept. The key matches every labelled row and every private-test row, and the row count does not change. The copied fields are latitude, longitude, postal code, with the token `NIL` stored as null, maximum floor, year of completion, subzone, planning area, and region. Building age is the approval year minus the completion year. Lease age uses the lease commencement year instead. A third column is the gap between those two ages, and a product of building age with a Central Region flag lets a linear model treat age differently in the centre. Town alone does not say whether the block is central, new, or tall, and the same completion year is a different age in 2021 and in 2026. Figure 6 shows the joined region and the age and floor distributions.





Figure 5: Lagged monthly-return availability for all 77 audited symbols. The property basket is missing on early rows because one constituent starts later.



(a) Region after the address join.

(b) Age at approval, and maximum floor.

Figure 6: Block attributes copied onto the rental rows.

4.3 MRT


Distances are great-circle kilometres with Earth radius 6,371 km. Two open-station pools are in the record, and they are not interchangeable.

The columns in the 94-column auxiliary table use an open trunk pool. A station is in that pool when its status is open and its code prefix is NS, NE, CC, DT, TE, EW, or CG. The two open Changi Airport (CG) stations are labelled EW. For each block the table stores the nearest trunk station's distance, code, normalized name, and line, the nearest station and distance on each of the six lines, and the number of trunk codes within 0.5, 1, and 2 km. Ties closer than 10^{-6} km keep the lexicographically smallest code. Planned stations, and prefixes CR, JE, JS, JW, and CP, stay in their own distance columns, so they cannot shrink the open-station distance. A flag is 1 when the nearest trunk station's name has at least two codes. The reason for the split is access. A flat near a station is easier to commute from, one distance does not say which corridor that station serves, and a count separates a single station from a cluster. Figure 7 shows that most rentals are within about 1 km of some trunk station, that 0.5 km is often empty, and that the North East Line is farther than the East–West Line. An interchange is counted once per code.


The rebuilt audit uses a wider open-distance pool: every supplied snapshot-open station entity, which can include LRT, rather than the trunk-prefix pool. Observed prefixes are not a verified external line taxonomy. Station-name and line-count descriptors may combine open and planned codes at one entity, and they are read only as snapshot descriptions. The add-MRT configuration in Section 5 belongs to that rebuilt comparison. It is not given a second definition here as the trunk-prefix columns.

4.4 Schools and malls


Primary schools are rows whose main level is primary: 179 schools. Secondary schools are the two strings for secondary years S1–S5 and S1–S4: 133 schools. Each set contributes a nearest distance, the normalized school name, and a count within 1 km. Primary schools also have a 2 km count. All 337 schools add one further nearest distance, name, and 1 km count. All 113 malls contribute the nearest distance, normalized name, and counts within 1 and 2 km. Names are kept because those tables have no code, and the normalized name is unique. Households pay for a short walk to a primary school or a shop, and a count distinguishes one neighbour from several. Figure 8 shows schools packed closer than malls, and many rentals with no mall inside 1 km.



(a) Nearest open trunk station.




(b) Trunk-line codes within 0.5, 1, and 2 km.




(c) Nearest station on each trunk line.

Figure 7: MRT access under the trunk-prefix pool. An interchange is counted once per code.



(a) Nearest primary school, secondary school, and mall.



(b) Counts within 1 km. Zero is a real zero.

Figure 8: Schools and malls around the labelled rentals.

4.5 Position inside the town

The number of other HDB blocks within 500 m uses the same block coordinates and excludes the block itself. The town centroid is the mean latitude and longitude of blocks in that town, and each block is measured to its own centroid. Distance to the central business district is the great-circle distance to the fixed Raffles Place coordinate (1.283889, 103.851389), taken from station codes `ns26` and `ew14`. A log of the nearest trunk distance, $\ln(d + 0.001)$, gives nearby changes more weight than a linear model would give the raw kilometres. Two flats in the same town can still sit at the edge or next to downtown. These density columns do not use rent. Cluster labels were not adopted. The official areas already exist, and clustering on rent would put the target into the features.

4.6 COE, stocks, and recent local rents

COE amounts are parsed by stripping dollar signs and commas. Each category-month uses bidding round 2, or round 1 when round 2 is absent. A rental in month T receives the premium,

the change from $T-2$ to $T-1$, and bids divided by quota, all from month $T-1$. Categories A, B, and E have those three columns. Category A also has the mean of $T-1$, $T-2$, and $T-3$. Category C has only the lagged premium. The four COE premiums are correlated about 0.93 with each other. The region model in Section 5.3 therefore keeps one premium.

Stock features in this auxiliary table use month-end adjusted closes. The bank basket is the equal-weight mean of `D05.SI`, `O39.SI`, and `U11.SI`. The property basket is `C09.SI`, `U14.SI`, and `9CI.SI`. A month is used only when all three symbols have a close. The rental again sees month $T-1$, both as a level and as that month's return. Dearer car quotas or weaker bank shares may coincide with tighter household budgets, which floor area and town cannot express. Figure 9 shows that both series are constant across flats approved in the same month. January 2021 COE lags are null because December 2020 is absent.



(a) Lagged COE premium. (b) Lagged bank and property baskets.

Figure 9: Month-level series shared by every flat approved in that month.

Six columns are target encodings of recent rent. The groups are the first two digits of the postal code, the legacy district implied by those digits, the nearest mall name, the nearest open MRT code, the nearest primary-school name, and the nearest secondary-school name. The sector and district strings are not stored. For a row in month T, only labelled rents from $T-1$, $T-2$, and $T-3$ are used:

$$\frac{n\,\bar{r}_g + 20\,\bar{r}}{n+20}. \tag{2}$$

Here $\bar{r}_g$ is the group mean inside that window, n is the number of those labelled rows, and $\bar{r}$ is the island-wide mean inside the same three months. If $n=0$, the value is $\bar{r}$. January 2021 has none of those months in the file, so all six columns are null. February 2021 uses January only. Rows in the private test set never contribute rents. The strength 20 is fixed and was not tuned. A mean accumulated since 2021 would still carry old rent levels into 2025, while the previous quarter moves with the market. Shrinkage keeps a thin quarter from being dominated by a few leases. A mall mean is the mean of rentals for which that mall is the nearest mall, not every flat inside a radius.

Month-by-group heatmaps draw Equation (2) even when that month has no rental in the group. A cell is blank only when the three-month window contains no labelled rents. Maps on a street background do the same for each June and December whose window overlaps the labelled months. Each land cell takes the colour of its single nearest mall, primary school, or open MRT station, and each map has its own colour scale. Figure 10 is the June 2025 MRT map. Its window is March, April, and May 2025. The labelled table ends in March 2025, so the colours use March 2025 rents only. A darker patch is the service area of one station whose recent rents were higher. The scale belongs to this map alone.

4.7 Limits of the columns

- The maximum floor is the top floor of the block, not the flat's own floor. Values of -1 on floor and completion year are sentinels and are stored as null: 159 labelled rows, and none in the private test set.




Figure 10: Nearest open MRT station, June 2025. Colour is the smoothed mean of labelled rents in the previous three months for that station. Each area is one station. The labelled table ends in March 2025, so the colours use March 2025 rents only.

- The MRT file has no opening date. A station marked open may have opened after January 2021. In the trunk-prefix columns, planned stations and future-line prefixes stay out of the open-station distance.
- About 20 MRT longitudes have only one to three decimal places. Switching from the great-circle formula to a projected coordinate system does not repair that.
- Great-circle distance is not walking time. School and mall tables have no opening dates, and the school table has no university.
- COE and stock columns are constant within an approval month. January 2021 COE lags are null because December 2020 is missing. The property basket is missing on early labelled rows because one constituent starts later.
- Group means are target encodings of the previous three months of labelled rents. They are not properties of a mall, a station, or a school. January 2021 is null. A mall mean covers rentals for which that mall is the nearest mall, not every flat inside a radius.
- Empty postal codes, 285 blocks, have no postal-sector group and fall back to that quarter's island-wide mean once the three-month window contains any labelled rent.

5 Models

Three models were fit. Model 1 is a core CatBoost on the cleaned rental fields, with nested means, a random hold-out of the same size, and rolling one-year folds. Model 2 is the rebuilt auxiliary CatBoost, under development folds and a 17-month assessment, with ridge checks

beside it. Model 3 is the multistage stack. The best private-test result is add_mrt. Each model is stated as a motivation, a structure, and a performance. Section 5.4 compares them after those three accounts. Table 7 names the windows before any score is quoted. A score belongs to the window in its row.

Table 7: Time windows. The first four rows are the only names used for the multistage model. Later rows are separate experiments.

Name	Definition
Training set	Labelled months through September 2024. The only months that fit multistage parameters.
Validation set	October–December 2024. The only months that stop or choose the multistage model.
Test set	January–March 2025. Scored after that choice.
Private test set	Unlabelled competition file after the labelled period. A private-test RMSE did not stop or choose the multistage model.
Six-month hold-out	Fit January 2021–September 2024 (132,802 rows). Score October 2024–March 2025 (17,198 rows). Core baselines.
One-year hold-out	Fit January 2021–March 2024 (114,842 rows). Score April 2024–March 2025 (35,158 rows).
Rolling folds	Three expanding fits. Each scores the next April–March year. Table 10.
Development folds	Fit through April 2022, October 2022, and April 2023. Score the next six months: May–October 2022, November 2022–April 2023, and May–October 2023. The development pooled RMSE combines squared error and row count across the three folds.
17-month assessment	Fit through October 2023. Score November 2023–March 2025.

The six-month hold-out fits on the same months as the training set. Its 17,198 scored rows are the validation set and the test set placed end to end. The one-year hold-out and the 17-month assessment cut the timeline in other places. Development folds end in October 2023, so their scored months lie inside the months of the training set, and they are not the validation set.

5.1 Model 1: Core CatBoost

5.1.1 Motivation

The competition file is mostly a later period than the labelled table. March 2025 is the only overlapping calendar month. A model that is judged on a random mix of years can look accurate while missing the shift it will face on a later month. Model 1 therefore fits on earlier approval months and scores later ones. A boosted tree is a reasonable next step after the nested means: flat type, town, time, and area interact, and the tree can split on a street or a flat model without a hand-built interaction list.

5.1.2 Structure

The comparison uses the six-month hold-out. Four predictors are nested. The global mean predicts the mean rent of the fitting portion for every scored row. The town mean replaces that with the fitting-portion mean of the same town. The town and flat-type mean uses the fitting-portion mean of that pair, and it falls back to the town mean and then the global mean when the pair is unseen. All of those means use the fitting portion only. The fourth predictor is a CatBoost regressor on the original property attributes and the derived time and age fields. Categories are passed to the tree directly. The tree uses 600 iterations, learning rate 0.05, depth 8, and random seed 42. The time fields are approval year, calendar month, and the month index in Equation (1). Sine and cosine of the calendar month were added on the three rolling folds,

so that December and January become neighbours in that pair of features. The pair did not lower the rolling-fold RMSE on any fold, and the features were not kept. Calendar month itself stays through the numerical month. The fold-level cyclical numbers are in Appendix A.

5.1.3 Performance

Table 8 is the six-month hold-out. On that six-month hold-out, town alone moves RMSE only from 795.76 to 778.62, town and flat type together move it to 565.58, and CatBoost reaches 454.29. Relative to the global mean, that is a reduction of about 42.9% in six-month hold-out RMSE. The interaction of property type, location, time, and the other dwelling fields carries information that the historical averages do not.

Table 8: Core baselines on the six-month hold-out, October 2024–March 2025, after a fit through September 2024. Six-month hold-out RMSE is in SGD of monthly rent.

Model	RMSE
Global mean	795.76
Town mean	778.62
Town + flat type mean	565.58
CatBoost	454.29

The same CatBoost configuration was also scored on a random hold-out with the same number of fitting rows and the same number of scored rows. Table 9 compares the two schemes. The random hold-out has RMSE 476.25, about 22 SGD higher than the six-month hold-out RMSE of 454.29. The chronological split was kept because its information flow matches a later scoring period, not because it produces a lower number. The mean errors differ in a more specific way. Mean error is predicted rent minus observed rent. The random hold-out has mean error −6.64. The six-month hold-out has mean error −36.29: the model underpredicts later rents by about 36 SGD on average. Mixing all years hides part of that bias.

Table 9: Core CatBoost on a chronological six-month hold-out and on a random hold-out of the same size. RMSE is the six-month hold-out RMSE or the random-hold-out RMSE, in SGD of monthly rent. Mean error is predicted minus observed rent, in SGD.

Scheme	RMSE	Mean error
Six-month hold-out	454.29	−36.29
Random hold-out	476.25	−6.64

Rolling one-year folds. One hold-out can be an accident of the months it covers. Three expanding folds each score a full April–March year, so every calendar month appears once in the scored year. Table 10 is the result for the same core CatBoost. Rolling-fold RMSE falls from 719.52 to 599.59 to 477.47. The mean errors are −370.41, −146.57, and −35.74. The earliest fit underpredicts the next year by a large margin. The latest fold is much closer to zero mean error. The rental level moved across years, and one pooled cross-validation number would hide that movement. The most recent one-year fold is the primary long window for Model 1. The earlier folds are the robustness check. Fold 3 scores April 2024 through March 2025 after a fit through March 2024. That scored year mixes months which, under the multistage names, sit in the training set, the validation set, and the test set. The one-year hold-out RMSE of 477.47 belongs to Model 1. It is not a validation RMSE and it is not a test RMSE.

The year-to-year change in Table 10 is much larger than the change from the cyclical pair, which is why that pair was dropped in Section 5.1.

Table 10: Expanding-window core CatBoost on the rolling folds. Each scored period is one April–March year. Rolling-fold RMSE is in SGD of monthly rent.

Fold	Fit	Scored	Fit rows	Scored rows	RMSE
1	Jan 2021–Mar 2022	Apr 2022–Mar 2023	46,756	32,204	719.52
2	Jan 2021–Mar 2023	Apr 2023–Mar 2024	78,960	35,882	599.59
3	Jan 2021–Mar 2024	Apr 2024–Mar 2025	114,842	35,158	477.47

Where the model errs. On the six-month hold-out, monthly CatBoost RMSE stays between 438.22 and 471.08 (Table 11). Mean error is negative in every month, and the underprediction is larger again in February and March 2025. That pattern agrees with the rolling folds: forward prediction is sensitive to the level of the market. The monthly table does not by itself identify why the level moved.

Table 11: Monthly core CatBoost errors on the six-month hold-out. Six-month hold-out RMSE and MAE are in SGD of monthly rent. Mean error is predicted minus observed rent, in SGD.

Month	RMSE	MAE	Mean error
Oct 2024	438.22	326.54	−35.05
Nov 2024	464.91	330.08	−22.80
Dec 2024	447.66	325.29	−18.14
Jan 2025	471.08	346.60	−37.51
Feb 2025	453.18	338.46	−48.63
Mar 2025	449.69	332.37	−53.33

Errors also differ by flat type (Table 12). Among types with a substantial count, executive flats have the highest six-month hold-out RMSE, then 5-room flats. The 1-room row has seven scored leases and is not interpreted. The executive gap is one reason to look at building and location information beyond flat type.

Table 12: Core CatBoost errors by flat type on the six-month hold-out. RMSE is the six-month hold-out RMSE, in SGD of monthly rent.

Flat type	Scored rows	RMSE	MAE
Executive	852	537.59	394.18
5-room	3,908	471.58	334.12
4-room	6,268	456.66	335.12
2-room	476	434.03	312.54
3-room	5,687	426.74	323.41
1-room	7	461.55	428.94

Table 13 is a diagnostic of this fitted baseline, not a causal ranking. Flat type, the month index, and town account for most of the reported importance. The month index agrees with the temporal-shift results: time is part of the hold-out design, not only another covariate. Several columns encode related facts, so the shares are not independent effects. The importance names are the names recorded for this preliminary model. Furnished status and the fee received zero importance here, which agrees with the audit that both are constant.

5.2 Model 2: Auxiliary CatBoost

5.2.1 Motivation

Model 2 asks whether the auxiliary families lower the development pooled RMSE or the 17-month RMSE once dwelling, address, and calendar fields are already present. It keeps the same tree family as Model 1 and changes the column set.

Table 13: Leading feature importances in the preliminary core CatBoost.

Feature	Importance
FLAT_TYPE	28.04
MONTH_INDEX	22.62
TOWN	16.69
FLOOR_AREA_SQM	7.62
STREET	5.27
LEASE_COMMENCE_DATE	4.71
FLAT_MODEL	4.71
FLAT_AGE	3.13
BLOCK	2.92
RENT_YEAR	2.32
RENT_MONTH	1.99

5.2.2 Structure

All tree configurations share one recorded hyperparameter setting. Mean and ridge checks use the same windows. A positive addition is the original-address RMSE minus the augmented RMSE on the same window. A positive removal cost is the ablated RMSE minus the full-model RMSE on that same window. Those windows are the development pooled RMSE and the 17-month RMSE. The development pooled RMSE combines squared error and row count across the three development folds. It is not the average of three development-fold RMSE values.

Two macro timings are reported. Cutoff-frozen holds the scored months' macro descriptors at the feature vector available at the preceding cutoff. Provided-lagged conditions each rental month on supplied observations from the preceding completed month. Provided-lagged is a batch setting in which that lag is available. Missing source observations are left missing. Stock principal components are learned with one row per fitting month, not with the rental row repeated once per flat.

Before the configuration table, each numeric spatial exposure was screened on its own, on development data through October 2023, after controls for area, log area, lease age, flat type, flat model, town, and approval-month fixed effects. The exposures are not entered jointly. Intervals are clustered by address. The coefficients in Table 14 are SGD per original feature unit. They are conditional associations. They are not causal premiums for a facility: unit floor, renovation, household composition, and other neighbourhood differences can remain. Building age's interval includes zero. Distance to the central business district, to an open MRT station, and to a mall have negative intervals. The two secondary-school definitions do not share a sign. Figure 11 shows zero-centred adjusted-rent residuals in quantile bins of distance, without adding back a baseline rent and without choosing a reference band. The pointwise address-cluster intervals omit uncertainty from the control fit.

Table 14: Conditional associations on development data through October 2023. Each spatial column is entered separately. Intervals cluster by address. Units are SGD per original feature unit.

Spatial variable (unit)	SGD per unit	95% interval
Maximum block floor (floor)	+6.49	[5.25, 7.73]
Building age (year)	−1.36	[−4.86, 2.13]
CBD distance (km)	−31.22	[−37.04, −25.40]
Open MRT distance (km)	−132.52	[−147.89, −117.16]
Mall distance (km)	−97.26	[−109.04, −85.49]
Primary distance (km)	−22.50	[−42.27, −2.74]
Secondary S1–S4 (km)	−36.82	[−43.30, −30.35]
Secondary S1–S5 (km)	+19.22	[4.72, 33.71]




Figure 11: Zero-centred adjusted-rent residuals by distance bin, on the development screen. The curves do not add back baseline rent.

5.2.3 Performance

Tables 15 and 16 are the locked CatBoost configurations. Among the predefined main CatBoost configurations, excluding the retrospective adjusted-price sensitivity, the lowest development pooled RMSE belongs to add-MRT. That ranking uses the development results only. On the 17-month assessment, add-MRT has 17-month RMSE 499.53 and original plus address has 17-month RMSE 501.83. All-auxiliary has a higher 17-month RMSE in both macro timings: 517.51 cutoff-frozen and 553.50 provided-lagged. The add-MRT row does not depend on the macro timing, and it is the same number in both tables. Ridge all-auxiliary has a lower development pooled RMSE than add-MRT. The development ranking quoted above is the CatBoost ranking, not a ranking across model families. The 17-month assessment fits through October 2023. That 17-month RMSE is not comparable with the six-month hold-out RMSE of 454.29, which fits through September 2024.

Table 15: Cutoff-frozen macro. The development pooled RMSE combines squared error and row count across the three development folds. The 17-month assessment fits through October 2023 and scores November 2023–March 2025. The 17-month RMSE is not the six-month hold-out. Adjusted-price sensitivity is retrospective and is excluded from the CatBoost ranking.

Configuration	Dev. pooled RMSE	17-month RMSE
Training mean	939.64	894.19
Ridge, original + address	632.91	677.64
Ridge, all auxiliary	615.95	544.21
Original dwelling	640.49	509.53
Original + address	627.84	501.83
All main auxiliary	631.09	517.51
Add MRT	622.58	499.53
Adjusted-price sensitivity	640.58	520.05

Figure 12 draws the addition and the removal of families under both macro timings. Figure 13 is the monthly error on the 17-month assessment. Figure 14 shows leading attributions of the fitted full model on the recorded assessment sample. They locate predictive signal in dwelling attributes, calendar, and location. They are attributions of that fit, not a causal decomposition.

Table 16: Provided-lagged macro. Windows match Table 15. Configurations that do not use the macro timing match that table.

Configuration	Dev. pooled RMSE	17-month RMSE
Training mean	939.64	894.19
Ridge, original + address	632.91	677.64
Ridge, all auxiliary	613.40	509.29
Original dwelling	640.49	509.53
Original + address	627.84	501.83
All main auxiliary	643.79	553.50
Add MRT	622.58	499.53
Adjusted-price sensitivity	661.29	549.25




Figure 12: Family additions and removals. A positive addition is the original-address RMSE minus the augmented RMSE on the same window. A positive removal cost is the ablated RMSE minus the full-model RMSE on that same window. The development pooled RMSE combines squared error and row count. The lower panels are the 17-month assessment.




Figure 13: Monthly error on the 17-month assessment, November 2023–March 2025, after a fit through October 2023.




Figure 14: Leading full-model attributions on the recorded assessment sample.

5.3 Model 3: Multistage model

5.3.1 Motivation

Model 3 is the multistage stack. It separates a town-month path from the within-town gap, and then converts both into monthly rent. The motivation is the Model 1 result that town, flat type, and the month index already carry most of the baseline importance, while a single town mean is still a weak predictor of the flat. Flats in one town move together through the month, and a flat's own site and type explain the rest. A recurrent network is a reasonable model of the shared path because the path is an ordered series and the hidden state can carry the economic inputs already observed before the month being predicted. A tree is a reasonable model of one gap because the within-town columns include names and codes. A Gaussian mixture is a reasonable model of the other gap because the remaining difference still varies smoothly inside the town. The two gap models are fit separately and do not see each other, so the shared network receives two estimates of the same residual rather than one estimate passed through the other. One shared network, not one network per town, maps those pieces to monthly rent.

Why the region is a town. A partition check compared five geographic units as the cell of a month mean, on the training set. A cell is one geographic unit in one approval month. Table 17 is that count. Town has no missing rows. A typical town-month cell has about 110 flats, and 5.9% of town-month cells have fewer than 30. Planning areas are thinner. Postal districts and postal sectors also drop 4,685 rows with no postal code. Postal sectors then have a median of 34 rows, and 43.5% of their cells are under 30. Town is fine enough that towns differ, and it is still large enough that a typical cell is not a handful of leases.

Table 17: Cells in the training set. A cell is one geographic unit in one approval month. "Under 30" is the share of cells with fewer than 30 flats.

Unit	Groups	Missing rows	Cells	Median rows	Under 30
Region	5	0	225	638	0%
Town	26	0	1,170	110.5	5.9%
Planning area	31	0	1,341	96	19.2%
Postal district	24	4,685	1,035	78	25.7%
Postal sector	53	4,685	2,261	34	43.5%

Figure 15 is the observed town mean of rent per square metre in May 2024. The colour is that observed mean, not a forecast, and the map was not scored. Central and southern towns are darker than the north and west, so the town mean is not one island-wide number.




Figure 15: May 2024 mean of rent per square metre by town. Each patch is the town of the nearest HDB block. The colour is the unweighted mean of the flats approved in that month. The map was not scored.

Table 18 is a ridge of the town-month mean of monthly rent, in SGD, weighted by the cell. Town indicators plus a month index leave a large dollar cell RMSE on both the validation set and the test set. Adding the category-C COE premium and the bank-basket level removes most of that dollar cell RMSE. Adding the property-basket level lowers the validation cell RMSE further, from 94.37 to 93.36, and lowers the test cell RMSE from 112.85 to 103.31. Using all 15 COE and stock columns, including changes, bid ratios, and returns, raises the validation cell RMSE to 104.81 and the test cell RMSE to 229.70. Month-to-month COE changes and bid ratios alone do not beat the month index on the validation cell RMSE or the test cell RMSE. A separate month slope for each town was worse than one shared slope. The economy inputs adopted for the region mean are therefore the month index and those three level series. These figures are dollar cell RMSEs of the town-month mean of monthly rent. They are not the per-square-metre cell RMSEs of the recurrent network reported below.

Table 18: Weighted cell RMSE of the town-month mean of monthly rent, in SGD. The validation set is October–December 2024. The test set is January–March 2025 and did not choose the specification. These are dollar cell RMSEs, not per-square-metre cell RMSEs.

Specification	Validation	Test
Town and month index	291.65	366.09
Plus COE C premium and bank basket	94.37	112.85
Plus property basket	93.36	103.31
All 15 COE and stock columns	104.81	229.70

5.3.2 Structure

Figure 16 is the architecture.




Figure 16: Multistage prediction. The recurrent network estimates the town-month rent per square metre. CatBoost and the Gaussian mixture are fit separately and estimate the unit-price gap from that mean. One shared multilayer perceptron receives the mean, both gaps, floor area, and the flat's other features, and it outputs monthly rent.

Region mean. The region model predicts the town-month mean of rent per square metre, monthly rent divided by floor area, with equal weight per flat. Each town has its own network. The network is a recurrent net with hidden size 16, three layers, and a tanh nonlinearity, followed by a linear map from 16 units to one output. The input is the time index and the economic trend already observed before the month being predicted. The network does not see the true subsequent town-month rents. The hidden state carries the earlier economic inputs. Running the sequence from 2021 is required: a zero initial state would drop that history. The training schedule is in Appendix B.

Within-town gap. CatBoost and a Gaussian mixture are fit separately, one pair per town, to the same target: unit rent minus the recurrent-network town-month unit mean. Neither model sees the other's output. The mixture is a full-covariance Gaussian mixture in five dimensions: latitude and longitude standardized inside the town, flat-type rank and flat-model rank standardized inside the town, and the per-square-metre residual. The residual is a coordinate. It may be negative, so a component can sit below the region mean. The prediction is the responsibility-weighted conditional mean of that residual given the location and the two ranks. It is not a probability multiplied by the region mean. The component-count rule, the tree's column list, and the earlier dollar location check are in Appendix C. Both gap predictions are turned back into a monthly rent by adding the gap to the recurrent-network mean and multiplying by floor area. Both gaps are then passed to the shared network.

Figure 17 is Bukit Panjang, drawn from the saved stack mixture. The town kept six components. The surface is the mixture's conditional per-square-metre gap at that town's mean flat-type rank and mean flat-model rank. It is the predicted gap from the region mean, not the rent itself. December 2024 points are that month's unit rent minus Bukit Panjang's true December unit mean. The true December mean is 30.19 SGD per square metre, and the recurrent-network region mean is 30.71. A point and the cell under it do not use the same baseline. The point uses the true December mean. The surface uses the predicted gap from the region mean. The colour scale is shared across towns, symmetric about zero, at the 98th percentile of absolute values. A cell more than 400 m from a flat in the training set is blank. The figure was not scored.




Figure 17: Bukit Panjang. The surface is the conditional per-square-metre gap at the town's mean flat ranks. December 2024 points are unit rent minus that town's true December unit mean, 30.19 SGD per square metre. The recurrent-network region mean for that month is 30.71. Cells farther than 400 m from a flat in the training set are blank. The figure was not scored.

The shared network. One multilayer perceptron sees every town. It is not trained separately by town. The town-specific pieces it receives are the recurrent-network mean, the CatBoost gap, and the mixture gap, together with floor area and the flat's other features. The network has a linear map to 128 units, a ReLU, dropout 0.1, a linear map to 64 units, a ReLU, dropout 0.1, and a linear map to one output. The output is monthly rent. Floor area is not applied again after the network. The input list and the optimiser are in Appendix C. The six group-mean columns are not among those inputs. A different 40-column CatBoost keeps five of them. That model is not the town stage, and the stack does not replace it.

5.3.3 Performance

Weighted cell RMSE of the unit-price mean is 0.9707 on the validation set and 1.0897 on the test set. The weights are the number of flats in the cell. These validation and test figures are per-square-metre cell RMSEs of the town-month unit-price mean. They are not the flat-level RMSE of monthly rent, and they are not comparable with a dollar cell RMSE. The test-set per-square-metre cell RMSE did not choose the network.

Table 19 records the flat-level validation RMSE and test RMSE of the two gap models after the gap is added back to the recurrent-network mean and multiplied by floor area. The per-square-metre columns and the rent columns are the same predictions expressed in two units. They are not the validation or test per-square-metre cell RMSE of the region mean. On the validation set, the town CatBoost has a lower validation rent RMSE than the mixture. On the

test set, it has a lower test rent RMSE than the mixture. The test set did not choose either model.

Table 19: Flat-level RMSE after adding the predicted gap to the recurrent-network unit mean. The rent columns multiply that unit price by floor area. The validation set is October–December 2024. The test set is January–March 2025 and did not choose either model.

	SGD per square metre		Monthly rent, SGD	
Model	Validation	Test	Validation	Test
CatBoost	5.3811	5.4562	455.06	469.19
Mixture	5.7707	5.8380	490.02	502.48

Training runs for at most 100 epochs. After each epoch the validation RMSE of monthly rent is computed. If that RMSE does not fall by more than 10^{-6} for 10 consecutive epochs, training stops and the weights from the best validation epoch are restored. The kept run stops at epoch 8. Validation RMSE is 448.24. Test RMSE is 462.87. Training RMSE on the training set is 461.25. The test set did not choose the epoch. A private-test RMSE did not choose it either. On the validation set, the validation RMSE 448.24 is lower than either gap model's validation rent RMSE in Table 19. On the test set, the test RMSE 462.87 is lower than either gap model's test rent RMSE in that table. The CatBoost gap on the training set is the saved full model's prediction on its own training rows, because out-of-fold vectors were not stored. Validation, test, and private-test CatBoost features are that same full model applied to those rows.

5.4 Comparison

Table 20 keeps two windows only: the validation set and the private test set. The validation sets are not the same cut of months. Model 1 scores October 2024 through March 2025 after a fit through September 2024. Model 2 scores November 2023 through March 2025 after a fit through October 2023. Model 3 scores October through December 2024 after a fit through September 2024, and that validation RMSE is the one that stops the model.

Table 20: Comparison of monthly-rent RMSE, in SGD. The window is either the validation set or the private test set. Those validation sets are defined separately above. The best private-test RMSE is 432.50, from add_mrt. The row 451.26 is an earlier private-test submission.

Model	Window	RMSE
Model 1, global mean	Validation set	795.76
Model 1, town mean	Validation set	778.62
Model 1, town + flat type	Validation set	565.58
Model 1, CatBoost	Validation set	454.29
Model 2, original + address	Validation set	501.83
Model 2, add_mrt	Validation set	499.53
Model 2, all auxiliary, cutoff-frozen	Validation set	517.51
Model 2, all auxiliary, provided-lagged	Validation set	553.50
Model 3	Validation set	448.24
Model 3	Private test set	451.26
Model 2, add_mrt	Private test set	432.50

On the validation set, Model 1's CatBoost RMSE is 454.29, against 795.76 for the global mean, 778.62 for the town mean, and 565.58 for the town and flat-type mean. Model 2's add_mrt validation RMSE is 499.53, a small improvement on original plus address at 501.83, while both all-auxiliary rows are higher. Model 3's validation RMSE is 448.24, and that is the score that chose its epoch. On the private test set, add_mrt has RMSE 432.50. That is the best private-test

RMSE. Gold Miner (Group 12) is rank 21 after eight submissions. The latest submission scored a private-test RMSE of 441.46 and did not replace that best. Model 3's earlier private-test submission scored 451.26. A private-test RMSE is not the validation RMSE of another row, and it did not choose Model 3's epoch.

6 Limits and discussion

The column limits in Section 4.7 still apply to every model that uses those columns. Great-circle distance is not walking time, opening dates are missing, and a group mean is a lagged rent rather than an attribute of the nearest school or station. Furnished status and the fee do not vary. They were removed from the core modelling table. The fee name still occurs in the shared network's input list, and the value is 0 on every row, so that column carries no variation.

Scores from different windows do not rank the models. The six-month hold-out RMSE of 454.29 and the computed multistage pool of 455.89 share the calendar months October 2024 through March 2025, and both fits can use months through September 2024. They are still different procedures, and neither number is a private-test RMSE. The multistage epoch was chosen on the validation set, October–December 2024, where the validation RMSE is 448.24. The six-month hold-out RMSE is one evaluation of a fixed tree on all 17,198 rows. The one-year hold-out RMSE of 477.47 fits only through March 2024 and scores a full year. The 17-month add-MRT RMSE of 499.53 fits through October 2023. A lower number on an easier or later cutoff is not evidence that one family dominates the other. The best private-test RMSE is 432.50, from add_mrt. A private-test score is not comparable with a validation RMSE or a test RMSE as if they were the same split. That private-test score did not choose Model 3's epoch. An earlier private-test submission scored 451.26. It is no longer the best and no longer the latest. The latest submission scored a private-test RMSE of 441.46 and did not replace the best.

Inside the rebuilt CatBoost comparison, adding every auxiliary family did not lower the 17-month RMSE relative to original plus address. Add-MRT did, by a small margin on that 17-month assessment, and it was the best predefined main CatBoost configuration on the development pooled RMSE. The conditional distance screen is an association after controls. It is not the selection rule, and the two secondary-school codings do not agree in sign.

The region mean uses a tanh hidden state, so it cannot grow without a bound. On the private test set the multistage network's cross-town unit-price mean stays near 35.99 in April 2025 and 35.79 in July 2026. A linear bypass can keep a slope past the training set. The comparisons that were run still favoured the recurrent network. On the dollar town-month mean, the linear bypass had validation cell RMSE 170.56. A one-layer dollar recurrent network, whose cross-town mean moved from 3192 in April 2025 to 3274 in July 2026, stayed closest to an external approved-rent path of about 3179 to 3280. Those public rents were an external check only. They were not training labels. On the per-square-metre target, a linear-bypass LSTM had validation cell RMSE 1.9646 and test cell RMSE 3.4044, against validation cell RMSE 0.9707 and test cell RMSE 1.0897 for the three-layer network in the stack. Dollar cell RMSEs and per-square-metre cell RMSEs are different targets. Appendix B keeps them in separate tables.

The training-set rent RMSE of 461.25 uses the town CatBoost's predictions on its own training rows. The validation features of that CatBoost come from a model whose iteration was stopped on the validation set. The test RMSE of 462.87 is the labelled score after the choice. An earlier correlation of 0.890, with mean absolute error 69.1 across 76 components, is a dollar location check. It was not recomputed on the five-dimensional per-square-metre mixture. The Bukit Panjang figure was not scored. The best private-test RMSE of 432.50 did not choose the epoch, the mixture, or the region network.

7 Conclusion

The core audit supports a chronological split. On its validation set, Model 1's CatBoost reaches RMSE 454.29, against 795.76 for the global mean, 778.62 for the town mean, and 565.58 for the town and flat-type mean. Among the rebuilt CatBoost configurations, add_mrt is the best. Its validation RMSE is 499.53, and using every auxiliary family is higher than original plus address.

The best private-test submission is add_mrt. Its private-test RMSE is 432.50. Gold Miner (Group 12) is rank 21 after eight submissions. The latest submission scored a private-test RMSE of 441.46 and did not replace that best. An earlier private-test submission scored 451.26. It is no longer the best and no longer the latest. The private-test score did not stop or choose Model 3. Figure 18 is that private test set.

Model 3 remains the multistage stack. A per-town recurrent network estimates the town-month rent per square metre from the time index and the economic trend already observed before the month being predicted. A per-town CatBoost and a per-town Gaussian mixture estimate the unit-price gap separately. One shared network turns the mean, both gaps, floor area, and the flat's other features into monthly rent. The validation set selected epoch 8, with validation RMSE 448.24. The test RMSE is 462.87 and did not make that choice. Training RMSE on the training set is 461.25.




Figure 18: Private test set, Gold Miner (Group 12), rank 21, eight submissions, best private-test RMSE 432.50. The latest submission scored a private-test RMSE of 441.46 and did not replace that best.

A Core CatBoost settings and the cyclical month

The core CatBoost in Section 5.1 uses 600 boosting iterations, learning rate 0.05, depth 8, and random seed 42. Categorical fields are supplied directly. The cyclical check adds

$$\sin\Big(2\pi\frac{m-1}{12}\Big) \quad \text{and} \quad \cos\Big(2\pi\frac{m-1}{12}\Big),$$

where m is the calendar month, on top of the year, the numerical month, and the month index. Table 21 is the three rolling folds. A positive change is an increase in rolling-fold RMSE. The pair is not kept.

Table 21: Sine and cosine of calendar month, added to the core CatBoost on the rolling folds. Positive change means a higher rolling-fold RMSE. The mean row averages the three rolling-fold RMSEs.

Fold	Existing time features	Plus cyclical month	Change
1	719.52	729.00	+9.49
2	599.59	610.34	+10.75
3	477.47	477.83	+0.36
Mean	598.86	605.73	+6.87

B Dollar town-month trials

The recurrent network in the stack is trained for 50 epochs at learning rate 0.01 with seed 5228, on cells in the training set. The trials in Table 22 predict the town-month mean of monthly

rent, in SGD. They are not the per-square-metre target. The one-layer dollar network's private-test cross-town mean moves from 3192 in April 2025 to 3274 in July 2026, closest among these dollar paths to the external approved-rent path of about 3179 to 3280. That external path was a check, not a training label. The four-input three-layer LSTM moves from 3132 to 3109. The linear bypass beside that LSTM fits the training cells, with training-set cell RMSE 83.73, and then overshoots: validation cell RMSE 170.56, test cell RMSE 261.29, and a private-test path from 3339 to 3821.

Table 22: Dollar town-month mean of monthly rent. Cell RMSE is in SGD. These numbers are not comparable with Table 23.

Model	Validation cell RMSE	Test cell RMSE
One-layer recurrent network	93.25	88.04
Four-input, three-layer LSTM	88.75	83.39
Linear bypass beside that LSTM	170.56	261.29

Table 23 is the per-square-metre target. The three-layer recurrent network is the region mean in the multistage stack. Its cross-town unit mean on the private test set goes from 35.99 in April 2025 to 35.79 in July 2026. The test-set per-square-metre cell RMSE did not choose the network.

Table 23: Town-month mean of rent per square metre. Cell RMSE is in SGD per square metre, weighted by the number of flats in the cell. These numbers are not comparable with Table 22.

Model	Validation cell RMSE	Test cell RMSE
Three-layer recurrent network	0.9707	1.0897
Linear-bypass LSTM	1.9646	3.4044

A wider perceptron, with widths 512, 256, 128, and 64, dropout 0.3, and patience 40, was tried on an earlier dollar region mean. Its validation RMSE of monthly rent was 448.88 and its test RMSE was 461.87 at epoch 29. That validation RMSE belongs to a different region mean. It is not a comparison with the stack's validation RMSE of 448.24, and it is not the stack prediction.

C Gap models and the shared network

The town CatBoost uses depth 8, learning rate 0.05, at most 1000 iterations, and early stopping of 50 rounds on the validation set. Its columns are latitude and longitude; the block key and the street key; flat-type rank, flat-model rank, and flat-model name; nearest open MRT code, distance, and log distance; nearest mall name and distance; and nearest primary and secondary names and distances. Categories stay native. Numeric columns are median-imputed and are not scaled. A rare level needs 30 rows. An unseen category becomes a missing token. This list is not the feature set produced by the column-by-column ablation in Appendix D. That ablation does not choose the town stage, and the stack does not replace it.

Each town's mixture starts at 20 components. If any component that is hard-assigned on the training set has fewer than 30 rows, the count drops by one and the town is refit, down to one component. Bukit Panjang kept 6. Across towns the kept counts in the scored training run from 3 to 19.

An earlier location check, on a dollar gap rather than this five-dimensional unit-price mixture, is a separate result. Across 76 components, the training-set dollar gap and the validation-set gap correlate 0.890, with mean absolute error 69.1. An own-town surface starting at three components has validation RMSE 578.11 and test RMSE 593.19. A density blend across towns has validation RMSE 579.76 and test RMSE 594.42. Starting the own-town surface at 10, with

the same drop rule, has validation RMSE 566.55 and test RMSE 580.58. That correlation was not recomputed for the per-square-metre mixture in the stack. The multistage mixture's flat-level validation RMSE and test RMSE are in Table 19.

The shared network is optimised with Adam, learning rate 0.001, and batch size 1024. The target is monthly rent, standardized on the training set and restored before the error is computed. The 27 inputs are the recurrent-network unit mean, the CatBoost unit gap, the mixture unit gap, and floor area; the fee, which is 0 on every labelled row and every private-test row and so does not vary; lease commencement year; building age; month index; latitude and longitude after within-town standardization; raw latitude and longitude in degrees; flat-type rank; flat-model rank; maximum floor; year completed; flat age from the lease; distances to the nearest open MRT station, mall, primary school, and secondary school; the log MRT distance; counts of open MRT stations, malls, primary schools, and secondary schools within 1 km; and the count of other HDB blocks within 500 m. Furnished status is not an input.

D Feature ablation

The ablation adds auxiliary columns one at a time. It starts from a model already fit on the ten source columns. Architecture and preprocessing stay fixed. Only the validation RMSE decides whether a column is kept. The test RMSE is recorded after that decision and does not enter it.

Set A is the column list saved at the start of a round. Each auxiliary column that is not already in set A is tried on its own. That probe is set B, equal to set A plus the one new column, trained with the same budget as set A. A probe does not replace the saved list. For ridge and the multilayer perceptron, the column is promising only when the probe's validation RMSE is at least 1% below set A's validation RMSE. For XGBoost and CatBoost, the column is promising when the probe's validation RMSE is strictly lower. Set C is set A plus every promising column from that round, trained once. Set C replaces the saved list only when its own validation RMSE is lower than set A's. The next round then treats that new list as set A. The loop stops when a round has no promising column, or when set C does not win. A later retraining uses only the columns already kept, with a larger budget, and does not add or drop columns.