




**NOVA**  
**IMS**  
Information  
Management  
School

# Data Mining

NOVA-IMS  
10/11/2021  
Fernando Lucas Bação  
[bacao@isegi.unl.pt](mailto:bacao@isegi.unl.pt)  
<http://www.isegi.unl.pt/fbacao>

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

1



**NOVA**  
**IMS**  
Information  
Management  
School

## AGENDA

- Cluster analysis
  - Clustering techniques
    - Hierarchical Methods (agglomerative)
    - Partitioning Methods (kmeans and k-meansoids)

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa


2

**NOVA**  
**IMS**  
Information Management School

# Clustering

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

3



4

**NOVA**  
**IMS**  
Information Management School

# Hierarchical Methods

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

5

**NOVA**  
**IMS**  
Information Management School

## Clustering

- Hierarchical Clustering**

Data Matrix

	$X_1$	$X_2$	...	$X_p$
$I_1$				
$I_2$				
...				
$I_n$				

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

6

**NOVA**  
**IMS**  
Information Management School

## Clustering

- Hierarchical Clustering**

	$X_1$	$X_2$
$l_1$		
$l_2$		
...		
$l_n$		

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

7

**NOVA**  
**IMS**  
Information Management School

## Clustering

- Hierarchical Clustering**

$$d_{ij} = \sqrt{\sum_{v=1}^p (x_{iv} - x_{jv})^2}$$

	$X_1$	$X_2$
$l_1$		
$l_2$		
...		
$l_n$		

	$l_1$	$l_2$	...	$l_n$
$l_1$	0			
$l_2$	$d(l_2, l_1)$	0		
...	$d(l_{\dots}, l_1)$	$d(l_{\dots}, l_2)$	0	
$l_n$	$d(l_n, l_1)$	$d(l_n, l_2)$	$d(l_n, l_{\dots})$	0

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

8

**NOVA**  
**IMS**  
Information Management School

## Clustering

	BA	FI	MI	NA	RM	TO
BA	0	662	877	255	412	996
FI	662	0	295	468	268	400
MI	877	295	0	754	564	138
NA	255	468	754	0	219	869
RM	412	268	564	219	0	669
TO	996	400	138	869	669	0

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

9

**NOVA**  
**IMS**  
Information Management School

## Clustering

- Hierarchical Clustering**
  - Linkage or Aggregation Rules

- Single Linkage**  
 $D(c, c_j) = \min D(x_i, x_j)$   
 Minimum distance or distance between closest elements in clusters
- Complete Linkage**  
 $D(c, c_j) = \max D(x_i, x_j)$   
 Maximum distance between elements in clusters
- Average Linkage**  
 $D(c, c_j) = \frac{1}{|c|} \frac{1}{|c_j|} \sum \sum D(x_i, x_j)$   
 Average of the distances of all pairs

- Centroid Method**  
 Combining clusters with minimum distance between the centroids of the two clusters
- Ward's Method**
  - Combining clusters where increase in within cluster variance is to the smallest degree.
  - Objective is to minimize the total within cluster variance

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

10

## Clustering

	BA	FI	MI/TO	NA	RM
BA	0	662	877	255	412
FI	662	0	295	468	268
MI/TO	877	295	0	754	564
NA	255	468	754	0	219
RM	412	268	564	219	0


 Instituto Superior de Estatística e Gestão de Informação  
 Universidade Nova de Lisboa

11

## Clustering

	BA	FI	MI/TO	NA/RM
BA	0	662	877	255
FI	662	0	295	268
MI/TO	877	295	0	564
NA/RM	255	268	564	0


 Instituto Superior de Estatística e Gestão de Informação  
 Universidade Nova de Lisboa

12

**NOVA**  
**IMS**  
Information Management School

## Clustering

	BA/NA/RM	FI	MI/TO
BA/NA/RM	0	268	564
FI	268	0	295
MI/TO	564	295	0

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

13


**NOVA**  
**IMS**  
Information Management School

## Clustering

	BA/FI/NA/RM	MI/TO
BA/FI/NA/RM	0	295
MI/TO	295	0

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

14



15

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **Hierarchical Clustering**
  - Hierarchical Clustering - Interactive demo
  - You can find a nice worked example of hierarchical clustering at:
   
[https://matteucci.faculty.polimi.it/Clustering/tutorial\\_html/hierarchical.html](https://matteucci.faculty.polimi.it/Clustering/tutorial_html/hierarchical.html)

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

16

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **Hierarchical Clustering**
  - Dendrogram

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

17

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **Hierarchical Clustering (disadvantages)**
  - Have an essential problem, once an interaction is performed (merge or separation) we **cannot go back**;
    - This strictness is useful in terms of **computational costs**, because it avoids the cost that originates from the different combinatorial choices;
    - However, this low cost is related to the **impossibility to correct wrong decisions**;
  - Time complexity: not suitable for large datasets
    - Due to its calculation needs, several operations with large matrices **do not always work very well with large datasets**.

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

18

**NOVA**  
**IMS**  
Information Management School


## Clustering

- **Hierarchical Clustering (other variants)**
  - There are two ways of improving the performance of hierarchical methods:
    - To perform a careful analysis of the links produced in each hierarchical partition (CURE and Chameleon methods);
    - To integrate hierarchical clustering and optimization, first using an agglomerative algorithm and then refining the results by using iterative optimization (BIRCH method).

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa


19

**NOVA**  
**IMS**  
Information Management School



## K-Means Algorithm

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa



20

NOVA

IMS

Information  
Management  
School

Clustering

- **K-means algorithm**
  - K-means is a partitional clustering algorithm
  - Let the set of data points (or instances)  $D$  be
 
$$\{x_1, x_2, \dots, x_n\},$$

where  $x_i = (x_{i1}, x_{i2}, \dots, x_{ir})$  is a vector in a real-valued space  $x \in R^r$ , and  $r$  is the number of attributes (dimensions) in the data.
  - The k-means algorithm partitions the given data into  $k$  clusters.
    - Each cluster has a cluster center, called centroid.
    - $k$  is specified by the user
    - $k \ll n$ .

Instituto Superior de Estatística e Gestão de Informação  
 Universidade Nova de Lisboa

21

NOVA

IMS

Information  
Management  
School

Clustering

- **K-means algorithm**
  - Classifies the data into  $K$  groups, by satisfying the following requirements:
    - each group contains at least one point;
    - each point belongs to exactly one cluster.

Instituto Superior de Estatística e Gestão de Informação  
 Universidade Nova de Lisboa

22

NOVA

IMS

Information  
Management  
School

Clustering

- **K-means algorithm**
  - Given k, the partition method creates an initial partition (typically randomly);
  - Next, uses an iterative relocation technique that tries to improve the partition, moving objects from one group to another;
  - Generically, the criterion for a good partitioning is that of objects belonging to the same cluster should be close or related to each other.

Instituto Superior de Estatística e Gestão de Informação  
 Universidade Nova de Lisboa

23

NOVA

IMS

Information  
Management  
School

Clustering

- **K-means algorithm**
  - Algorithm:
    1. Choose the seeds;
    2. Each individual is associated with the nearest seed;
    3. Calculate the centroids of the formed clusters;
    4. Go back to step 2;
    5. End when the centroids cease to be recentered.

Instituto Superior de Estatística e Gestão de Informação  
 Universidade Nova de Lisboa

24

**NOVA**  
**IMS**  
Information Management School


## Clustering

- **K-means algorithm**
  - The goal is to minimize intra-group variance (sum of squared error):
$$SSE = \sum_{i=1}^K \sum_{x \in C_i} dist^2(m_i, x)$$
  - $x$  is a data point in cluster  $C_i$  and  $m_i$  is the representative point (centroid) for cluster  $C_i$
  - One easy way to reduce SSE is to increase  $K$  (number of clusters)
  - A good clustering with smaller  $K$  can have a lower SSE than a poor clustering with higher  $K$

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

25

**NOVA**  
**IMS**  
Information Management School




## K-Means Algorithm in figures


Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

UNICIS ASES Schools educoversal


26




27




28




29




30




31



32



33



34

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means**
- Movement of centroids during optimization process

Source: Fiona Cameron, Techniques for Neighbourhood Classification

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

35

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means algorithm (strengths)**
  - Simple: easy to understand and to implement
  - Efficient: Time complexity  $O(tkn)$ ,
    - where  $n$  is the number of data points,
    - $k$  is the number of clusters, and
    - $t$  is the number of iterations.
  - Since both  $k$  and  $t$  are small, k-means is considered a linear algorithm.
  - K-means is the most popular clustering algorithm.
  - Note that: it terminates at a local optimum if SSE is used. The global optimum is hard to find due to complexity.

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

36

**NOVA**  
**IMS**  
Information Management School


## Clustering

- **K-means algorithm (weaknesses)**
  - Very sensitive to the existence of outliers;
  - Very sensitive to the initial positions of the seeds;
  - Partitioning methods work well with spherical-shaped clusters;
    - Partitioning methods are not the most suitable to find clusters with complex shapes and different densities;
  - The need to set from the start the number of clusters to create.

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa


37

**NOVA**  
**IMS**  
Information Management School



## The Algorithm variant

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa



38

**NOVA**  
**IMS**  
Information  
Management  
School

## Clustering

- **K-means and k-medoids algorithms**
  - Most algorithms adopt one of two very popular heuristics:
    - k-means algorithm, where each cluster is represented by the average of the values of the points in a cluster;
    - k-medoids algorithm, where each cluster is represented by one of the points located near the center of the cluster.


Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

39

**NOVA**  
**IMS**  
Information  
Management  
School

## Clustering

- **K-means and k-medoids algorithms**



Source: Fiona Cameron, Techniques for  
Neighbourhood Classification


Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

40

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means and k-medoids algorithms**



Source: CS583, Bing Liu, UIC, Chapter 4: Unsupervised Learning


Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

41

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means and k-medoids algorithms**



Source: CS583, Bing Liu, UIC, Chapter 4: Unsupervised Learning


Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

42

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means and k-medoids algorithms**



Source: CS583, Bing Liu, UIC, Chapter 4: Unsupervised Learning


Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

43

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means and k-medoids algorithms**



Source: CS583, Bing Liu, UIC, Chapter 4: Unsupervised Learning


Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

44

**NOVA**  
**IMS**  
Information Management School

## Clustering

- K-means and k-medoids algorithms**




Source: CS583, Bing Liu, UIC, Chapter 4: Unsupervised Learning

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa


45

**NOVA**  
**IMS**  
Information Management School

## The initialization problem



Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa




46

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means algorithm (weaknesses)**
  - The algorithm is sensitive to initial seeds.




Source: Tan, Steinbach, Kumar, Introduction to Data Mining 2004

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

47

**NOVA**  
**IMS**  
Information Management School


## Clustering



Source: Tan, Steinbach, Kumar, Introduction to Data Mining 2004

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

48



49

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means algorithm (weaknesses)**
  - The algorithm is sensitive to initial seeds.
  - Use multiple forms of initialization;
  - Re-initialize several times;
  - Use more than one method;
  - Use a relatively large number of clusters and proceed to their regrouping by the choice of centroids.

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

50

**NOVA**  
**IMS**  
Information Management School

# Shape and density

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa


UNIGES, A3ES, eSchools, eaduniversal

51

**NOVA**  
**IMS**  
Information Management School

## Clustering

- K-means algorithm (weaknesses)**



**Original Points**

**K-means (2 Clusters)**


Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

52

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means algorithm (weaknesses)**
  - Have difficulties in dealing with clusters of different size and density;



Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

53

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means algorithm (weaknesses)**
  - Each individual either belongs or does not belong to the cluster, having no notion of probability of belonging, in other words, there is no consideration of the quality of the representation of a particular individual in a given cluster.


Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

54

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means algorithm (weaknesses)**




Source: Fiona Cameron, Techniques for Neighbourhood Classification

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa


55

**NOVA**  
**IMS**  
Information Management School

## The number of clusters



Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa



56

**NOVA**  
**IMS**  
Information Management School

## Clustering

- K-means algorithm the number of clusters**

How many clusters?

Six Clusters

Two Clusters

Four Clusters

Source: Tan, Steinbach, Kumar, Introduction to Data Mining 2004

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

57

**NOVA**  
**IMS**  
Information Management School

## Clustering

- K-means algorithm the number of clusters**
  - This is always a difficult problem to solve, and there are no recipes to fix this.
  - One way to minimize the problem is to create various classifications with different K, and choose the best.
  - Use a hierarchical method in order to choose the number of clusters based on the dendrogram.

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

58

**NOVA**  
**IMS**  
Information Management School

## Clustering

- K-means algorithm the number of clusters**

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

59

**NOVA**  
**IMS**  
Information Management School

## Clustering

- K-means algorithm the number of clusters**
  - The choice should be guided by three fundamental criteria:
    - intra-cluster variance,
    - evaluation of the profile of the cluster (subjective),
    - operational considerations.

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

60

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means algorithm the number of clusters**
  - Regarding the first criterion, the analysis is simple and not too subjective, since we know that the lower the intra-cluster variability the greater the cohesion of the cluster, a highly desirable feature in this type of analysis. However, as  $k$  increases, variability decreases;
  - Regarding the second criterion, the question is not as simple in the sense that it requires much more subjective assessments, which relate to the interpretation of the obtained clusters;
  - The third criterion is relatively simple in the sense that these issues are imposed on the analyst.

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

61

**NOVA**  
**IMS**  
Information Management School

## Clustering

- **K-means algorithm the number of clusters**

**Elbow method**

Objective Function Value  
i.e., Distortion

Number of Clusters

Within Groups Sum of Squares

Number of Clusters

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

62

**NOVA**  
**IMS**  
Information  
Management  
School

## Clustering

- **K-means algorithm the number of clusters**
  - To test the results by varying k (number of clusters);
  - This procedure allows a series of analyzes that can instruct the choice of the number of clusters;
  - To compare the totals of the distances of the different solutions.

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

63

**NOVA**  
**IMS**  
Information  
Management  
School

## Clustering

- **K-means algorithm the number of clusters**
  - Operational considerations are related to business environment and usually affect the decisions of the analyst:
    - A number small enough for developing a specific strategy;
    - A number of individuals large enough to be worth it to develop a specific strategy;
    - A good way to accomodate these considerations is the use of a high initial k and then proceed to the grouping of clusters.

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

64

**NOVA**  
**IMS**  
Information Management School

## Clustering

- K-means algorithm the number of clusters**

CLUSTER	Cluster 1	Cluster 2	Cluster 3	Cluster 4
1	0	46.88621549	53.629114781	51.055735073
2	46.88621549	0	35.424488679	48.408611185
3	53.629114781	35.424488679	0	58.950971223
4	51.055735073	48.408611185	58.950971223	0

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

65

**NOVA**  
**IMS**  
Information Management School

## Clustering

- K-means algorithm the number of clusters**
  - This evaluation is carried out by comparing the mean values for each variable in each cluster with the mean values of the population for each variable;
  - In this case, it is particularly relevant to take into account the most important differences within the different clusters and the mean population.
  - That is why profiling is so important.

Instituto Superior de Estatística e Gestão de Informação  
Universidade Nova de Lisboa

66