2026 Edition

2026 Q4上市

eCandle DC-DC

Portable Power Station



- 多个输出接口
- 320Wh 超大容量
- 100W MPPT 光伏输入
- 6000+次循环次数
- 磷酸铁锂电芯
- 极简架构设计

Model	eCandle DC-DC
光伏输入	
最大光伏输入功率	100W
光伏输入电压范围	12~30V
交流输入	
输入电压范围	5~20V
最大交流输入功率	100W
直流输出	
5521接口	12V/3.75A（共享），45W Max(x2)
USB-A	5V/3A（共享），15W Max(x2)
Type-C1（双向）	5V/9V/12V/15V@3A、20V@3.25A，65W Max(x1)
Type-C2	5V/3A，9V/2A，12V/1.67A，20W Max(x1)
电池	
电池类型	LiFePO4 (Lithium Iron Phosphate)
电池容量	320Wh Max
循环寿命	≥6000Times
一般参数	
产品尺寸	222×207×91.5mm
产品重量	≈3.5kg
工作温度范围	-10~40℃
存储温度范围	-20~70℃
环境湿度	10% 至 90% 相对湿度（无冷凝）
最大工作海拔	4000m，以 3000m 为基础，海拔每升高 200 m，规格最高温度降低 1℃。
电池电量指示器	数码屏显示
散热方式	自然散热
LED照明功能	YES
颜色	可定制
出厂SOC	50~60%
认证等级	UN38.3
保护功能	
输入过压保护	Yes
输入欠压保护	Yes
光伏输入过压保护	Yes
光伏输入欠压保护	Yes
短路保护	Yes
电池高温保护	Yes
电池低温保护	Yes

2026 Edition

Listing in Q4 2026

eCandle DC-DC

Portable Power Station



- **Multiple output ports**
- **100W MPPT Photovoltaic Input**
- **Lithium Iron Phosphate Battery**
- **320Wh Ultra-High Capacity**
- **Over 6,000 Cycles**
- **Minimalist Architecture Design**

Model	eCandle DC-DC
PV Input	
Maximum PV Input Power	100W
PV Input Voltage Range	12~30V
AC Input	
Input Voltage Range	5~20V
Maximum AC Input Power	100W
DC Output	
5521 Connector	12V/3.75A (shared), 45W Max (x2)
USB-A	5V/3A (shared), 15W Max (x2)
Type-C1 (bidirectional)	5V/9V/12V/15V@3A、20V@3.25A，65W Max(x1)
Type-C2	5V/3A，9V/2A，12V/1.67A，20W Max(x1)
Battery	
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Battery Capacity	320Wh Max
Cycle Life	≥6000Times
General Specifications	
Product Dimensions	222×207×91.5mm
Product Weight	≈3.5kg
Operating Temperature Range	-10~40℃
Storage Temperature Range	-20~70℃
Ambient Humidity	10% to 90% RH (Non-condensing)
Maximum Operating Altitude	4000m, >3000m Temperature Derating (1℃ per 200m increase)
Battery Level Indicator	Digital Display
Cooling Method	Passive Cooling
LED Lighting Features	YES
Color	Customizable
Factory SOC	50~60%
Certification Level	UN38.3
Protection Features	
Input Overvoltage Protection	Yes
Input Undervoltage Protection	Yes
PV Input Overvoltage Protection	Yes
PV Input Undervoltage Protection	Yes
Short-Circuit Protection	Yes
Battery Over-Temperature Protection	Yes
Battery Under-Temperature Protection	Yes