2026 Edition

2-YEAR WARRANTY

eCandle Pro

UPGRADED NEW EDITION OPTIMIZED PERFORMANCE

Portable Power Station



- 500W 双向逆变
- 1004Wh 超大容量
- 500W MPPT 光伏输入
- 6000+次循环次数
- 磷酸铁锂电芯
- UPS 不间断电源

多样化外观工艺选择



型号	eCandle Pro（AC+DC）	eCandle Pro（AC+AC）
光伏输入		
最大光伏输入功率	500W	
光伏输入电压范围	12~60V	
交流输入		
输入电压范围	90-280Vac	
输入频率范围	45~65Hz	
最大交流输入功率	500W	
交流输出		
额定交流输出功率（逆变器模式）	500W	
额定交流输出电压（逆变器模式）	220-240VAC，110V可选	
额定交流频率	50Hz/60Hz	
UPS切换时间	≤10ms	
交流输出端口数量	1	2
直流输出		
Type-C	20W Max(x1)	/
USB-A	10W Max,Total 15W (x2)	/
电池		
电池类型	LiFePO4 (Lithium Iron Phosphate)	
电池容量	1004Wh Max	
循环寿命	≥6000 Times	
一般参数		
产品尺寸	290×168×248mm	
产品重量	≈10kg	
工作温度范围	0~55℃	
存储温度范围	-20~55℃	
环境湿度	10% 至 90% 相对湿度（无冷凝）	
最大工作海拔	4000m，以 3000m 为基础，海拔每升高 200 m，规格最高温度降低 1℃。	
电池电量指示器	4段式LED	
WiFi/4G	Optional	
散热方式	风冷	
颜色	可定制	
出厂SOC	50~60%	
认证等级	UN38.3/CE	
保护功能		
交流输入欠压保护	Yes	
交流输入过压保护	Yes	
电池欠压保护	Yes	
电池过压保护	Yes	
交流输出欠压保护	Yes	
交流输出过压保护	Yes	
交流输出过载保护	Yes	
交流输出短路保护	Yes	
过温保护	Yes	

2026 Edition

2-YEAR WARRANTY

eCandle Pro

UPGRADED NEW EDITION OPTIMIZED PERFORMANCE

Portable Power Station



- 500W Bidirectional Inverter
- 1004Wh Ultra-High Capacity
- 500W MPPT Photovoltaic Input
- Over 6,000 Cycles
- Lithium Iron Phosphate Battery
- UPS Uninterruptible Power Supply

A VARIETY OF FINISHING OPTIONS



Model	eCandle Pro（AC+DC）	eCandle Pro（AC+AC）
PV Input		
Max. PV Input Power	500W	
PV Input Voltage Range	12~60V	
AC Input		
Input Voltage Range	90-280Vac	
Input Frequency Range	45~65Hz	
Maximum AC Input Power	500W	
AC Output		
Nominal AC Output Power (Inverter Mode)	500W	
Nominal AC Output Voltage (Inverter Mode)	220-240VAC，110V Optional	
Nominal AC Frequency	50Hz/60Hz	
UPS Switch Time	≤10ms	
Number of AC Output Ports	1	2
DC Output		
Type-C	20W Max(x1)	/
USB-A	10W Max,Total 15W (x2)	/
Battery		
Battery Type	LiFePO4 (Lithium Iron Phosphate)	
Battery Energy	1004Wh Max	
Cycle Life	≥6000 Times	
General Data		
Product Dimensions	290×168×248mm	
Product Weight	≈10kg	
Operating Temperature Range	0~55℃	
Storage Temperature Range	-20~55℃	
Environmental Humidity	10% to 90% RH (Non-condensing)	
Max. Operating Altitude	4000m, >3000m Temperature Derating (1℃ per 200m increase)	
Battery Level Indicator	4-segment LED	
WiFi/4G	Optional	
Cool Method	Air-cooled	
Color	Customizable	
Shipping SOC	50~60%	
Authentication Level	UN38.3/CE	
Protection		
AC Input Under Voltage Protection	Yes	
AC Input Over Voltage Protection	Yes	
Battery Under Voltage Protection	Yes	
Battery Over Voltage Protection	Yes	
AC Output Under Voltage Protection	Yes	
AC Output Over Voltage Protection	Yes	
AC Output Overload Protection	Yes	
AC Output Short Circuit Protection	Yes	
Over-Temperature Protection	Yes	