

Project CUDC Report

OUNAN DING
Student ID: 861194909
oding001@ucr.edu

Contents

1	Overview	1
2	Design and Implementation	2
2.1	General Overview	2
2.2	The CPU Version	3
2.3	The CUDA Version	3
3	Analysis	3
4	Conclusion	3
	References	4

1 Overview

This report is for the final project of CS/EE-217 GPU Architecture and Programming. Implementations of dual contouring will be presented and analyzed.

We provide a CPU implementation written in C++ first as our baseline, then move on to introduce the CUDA implementations. We will see what the bottle neck is in our CPU version, and how we make trade off in the CUDA version to overcome that bottle neck. A visualizer is also provided as a Blender add-on to preview the results and check the correctness.

Finally we will provide some performance testing and detailed analysis in the last part of this report.

2 Design and Implementation

2.1 General Overview

In this section we will provide a general overview of dual contouring. The architecture-independent perspectives of this algorithm will be discussed.

The primary paper used for this project is [JLSW02]. [SWU] also provides supplemental materials on how to construct and solve the Quadratic Error Function(QEF).

For the first step in dual contouring, given an implicit function such as $(x^2 + y^2 - 1)^3 - x^2y^3$ in 2D, or $x^2 + y^2 + z^2 - 1$ in 3D, we will sample the function on a uniform grid. Here is an example in figure 1, where we sample the function $x^2 + y^2 - 1.7$. The 0 level set of this function is plotted as a circle of radius 1.7. The samples which have a negative value are drawn with filled dots.




Figure 1: Sampling of $x^2 + y^2 - 1.7$

Every edge which exhibits different signs at its ends has a potential intersection with the 0 level set of the function. We highlight these edges in figure 2.

The intersections of these edges can be found by a binary search. And the gradients at the intersections (the Hermitian data in the glossary of [JLSW02]) can be computed by finite differencing.




Figure 2: The intersected edges

2.2 The CPU Version

2.3 The CUDA Version

3 Analysis

4 Conclusion

References

- [JLSW02] Tao Ju, Frank Losasso, Scott Schaefer, and Joe Warren. Dual contouring of hermite data. *ACM Transactions on Graphics (TOG)*, 21(3):339–346, 2002.
- [SWU] Scott Schaefer, Joe Warren, and Rice UniversityE. Dual contouring: The secret saucec.