ECE 485/585
Computer Organization and Design

Lecture 10: Pipelining and Hazards
Fall 2022

Won-Jae Yi, Ph.D.

Department of Electrical and Computer Engineering
Illinois Institute of Technology

Summary So Far…

- First analyze the instructions… then build the processor
- If instructions take different amounts of time, multi-cycle is better
- Datapath implemented using:
  - Combinational logic for arithmetic
  - State holding elements to remember bits
- Control implemented using:
  - Combinational logic for single-cycle implementation
  - More complicated logic for multi-cycle implementation
- We will Improve Performance by Pipelining

Pipelining Analogy

- Pipelined laundry: overlapping execution
  - Parallelism improves performance



- **Four loads:**
  - Speedup = 8/3.5 = 2.3
- **Non-stop:**
  - Speedup = number of stages

MIPS Pipeline

- Five stages, one step per stage
  1. IF: Instruction fetch from memory
  2. ID: Instruction decode & register read
  3. EX: Execute operation or calculate address
  4. MEM: Access memory operand
  5. WB: Write result back to register



Pipeline Performance

- Assume time for stages is
  - 100ps for register read or write
  - 200ps for other stages
- Compare pipelined datapath with single-cycle datapath

Instr	Instr fetch	Register read	ALU op	Memory access	Register write	Total time
lw	200ps	100 ps	200ps	200ps	100 ps	800ps
sw	200ps	100 ps	200ps	200ps		700ps
R-format	200ps	100 ps	200ps		100 ps	600ps
beq	200ps	100 ps	200ps			500ps

Pipeline Performance



Pipeline Speedup

- If all stages are balanced
  - e.g., all take the same time
  - Time between instructions$_{pipelined}$ = Time between instructions$_{nonpipelined}$ / Number of stages
- If not balanced, speedup is less
- Speedup due to increased throughput
  - Latency (time for each instruction) does not decrease

Pipelining and ISA Design

- MIPS ISA designed for pipelining
  - All instructions are 32-bits
    - Easier to fetch and decode in one cycle
    - c.f. x86: 1- to 17-byte instructions
  - Few and regular instruction formats
    - Can decode and read registers in one step
  - Load/store addressing
    - Can calculate address in 3rd stage
    - Access memory in 4th stage
  - Alignment of memory operands
    - Memory access takes only one cycle

Pipeline Hazards

- Situations that prevent starting the next instruction in the next cycle
  - Cannot execute in the following clock cycle due to dependencies
- **Structure hazards**
  - A required resource is busy
- **Data hazards**
  - Need to wait for previous instruction to complete its data read/write
- **Control hazards**
  - Deciding on control action depends on previous instruction



Structure Hazards

- Conflict for use of a resource
- In MIPS pipeline with a single memory
  - Load/store requires data access
  - Instruction fetch would have to *stall* for that cycle
    - Would cause a pipeline "bubble"
- Hence, pipelined datapaths require separate instruction/data memories
  - Or separate instruction/data caches
- For example, we had a single memory instead of two memories:
  - What happens if there's a 4th memory instruction?



Data Hazards

- An instruction depends on completion of data access by a previous instruction



RAW → Read After Write
R2 ← R1 + R3
R4 ← R2 + R3

WAR → Write After Read
R2 ← R1 + R3
R3 ← R4 + R5

WAW → Write after write
R2 ← R1 + R3
R2 ← R4 + R5



Forwarding (Bypassing)

- Use result when it is computed
  - Don't wait for it to be stored in a register
  - Requires extra hardware/connections in the datapath



Load-Use Data Hazard

- Can't always avoid stalls by forwarding
  - If value not computed when needed
  - Can't forward backward in time!



Code Scheduling to Avoid Stalls

- Reorder code to avoid use of load result in the next instruction
- C code for A = B + E; C = B + F;





Control Hazards

- Arises from the need to make a decision based on the results of one instruction while others are executing (e.g., branch instruction)
- Branch determines flow of control
  - Fetching next instruction depends on branch outcome
  - Pipeline can't always fetch correct instruction
    - Still working on ID stage of branch
- In MIPS pipeline
  - Need to compare registers and compute target early in the pipeline
  - Add hardware to do it in ID stage

Stall on Branch

- Wait until branch outcome determined before fetching next instruction



Branch Prediction

- Longer pipelines can't readily determine branch outcome early
  - Stall penalty becomes unacceptable
- Predict outcome of branch
  - Only stall if prediction is wrong
- In MIPS pipeline
  - Can predict branches not taken
  - Fetch instruction after branch, with no delay
  - Only stall if branches are taken

MIPS with Prediction Not Taken



More-Realistic Branch Prediction

- Static branch prediction
  - Based on typical branch behavior
  - Example: loop and if-statement branches
    - Predict backward branches taken
    - Predict forward branches not taken
- Dynamic branch prediction
  - Hardware measures actual branch behavior
    - e.g., record recent history of each branch
  - Assume future behavior will continue the trend
    - When wrong, stall while re-fetching, and update history

MIPS Pipelined Datapath



Pipeline Registers

- Need registers between stages
  - To hold information produced in previous cycle



Pipeline Operation

- Cycle-by-cycle flow of instructions through the pipelined datapath
  - "Single-clock-cycle" pipeline diagram
    - Shows pipeline usage in a single cycle
    - Highlight resources used
  - c.f. "multi-clock-cycle" diagram
    - Graph of operation over time
- We'll look at "single-clock-cycle" diagrams for load & store

IF for Load, Store, …



ID for Load, Store, …



EX for Load, Store, …



MEM for Load



WB for Load



need to prevent writing reg. 10 from 2nd stage of lw

Corrected Datapath for Load



EX for Store



MEM for Store



WB for Store

- nothing needed
- but still counted as one of the stages for SW



Multicycle Pipeline Diagram

- Form showing resource usage



Multicycle Pipeline Diagram

- Traditional Form



Single-Cycle Pipeline Diagram

- State of pipeline in a given cycle



Pipelined Control (Simplified)



Control Lines grouped into 3 Stages

Instruction	Execution/address calculation stage control lines				Memory access stage control lines			Write-back stage control lines	
	RegDst	ALUOp1	ALUOp0	ALUSrc	Branch	Mem-Read	Mem-Write	Reg-Write	Memto-Reg
R-format	1	1	0	0	0	0	0	1	0
lw	0	0	0	1	0	1	0	1	1
sw	X	0	0	1	0	0	1	0	X
beq	X	0	1	0	1	0	0	0	X

Pipelined Control

- Control signals derived from instruction
  - As in single-cycle implementation



Pipelined Control



Pipeline Summary

The BIG Picture

- Pipelining improves performance by increasing instruction throughput
  - Executes multiple instructions in parallel
  - Each instruction has the same latency
- Subject to hazards
  - Structure, data, control
- Instruction set design affects complexity of pipeline implementation

Data Hazards in ALU Instructions

= Data dependencies

- Consider this sequence:

```
sub $2, $1,$3
and $12,$2,$5
or  $13,$6,$2
add $14,$2,$2
sw  $15,100($2)
```



- We can resolve hazards with forwarding
  - How do we detect when to forward?

Page 45

Dependencies & Forwarding



Detecting the Need to Forward

- Pass register numbers along pipeline
  - e.g., ID/EX.RegisterRs = register number for Rs sitting in ID/EX pipeline register
- ALU operand register numbers in EX stage are given by
  - ID/EX.RegisterRs, ID/EX.RegisterRt
- Data hazards when
  - 1a. EX/MEM.RegisterRd = ID/EX.RegisterRs
  - 1b. EX/MEM.RegisterRd = ID/EX.RegisterRt
  - 2a. MEM/WB.RegisterRd = ID/EX.RegisterRs
  - 2b. MEM/WB.RegisterRd = ID/EX.RegisterRt

Fwd from EX/MEM pipeline reg

Fwd from MEM/WB pipeline reg

Detecting the Need to Forward

- But only if forwarding instruction will write to a register!
  - EX/MEM.RegWrite, MEM/WB.RegWrite
- And only if Rd for that instruction is not $zero
  - EX/MEM.RegisterRd ≠ 0, MEM/WB.RegisterRd ≠ 0

Forwarding Paths



Forwarding Conditions

- EX hazard
  - if (EX/MEM.RegWrite and (EX/MEM.RegisterRd ≠ 0) and (EX/MEM.RegisterRd = ID/EX.RegisterRs))
    ForwardA = 10
  - if (EX/MEM.RegWrite and (EX/MEM.RegisterRd ≠ 0) and (EX/MEM.RegisterRd = ID/EX.RegisterRt))
    ForwardB = 10
- MEM hazard
  - if (MEM/WB.RegWrite and (MEM/WB.RegisterRd ≠ 0) and (MEM/WB.RegisterRd = ID/EX.RegisterRs))
    ForwardA = 01
  - if (MEM/WB.RegWrite and (MEM/WB.RegisterRd ≠ 0) and (MEM/WB.RegisterRd = ID/EX.RegisterRt))
    ForwardB = 01

Double Data Hazard

- Consider the sequence:

```
add $1,$1,$2
add $1,$1,$3
add $1,$1,$4
```

- Both hazards occur
  - Want to use the most recent
- Revise MEM hazard condition
  - Only forward if EX hazard condition isn't true

Revised Forwarding Condition

- MEM hazard
  - if (MEM/WB.RegWrite and (MEM/WB.RegisterRd ≠ 0) and not (EX/MEM.RegWrite and (EX/MEM.RegisterRd ≠ 0) and (EX/MEM.RegisterRd = ID/EX.RegisterRs)) and (MEM/WB.RegisterRd = ID/EX.RegisterRs))
    ForwardA = 01
  - if (MEM/WB.RegWrite and (MEM/WB.RegisterRd ≠ 0) and not (EX/MEM.RegWrite and (EX/MEM.RegisterRd ≠ 0) and (EX/MEM.RegisterRd = ID/EX.RegisterRt)) and (MEM/WB.RegisterRd = ID/EX.RegisterRt))
    ForwardB = 01

Datapath with Forwarding



Load-Use Data Hazard



Load-Use Data Hazard Detection

- Check when using instruction is decoded in ID stage
- ALU operand register numbers in ID stage are given by
  - IF/ID.RegisterRs, IF/ID.RegisterRt
- Load-use hazard when
  - ID/EX.MemRead and ((ID/EX.RegisterRt = IF/ID.RegisterRs) or (ID/EX.RegisterRt = IF/ID.RegisterRt))
- If detected, stall and insert bubble

How to Stall the Pipeline

- Force control values in ID/EX register to 0
  - EX, MEM and WB do **nop** (no-operation)
- Prevent update of PC and IF/ID register
  - Using instruction is decoded again
  - Following instruction is fetched again
  - 1-cycle stall allows MEM to read data for lw
    - Can subsequently forward to EX stage

Stall/Bubble in the Pipeline





Stall/Bubble in the Pipeline



Datapath with Hazard Detection



Stalls and Performance

The BIG Picture

- Stalls reduce performance
  - But are required to get correct results
- Compiler can arrange code to avoid hazards and stalls
  - Requires knowledge of the pipeline structure