

ECE 449/590 – OOP and Machine Learning

Lecture 10 Class Invariant

Professor Jia Wang
Department of Electrical and Computer Engineering
Illinois Institute of Technology

September 26, 2022

Outline

Class Design

Class Invariant

More on Default Constructor

Reading Assignment

- ▶ This lecture: Accelerated C++ 9
- ▶ Next lecture: Accelerated C++ 9

Outline

Class Design

Class Invariant

More on Default Constructor

(Simple) Class Design Overview

- ▶ Class types group data and functions together.
- ▶ Data members
 - ▶ Holding data for the objects of the class type.
 - ▶ Usually `private` for encapsulation.
- ▶ Member functions
 - ▶ Define valid operations available to the class type.
 - ▶ Constructors are special member functions that initialize objects.
- ▶ What language features are available to help us define more complicated class types?

Class Design for Calendar Dates

```
class date {  
    int year_, month_, day_;  
public:  
    date(int y, int m, int d);  
  
    bool set(int y, int m, int d);  
  
    int get_year();  
    int get_month();  
    int get_day();  
  
    std::string to_string();  
}; // class date
```

- ▶ An intuitive and typical class design.
 - ▶ A ctor(constructor) to initialize `date` objects so that data members won't have undefined values.
 - ▶ Setter and getters.
 - ▶ Helper functions like `to_string` for printing and troubleshooting so that one don't have to use getters extensively.

Using Constructor

```
date first(2021, 1, 1);  
std::cout << first.to_string() << std::endl;  
date someday; // compiling error
```

- ▶ You can provide year/month/day to construct a `date` object.
 - ▶ The ctor is called implicitly and automatically.
- ▶ You have to provide them to construct any `date` object.
 - ▶ It is guaranteed by compiler that there is no undefined behavior because of members not initialized.

Multiple Constructors

```
class date {  
public:  
    date(int y, int m, int d);  
    date(std::string str);  
    ...  
}; // class date  
  
date first(2021, 1, 1);  
date first_from_str("2021/1/1");
```

- ▶ A class can have multiple ctors.
 - ▶ They should have different parameters types – so the compiler can decide which one to call given the arguments.

Default Constructor

```
class date {  
public:  
    date();  
    ...  
}; // class date
```

```
date::date() : year_(1970), month_(1), day_(1) {  
}
```

`date epoch;` // epoch contains 1970/1/1 instead of undefined values

- ▶ Default constructor: a ctor takes no arguments.
- ▶ Default-initialization: constructing an object without providing any arguments
 - ▶ Don't put `()` after `epoch`.
- ▶ Default ctor is called automatically for default-initialization.

Constness

```
date first(2021, 1, 1);  
  
const date const_first = first;  
  
std::cout << first.to_string() << std::endl;  
std::cout << const_first.to_string() << std::endl; // compiling error
```

- ▶ We cannot change `const_first`.
- ▶ Although we won't change `const_first` in the member function `to_string`, the compiler doesn't know that and will complain if we call it.
 - ▶ We need to tell the compiler so.

Handle Constness in Member Functions

```
class date {  
public:  
    ...  
    int get_year() const;  
    int get_month() const;  
    int get_day() const;  
    std::string to_string() const;  
}; // class date  
  
std::string date::to_string() const {  
    ...  
}
```

- ▶ You create a `const` member function by adding `const` after its parameter list.
 - ▶ The compiler will complain for any modification to the object in `const` member functions.
- ▶ For `const` objects, you can only call `const` member functions.

Outline

Class Design

Class Invariant

More on Default Constructor

Language Features vs. Design Decisions

- ▶ We start to see more language features for class design.
 - ▶ Why are there so many rules that seem restricting?
- ▶ Defining a nice class in C++ is a very challenging task.
 - ▶ Nice: easy to use, less chance to make mistakes.
 - ▶ Need to use many language features.
 - ▶ Need to make design decisions.
- ▶ Language features and design decisions are actually closely related.
 - ▶ C++ is designed to support established design practices.
- ▶ How to design a class?
 - ▶ Beyond the simple `date` class where we can rely on intuitions.
 - ▶ What should be the data members?
 - ▶ What should be the member functions?

State of Object

- ▶ Consider any object.
 - ▶ Consisting of data members and member functions specified by its type
- ▶ The values of the members and the objects referred to by members are collectively called the state of the object.
 - ▶ Or simply called its value
- ▶ For example,
 - ▶ State of `date`: values of `year_`, `month_`, `day_`
 - ▶ State of `expression`: values of `expr_id_`, `op_name_`, `op_type_`, `inputs_`
- ▶ To use an object, the major concern is to keep its state valid, or well defined.

Class Invariant

- ▶ An invariant is something that will always remain true during some progress.
- ▶ If we consider a `date` or an `expression` object during program execution,
 - ▶ We expect `year_/month_/day_` to be a valid calendar date.
 - ▶ We expect the expression with `expr_id_` to use an operation with `op_name_` and `op_type_` and `n` operands from `inputs_`.
- ▶ Class invariant: the condition for the state of an object to be valid
 - ▶ It is implied by the type of the object so we call it class invariant.
 - ▶ The class invariants of `date` and `expression` are shown above.

Roles of Class Interface

- ▶ Class interface: declarations of constructors and public member functions
- ▶ Constructors should establish the class invariant for the objects when they are constructed.
- ▶ Public member functions should maintain the class invariant.
- ▶ Therefore, one can safely assume all the objects of the class always satisfy the invariant as long as they are manipulated through the class interface.
 - ▶ As guaranteed by mathematical induction.

Precondition and Postcondition

- ▶ Precondition: the constraints that arguments of a function should satisfy.
 - ▶ E.g. when calling `date::set`, the provided year/month/day should be valid.
- ▶ Postcondition: the constraints that returned and modified values of a function should satisfy.
 - ▶ E.g. after calling `date::set`, the object should have the desired year/month/day while remaining valid.
- ▶ Garbage in, garbage out
 - ▶ A correct function may perform errorously, i.e. violating the postcondition, if the precondition is violated.
 - ▶ This is the most usual mistake made by programmers.
- ▶ How to ENFORCE preconditions?

Public Member Functions

- ▶ Class invariant should hold before and after a call to a public member function.
 - ▶ It serves as part of the precondition and the postcondition regarding data members for any public member function.
- ▶ Holding class invariant is easy for `const` member functions.
 - ▶ Nothing is changed: class invariant remains valid
- ▶ Non-`const` public member functions are expected to make some progress: change the state of the object from a valid one to another valid one.
 - ▶ When we refer to implementation, we mean how that change is computed.
 - ▶ The class invariant may be violated during the computation.

Private Member Functions

- ▶ Implementations could be very complicated.
 - ▶ Class designers need to organize the computations into functions.
 - ▶ Those functions should be private member functions.
- ▶ It is not necessary for the private member functions to have the class invariant as the pre- and the postcondition.
- ▶ In other words,
 - ▶ If a member function may violate class invariant, it need to be private.
 - ▶ Otherwise, it could be public.

Data Members

- ▶ If invariants exist among a set of variables, it is a good idea to form a class with them as data members.
 - ▶ `year_`, `month_`, `day_`.
 - ▶ `expr_id_`, `op_name_`, `op_type_`, `inputs_`
- ▶ Avoid to design a class that leads to a god object – the object that tries to do everything.
 - ▶ Variables where no invariant exist should not be bundled into a class directly.

Outline

Class Design

Class Invariant

More on Default Constructor

Implicitly-Declared Default Constructor

- ▶ The compiler will generate a public default ctor for any non-reference type if the type has no user-defined ctors.
- ▶ For built-in types, e.g. `int` and `bool`, it will do nothing.
- ▶ For class types, it will default-initialize their members.
 - ▶ There will be a compiling error if a member has no default constructor.

Why?

- ▶ Having a user-defined ctor is a hint of non-trivial class invariants.
 - ▶ The compiler expects the class designer to provide a default ctor if one tries to default-initialize an object.
- ▶ Otherwise, the compiler attempts to maintain the weakest class invariant – members should satisfy their individual class invariant, by default-initializing them.
- ▶ Why don't default ctors assign some value to built-in types to avoid undefined behaviors?
 - ▶ Again, this is a rule from the C language for performance reasons.

Default Constructor: Example I

```
class date {  
public:  
    date();  
    date(int y, int m, int d);  
    date(std::string str);  
    ...  
}; // class date
```

`date epoch; // will not compile if date::date() is not provided`

- ▶ Has user-defined ctor.
- ▶ So there will be no implicitly-declared default ctor.
- ▶ One must provide the default ctor for default-initialization to compile.

Default Constructor: Example II

```
class vec_ref {  
    std::vector<int> &ref;  
}; // class vec_ref  
  
vec_ref vref; // compiling error
```

- ▶ No user-defined ctor
- ▶ So there will be an implicitly-declared default ctor.
- ▶ It will default-initialize `ref`.
 - ▶ It's a reference type and default-initialization makes no sense.
 - ▶ So there is a compiling error.

Default Constructor: Example III

```
// our very first definition of expression
struct expression {
    int expr_id;
    std::string op_name;
    std::string op_type;
    std::vector<int> inputs;
}; // struct expression

expression expr; // compile OK but not nice
```

- ▶ No user-defined ctor
- ▶ So there will be an implicitly-declared default ctor.
 - ▶ Default-initialize `op_name` and `op_type` to an empty string by the default ctor of `std::string`.
 - ▶ Default-initialize `inputs` to an empty vector by the default ctor of `std::vector`.
- ▶ `expr_id`, which is of built-in types, will be default-initializd as undefined values.
 - ▶ Not nice: compiler won't help if someone forgets to assign a value to `expr_id`.

Default Constructor: Example IV

```
// our better expression design
class expression {
    ...
public:
    expression(...);
    ...
}; // class expression

expression expr; // compiling error
```

- ▶ There is a user-defined ctor.
- ▶ So there is no implicitly-declared default ctor.
- ▶ There is a compiling error since the compiler fails to find the default ctor for default-initialization.
 - ▶ Nice design: compiler enforces that all arguments to the ctor should be provided.

How to initialize reference members?

```
class vec_ref {
    std::vector<int> &ref;
public:
    vec_ref(std::vector<int> &param);
}; // class vec_ref

vec_ref::vec_ref(std::vector<int> &param)
    : ref(param) {
}

std::vector<int> int_vec
vec_ref vref(int_vec);
```

- ▶ You have to initialize reference members using the constructor initializers.

Summary and Advice

- ▶ Each class type should have a class invariant.
 - ▶ Constructors establish the class invariant.
 - ▶ Public member functions maintain the class invariant.
- ▶ Implicitly-declared default ctor
 - ▶ Generated automatically for types w/o user-defined ctors
 - ▶ It will default-initialize the members recursively.
 - ▶ Do nothing for a member of a built-in type.
- ▶ Member functions can be `const` or non-`const`, depending on their semantics.