

ECE 449/590 – OOP and Machine Learning

Lecture 21 Resource Management and Object Composition

Professor Jia Wang
Department of Electrical and Computer Engineering
Illinois Institute of Technology

November 7, 2022

Outline

Resource Management

Object Composition

Reading Assignment

- ▶ This lecture: Accelerated C++ 11
- ▶ Next lecture: Accelerated C++ 11

Outline

Resource Management

Object Composition

Resource Management

- ▶ Resources: things with limited availability
 - ▶ Memory
 - ▶ File handles
 - ▶ Network connections
 - ▶ Database connections
 - ▶ etc.
- ▶ Management: release a resource promptly
 - ▶ Only when the resource was acquired successfully.
 - ▶ After all the usages of the resource.

Resource management seems to be easy.

```
void some_function() {  
    FILE *fp = fopen("input_file", "r");  
    ... // do something with the file  
    fclose(fp);  
}
```

- ▶ Consider file operations in C.
 - ▶ The file handle is acquired by `fopen` and released by `fclose`.
- ▶ A typical code sandwich: acquire – use – release.

Resource management could become complicated.

```
// C-style resource management
void some_function() {
    FILE *fp = fopen("input_file", "r");
    if (...) {
        ...
        fclose(fp);
        return;
    }
    for (...) {
        if (...) {
            ...
        }
        else {
            ...
            fclose(fp);
            return;
        }
    }
    fclose(fp);
}
```

- ▶ When there are many returns, the programmer is responsible to make sure the resource is always released.

The previous programs are WRONG!

```
void some_function() {  
    FILE *fp = fopen("input_file", "r");  
    another_function(fp);  
    fclose(fp);  
}
```

- ▶ If `another_function` throws an exception, `fclose(fp);` won't be executed.
- ▶ There will be resource leakage.
 - ▶ A function in the call stack may allow the program to recover from the exception.
 - ▶ However, you won't be able to release the file handle `fp`. It's lost.

Thinking of try-catch?

```
void some_function() {  
    FILE *fp = NULL;  
    try {  
        fp = fopen("input_file", "r");  
        another_function(fp);  
        fclose(fp);  
    }  
    catch (...) {  
        if (fp != NULL) fclose(fp);  
    }  
}
```

- ▶ I should use “finally” as in many other languages.
- ▶ Though in C++ we don't have it since we don't need it.
 - ▶ Those languages eventually learned from C++ so that “finally” is not needed in many cases nowadays.

Too complicated!

```
// similar to Java resource management prior to Java 1.7
void some_function() {
    FILE *fp_in = NULL; FILE *fp_out = NULL;
    try {
        fp_in = fopen("input_file", "r");
        do_something(fp_in);
        if (...) { fclose(fp_in); return;}
        fp_out = fopen("output_file", "w");
        do_something_else(fp_in, fp_out);
        for (...) {
            ...
            if (...) { fclose(fp_out); fclose(fp_in); return;}
        }
        another_function(fp_out);
        fclose(fp_out); fclose(fp_in);
    } catch (...) {
        if (fp_in != NULL) fclose(fp_in);
        if (fp_out != NULL) fclose(fp_out);
    }
}
```

- ▶ When there are many returns and many resources.
- ▶ I can't guarantee the correctness of the above code since it is too complicated.

Resource Acquisition Is Initialization (RAII)

```
void some_function() {  
    std::ifstream fin("input_file");  
    do_something(fin);  
    if (...) return;  
    std::ofstream fout("output_file");  
    do_something_else(fin, fout);  
    for (...) {  
        ...  
        if (...) return;  
    }  
    another_function(fout);  
}
```

- ▶ C++ makes programmer's life much easier via RAII.
 - ▶ Leverage object lifetime for resource management (as adopted by many other languages).
 - ▶ Use object composition to manage multiple resources.

RAII (Cont.)

```
void some_function() {  
    std::ifstream fin("input_file");  
    do_something(fin);  
    if (...) return;  
    std::ofstream fout("output_file");  
    do_something_else(fin, fout);  
    for (...) {  
        ...  
        if (...) return;  
    }  
    another_function(fout);  
}
```

- ▶ Lifetime of the local objects like `fin` and `fout` is within the function.
 - ▶ A resource is acquired in ctor when the object is constructed.
 - ▶ The resource is released in dtor when the object is destroyed.
- ▶ What about exceptions?

Stack Unwinding

```
void some_function() {  
    std::ifstream fin("input_file");  
    do_something(fin);  
    if (...) return;  
    std::ofstream fout("output_file");  
    do_something_else(fin, fout);  
    for (...) {  
        ...  
        if (...) return;  
    }  
    another_function(fout);  
}
```

- ▶ Local objects are destroyed automatically when the function exits, either normally or due to an unhandled exception, e.g. from `do_something`.
- ▶ Since dtors may be called during exception handling, they SHOULD NEVER throw exceptions.

Resource Management and Object Composition

- ▶ How to design our own class for resource management via RAII?
 - ▶ E.g. `std::vector<T>` and `std::shared_ptr<T>`?
 - ▶ For curiosity and to understand C++ better.
- ▶ Need to understand how RAII interacts with object composition.
 - ▶ Object composition: compose larger object from smaller ones.
 - ▶ E.g. `std::vector<T>` contains many objects of type `T`.

Outline

Resource Management

Object Composition

Object Composition

- ▶ Object composition: compose larger object from smaller ones
 - ▶ The parent (larger) object holds the smaller objects via member variables.
- ▶ Many methods to compose the parent object from smaller objects of type `T`.
 - ▶ Use class types: a member of type `T`, or other types holding objects of type `T` like `std::vector<T>` and `std::shared_ptr<T>`.
 - ▶ Use raw pointers: a member of type `T *` with the objects on the heap.
- ▶ Composition means ownership.
 - ▶ When the parent object is constructed, the objects it holds should be constructed.
 - ▶ When the parent object is destroyed, the objects it holds should be destroyed.

Object Composition \neq Association

- ▶ Association: objects may interact with each other
 - ▶ Associations are implemented as pointers and references.
- ▶ However, association does not imply ownership.
- ▶ Object composition or association?
 - ▶ There are cases where it is difficult to tell one from the other – so we need GC.
 - ▶ Otherwise, it is still preferable in C++ to distinguish the two because ownership and lifetime matter for predictable performance.

Lifetime Management for Member Variables

- ▶ Member variables are constructed before any ctor body.
 - ▶ They are constructed in the order they appear in the class definition.
 - ▶ Programmers may specify how the members are constructed using the initializer list.
 - ▶ The compiler will default initialize all the members whose constructions are not specified by programmers.
 - ▶ So you can use the members in the ctor body.
- ▶ Member variables are destroyed automatically after the dtor body.
 - ▶ So you can use the members in the dtor body.
 - ▶ In the reversed order they appear in the class definition – compiler generates such code and you shouldn't destroy the members explicitly.
 - ▶ Moreover, the compiler will generate an empty public dtor for any non-reference type if the type has no user-defined dtor.
 - ▶ For built-in types, it will do nothing.
 - ▶ For class types, it will destroy their members.

Exception in Ctors and Dtors

- ▶ If a ctor fails, i.e. `throws` an exception, compiler guarantees that,
 - ▶ All-or-None: either the parent object is constructed successfully or (as if) none of the members got constructed.
- ▶ What if a dtor fails?
 - ▶ Dtors should never fail – you should not throw exceptions out of dtors.

Example I: The Classes

```
struct will_not_throw {
    will_not_throw() {std::cout << "ctor of will_not_throw" << std::endl;}
    ~will_not_throw() {std::cout << "dtor of will_not_throw" << std::endl;}
}; // struct will_not_throw

class ctor_throw {
    will_not_throw wnt_;
public:
    ctor_throw() {
        std::cout << "ctor of ctor_throw" << std::endl;
        throw std::runtime_error("from ctor of ctor_throw");
    }
    ~ctor_throw() {std::cout << "dtor of ctor_throw" << std::endl;}
}; // class ctor_throw
```

Example I: Parent Object on the Stack

```
void some_function() {  
    ctor_throw ct;  
}  
  
void some_caller() {  
    try {  
        some_function();  
    }  
    catch (std::exception &e) {  
        std::cout << "exception " << e.what() << std::endl;  
    }  
}
```

- ▶ The output

```
ctor of will_not_throw  
ctor of ctor_throw  
dtor of will_not_throw  
exception from ctor of ctor_throw
```

- ▶ When the ctor of the parent object fails, the members are destroyed automatically.
 - ▶ The dtor of the parent object will not be called since the object has not been constructed – this is exactly what resource management needs!

Example I: Parent Object on the Heap

```
void another_function() {  
    ctor_throw *pct = new ctor_throw;  
}  
  
void another_caller() {  
    try {  
        another_function();  
    }  
    catch (std::exception &e) {  
        std::cout << "exception " << e.what() << std::endl;  
    }  
}
```

- ▶ The output is the same as in the previous slide.
- ▶ No memory leakage: when the construction fails, the piece of allocated memory is returned to the heap automatically.

Example II: The Classes

```
struct will_throw {
    will_throw() {
        std::cout << "ctor of will_throw" << std::endl;
        throw std::runtime_error("from ctor of will_throw");
    }
    ~will_throw() {std::cout << "dtor of will_throw" << std::endl;}
}; // struct will_throw

class member_throw {
    will_not_throw wnt_;
    will_throw wt_;
public:
    member_throw() {std::cout << "ctor of member_throw" << std::endl;}
    ~member_throw() {std::cout << "dtor of member_throw" << std::endl;}
}; // class member_throw
```

Example II: The Output

```
void some_function() {
    member_throw mt;
}

void some_caller() {
    try {
        some_function();
    }
    catch (std::exception &e) {
        std::cout << "exception " << e.what() << std::endl;
    }
}
```

► The output

```
ctor of will_not_throw
ctor of will_throw
dtor of will_not_throw
exception from ctor of will_throw
```

- When the ctor of a member fails, the members that are already constructed will be destroyed automatically.
 - The body of the ctor of the parent object won't be executed.
- Same output if the parent object is created on the heap.

Discussions

- ▶ What about smaller objects on the heap managed via raw pointers as members?
- ▶ Dtor of the parent object will not `delete` those pointers.
 - ▶ Those pointers as member variables will be destroyed after dtor of parent object.
 - ▶ If you recall that to destroy objects means to call dtors on them, then as pointers are built-in types, their dtors will do nothing.
- ▶ It is the responsibility of programmers to manage those pointers through the ctors/dtor of the parent object.
 - ▶ Exception safety: one need to provide the same All-or-None guarantee as the compiler if there are exceptions.

Summary and Advice

- ▶ Member variables are constructed before the ctor body and destroyed after the dtor body.
- ▶ Exceptions interact with objects in a complicated way.
 - ▶ Stack unwinding: local objects are automatically destroyed even when there is an unhandled exceptions.
 - ▶ All-or-None: either the parent object is constructed successfully or none of the members got constructed.