



Geodesic Patterns

Alan Rynne September 2018

UPC - MPDA'18

Objective

Objective

Discretize a given freeform surface into panels with the following properties:

- 1. Panels must be *developable* (Shelden 2002)
- 2. Panels should be of approximate equal width
- 3. Panels should be as straight as possible
- 4. Panels should **bend by their weak axis** to approximate the surface.

Notes: This are reveal notes

Objective

Background

Boat-building

The use of sraight developable planks is widely used in traditional boat building

Some Algorithm

```
1: for i = 1 to N do

2: for j = 1 to JJJJ do

3: energy[i * JJJ + j] = interpolate(AAA[i * JJJ + j], ZZZ)

4: end for

5: end for

Algorithm 1: pseudocode for the calculation of
```

Developable hulls

Connected developable patches for boat hull design.

1. Common practice in naval engineering industry.



Figure 1: Developable hull model

Frank Ghery

This techniques have also been used in the architecture world, mainly by **Frank Ghery**.

His façades are usually a collection of connected developable surfaces.

Burj Khalifa

Latest architectural work following this techiques was:

Burj Khalifa by Frank Ghery

Burj Khalifa

It was designed as a collection of:

- Developable surfaces
 - Which can be covered by equal width planks
- Surfaces of constant cuvrature
 - Which can be covered by repeating the same profile

Burj Khalifa

Construction technique

Geodesic curves

A geodesic curve is the generalization of a $straight\ line$ into $curved\ spaces.$

$$\nabla + \alpha^2 = \sqrt{8} * A$$

Geodesic curves

It could be easiy understood as:

The path that a bug follows on a surface if it only moves forward

Straightest geodesics

In this research, we concentrate on the concept of straightest geodesics.

Developable surfaces

Surfaces with *O gaussian curvature*. Meaning, they can be flattened onto a plane *without distorsion*

Developable surfaces

$Developable\ surfaces$

- can be flattened
- can be generated by a single curve.

and

Geodesic curves

 $\bullet\,$ are straight lines in a curved space.

Therefore

Therefore

We wish to generate panels using geodesic curves in order to achieve straight developable panels

Developable surfaces

In other words:

We wish to cover a given freeform surface with a pattern of **geodesic curves** with equal spacing.

This can only be achieved if the provided surface is already developable.

A compromise exists between the curve spacing and the curve geodesic property

Algorithmic strategies

Obtaining Geodesic Patterns

There are three main methods for the obtaining successful geodesic patterns:

- 1. The parallel transport method
- 2. The evolution method
- 3. The piecewise geodesic vector-field method

The parallel transport method

Vector parallel transport

Parallel transport of a vector on a sphere

Implementation details

 $Parallel\ transport\ method\ over\ positive\ curvature\ surface$

Results

Results

The evolution method

Implementation details

Results

The piecewise evolution method

Implementation details

Results

The level set method

Implementation details

Results

Modeling planks

Tangent developable method

Bi-Normal method

Comparisson

Optimization

Piecewise geodesic vector-fields

Developability of triangle meshes

Analysis

Conclusion

Thanks

Conclusion

Thanks

References i

Shelden, Dennis Robert. 2002. "Digital Surface Representation and the Constructibility of Gehry's Architecture." PhD thesis, Massachusetts Institute of Technology. http://hdl.handle.net/1721.1/16899.