

HOMEWORK ASSIGNMENT #5

DUE: Thursday, November 12, 2019, 5.30PM

CSCI677: Computer Vision, Prof. Nevatia

Fall Semester, 2020

This is a programming assignment to create, train, and test a CNN for the task of semantic segmentation following the FCN32s method described in <https://people.eecs.berkeley.edu/~shelhamer/data/fcn.pdf> (also in KRSB book, section 7.3.1).

a) Architecture:

Construct a Fully Convolutional Network FCN-32s. FCN-32s network is based on VGG-16 network with 3 modifications. You can obtain a pre-trained VGG16 using ``torchvision.models.vgg16 (pretrained=True)`` and use ``features`` method to perform forward pass till before the linear layers.

(i) Replace the first FC layer by a convolutional layer (refer as “conv6”) with kernel size of 7 x 7. Number of filters is the output dimension of the original FC layer, which is **4096**;

(ii) Replace the second FC layers by a convolutional layer (refer as “conv7”) with a kernel size of 1 x 1. The output dimension is **4096**.

(iii) Replace the third FC layers by a convolutional layer (refer as “score”) with a kernel size of 1 x 1. The output dimension is **number of classes**.

(iv) Add a single transpose convolutional layer after the third FC layer. The configuration for the transpose convolutional layer in this assignment is stride=32, that up-sample the feature tensor back to the input image size. In PyTorch you could use ``torch.nn.ConvTranspose2d`` for transpose convolution.

Note that for stride=32, the kernel size should be larger than 32 to avoid having hollow pixels in your output.

For example, you can refer to (but not limit to) the following options:

- with kernel size of 32:
 - `torch.nn.ConvTranspose2d(num_class, num_class, kernel_size=(32, 32), stride=32 padding=0, bias=False)`
- with kernel size of 64:
 - `torch.nn.ConvTranspose2d(num_class, num_class, kernel_size=(64, 64), stride=32 padding=16, bias=False)`

Except for the three modifications above, other parts of FCN-32s remain the same as for VGG-16. Below is the table from the VGG paper(<https://arxiv.org/pdf/1409.1556.pdf>), **ConvNet Configuration D** is the one we want to use.

ConvNet Configuration					
A	A-LRN	B	C	D	E
11 weight layers	11 weight layers	13 weight layers	16 weight layers	16 weight layers	19 weight layers
input (224 × 224 RGB image)					
conv3-64	conv3-64 LRN	conv3-64 conv3-64	conv3-64 conv3-64	conv3-64 conv3-64	conv3-64 conv3-64
maxpool					
conv3-128	conv3-128	conv3-128 conv3-128	conv3-128 conv3-128	conv3-128 conv3-128	conv3-128 conv3-128
maxpool					
conv3-256 conv3-256	conv3-256 conv3-256	conv3-256 conv3-256	conv3-256 conv3-256 conv1-256	conv3-256 conv3-256 conv3-256	conv3-256 conv3-256 conv3-256 conv3-256
maxpool					
conv3-512 conv3-512	conv3-512 conv3-512	conv3-512 conv3-512	conv3-512 conv3-512 conv1-512	conv3-512 conv3-512 conv3-512	conv3-512 conv3-512 conv3-512 conv3-512
maxpool					
conv3-512 conv3-512	conv3-512 conv3-512	conv3-512 conv3-512	conv3-512 conv3-512 conv1-512	conv3-512 conv3-512 conv3-512	conv3-512 conv3-512 conv3-512 conv3-512
maxpool					
FC-4096					
FC-4096					
FC-1000					
soft-max					

Once we have the FCN-32s structure, we would like to use FCN-16s as well.

In FCN32s, it applies a 32x upsample to map the “score” layer back to the input image size (in terms of height and width).

For FCN-16s, we want to additionally consider the information from the lower layer “pool4” output, whose output tensor has 1/16 spatial size of compare to the input image. To make prediction from both “pool4” and “score”, we need to

- Upsample the “score” by 2 times so it also reaches the 1/16 spatial size of input
- For “pool4” output, apply a Conv2D layer with kernel=1x1 to map it to **number of classes** output dimension.
- Add two resulting tensors together (both of size [num_class, h/16, w/16]), and then upsample the resulting tensor by 16 times, to match the input image resolution.

The above procedure is defined in the FCN paper, please refer to the paper for more details

Note that for FCN-16s you would need output from a previous layer and the default module obtained from `torchvision` doesn't contain a function to obtain output from a different layer. There are two ways to go about this:

(i) copy-paste the whole forward function of vgg16 and create a new function which does forward pass only till the required layer or change the outputs of the forward function to return all the layers. For example:

Default torchvision function:

```
'''  
  
def forward(self, x):  
  
    x1 = self.layer1(x)  
  
    x2 = self.layer2(x1)  
  
    return x2  
  
'''
```

New function:

```
'''  
  
def forward(self, x):  
  
    x1 = self.layer1(x)  
  
    x2 = self.layer2(x1)  
  
    return x2, x1  
  
'''
```

(ii) Use class IntermediateLayerGetter

(https://github.com/pytorch/vision/blob/master/torchvision/models/_utils.py)

Here is an example provided by Pytorch, you need to replace the model and intermediate layer according to HW requirements.

```
>>> m = torchvision.models.resnet18(pretrained=True)
>>> # extract layer1 and layer3, giving as names `feat1` and feat2`
>>> new_m = torchvision.models._utils.IntermediateLayerGetter(m,
>>>     {'layer1': 'feat1', 'layer3': 'feat2'})
>>> out = new_m(torch.rand(1, 3, 224, 224))
>>> print([(k, v.shape) for k, v in out.items()])
>>>     [('feat1', torch.Size([1, 64, 56, 56])),
>>>     ('feat2', torch.Size([1, 256, 14, 14]))]
```

Hence, you can use the other output.

b) Dataset

We will use the Kitti dataset for semantic segmentation.

You will need to download dataset from

http://www.cvlibs.net/datasets/kitti/eval_semseg.php?benchmark=semantics2015.

- Go to website
- Download dataset by clicking

The data can be downloaded here:

- [Download label for semantic and instance segmentation \(314 MB\)](#)
- [Download development kit \(1 MB\)](#)

- You will need to provide your email to get download link
- Once downloaded, you can upload the zip file to Colab
- In the execution cell, run `!unzip path_to_the_file` (e.g. `!unzip data_semantics.zip`) to unzip the file
- For visualization, you also need to download development kit and unzip it in the same way as above

You should now have: 1. **data_semantics** which contains images and ground truth and 2. **devkit_semantics** which contains metadata of Kitti.

data_semantics has two folders: **training** and **testing**, we will not use **testing** folder.

In training folder, you can find four folders: **image_2**, **instance**, **semantic**, **semantic_rgb**. We will not use the **instance** folder.

In model training, you will use **image_2** and **semantic** folder.

image_2 contains 200 images and **semantic** contains corresponding ground truth. You can use

`opencv` or `skimage` to read image and ground truth.

Ground truth gives the category of each pixel, there are total 35 categories (see figure below) defined in Kitti (not all of them exists in image but you don't need to care missing classes), you can find the corresponding label in the file "devkit_semantics/devkit/helpers/labels.py". In this label file, we only care about 3 columns, "name", "id" and "color", you can ignore other columns. "name" is the human readable label for each class. "id" is each class's corresponding label in ground truth. "color" gives the color mapping from class to RGB color. For visualization result in the report, you will need to map your prediction to color according to ("id", "color") correspondence.

```
labels = [
#       name            id  trainId  category      catId  hasInstances  ignoreInEval  color
Label( 'unlabeled'      , 0 ,    255 , 'void'        , 0      , False      , True        , ( 0, 0, 0) ),
Label( 'ego vehicle'    , 1 ,    255 , 'void'        , 0      , False      , True        , ( 0, 0, 0) ),
Label( 'rectification border' , 2 ,    255 , 'void'        , 0      , False      , True        , ( 0, 0, 0) ),
Label( 'out of roi'     , 3 ,    255 , 'void'        , 0      , False      , True        , ( 0, 0, 0) ),
Label( 'static'         , 4 ,    255 , 'void'        , 0      , False      , True        , ( 0, 0, 0) ),
Label( 'dynamic'        , 5 ,    255 , 'void'        , 0      , False      , True        , (111, 74, 0) ),
Label( 'ground'         , 6 ,    255 , 'void'        , 0      , False      , True        , ( 81, 0, 81) ),
Label( 'road'           , 7 ,     0 , 'flat'        , 1      , False      , False       , (128, 64, 128) ),
Label( 'sidewalk'       , 8 ,     1 , 'flat'        , 1      , False      , False       , (244, 35, 232) ),
Label( 'parking'        , 9 ,    255 , 'flat'        , 1      , False      , True        , (250, 170, 160) ),
Label( 'rail track'     , 10 ,    255 , 'flat'        , 1      , False      , True        , (230, 150, 140) ),
Label( 'building'      , 11 ,     2 , 'construction', 2      , False      , False       , ( 70, 70, 70) ),
Label( 'wall'           , 12 ,     3 , 'construction', 2      , False      , False       , (102, 102, 156) ),
Label( 'fence'          , 13 ,     4 , 'construction', 2      , False      , False       , (190, 153, 153) ),
Label( 'guard rail'     , 14 ,    255 , 'construction', 2      , False      , True        , (180, 165, 180) ),
Label( 'bridge'         , 15 ,    255 , 'construction', 2      , False      , True        , (150, 100, 100) ),
Label( 'tunnel'         , 16 ,    255 , 'construction', 2      , False      , True        , (150, 120, 90) ),
Label( 'pole'           , 17 ,     5 , 'object'      , 3      , False      , False       , (153, 153, 153) ),
Label( 'polegroup'      , 18 ,    255 , 'object'      , 3      , False      , True        , (153, 153, 153) ),
Label( 'traffic light'  , 19 ,     6 , 'object'      , 3      , False      , False       , (250, 170, 30) ),
Label( 'traffic sign'   , 20 ,     7 , 'object'      , 3      , False      , False       , (220, 220, 0) ),
Label( 'vegetation'     , 21 ,     8 , 'nature'      , 4      , False      , False       , (107, 142, 35) ),
Label( 'terrain'        , 22 ,     9 , 'nature'      , 4      , False      , False       , (152, 251, 152) ),
Label( 'sky'            , 23 ,    10 , 'sky'         , 5      , False      , False       , ( 70, 130, 180) ),
Label( 'person'         , 24 ,    11 , 'human'       , 6      , True       , False       , (220, 20, 60) ),
Label( 'rider'          , 25 ,    12 , 'human'       , 6      , True       , False       , (255, 0, 0) ),
Label( 'car'            , 26 ,    13 , 'vehicle'     , 7      , True       , False       , ( 0, 0, 142) ),
Label( 'truck'          , 27 ,    14 , 'vehicle'     , 7      , True       , False       , ( 0, 0, 70) ),
Label( 'bus'            , 28 ,    15 , 'vehicle'     , 7      , True       , False       , ( 0, 60, 100) ),
Label( 'caravan'        , 29 ,    255 , 'vehicle'     , 7      , True       , True        , ( 0, 0, 90) ),
Label( 'trailer'        , 30 ,    255 , 'vehicle'     , 7      , True       , True        , ( 0, 0, 110) ),
Label( 'train'          , 31 ,    16 , 'vehicle'     , 7      , True       , False       , ( 0, 80, 100) ),
Label( 'motorcycle'     , 32 ,    17 , 'vehicle'     , 7      , True       , False       , ( 0, 0, 230) ),
Label( 'bicycle'        , 33 ,    18 , 'vehicle'     , 7      , True       , False       , (119, 11, 32) ),
Label( 'license plate'  , -1 ,    -1 , 'vehicle'     , 7      , False      , True        , ( 0, 0, 142) ),
]
```

Ground truth metadata file (devkit_semantics/devkit/helpers/labels.py)

Kitti does not offer ground truth for testing set. So for this assignment, you should split the original training set into training/validation/testing sets. Sort images alphabetically and split by ratio 70%/15%/15% for training/validation/testing. (Hint: use `os.listdir()` to read files may give file order shuffled, use `sorted()` function after getting files)

Folder **semantic_rgb** contains the visual ground truth of the segmentations. You will use it in visual comparison with your prediction.

PyTorch does not offer a predefined dataset class for Kitti. You will need to implement a `KittiDataset` class by yourself.

c) Training:

Train the network using the images in the train set mentioned in the **Dataset** section.

We suggest using a batch size of 5, ADAM optimizer, learning rate = 0.001, momentum = 0.99. though you are free to experiment with other values.

Use cross entropy loss over the individual pixels as the loss function. You could use ``torch.nn.CrossEntropyLoss``.

It should not be necessary to do data augmentation as there are many samples in each image. However, if you choose to experiment with augmentations, please note that you would need to perform the same augmentation on the ground-truth segmentation mask as well. As an example, in classification setting, a flipped dog is still a dog, however, in the image segmentation setting, a flipped dog will require a flipped mask.

Record the IoU and loss after each iteration so that you can monitor it and plot it to show results.

d) Evaluation metric:

Use the following two evaluation metrics:

- (1) Pixel-level intersection-over-union (IoU): Pixel-level $\text{IoU} = \text{TP} / (\text{TP} + \text{FP} + \text{FN})$, where TP, FP, and FN are the numbers of true positive, false positive, and false negative pixels, respectively. Pixel-level IoU should be computed on each class separately (treat other classes as negative when computing for one class). NOTE: You should compute IoU over all testing images not on single image and then do average.
- (2) mean intersection-over-union (mIoU): mIoU is just a simple average of per-class pixel-level IoU, it reflects your model's generality on all classes.

Please write your own code to evaluate network performance.

e) Results:

Map your output labels to color images which should look like the images in the **semantic_rgb** folder. Color mapping is provided in the file `"devkit_semantics/devkit/helpers/labels.py"`

SUBMISSION:

You should turn in a single PDF file with the following components:

1. A brief description of the programs you write, including the source listing.
2. Evolution of loss function with multiple steps.
3. A summary and discussion of the results, including the effects of parameter choices. Compare the 2 versions of FCN (32s and 16s). Include the visualization of results; show some examples of successful and some failure examples.