YaoCompiler: Unleash Julia on quantum devices

Xiu-zhe (Roger) Luo, Chen Zhao, Valentin Churavy, Roger Melko

QUANTUM INTELLIGENCE LAB University of Waterloo
中国科学院数学与系统科学研究院 Academy of Mathematics and Systems Science, CAS
Massachusetts Institute of Technology
Unitary Fund

Quantum Information on Real Hardware



Google's superconducting device



cold atom device, Harvard



Ion trap device, Harvard

Jiuzhang optical device, USTC

Superconducting device, IBM

And more…

Applications



optimization



simulate quantum system



variational eigensolver/machine learning

Ebadi, S., Wang, T.T., Levine, H. *et al.* Quantum phases of matter on a 256-atom programmable quantum simulator. *Nature* **595,** 227–232 (2021).

Farhi E, Goldstone J, Gutmann S. A quantum approximate optimization algorithm[J]. arXiv preprint arXiv:1411.4028, 2014.

Peruzzo A, McClean J, Shadbolt P, et al. A variational eigenvalue solver on a photonic quantum processor[J]. Nature communications, 2014, 5(1): 1-7

Programability of Quantum Devices



How do we program these devices?



New high-level language?
New compiler?
New assembly?

Julia: we want one language rather than two!

Static Compiled Language

good compiler analysis! But not interactive

Interpreter Language:

Interactive but not much compiler analysis!

The language designed for JIT!



Julia: come for the syntax, stay for the speed, nature, 30 July 2019

Can we have just one language for quantum device?

YaoCompiler

Goal of Yao Ecosystem

- Power quantum information research in Julia

Goal of YaoCompiler

- Foundation of quantum compilation in Julia

```
jp (julia)                                                    ⌥⌘3

julia> using YaoCompiler

julia> qasm"""OPENQASM 2.0;
       include "qelib1.inc";

       gate post q { x q;}
       """
post (generic routine with 1 methods)

julia> @device function circuit()
           1:3 => ccx()
           (2,3) => cx()
           2=>h()
           c = @measure 1
           if c == 1
               3 => post()
           end
           3=>rx(1.0)
           return (c=c, )
       end
circuit (generic routine with 1 methods)

julia> @code_qasm circuit()
OPENQASM 2.0
creg c[1];
qreg qreg_1[3];
ccx qreg_1[0], qreg_1[1], qreg_1[2];
cx qreg_1[1], qreg_1[2];
h qreg_1[1];
measure qreg_1[0] -> c[0];
if (c == 1) post qreg_1[2];
post qreg_1[2];
rx(1.0) qreg_1[2];

julia>
```

Powered by the GPUCompiler infrastructure !

Live demo

Compile a quantum program to openQASM

Julia in heterogonous computing era

DSL for heterogonous computing
(new language/API with new compiler)



Julia with Compiler Plugins
(new intrinsic with the same language)



JuliaGPU (CUDA, AMDGPU, Metal)

And TPU!

How to train your GPU: 10.000 foot view

Fortran

OpenACC

CUDA
C/C++

Application

Data-parallel operations

CUDA kernels



julia

AbstractArrays CuArrays.jl CUDAnative.jl

5

Tim Besard

Valentin Churavy

What about…?

	YaoCompiler	QCOR	Q#	Quingo	qiskit
extends	Julia	C++ & Python	.Net	N/A	Python
level	High-level	System	System	System	High-level
Hybrid program	Yes	Yes	Yes	Yes	N/A
Kernel Language	Julia	C++/Python	Q#	Quingo	Python (class)
Host Language	Julia	C++/Python	C#	Python	Python (class)

Advantage of writing quantum program with YaoCompiler in Julia

- Interactive, nice REPL, interactive code generation for debugging
- Only one language needed for compiler, kernel and host
- Ecosystem for algebraic transform, LLVM.jl, Metatheory.jl, Symbolics.jl, Optimization, Graphs
- Composability, compiler understands the whole ecosystem!

- Mintz T M, Mccaskey A J, Dumitrescu E F, et al. Qcor: A language extension specification for the heterogeneous quantum-classical model of computation[J]. ACM Journal on Emerging Technologies in Computing Systems (JETC), 2020, 16(2): 1-17.
- McCaskey A, Nguyen T. A MLIR Dialect for Quantum Assembly Languages[J]. arXiv preprint arXiv:2101.11365, 2021.
- Cross A. The IBM Q experience and QISKit open-source quantum computing software[C]//APS March Meeting Abstracts. 2018, 2018: L58. 003.
- Team T Q D. Quingo: A Programming Framework for Heterogeneous Quantum-Classical Computing with NISQ Features[J]. arXiv preprint arXiv:2009.01686, 2020.



What has been done or has prototype?

Code generation

- ✓ LLVM IR code generation
- ✓ OpenQASM frontend/codegen

Hardware Targets

- ✓ IBM Q service as backend
- ○ AWS Braket as backend (WIP)

Compiler Optimization

- ✓ ZX calculus-based circuit simplification
- ✓ Hybrid program analysis (via Julia compiler)
- ○ Brute force pattern match via egg (WIP)

Landscape of compiler toolchain (2021)
QEDC Compiler workshop

YaoCompiler pipeline

JuliaCompilerPlugin org

Challenge for modern compilers

How to:

- Compile a high-level language all the way to down to the hardware? (architecture, this work)
- simplify a quantum circuit to reduce gate count? (ZX calculus, pattern matching)
- decompose arbitrary gate into given gate set? (circuit synthesis)
- decompose long entangled gates into more local gates? (circuit synthesis, mapping)
- decompose a gate operator into pulse sequence? (pulse design)
- mitigate noise effects? (error mitigation)
- find the effective Hamiltonian of a Hamiltonian in question?
- Assert the error due to ill-defined quantum operation? (quantum programming theory)