

Zceb 0.53

This document is in the Stable state. Assume anything could still change, but limited change should be expected. For more information see: <https://riscv.org/spec-state>

This extension reuses encodings from the *D*-extension. Therefore it is *incompatible* with D. It is fully compatible with F and also with Zdinx.

The instructions are all 16-bit versions of existing 32-bit load/store instructions.

RV32	RV64	Mnemonic	Instruction
✓	✓	c.lbu <i>rd'</i> , uimm(<i>rs1'</i>)	Load unsigned byte, 16-bit encoding
✓	✓	c.lb <i>rd'</i> , uimm(<i>rs1'</i>)	Load signed byte, 16-bit encoding
✓	✓	c.lhu <i>rd'</i> , uimm(<i>rs1'</i>)	Load unsigned halfword, 16-bit encoding
✓	✓	c.lh <i>rd'</i> , uimm(<i>rs1'</i>)	Load signed halfword, 16-bit encoding
✓	✓	c.sb <i>rs2'</i> , uimm(<i>rs1'</i>)	Store byte, 16-bit encoding
✓	✓	c.sh <i>rs2'</i> , uimm(<i>rs1'</i>)	Store halfword, 16-bit encoding

c.lbu

Synopsis

Load unsigned byte, 16-bit encoding

Mnemonic

c.lbu *rd'*, *uimm(rs1')*

Encoding (RV32, RV64)

```
Failed to generate image: wavedrom-cli.CMD failed:
{reg:[
  { bits:  2, name: 0x2, attr: ['C0'] },
  { bits:  3, name: 'rd\'' },
  { bits:  2, name: 'uimm[2:1]' },
  { bits:  3, name: 'rs1\'' },
  { bits:  2, name: 'uimm[0|3]' },
  { bits:  1, name: 0x0 },
  { bits:  3, name: 0x1, attr: ['FUNCT3'] },
],config:{bits:16}}
```

Description

This instruction loads a byte from the memory address formed by adding *rs1'* to the zero extended immediate *uimm*. The resulting byte is zero extended to XLEN bits and is written to *rd'*.

NOTE

rd' and *rs1'* are from the standard 8-register set x8-x15.

Prerequisites

The C-extension. This encoding conflicts with the D-extension, but there is no conflict with Zdinx if double-precision arithmetic is required.

32-bit equivalent

[\[insns-lbu\]](#)

Operation

```
//This is not SAIL, it's pseudo-code. The SAIL hasn't been written yet.

X(rdc) = EXTZ(mem[X(rs1c)+EXTZ(imm)][7..0]);
```

Included in

Extension	Minimum version	Lifecycle state
Zceb (Zceb 0.53)	0.53	Stable

c.lb


Synopsis

Load signed byte, 16-bit encoding

Mnemonic

c.lb *rd'*, *uimm(rs1')*

Encoding (RV32, RV64)



Description

This instruction loads a byte from the memory address formed by adding *rs1'* to the zero extended immediate *uimm*. The resulting byte is sign extended to XLEN bits and is written to *rd'*.

NOTE | *rd'* and *rs1'* are from the standard 8-register set x8-x15.

Prerequisites

The C-extension. This encoding conflicts with the D-extension, but there is no conflict with Zdinx if double-precision arithmetic is required.

32-bit equivalent

[\[insns-lb\]](#)

Operation

```
//This is not SAIL, it's pseudo-code. The SAIL hasn't been written yet.  
  
X(rdc) = EXTZ(mem[X(rs1c)+EXTZ(imm)] [7..0]);
```

Included in

Extension	Minimum version	Lifecycle state
Zceb (Zceb 0.53)	0.53	Stable

c.lhu

Synopsis

Load unsigned halfword, 16-bit encoding

Mnemonic

c.lhu *rd'*, *uimm(rs1')*

Encoding (RV32, RV64)

15	13	12	11	10	9	7	6	5	4	2	1	0
0	0	1	1	uimm[4:3]		rs1'		uimm[2:1]		rd'	1	0
FUNCT3											C0	

Description

This instruction loads a halfword from the memory address formed by adding *rs1'* to the zero extended immediate *uimm*. The resulting halfword is zero extended to XLEN bits and is written to *rd'*.

NOTE

rd' and *rs1'* are from the standard 8-register set x8-x15.

Prerequisites

The C-extension. This encoding conflicts with the D-extension, but there is no conflict with Zdinx if double-precision arithmetic is required.

32-bit equivalent

[\[insns-lhu\]](#)

Operation

```
//This is not SAIL, it's pseudo-code. The SAIL hasn't been written yet.  
  
X(rdc) = EXTZ(load_mem[X(rs1c)+EXTZ(imm)] [15..0]);
```

Included in

Extension	Minimum version	Lifecycle state
Zceb (Zceb 0.53)	0.53	Stable

c.lh


Synopsis

Load signed halfword, 16-bit encoding

Mnemonic

c.lh *rd'*, *uimm*(*rs1'*)

Encoding (RV32, RV64)



Description

This instruction loads a halfword from the memory address formed by adding *rs1'* to the zero extended immediate *uimm*. The resulting halfword is sign extended to XLEN bits and is written to *rd'*.

NOTE | *rd'* and *rs1'* are from the standard 8-register set x8-x15.

Prerequisites

The C-extension. This encoding conflicts with the D-extension, but there is no conflict with Zdinx if double-precision arithmetic is required.

32-bit equivalent

[\[insns-lh\]](#)

Operation

```
//This is not SAIL, it's pseudo-code. The SAIL hasn't been written yet.  
  
X(rdc) = EXTS(load_mem[X(rs1c)+EXTZ(imm)] [15..0]);
```

Included in

Extension	Minimum version	Lifecycle state
Zceb (Zceb 0.53)	0.53	Stable

c.sb

Synopsis

Store byte, 16-bit encoding

Mnemonic

c.sb *rs2'*, *uimm(rs1')*

Encoding (RV32, RV64)

```
Failed to generate image: wavedrom-cli.CMD failed:
{reg:[
  { bits: 2, name: 0x0, attr: ['C0'] },
  { bits: 3, name: 'rs2\'' },
  { bits: 2, name: 'uimm[2:1]' },
  { bits: 3, name: 'rs1\'' },
  { bits: 2, name: 'uimm[0|3]' },
  { bits: 1, name: 0x0},
  { bits: 3, name: 0x5, attr: ['FUNCT3'] },
],config:{bits:16}}
```

Description

This instruction stores the least significant byte of *rs2'* to the memory address formed by adding *rs1'* to the zero extended immediate *uimm*.

NOTE

rd' and *rs1'* are from the standard 8-register set x8-x15.

Prerequisites

The C-extension. This encoding conflicts with the D-extension, but there is no conflict with Zdinx if double-precision arithmetic is required.

32-bit equivalent

[\[insns-sb\]](#)

Operation

```
//This is not SAIL, it's pseudo-code. The SAIL hasn't been written yet.

mem[X(rs1c)+EXTZ(uimm)] [7..0] = X(rs2c)
```

Included in

Extension	Minimum version	Lifecycle state
Zceb (Zceb 0.53)	0.53	Stable

c.sh


Synopsis

Store halfword, 16-bit encoding

Mnemonic

c.sh *rs2'*, *uimm(rs1')*

Encoding (RV32, RV64)



Description

This instruction stores the least significant halfword of *rs2'* to the memory address formed by adding *rs1'* to the zero extended immediate *uimm*.

NOTE *rd'* and *rs1'* are from the standard 8-register set x8-x15.

Prerequisites

The C-extension. This encoding conflicts with the D-extension, but there is no conflict with Zdinx if double-precision arithmetic is required.

32-bit equivalent

[\[insns-sh\]](#)

Operation

```
//This is not SAIL, it's pseudo-code. The SAIL hasn't been written yet.

mem[X(rs1c)+EXTZ(uimm)] [15..0] = X(rs2c)
```

Included in

Extension	Minimum version	Lifecycle state
Zceb (Zceb 0.53)	0.53	Stable