



KubeCon



CloudNativeCon

China 2018

Securing the Perimeter

CFCR/CFAR Chain Of Custody With CI/CD Pipelines





KubeCon



CloudNativeCon

China 2018


Who We Are...

Keith Strini ...



.... Shaozhen Ding

- Provide operational assistance and guidance
- Build balanced customer product teams delivering “Platform” as a capability within their organization
- Establish and maintain continuous delivery pipelines for deployment of Pivotal Cloud Foundry and related products in a customer’s infrastructure
- Design and implement continuous integration and continuous delivery processes to deliver customer applications to production, fostering a culture of continuous process improvement



Shift the Mindset



KubeCon



CloudNativeCon

China 2018

*"Assume The Continuous Threat of Compromise and Then
Continuously Move The Target "*

From Reactive Courses of Action into Proactive Security Policy

◆ Recovery Point Objective

- The recovery point objective (RPO) is the point in time that you wish to recover to.

◆ Recovery Time Objective

- The recovery time objective (RTO) is how long it takes to recover, taken irrespective of the RPO. That is, after the disaster, how long until you have recovered to the point determined by the RPO.

A Standard Delivery Pipeline




KubeCon



CloudNativeCon

China 2018



Defending the Supply Chain Threat




KubeCon



CloudNativeCon

China 2018



Limiting CI/CD Breakout Exposure




KubeCon



CloudNativeCon

China 2018



Defending the Application Integrity




KubeCon



CloudNativeCon

China 2018





KubeCon




CloudNativeCon

China 2018

So What Happens During The Push?

Code Built,
Tested,
Security Scanned



Defending the Continuous Threat

(Privilege Escalation, File System Modification, Container Breakout)



KubeCon



CloudNativeCon

China 2018

phase


4

User Namespace => Restricted User Scope

Mount Namespace + pivot_root => File System Isolation

Each Container can have its own root filesystem separate from the host

- PCF uses hardened, streamlined Ubuntu stemcell
- VMs use hardened, streamlined cflinuxfs3 rootFS
- PCF uses a combination of OverlayFS and XFS as a filesystem for containers
- The read-only layer in all containers is RootFS
- The application binaries are in a very small read-write layer of the file system



Defending the Continuous Threat

(DoS of Containers, DoS of Service to Host, Kernel Mods, MITM Attacks)



KubeCon



CloudNativeCon

China 2018

phase

4


Network Namespace + port
virtualization => Network Isolation

CGroups => Resource Isolation (CPU
share Capping), Device Access WL

Rootless containers

App Armor confines untrusted
processes

Seccomp system call filtering



Defending the Continuous Threat

(Malware)






KubeCon



CloudNativeCon

China 2018

 Continuous Zero
Downtime CVE Patching
(Repair Vulnerable Components)



Defending the Continuous Threat

(Advanced Persistent Threat)




KubeCon




CloudNativeCon

China 2018



 Canary Style deployment model plus Infrastructure as code from version control (Repave all system components)



Defending the Continuous Threat

(Leaked Credentials)



KubeCon




CloudNativeCon

China 2018



Continuous Zero
Zero Trust Network
Model (Rotation of all
system credentials)



Bringing it all together




KubeCon



CloudNativeCon

China 2018



Conclusion - Move The Target



KubeCon



CloudNativeCon

China 2018

Proactive Security Policy

Phase I - Aggressive Rotation of the issued Developer Keys

Phase II – Rotation of Environment Credentials, End Point IPs, and Dynamic Management of IP WL/ACLs

Phase III - Continuous Verification of the Application Integrity

Phase IV – Continuous Authorization for Runtime Validation

Phase V – Continuous Paving of the Environment, Rotation of the Keys, Renewal of Authorizing Credentials plus Least Privilege Container Authority



KubeCon



CloudNativeCon

China 2018



What Does Bosh Do



KubeCon



CloudNativeCon

China 2018

CLOUDFOUNDRY



BOSH is an open source tool for release engineering, deployment, lifecycle management, and monitoring of distributed systems such as Kubernetes.

Packaging w/ embedded OS

Server provisioning on any IaaS

Software deployment across availability zones

Health monitoring (server AND processes)

Self-healing w/ Resurrector

Storage management

Rolling upgrades via canaries

Easy scaling of clusters

Backup and Restore

Rotating Server Credentials

- Cloud Native Security

- Repair
- Repave
- Rotate

Enterprise Docker Registry - Harbor



KubeCon



CloudNativeCon

China 2018

- LDAP Integration
- Clair Security Scanning
- **Docker Content Trust via Notary**
- Role Based Access Control

