



KubeCon



CloudNativeCon

China 2018

# SIG Cluster Lifecycle: Deep Dive

Di Xu & Alexander Kanevskiy  
2018-11-15



# Who Are We?



KubeCon



CloudNativeCon

China 2018



Di Xu  
Kubernetes Member  
Top 50 Code Contributor to K/K  
Ant Financial  
@dixudx



Alexander Kanevskiy  
Kubernetes Member  
Open Source Technology Center  
Intel  
@kad

# Our Mission



KubeCon



CloudNativeCon

China 2018

*SIG Cluster Lifecycle's objective is to simplify creation, configuration, upgrade, downgrade, and teardown of Kubernetes clusters and their components.*



# SIG Cluster Lifecycle Projects



KubeCon



CloudNativeCon

China 2018

- **kubeadm**
- **cluster-api**
- kops
- kubespray
- minikube
- bootkube
- kubeadm-dind-cluster
- ...

# Agenda



KubeCon



CloudNativeCon

China 2018

- kubeadm
  - Best practices: install and fine-tuning
  - How it works
  - Current status and plans
- Cluster API
- Join and contribute!



KubeCon



CloudNativeCon

China 2018

# kubeadm Best Practices



# Installing kubeadm

## Ways of installing kubeadm:

- Supported distributions
  - Container Linux
  - DEBs and RPMs:  
Ubuntu, Debian, Hypriot, RHEL,  
CentOS, Fedora
- There are other distros
  - OpenSuSE, ArchLinux, ...

## What is actually needed on the node:

- kubeadm
- kubelet
- kubectl
- CNI plugins
- cri-tools

For distros without official support you can use Container Linux section for manually install binaries  
<https://kubernetes.io/docs/setup/independent/install-kubeadm/>



# kubeadm: fine-tuning kubelet



KubeCon



CloudNativeCon

China 2018

- systemd
  - `/etc/systemd/system/kubelet.service.d/10-kubeadm.conf`
    - **Don't edit it!**
- Override a instance-specific kubelet flag via environment file
  - `/etc/default/kubelet` or `/etc/sysconfig/kubelet`
    - `KUBELET_EXTRA_ARGS="--flag=..."`
- ConfigMap in “kube-system” namespace
  - “kubelet-config-1.X”
- kubeadm-managed files
  - `/var/lib/kubelet/kubeadm-flags.env`
  - `/var/lib/kubelet/config.yaml`



# kubeadm: Offline installation

- Offline and air-gapped detection improved in v1.12
- “Calling home”
  - `--kubernetes-version`
    - `stable`, `stable-1`, `stable-1.12`, ...
    - `latest`, `latest-1`, `latest-1.12`, ...
    - `ci/latest-1.13`
  - `upgrade plan`

```
$ kubeadm config images list
```

- `k8s.gcr.io/kube-apiserver`
- `k8s.gcr.io/kube-controller-manager`
- `k8s.gcr.io/kube-scheduler`
- `k8s.gcr.io/kube-proxy`
- `k8s.gcr.io/pause`
- `k8s.gcr.io/etcd`
- `k8s.gcr.io/coredns`


```
$ kubeadm config images pull
```

[https://dl.k8s.io/release/\\${RELEASE}/bin/linux/amd64/](https://dl.k8s.io/release/${RELEASE}/bin/linux/amd64/)

```
$ gsutil ls -l gs://kubernetes-release/release/v1.12.2/bin/linux/amd64/
```

# kubeadm: Network and Proxies

- Proxy for CRI
  - HTTP\_PROXY
  - HTTPS\_PROXY
  - NO\_PROXY
    - Attention: local registries
- Proxy for kubeadm
  - HTTP\_PROXY
  - HTTPS\_PROXY
  - NO\_PROXY
    - Node IPs range
    - Service IPs range
    - POD IPs range
    - Cluster domains



`NO_PROXY=tld.com,192.168.0.0/16,10.0.0.0/8,cluster.local`

# kubeadm: Using own certificates



KubeCon



CloudNativeCon

China 2018

- Directory with all your custom certificates (--cert-dir)
  - etcd serving: **etcd/ca.key** and **etcd/ca.crt**
  - Cluster CA: **ca.key** and **ca.crt**
  - API Server serving: **apiserver.key** and **apiserver.crt**
  - ServiceAccount signing key: **sa.pub** and **sa.key**
  - API Server Kubelet client: **apiserver-kubelet-client.key** and **apiserver-kubelet-client.crt**
  - Frontend Proxy -- for API Aggregation
    - CA: **front-proxy-ca.key** and **front-proxy-ca.crt**
    - Client: **front-proxy-client.key** and **front-proxy-client.crt**



# kubeadm: Using ComponentConfig



KubeCon



CloudNativeCon

China 2018

- Why use a config file for configuring kubeadm?
  - Tired of long complicated flags
  - Wants more advanced features, including more customized parameters
  - The API spec in v1.12 is unstable, *but there's always an upgrade path*
  - The API spec is graduated to v1beta1 in v1.13
- Supported Kinds in config file
  - InitConfiguration: kubeadm init master-local runtime config
  - ClusterConfiguration: cluster-wide settings, wide range of parameters
  - KubeletConfiguration: cluster-wide kubelet options
  - JoinConfiguration: kubeadm join node-local runtime config
- Saved to ConfigMaps for future upgrading
  - **“kubeadm-config”** and **“kubelet-config-1.x”** in **“kube-system”**

# kubeadm: InitConfiguration



KubeCon



CloudNativeCon

China 2018

```
kubeadm config print-default --api-objects InitConfiguration
```

- Usage
  - “kubeadm init --config ...”
- Why
  - Custom API endpoint address
  - Specify init bootstrap tokens
  - Pass custom kubelet flags
  - Set node name/taints

```
apiVersion: kubeadm.k8s.io/v1beta1
kind: InitConfiguration
localAPIEndpoint:
  advertiseAddress: "10.100.0.1"
  bindPort: 6443
nodeRegistration:
  criSocket: "/var/run/crio/crio.sock"
  kubeletExtraArgs:
    cgroupDriver: "cgroupfs"
bootstrapTokens:
  ...
```

# kubeadm: ClusterConfiguration



KubeCon



CloudNativeCon

China 2018

```
kubeadm config print-default --api-objects ClusterConfiguration
```

- Usage
  - “kubeadm init --config ...”
- Why
  - Fine tune cluster defaults
  - Custom args and volume mounts to control plane components

```
apiVersion: kubeadm.k8s.io/v1beta1
kind: ClusterConfiguration
kubernetesVersion: "v1.12.2"
imageRepository: registry.example.com
networking:
  serviceSubnet: "10.96.0.0/12"
  dnsDomain: "cluster.local"
etcd:
  ...
apiServer:
  extraArgs:
    ...
  extraVolumes:
    ...
```



# Kubeadm: KubeletConfiguration



KubeCon



CloudNativeCon

China 2018

```
kubeadm config print-default --api-objects KubeletConfiguration
```

- Usage
  - “kubeadm init --config ...”
- Why
  - Fine tuning kubelet parameters

```
apiVersion: kubelet.config.k8s.io/v1beta1
kind: KubeletConfiguration
cpuManagerPolicy: static
failSwapOn: false
maxPods: 110
resolvConf: /etc/my-cluster-resolv.conf
```

# Kubeadm: JoinConfiguration



KubeCon



CloudNativeCon

China 2018

```
kubeadm config print-default --api-objects JoinConfiguration
```

- Usage
  - “kubeadm join --config ...”
- Why
  - Customize discovery options
  - Pass custom kubelet flags
  - Set node name/taints

```
apiVersion: kubeadm.k8s.io/v1beta1
kind: JoinConfiguration
nodeRegistration:
  criSocket: /var/run/crio/crio.sock
  name: k8s-node2.example.com
  kubeletExtraArgs:
    cgroupDriver: "cgroupfs"
discovery:
  bootstrapToken:
    apiServerEndpoint: kube-apiserver:6443
    token: abcdef.0123456789abcdef
```

# Kubeadm: KubeProxyConfiguration



KubeCon



CloudNativeCon

China 2018

```
kubeadm config print-default --api-objects KubeProxyConfiguration
```

- Usage
  - “kubeadm init --config ...”
- Why
  - Fine tuning kubeproxy parameters

```
apiVersion: kubeadm.k8s.io/v1beta1
kind: KubeProxyConfiguration
iptables:
  masqueradeAll: false
  masqueradeBit: 14
  syncPeriod: 30s
ipvs:
  syncPeriod: 30s
```



# kubeadm: Managing “addons”



KubeCon



CloudNativeCon

China 2018

- Installed and configured by kubeadm
  - DNS
    - CoreDNS has already been marked as default starting from 1.12
    - kube-dns can be used via feature-gate
  - kube-proxy - deployed as a DaemonSet
- Anything that isn't required for meeting the Conformance criteria is outside of kubeadm scope
  - Dashboard
  - CNI plugins
- Future: [Cluster Bundles](#)...



KubeCon



CloudNativeCon

China 2018

# kubeadm Under the hood



# kubeadm: Atomic work “phases”



KubeCon



CloudNativeCon

China 2018

preflight	Run pre-flight checks
kubelet	Commands related to handling the kubelet.
certs	Generates certificates for a Kubernetes cluster
kubeconfig	Generates all kubeconfig files for the control plane and the admin kubeconfig file
controlplane	Generates all static Pod manifest files necessary to establish the control plane
kubeconfig	Generates all kubeconfig files for the control plane and the admin kubeconfig file
upload-config	Uploads the currently used configuration for kubeadm to a ConfigMap
mark-master	Mark a node as master
bootstrap-token	Manage kubeadm-specific bootstrap token functions
addon	Installs required addons for passing Conformance tests



# kubeadm init




KubeCon



CloudNativeCon

China 2018



# kubeadm join




KubeCon



CloudNativeCon

China 2018



# kubeadm upgrade: Control Plane




KubeCon



CloudNativeCon

China 2018



# kubeadm upgrade: Node



KubeCon



CloudNativeCon

China 2018

- Currently kubeadm only supports upgrading the kubelet ***configuration***, **NOT** the kubelet itself.
  - Manually upgrade the kubelet package using your package manager (e.g. apt, yum)
- Kubeadm will download ConfigMap “*kubelet-config-1.x*” in the “*kube-system*” namespace for global cluster kubelet settings
  - Will be stored as “/var/lib/kubelet/config.yaml”
  - Require kubelet version v1.11+





KubeCon



CloudNativeCon

China 2018

# kubeadm Status and Roadmap





# kubeadm 1.12 Changelog



KubeCon



CloudNativeCon

China 2018

- Config / ComponentConfig
- Experimental: join master
- Improved CRI support
- Improved offline / air-gapped support
- Deprecating of SelfHosting, HA

# kubeadm 1.13 Roadmap



KubeCon



CloudNativeCon

China 2018

- kubeadm is graduated to GA/stable!!!
- Promote the config file from v1alpha3 to v1beta1
- Phases graduated to beta
  - addon, bootstrap-token, certs, control-plane, etcd, kubeconfig, kubelet-start, mark-control-plane, preflight, upload-config
- Bug fixes



**KubeCon**



**CloudNativeCon**

China 2018

# Cluster API



# What is the Cluster API?




KubeCon



CloudNativeCon


China 2018

Declarative API




Cluster  
Machine  
Machine Set + Machine Deployment

Common Logic




Machine Lifecycle (including Provisioning)  
Machine Upgrade

Pluggable Architecture



Infrastructure platform (vSphere, GCP, AWS, etc.)  
Support for various Operating Systems

Tooling, Services



Cluster Bootstrapping, Upgrade  
Auto-scaling, Repair, Node Auto-provisioning



# Bootstrapping - 10 km view




KubeCon



CloudNativeCon

China 2018





# Cluster API: Status



KubeCon



CloudNativeCon

China 2018

- Actively developed providers
  - AWS: <https://github.com/kubernetes-sigs/cluster-api-provider-aws>
    - v1.0.0-alpha.3
  - DigitalOcean: <https://github.com/kubernetes-sigs/cluster-api-provider-digitalocean>
    - v0.2.0
  - AWS/Openshift: <https://github.com/openshift/cluster-operator>
  - Azure: <https://github.com/platform9/azure-provider>
  - GCE, <https://github.com/kubernetes-sigs/cluster-api-provider-gcp>
  - OpenStack: <https://github.com/kubernetes-sigs/cluster-api-provider-openstack>
  - vSphere: <https://github.com/kubernetes-sigs/cluster-api-provider-vsphere>



KubeCon



CloudNativeCon

China 2018

# SIG Cluster Lifecycle

## Join us and get involved!



# How can you contribute to our SIG



- [Contributing to SIG Cluster Lifecycle documentation](#)
- We're working on growing the contributor/reviewers pool; scaling the SIG
- We have "Office Hours" for our projects: weekly for kubeadm, bi-weekly for kops and kubespray...
- Cluster API office hours weekly for both US West Coast and EMEA
- Full list of SIG meetings and links to minutes and recordings can be found on [SIG page](#)
- Attend our Zoom meetings / be around on Slack
- Look for "**good first issue**", "**help wanted**" and "**sig/cluster-lifecycle**" labeled issues in our repositories



# What now?



KubeCon



CloudNativeCon

China 2018

- Follow the [SIG Cluster Lifecycle YouTube playlist](#)
- Check out the [meeting notes](#) for our bi-weekly SIG meetings
- Join [#sig-cluster-lifecycle](#), [#kubeadm](#), [#cluster-api](#), [#kops-dev](#), [#kops-users](#), [#kubespray](#), [#minikube](#), ...
- Prep for and take the [Certified Kubernetes Administrator](#) exam
- Check out the [kubeadm setup guide](#), [reference doc](#) and [design doc](#)
- Read how you can [get involved](#) and improve kubeadm!



**KubeCon**



**CloudNativeCon**

China 2018

# Thank You!







**KubeCon**



**CloudNativeCon**

China 2018

