

JSON2Video provides a simple RESTful web API to create and edit videos programmatically, so you can automate your production process, upgrade your existing product or create amazing new services based on the API.

How JSON2Video Works

The most common use case is creating videos from a pre-defined template. The process is simple:

- **Create a Template:** Use the template editor to design a video structure. Define elements like images, text, audio, and animations.
- **Introduce Variables:** Replace the elements that change from video to video with variables. These variables act as placeholders for your data.
- **Generate Videos:** Call the API with new values for your variables, and the API generates customized videos.

The template defines all necessary details, such as zoom effects, font family, and text size, ensuring consistency across videos. Once set up, you can connect a data source, such as a spreadsheet or database, to scale your production to tens, hundreds, or even thousands of videos.

Versatile Tools for Creative Video Templates

JSON2Video offers a versatile toolbox to create engaging videos. Templates can include:

- Video clips
- Audio files, including music
- Text and animated components

Additionally, the API supports advanced features such as:

- Generating voiceovers in multiple languages
- Adding audiogram waves
- Transcribing voiceovers and overlaying subtitles automatically

Integration Options for Different Users

The API can be integrated in multiple ways depending on your technical expertise:

- **For Developers:** Integrate the API directly into your projects using HTTP requests or SDKs for PHP and Node.js.
- **For Non-Coders:** Use platforms like [Make.com](#) or [Zapier](#) to incorporate JSON2Video into your workflows without coding.

Start Automating Your Video Production

JSON2Video is designed to empower businesses with scalable, automated video production for marketing and social media. Watch our other tutorial videos to learn more about maximizing the potential of this API.

Transkript Video Basic Concepts

Json 2 video is a powerful API that automates video creation enabling businesses to effortlessly generate engaging videos from their data for marketing and social media the most common use case is creating videos from a template the idea is that you create a template using the template editor and Define all elements that are part of the video like images texts audios or animations once you have a dummy video you replace those elements that will change from video to video by variables these variables will be replaced by your data in the next step when you want to create a video you call the API with new values for your variables and the API generates the video in the template we have defined the zoom effect the font family and size for each text element and all necessary details expect the magic when you connect a data source like a spreadsheet or database to Json 2 video scaling your video production to tens hundreds or even thousands of videos the API is designed to be a powerful tool for creating marketing and social media videos and provides a versatile toolbox of elements to create engaging videos your templates can contain other videos audios like music text and animated components the API also allows you to generate voiceover in multiple languages add audiogram waves and transcribe any voice over and overlay subtitles automatically the API can be used in different ways depending on your use case if you are a developer or the engineering resources you can integrate the API directly in your projects with HTTP requests or using the PHP or node.js sdks if you are a no coder you can integrate Json 2 video into your workflows in make.com or zappier thanks for watching this video and don't miss the other tutorial videos.

API server

The API base path is:

<https://api.json2video.com/v2>

Authentication

Add a x-api-key header to your POST and GET request with your API Key as value:

x-api-key: <Your API KEY>

Endpoints

Get the status of your movies

Get the status any of your movies by passing your project ID in the project query parameter. You can get your project ID from the response of the POST request.

Request

GET <https://api.json2video.com/v2/movies>

Create a new movie

Submit a new movie rendering job.

Request

POST <https://api.json2video.com/v2/movies>

body *object* *required* application/json

Instance of [Movie](#)

Schemas

Movie schema

Object defining the movie to be rendered

cache boolean

Use the cached version of the movie if its available

default: true

comment string

Used for adding your comments

draft boolean

Set to true to add a watermark to the movie. Free plans are not allowed to set draft to false

allowed values:

- true
- false

default: true

elements array of any of these

schemas: [Video](#), [Image](#), [Text](#), [HTML](#), [Component](#), [Template](#), [Audio](#), [Voice](#), [Audiogram](#), [Subtitles](#)

exports array of this object:

You can define different types of exports for your movie. Check the [documentation](#) for more information

heightinteger

Height of the movie. Only applicable if resolution is set to custom

default:360

minimum value:>=50

maximum value:<=3840

example value:360

idstring

Movie ID string. It must be unique per project

default:@randomString

qualitystring

Quality of the final rendered movie. Use it for speeding up the rendering process. low is the lowest quality, high is the highest quality

allowed values:

- low
- medium
- high

default:high

resolutionstring

Set the movie size based on common use cases. Use custom to set a custom size with the width and height properties

allowed values:

- sd
- hd
- full-hd
- squared
- instagram-story
- instagram-feed

- twitter-landscape
- twitter-portrait
- custom

default:custom

scenesarray of [Scene](#)*required*

variablesobject

Variables of the template. Variable names can only contain letters, numbers and underscores

default:{}

example value:{ "myVariable": "myValue", "myOtherVariable": true, "myThirdVariable": 123 }

widthinteger

Width of the movie. Only applicable if resolution is set to custom

default:640

minimum value:>=50

maximum value:<=3840

example value:640

Example of movie schema

```
{
  "comment": "MyProject",
  "resolution": "full-hd",
  "scenes": [
    {
      "elements": [
        {
          "type": "video",
          "src": "https://example.com/path/to/my/video.mp4"
        }
      ]
    }
  ]
}
```

```
    }  
  ]  
}
```

Scene schema

background-colorstring

A hexadecimal representation of a color or 'transparent'

default:#000000

example value:#FF0000

cacheboolean

Use the cached version of the scene if its available

default:true

commentstring

Used for adding your comments

conditionstring

OPTIONAL. Condition to be met for the scene to be rendered. If the value is false or empty string, the scene is removed from the movie

durationnumberfloat

Sets the scene duration in seconds. A value of -1 means that the scene lasts enough to contain all its elements

default:-1

elementsarray of any of these

schemas: [Video](#), [Image](#), [Text](#), [HTML](#), [Component](#), [Audio](#), [Voice](#), [Audiogram](#), [Subtitles](#)

idstring

ID of the scene

default:@randomString

transitionobject

durationnumberfloat

Duration of the transition in seconds

example value:1.5

stylestring

allowed values:

- fade
- wipeleft
- wiperight
- wipeup
- wipedown
- slideleft
- slideright
- slideup
- slidedown
- circlecrop
- rectcrop
- distance
- fadeblack
- fadewhite
- radial
- smoothleft
- smoothright
- smoothup
- smoothdown
- circleopen
- circleclose
- vertopen
- vertclose
- horzopen
- horzclose
- dissolve
- pixelize

- diagtl
- diagtr
- diagbl
- diagbr
- hlslice
- hrslice
- vuslice
- vdslice
- hblur
- fadegrays
- wipetl
- wipetr
- wipebl
- wipebr
- squeezeh
- squeezev

default:fade

example value:circleopen

typestring

allowed values:

- xfade

default:xfade

variablesobject

Local variables of the scene. Variable names can only contain letters, numbers and underscores

default: {}

example value: { "myVariable": "myValue", "myOtherVariable": true, "myThirdVariable": 123 }

Video schema

cachebooleanboolean

Use the cached version of the element if its available

default:true

example value:false

chroma-keyobject

Allows to define a color (or a range of colors) that will be converted to transparent

colorstring*required*

Set the color for which alpha will be set to 0 (full transparency)

example value:#00b140

toleranceinteger

Makes the selection more or less sensitive to changes in color. A value of 1 will select only the provided color. A value of 100 will select all colors, so the full canvas

default:25

minimum value:>=1

maximum value:<=100

commentstring

Used for adding your comments

conditionstring

OPTIONAL. Condition to be met for the element to be rendered. If the value is false or empty string, the element is removed from the scene

correctionobject

Allows to adjust the contrast, brightness, saturation and gamma of the element

brightnessnumber

Adjust the brightness

default:0

minimum value:>=-1

maximum value:<=1

contrastnumber

Adjust the contrast

default:1

minimum value: ≥ -1000

maximum value: ≤ 1000

gammanumber

Adjust the gamma

default:1

minimum value: ≥ 0.1

maximum value: ≤ 10

saturationnumber

Adjust the saturation

default:1

minimum value: ≥ 0

maximum value: ≤ 3

cropobject

Crops the element

heightinteger*required*

Sets the height of the cropping

widthinteger*required*

Sets the width of the cropping

xinteger

Sets the left point of cropping

default:0

yinteger

Sets the top point of cropping

default:0

durationnumberfloat

Element's duration in seconds. A value of -1 auto calculates the duration based on the asset/file intrinsic length. A value of -2 sets the element duration to the parent scene or element duration

default:-1

example value:7.3

extra-timenumberfloat

Element's time span added after the playback.

default:0

example value:0.5

fade-innumberfloat

Adds a fade in effect to the element. Value in seconds.

minimum value:>=0

fade-outnumberfloat

Adds a fade out effect to the element. Value in seconds.

minimum value:>=0

flip-horizontalboolean

Flips the element horizontally

default:false

flip-verticalboolean

Flips the element vertically

default:false

heightinteger

Sets the height of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default:-1

minimum value:>=-1

idstring

ID of the element

default:@randomString

loopinteger

Sets the number of loops the video to play. Use -1 for an infinite loop. The default value of 1 plays the video just once.

minimum value: ≥ -1

example value:-1

maskstring

URL to a PNG or video file defining a mask for the element. Black color is transparent, white is solid, and colors in between are partially transparent

mutedboolean

Mutes the audio

default:false

panstring

Pans the element to the specified direction. If zoom property is not specified, the effect is a non-zooming pan

allowed values:

- left
- top
- right
- bottom
- top-left
- top-right
- bottom-left
- bottom-right

pan-cropboolean

Enable or disable the crop effect when panning

default:true

pan-distancenumberfloat

Pans the element to the specified distance

default:0.1

minimum value: ≥ 0.01

maximum value: ≤ 0.5

positionstring

Sets the element position in the scene. A value of 'custom' sets a custom position based on the provided 'x' and 'y' properties

allowed values:

- top-left
- top-right
- bottom-right
- bottom-left
- center-center
- custom

default:custom

rotateobject

angle*numberrequired*

Sets the angle of rotation

default:0

minimum value: ≥ -360

maximum value: ≤ 360

speednumber

Sets the time it takes to rotate the provided angle. A zero value means no movement

default:0

minimum value: ≥ 0

scaleobject

This property is deprecated. Use 'width' and 'height' instead

heightinteger

Sets the height for scaling the element

default:-1

minimum value: ≥ -1

widthinteger

Sets the width for scaling the element

default:-1

minimum value: >=-1

seeknumberfloat

Seek to the specified time in seconds relative to the beginning of the asset. Use negative values to seek backwards

default: 0

srcstringuri

URL to the asset file. Videos can be in MP4, MKV, MOV but MP4 is recommended.

startnumberfloat

Element's starting time in seconds relative to the container scene or the movie if the element is in the Movie's elements array.

default: 0

typestring*required*

allowed values:

- video

variablesobject

Local variables of the element. Variable names can only contain letters, numbers and underscores

default: {}

example value: { "myVariable": "myValue", "myOtherVariable": true, "myThirdVariable": 123 }

volumenumber

Volume gain of the audio. A value of 1 means no gain. Higher values increase the volume. Values lower than 1 decrease the volume

default: 1

minimum value: >=0

maximum value: <=10

widthinteger

Sets the width of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default: -1

minimum value:>=-1

xnumberinteger

Sets the horizontal position of the element in the scene. The value 0 is on the left side

default:0

ynumberinteger

Sets the vertical position of the element in the scene. The value 0 is on the top side

default:0

z-indexnumberinteger

Element's z-index. Use this property to reorganize the layering of the elements like in HTML

default:0

minimum value:>=-99

maximum value:<=99

example value:3

zoominteger

Zooms the element with the specified level percentage. Positive values zoom in, negative values zoom out, zero does not zoom. Zoom can be combined with the pan property to set the focus point of the zooming

minimum value:>=-100

maximum value:<=100

Image schema

cachebooleanboolean

Use the cached version of the element if its available

default:true

example value:false

chroma-keyobject

Allows to define a color (or a range of colors) that will be converted to transparent

colorstring*required*

Set the color for which alpha will be set to 0 (full transparency)

example value:#00b140

toleranceinteger

Makes the selection more or less sensitive to changes in color. A value of 1 will select only the provided color. A value of 100 will select all colors, so the full canvas

default:25

minimum value:>=1

maximum value:<=100

commentstring

Used for adding your comments

conditionstring

OPTIONAL. Condition to be met for the element to be rendered. If the value is false or empty string, the element is removed from the scene

correctionobject

Allows to adjust the contrast, brightness, saturation and gamma of the element

brightnessnumber

Adjust the brightness

default:0

minimum value:>=-1

maximum value:<=1

contrastnumber

Adjust the contrast

default:1

minimum value:>=-1000

maximum value:<=1000

gammanumber

Adjust the gamma

default:1

minimum value:>=0.1

maximum value:<=10

saturationnumber

Adjust the saturation

default:1

minimum value: ≥ 0

maximum value: ≤ 3

cropobject

Crops the element

heightinteger*required*

Sets the height of the cropping

widthinteger*required*

Sets the width of the cropping

xinteger

Sets the left point of cropping

default:0

yinteger

Sets the top point of cropping

default:0

durationnumberfloat

Element's duration in seconds. A value of -1 auto calculates the duration based on the asset/file intrinsic length. A value of -2 sets the element duration to the parent scene or element duration

default:-1

example value:7.3

extra-timenumberfloat

Element's time span added after the playback.

default:0

example value:0.5

fade-innumberfloat

Adds a fade in effect to the element. Value in seconds.

minimum value: ≥ 0

fade-out number float

Adds a fade out effect to the element. Value in seconds.

minimum value: ≥ 0

flip-horizontal boolean

Flips the element horizontally

default: false

flip-vertical boolean

Flips the element vertically

default: false

height integer

Sets the height of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default: -1

minimum value: ≥ -1

id string

ID of the element

default: @randomString

mask string

URL to a PNG or video file defining a mask for the element. Black color is transparent, white is solid, and colors in between are partially transparent

pan string

Pans the element to the specified direction. If zoom property is not specified, the effect is a non-zooming pan

allowed values:

- left
- top
- right
- bottom

- top-left
- top-right
- bottom-left
- bottom-right

pan-cropboolean

Enable or disable the crop effect when panning

default:true

pan-distancenumberfloat

Pans the element to the specified distance

default:0.1

minimum value: ≥ 0.01

maximum value: ≤ 0.5

positionstring

Sets the element position in the scene. A value of 'custom' sets a custom position based on the provided 'x' and 'y' properties

allowed values:

- top-left
- top-right
- bottom-right
- bottom-left
- center-center
- custom

default:custom

rotateobject

anglenumber*required*

Sets the angle of rotation

default:0

minimum value: ≥ -360

maximum value: ≤ 360

speednumber

Sets the time it takes to rotate the provided angle. A zero value means no movement

default:0

minimum value:>=0

scaleobject

This property is deprecated. Use 'width' and 'height' instead

heightinteger

Sets the height for scaling the element

default:-1

minimum value:>=-1

widthinteger

Sets the width for scaling the element

default:-1

minimum value:>=-1

srcstringuri

URL to the asset file. Images can be in JPG, PNG, GIF or any common image format.

startnumberfloat

Element's starting time in seconds relative to the container scene or the movie if the element is in the Movie's elements array.

default:0

typestring

allowed values:

- image

variablesobject

Local variables of the element. Variable names can only contain letters, numbers and underscores

default: {}

example value: { "myVariable": "myValue", "myOtherVariable": true, "myThirdVariable": 123 }

widthinteger

Sets the width of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default:-1

minimum value:>=-1

xnumberinteger

Sets the horizontal position of the element in the scene. The value 0 is on the left side

default:0

ynumberinteger

Sets the vertical position of the element in the scene. The value 0 is on the top side

default:0

z-indexnumberinteger

Element's z-index. Use this property to reorganize the layering of the elements like in HTML

default:0

minimum value:>=-99

maximum value:<=99

example value:3

zoominteger

Zooms the element with the specified level percentage. Positive values zoom in, negative values zoom out, zero does not zoom. Zoom can be combined with the pan property to set the focus point of the zooming

minimum value:>=-100

maximum value:<=100

Text schema

Creates a text element of a given style

cachebooleanboolean

Use the cached version of the element if its available

default:true

example value:false

chroma-keyobject

Allows to define a color (or a range of colors) that will be converted to transparent

colorstring*required*

Set the color for which alpha will be set to 0 (full transparency)

example value:#00b140

toleranceinteger

Makes the selection more or less sensitive to changes in color. A value of 1 will select only the provided color. A value of 100 will select all colors, so the full canvas

default:25

minimum value:>=1

maximum value:<=100

commentstring

Used for adding your comments

conditionstring

OPTIONAL. Condition to be met for the element to be rendered. If the value is false or empty string, the element is removed from the scene

correctionobject

Allows to adjust the contrast, brightness, saturation and gamma of the element

brightnessnumber

Adjust the brightness

default:0

minimum value:>=-1

maximum value:<=1

contrastnumber

Adjust the contrast

default:1

minimum value:>=-1000

maximum value:<=1000

gammanumber

Adjust the gamma

default:1

minimum value: ≥ 0.1

maximum value: ≤ 10

saturationnumber

Adjust the saturation

default:1

minimum value: ≥ 0

maximum value: ≤ 3

cropobject

Crops the element

heightinteger*required*

Sets the height of the cropping

widthinteger*required*

Sets the width of the cropping

xinteger

Sets the left point of cropping

default:0

yinteger

Sets the top point of cropping

default:0

durationnumberfloat

Element's duration in seconds. A value of -1 auto calculates the duration based on the asset/file intrinsic length. A value of -2 sets the element duration to the parent scene or element duration

default:-2

minimum value: ≥ -2

example value:-1

extra-timenumberfloat

Element's time span added after the playback.

default:0

example value:0.5

fade-innumberfloat

Adds a fade in effect to the element. Value in seconds.

minimum value:>=0

fade-outnumberfloat

Adds a fade out effect to the element. Value in seconds.

minimum value:>=0

flip-horizontalboolean

Flips the element horizontally

default:false

flip-verticalboolean

Flips the element vertically

default:false

heightinteger

Sets the height of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default:-1

minimum value:>=-1

idstring

ID of the element

default:@randomString

maskstring

URL to a PNG or video file defining a mask for the element. Black color is transparent, white is solid, and colors in between are partially transparent

panstring

Pans the element to the specified direction. If zoom property is not specified, the effect is a non-zooming pan

allowed values:

- left
- top
- right
- bottom
- top-left
- top-right
- bottom-left
- bottom-right

pan-cropboolean

Enable or disable the crop effect when panning

default:true

pan-distancenumberfloat

Pans the element to the specified distance

default:0.1

minimum value: ≥ 0.01

maximum value: ≤ 0.5

positionstring

Sets the element position in the scene. A value of 'custom' sets a custom position based on the provided 'x' and 'y' properties

allowed values:

- top-left
- top-right
- bottom-right
- bottom-left
- center-center
- custom

default:custom

rotateobject

angle*numberrequired*

Sets the angle of rotation

default:0

minimum value: ≥ -360

maximum value: ≤ 360

speed*number*

Sets the time it takes to rotate the provided angle. A zero value means no movement

default:0

minimum value: ≥ 0

scale*object*

This property is deprecated. Use 'width' and 'height' instead

height*integer*

Sets the height for scaling the element

default:-1

minimum value: ≥ -1

width*integer*

Sets the width for scaling the element

default:-1

minimum value: ≥ -1

settings*object*

Text formatting settings. In general, these are CSS properties such as font-size, colour or font-weight. See the styles to confirm which properties are available.

default:{}

example value:{ "font-size": "60px", "color": "#FF0000" }

start*numberfloat*

Element's starting time in seconds relative to the container scene or the movie if the element is in the Movie's elements array.

default:0

style*string*

Style of the text element. Check all available text style at <https://json2video.com/resources/text/>

default:001

example value:003

text*stringrequired*

Text to be printed. The text string does not accept HTML formatting.

example value:Lorem ipsum dolor sit amet

type*stringrequired*

allowed values:

- text

variablesobject

Local variables of the element. Variable names can only contain letters, numbers and underscores

default: {}

example value: { "myVariable": "myValue", "myOtherVariable": true, "myThirdVariable": 123 }

widthinteger

Sets the width of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default:-1

minimum value:>=-1

xnumberinteger

Sets the horizontal position of the element in the scene. The value 0 is on the left side

default:0

ynumberinteger

Sets the vertical position of the element in the scene. The value 0 is on the top side

default:0

z-indexnumberinteger

Element's z-index. Use this property to reorganize the layering of the elements like in HTML

default:0

minimum value:>=-99

maximum value:<=99

example value:3

zoominteger

Zooms the element with the specified level percentage. Positive values zoom in, negative values zoom out, zero does not zoom. Zoom can be combined with the pan property to set the focus point of the zooming

minimum value:>=-100

maximum value:<=100

Component schema

Creates an element based on the specified feature

cachebooleanboolean

Use the cached version of the element if its available

default:true

example value:false

chroma-keyobject

Allows to define a color (or a range of colors) that will be converted to transparent

colorstring*required*

Set the color for which alpha will be set to 0 (full transparency)

example value:#00b140

toleranceinteger

Makes the selection more or less sensitive to changes in color. A value of 1 will select only the provided color. A value of 100 will select all colors, so the full canvas

default:25

minimum value:>=1

maximum value:<=100

commentstring

Used for adding your comments

componentstring*required*

ID of the Component element. Check all available components in the [library](#)

example value:basic/001

conditionstring

OPTIONAL. Condition to be met for the element to be rendered. If the value is false or empty string, the element is removed from the scene

correctionobject

Allows to adjust the contrast, brightness, saturation and gamma of the element

brightnessnumber

Adjust the brightness

default:0

minimum value: ≥ -1

maximum value: ≤ 1

contrastnumber

Adjust the contrast

default:1

minimum value: ≥ -1000

maximum value: ≤ 1000

gammanumber

Adjust the gamma

default:1

minimum value: ≥ 0.1

maximum value: ≤ 10

saturationnumber

Adjust the saturation

default:1

minimum value: ≥ 0

maximum value: ≤ 3

cropobject

Crops the element

heightinteger*required*

Sets the height of the cropping

widthinteger*required*

Sets the width of the cropping

xinteger

Sets the left point of cropping

default:0

yinteger

Sets the top point of cropping

default:0

durationnumberfloat

Element's duration in seconds. A value of -1 auto calculates the duration based on the asset/file intrinsic length. A value of -2 sets the element duration to the parent scene or element duration

default:-2

minimum value:>=-2

example value:-1

extra-timenumberfloat

Element's time span added after the playback.

default:0

example value:0.5

fade-innumberfloat

Adds a fade in effect to the element. Value in seconds.

minimum value:>=0

fade-outnumberfloat

Adds a fade out effect to the element. Value in seconds.

minimum value:>=0

flip-horizontalboolean

Flips the element horizontally

default:false

flip-verticalboolean

Flips the element vertically

default:false

heightinteger

Sets the height of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default:-1

minimum value:>=-1

idstring

ID of the element

default:@randomString

maskstring

URL to a PNG or video file defining a mask for the element. Black color is transparent, white is solid, and colors in between are partially transparent

panstring

Pans the element to the specified direction. If zoom property is not specified, the effect is a non-zooming pan

allowed values:

- left
- top
- right
- bottom
- top-left
- top-right
- bottom-left
- bottom-right

pan-cropboolean

Enable or disable the crop effect when panning

default:true

pan-distancenumberfloat

Pans the element to the specified distance

default:0.1

minimum value: ≥ 0.01

maximum value: ≤ 0.5

positionstring

Sets the element position in the scene. A value of 'custom' sets a custom position based on the provided 'x' and 'y' properties

allowed values:

- top-left
- top-right
- bottom-right
- bottom-left
- center-center
- custom

default:custom

rotateobject

anglenumber*required*

Sets the angle of rotation

default:0

minimum value: ≥ -360

maximum value: ≤ 360

speednumber

Sets the time it takes to rotate the provided angle. A zero value means no movement

default:0

minimum value: ≥ 0

scaleobject

This property is deprecated. Use 'width' and 'height' instead

heightinteger

Sets the height for scaling the element

default:-1

minimum value:>=-1

widthinteger

Sets the width for scaling the element

default:-1

minimum value:>=-1

settingsobject

Settings to be passed to the component

startnumberfloat

Element's starting time in seconds relative to the container scene or the movie if the element is in the Movie's elements array.

default:0

typestring*required*

allowed values:

- component

variablesobject

Local variables of the element. Variable names can only contain letters, numbers and underscores

default: {}

example value: { "myVariable": "myValue", "myOtherVariable": true, "myThirdVariable": 123 }

widthinteger

Sets the width of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default:-1

minimum value:>=-1

xnumberinteger

Sets the horizontal position of the element in the scene. The value 0 is on the left side

default:0

ynumberinteger

Sets the vertical position of the element in the scene. The value 0 is on the top side

default:0

z-indexnumberinteger

Element's z-index. Use this property to reorganize the layering of the elements like in HTML

default:0

minimum value:>=-99

maximum value:<=99

example value:3

zoominteger

Zooms the element with the specified level percentage. Positive values zoom in, negative values zoom out, zero does not zoom. Zoom can be combined with the pan property to set the focus point of the zooming

minimum value:>=-100

maximum value:<=100

HTML schema

Creates a video recording or a screenshot of the provided HTML snippet

cachebooleanboolean

Use the cached version of the element if its available

default:true

example value:false

chroma-keyobject

Allows to define a color (or a range of colors) that will be converted to transparent

colorstring*required*

Set the color for which alpha will be set to 0 (full transparency)

example value:#00b140

toleranceinteger

Makes the selection more or less sensitive to changes in color. A value of 1 will select only the provided color. A value of 100 will select all colors, so the full canvas

default:25

minimum value: ≥ 1

maximum value: ≤ 100

commentstring

Used for adding your comments

conditionstring

OPTIONAL. Condition to be met for the element to be rendered. If the value is false or empty string, the element is removed from the scene

correctionobject

Allows to adjust the contrast, brightness, saturation and gamma of the element

brightnessnumber

Adjust the brightness

default:0

minimum value: ≥ -1

maximum value: ≤ 1

contrastnumber

Adjust the contrast

default:1

minimum value: ≥ -1000

maximum value: ≤ 1000

gammanumber

Adjust the gamma

default:1

minimum value: ≥ 0.1

maximum value: ≤ 10

saturationnumber

Adjust the saturation

default:1

minimum value: ≥ 0

maximum value: ≤ 3

cropobject

Crops the element

heightinteger*required*

Sets the height of the cropping

widthinteger*required*

Sets the width of the cropping

xinteger

Sets the left point of cropping

default:0

yinteger

Sets the top point of cropping

default:0

durationnumberfloat

Element's duration in seconds. A value of -1 auto calculates the duration based on the asset/file intrinsic length. A value of -2 sets the element duration to the parent scene or element duration

default:-2

minimum value: ≥ -2

example value:-1

extra-timenumberfloat

Element's time span added after the playback.

default:0

example value:0.5

fade-innumberfloat

Adds a fade in effect to the element. Value in seconds.

minimum value: >=0

fade-out number float

Adds a fade out effect to the element. Value in seconds.

minimum value: >=0

flip-horizontal boolean

Flips the element horizontally

default: false

flip-vertical boolean

Flips the element vertically

default: false

height integer

Sets the height of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default: -1

minimum value: >=-1

html string

HTML snippet to render. Compatible with HTML5, CSS3 and Javascript

example value: <h1>Hello world</h1>

id string

ID of the element

default: @randomString

mask string

URL to a PNG or video file defining a mask for the element. Black color is transparent, white is solid, and colors in between are partially transparent

pan string

Pans the element to the specified direction. If zoom property is not specified, the effect is a non-zooming pan

allowed values:

- left

- top
- right
- bottom
- top-left
- top-right
- bottom-left
- bottom-right

pan-cropboolean

Enable or disable the crop effect when panning

default:true

pan-distancenumberfloat

Pans the element to the specified distance

default:0.1

minimum value: ≥ 0.01

maximum value: ≤ 0.5

positionstring

Sets the element position in the scene. A value of 'custom' sets a custom position based on the provided 'x' and 'y' properties

allowed values:

- top-left
- top-right
- bottom-right
- bottom-left
- center-center
- custom

default:custom

rotateobject

anglenumber*required*

Sets the angle of rotation

default:0

minimum value: ≥ -360

maximum value: ≤ 360

speednumber

Sets the time it takes to rotate the provided angle. A zero value means no movement

default:0

minimum value: ≥ 0

scaleobject

This property is deprecated. Use 'width' and 'height' instead

heightinteger

Sets the height for scaling the element

default:-1

minimum value: ≥ -1

widthinteger

Sets the width for scaling the element

default:-1

minimum value: ≥ -1

srcstring

URL to the web page

startnumberfloat

Element's starting time in seconds relative to the container scene or the movie if the element is in the Movie's elements array.

default:0

tailwindcssboolean

Enables usage of TailwindCSS for the HTML snippet

default:false

example value:true

typestring*required*

allowed values:

- `html`

variablesobject

Local variables of the element. Variable names can only contain letters, numbers and underscores

default: {}

example value: { "myVariable": "myValue", "myOtherVariable": true, "myThirdVariable": 123 }

waitnumber

Time in seconds to wait before taking the screenshot

default: 2

minimum value: ≥ 0

maximum value: ≤ 5

widthinteger

Sets the width of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default: -1

minimum value: ≥ -1

xnumberinteger

Sets the horizontal position of the element in the scene. The value 0 is on the left side

default: 0

ynumberinteger

Sets the vertical position of the element in the scene. The value 0 is on the top side

default: 0

z-indexnumberinteger

Element's z-index. Use this property to reorganize the layering of the elements like in HTML

default: 0

minimum value: ≥ -99

maximum value: ≤ 99

example value: 3

zoominteger

Zooms the element with the specified level percentage. Positive values zoom in, negative values zoom out, zero does not zoom. Zoom can be combined with the pan property to set the focus point of the zooming

minimum value: ≥ -100

maximum value: ≤ 100

Audio schema

cachebooleanboolean

Use the cached version of the element if its available

default:true

example value:false

commentstring

Used for adding your comments

conditionstring

OPTIONAL. Condition to be met for the element to be rendered. If the value is false or empty string, the element is removed from the scene

durationnumberfloat

Element's duration in seconds. A value of -1 auto calculates the duration based on the asset/file intrinsic length. A value of -2 sets the element duration to the parent scene or element duration

default:-1

example value:7.3

extra-timenumberfloat

Element's time span added after the playback.

default:0

example value:0.5

fade-innumberfloat

Adds a fade in effect to the element. Value in seconds.

minimum value: ≥ 0

fade-outnumberfloat

Adds a fade out effect to the element. Value in seconds.

minimum value: ≥ 0

idstring

ID of the element

default: @randomString

loopinteger

Sets the number of loops the video to play. Use -1 for an infinite loop. The default value of 1 plays the video just once.

minimum value: ≥ -1

example value: -1

mutedboolean

Mutes the audio

default: false

seeknumberfloat

Seek to the specified time in seconds relative to the beginning of the asset. Use negative values to seek backwards

default: 0

srcstringuri

URL to the asset file. Audios can be in MP3, WAV or any common audio format.

startnumberfloat

Element's starting time in seconds relative to the container scene or the movie if the element is in the Movie's elements array.

default: 0

typestring

allowed values:

- audio

variablesobject

Local variables of the element. Variable names can only contain letters, numbers and underscores

default: {}

example value:{ "myVariable": "myValue", "myOtherVariable": true, "myThirdVariable": 123 }

volumenumber

Volume gain of the audio. A value of 1 means no gain. Higher values increase the volume. Values lower than 1 decrease the volume

default:1

minimum value:>=0

maximum value:<=10

z-indexnumberinteger

Element's z-index. Use this property to reorganize the layering of the elements like in HTML

default:0

minimum value:>=-99

maximum value:<=99

example value:3

Voice schema

Creates a voice audio element from the provided text

cachebooleanboolean

Use the cached version of the element if its available

default:true

example value:false

commentstring

Used for adding your comments

conditionstring

OPTIONAL. Condition to be met for the element to be rendered. If the value is false or empty string, the element is removed from the scene

durationnumberfloat

Element's duration in seconds. A value of -1 auto calculates the duration based on the asset/file intrinsic length. A value of -2 sets the element duration to the parent scene or element duration

default:-1

example value:7.3

extra-timenumberfloat

Element's time span added after the playback.

default:0

example value:0.5

fade-innumberfloat

Adds a fade in effect to the element. Value in seconds.

minimum value:>=0

fade-outnumberfloat

Adds a fade out effect to the element. Value in seconds.

minimum value:>=0

idstring

ID of the element

default:@randomString

mutedboolean

Mutes the audio

default:false

startnumberfloat

Element's starting time in seconds relative to the container scene or the movie if the element is in the Movie's elements array.

default:0

textstring*required*

The sentence or sentences to be converted to voice audio

typestring*required*

allowed values:

- voice

variablesobject

Local variables of the element. Variable names can only contain letters, numbers and underscores

default: {}

example value: { "myVariable": "myValue", "myOtherVariable": true, "myThirdVariable": 123 }

voicestring

The voice name to be used. Check [available voices](#).

default: en-GB-LibbyNeural

volumenumber

Volume gain of the audio. A value of 1 means no gain. Higher values increase the volume. Values lower than 1 decrease the volume

default: 1

minimum value: ≥ 0

maximum value: ≤ 10

z-indexnumberinteger

Element's z-index. Use this property to reorganize the layering of the elements like in HTML

default: 0

minimum value: ≥ -99

maximum value: ≤ 99

example value: 3

Audiogram schema

Visualizes the audio of the scene or movie as an audiogram

amplitudenumberfloat

Relative amplitude of the audiogram

default: 5

minimum value: ≥ 0

maximum value: ≤ 10

cachebooleanboolean

Use the cached version of the element if its available

default:true

example value:false

chroma-keyobject

Allows to define a color (or a range of colors) that will be converted to transparent

colorstring*required*

Set the color for which alpha will be set to 0 (full transparency)

example value:#00b140

toleranceinteger

Makes the selection more or less sensitive to changes in color. A value of 1 will select only the provided color. A value of 100 will select all colors, so the full canvas

default:25

minimum value:>=1

maximum value:<=100

colorstring

Color of the audiogram waves in hexadecimal format

commentstring

Used for adding your comments

conditionstring

OPTIONAL. Condition to be met for the element to be rendered. If the value is false or empty string, the element is removed from the scene

correctionobject

Allows to adjust the contrast, brightness, saturation and gamma of the element

brightnessnumber

Adjust the brightness

default:0

minimum value:>=-1

maximum value:<=1

contrastnumber

Adjust the contrast

default:1

minimum value: ≥ -1000

maximum value: ≤ 1000

gammanumber

Adjust the gamma

default:1

minimum value: ≥ 0.1

maximum value: ≤ 10

saturationnumber

Adjust the saturation

default:1

minimum value: ≥ 0

maximum value: ≤ 3

cropobject

Crops the element

heightinteger*required*

Sets the height of the cropping

widthinteger*required*

Sets the width of the cropping

xinteger

Sets the left point of cropping

default:0

yinteger

Sets the top point of cropping

default:0

duration number float

Element's duration in seconds. A value of -1 auto calculates the duration based on the asset/file intrinsic length. A value of -2 sets the element duration to the parent scene or element duration

default:-2

minimum value: ≥ -2

example value:-1

extra-time number float

Element's time span added after the playback.

default:0

example value:0.5

fade-in number float

Adds a fade in effect to the element. Value in seconds.

minimum value: ≥ 0

fade-out number float

Adds a fade out effect to the element. Value in seconds.

minimum value: ≥ 0

flip-horizontal boolean

Flips the element horizontally

default:false

flip-vertical boolean

Flips the element vertically

default:false

height integer

Sets the height of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default:-1

minimum value: ≥ -1

id string

ID of the element

default:@randomString

mask string

URL to a PNG or video file defining a mask for the element. Black color is transparent, white is solid, and colors in between are partially transparent

Opacity numberfloat

Opacity of the audiogram

default:0.5

minimum value: ≥ 0

maximum value: ≤ 1

pan string

Pans the element to the specified direction. If zoom property is not specified, the effect is a non-zooming pan

allowed values:

- left
- top
- right
- bottom
- top-left
- top-right
- bottom-left
- bottom-right

pan-crop boolean

Enable or disable the crop effect when panning

default:true

pan-distance numberfloat

Pans the element to the specified distance

default:0.1

minimum value: ≥ 0.01

maximum value: ≤ 0.5

position string

Sets the element position in the scene. A value of 'custom' sets a custom position based on the provided 'x' and 'y' properties

allowed values:

- top-left
- top-right
- bottom-right
- bottom-left
- center-center
- custom

default:custom

rotate object

angle *numberrequired*

Sets the angle of rotation

default:0

minimum value: ≥ -360

maximum value: ≤ 360

speed number

Sets the time it takes to rotate the provided angle. A zero value means no movement

default:0

minimum value: ≥ 0

scaleobject

This property is deprecated. Use 'width' and 'height' instead

Height integer

Sets the height for scaling the element

default:-1

minimum value: ≥ -1

width integer

Sets the width for scaling the element

default:-1

minimum value: >=-1

start number float

Element's starting time in seconds relative to the container scene or the movie if the element is in the Movie's elements array.

default: 0

type string *required*

allowed values:

- audiogram

variables object

Local variables of the element. Variable names can only contain letters, numbers and underscores

default: {}

example value: { "myVariable": "myValue", "myOtherVariable": true, "myThirdVariable": 123 }

width integer

Sets the width of the element, scaling up or down if required. A value of '-1' means to keep the aspect ratio

default: -1

minimum value: >=-1

x number integer

Sets the horizontal position of the element in the scene. The value 0 is on the left side

default: 0

y number integer

Sets the vertical position of the element in the scene. The value 0 is on the top side

default: 0

z-index number integer

Element's z-index. Use this property to reorganize the layering of the elements like in HTML

default: 0

minimum value: >=-99

maximum value:<=99

example value:3

zoom integer

Zooms the element with the specified level percentage. Positive values zoom in, negative values zoom out, zero does not zoom. Zoom can be combined with the pan property to set the focus point of the zooming

minimum value:>=-100

maximum value:<=100

Subtitles schema

Adds subtitles to the scene or movie by transcribing the voice audio.

Captions string

Captions to use as subtitles. The string can be a URL to a file with the captions or the actual captions content properly encoded. Supported formats are SRT, VTT or ASS. If this property is omitted, the subtitles will be generated automatically from the audio.

commentstring

Use it for your comments

languagestring

Language of the audio. Use auto to let the API detect the language automatically.

allowed values:

- auto
- en
- bg
- ca
- cs
- da
- nl
- en-AU
- en-GB
- en-NZ
- en-IN

- en-US
- et
- fr
- fi
- nl-BE
- de
- de-CH
- el
- hi
- hi-Latn
- hu
- id
- it
- ja
- ko
- lv
- lt
- ms
- no
- pl
- pt
- pt-BR
- ro
- ru
- sk
- es
- es-419
- sv
- th

- tr
- uk
- vi
- zh
- zh-TW

default:auto

settingsobject

Settings to customize the subtitles.

default: {}

all-capsboolean

Makes the subtitles all caps

default:false

box-colorstring

Color of the box behind the subtitles. Depending on the style, it can be the background color of the spoken word or the full line

default:#000000

font-familystring

Font family of the subtitles

allowed values:

- Arial
- Libre Baskerville
- Lobster
- Luckiest Guy
- Nanum Pen Script
- Nunito
- Pacifico
- Roboto
- Comic Neue
- Orelega One

- Oswald
- Oswald Bold
- Shrikhand
- Fredericka the Great
- Permanent Marker
- Simplified Chinese
- Traditional Chinese
- Japanese
- Korean
- Korean Bold

default:Arial

font-size integer

Font size of the subtitles. Usual sizes are between 90 and 150. Defaults to 5% of the movie width.

Keywords array of this object:

Keywords provides additional vocabulary to the transcription process. Use it to improve the accuracy of the transcription of non-standard words or phrases.

line-color string

Color of the rest of words in the line

default:#FFFFFF

max-words-per-line integer

Maximum number of words per line

default:4

outline-color string

Outline color of the subtitles

default:#000000

outline-width integer

Width of the outline

default:0

position string

Position of the subtitles

allowed values:

- top-left
- top-center
- top-right
- center-left
- center-center
- center-right
- bottom-left
- bottom-center
- bottom-right
- mid-bottom-center
- mid-top-center
- custom

default:bottom-center

replace object

Replaces words with the specified replacement. Useful to correct the transcription of non-standard words or phrases.

shadow-color string

Shadow color of the subtitles

default:#000000

shadow-offset integer

Offset of the shadow

default:0

style string

Style of the subtitles. Check the tutorial for more details.

allowed values:

- classic

- classic-progressive
- classic-one-word
- boxed-line
- boxed-word

default:classic

word-color

string

Color of the spoken word

default:#FFFF00

x

integer

X coordinate of the subtitles

default:0

y

integer

Y coordinate of the subtitles

default:0

type

string *required*

allowed values:

- subtitles