Leopold-Franzens Universität Innsbruck
Faculty of Mathematics, Computer Science and Physics

Department of Computer Science



Bachelor's Thesis

submitted for the degree of

Bachelor of Science

Symbolic Regression for Surrogate Modeling - A Systematic Study

von

Tobias Albrecht
(Matr.-Nr.: 12206456)

Submission Date: TODO: Add Submission Date
Supervisor: Ass.-Prof. Philipp Zech, PhD

Eidesstattliche Erklärung

Ich erkläre hiermit an Eides statt durch meine eigenhändige Unterschrift, dass ich die vorliegende Arbeit selbstständig verfasst und keine anderen als die angegebenen Quellen und Hilfsmittel verwendet habe. Alle Stellen, die wörtlich oder inhaltlich den angegebenen Quellen entnommen wurden, sind als solche kenntlich gemacht.
Ich erkläre mich mit der Archivierung der vorliegenden Bachelorarbeit einverstanden.

Ort und Datum: _____

Unterschrift: _____

Disclaimer on the Use of AI

AI-assisted tools, specifically OpenAI Codex and GitHub Copilot, were used in a supportive capacity during the preparation of this thesis. They were employed for literature and research assistance, linguistic revision, paraphrasing, code refactoring suggestions and the documentation and commenting of code, with the aim of improving readability, comprehensibility and presentation.

The conceptual development, structure and scientific argumentation of the thesis were carried out independently by the author. All AI-assisted suggestions and modifications were critically reviewed and verified to ensure their accuracy and relevance.

Abstract

Surrogate models are often used in scientific and engineering applications to approximate computationally expensive simulations. However, many surrogate methods produce black-box models whose learned relationships are difficult to inspect. Symbolic Regression (SR) addresses this limitation by discovering explicit mathematical expressions directly from data, thereby combining predictive modeling with an inspectable model representation.

This thesis provides a systematic study of Symbolic Regression methods for surrogate modeling. The main goal is to compare open-source SR frameworks that employ different algorithmic approaches, including evolutionary, genetic programming, transformation-based and neural methods. The evaluated frameworks are gplearn, Operon, PySR, GeneticEngine, ITEA and EQL.

To evaluate these frameworks, the benchmark uses fifteen problems from different domains, including structural mechanics, energy systems, electronics, robotics, hydrodynamics, materials and reactor physics. The selected SR models are evaluated using identical training and test data and a common evaluation protocol with documented algorithm-specific search budgets. The evaluation considers predictive accuracy, computational efficiency, model complexity, stability across repeated trials, sensitivity to input scaling and practical usability. The thesis also investigates the trade-offs between accuracy and interpretability, as well as current challenges in Symbolic Regression for surrogate modeling.

Across 1800 planned trials, 1798 completed successfully. Operon achieved the lowest mean range-normalized RMSE in 21 of 30 problem–scaling combinations, the best median value of 0.0455 and the shortest median fitting time of 3.88 seconds. PySR produced the smallest expressions, ITEA offered a strong balance of accuracy, runtime and compactness and EQL benefited most consistently from input normalization. The results show that SR can provide inexpensive and inspectable surrogates, but suitability depends on the problem and objective and predictive success does not guarantee a simple, stable, or scientifically meaningful model.

Contents

Abstract II

List of Figures V

List of Tables VII

1 Introduction 1
- 1.1 The Need for Interpretable Models . . . 1
- 1.2 Symbolic Regression as a Candidate Approach . . . 2
- 1.3 Research Question and Contributions . . . 3

2 Background 5
- 2.1 Surrogate Modeling . . . 5
- 2.2 Symbolic Regression . . . 6
- 2.3 Main Symbolic Regression Method Families . . . 8
- 2.4 The Accuracy Complexity Trade-Off . . . 9
- 2.5 Interpretability in Scientific Modeling . . . 10

3 Related Work 11
- 3.1 Benchmark Studies . . . 11
- 3.2 Selected Frameworks . . . 13

4 Methodology 16
- 4.1 Framework Selection Criteria . . . 16
- 4.2 Dataset Selection Criteria . . . 17
- 4.3 Benchmark Protocol . . . 17
- 4.4 Evaluation Metrics . . . 19
  - 4.4.1 Predictive Performance . . . 19
  - 4.4.2 Computational Efficiency . . . 20
  - 4.4.3 Expression Complexity . . . 20
  - 4.4.4 Practical Usability . . . 20
- 4.5 Reproducibility Setup . . . 21
- 4.6 Interpretability Evaluation . . . 22
  - 4.6.1 Structural Measures . . . 22
  - 4.6.2 Parsing and Simplification Policy . . . 22
  - 4.6.3 Interpretive Scope . . . 23

5 Experiments **24**
5.1 Experimental Matrix and Task Roles . . . 24
5.2 Dataset Construction . . . 26
5.2.1 Common Construction Procedure . . . 26
5.2.2 Analytical Datasets . . . 26
5.2.3 External Datasets . . . 27
5.2.4 Input Normalization . . . 28
5.3 Framework Configurations . . . 28
5.4 Execution Procedure and Environments . . . 29
5.5 Repetitions and Trial Coverage . . . 30
5.5.1 Compatible Result Resolution . . . 30
5.5.2 Completed Trial Matrix . . . 31
5.6 Symbolic Post-Processing . . . 31

6 Results **33**
6.1 Trial and Analysis Coverage . . . 33
6.1.1 Trial Completion and Failures . . . 33
6.1.2 Symbolic-Analysis Coverage . . . 34
6.2 Predictive Performance . . . 35
6.2.1 Overall Framework Performance . . . 35
6.2.2 Performance by Problem . . . 40
6.2.3 Analytical and Empirical Problems . . . 41
6.3 Effects of Input Scaling and Repetition Variability . . . 42
6.3.1 Effect of Domain Normalization . . . 42
6.3.2 Stability Across Repetitions . . . 44
6.4 Symbolic Model Properties . . . 47
6.4.1 Expression Complexity . . . 47
6.4.2 Symbolic Simplification and Fallbacks . . . 50
6.5 Computational Efficiency . . . 51
6.5.1 Model-Fitting Time . . . 51
6.5.2 Prediction and Expression-Extraction Time . . . 53
6.6 Consolidated Framework Comparison . . . 54

7 Discussion **56**
7.1 Interpretation of Framework Trade-Offs . . . 56
7.2 Suitability for Interpretable Surrogate Modeling . . . 57
7.3 Research Gaps and Future Benchmarking Needs . . . 58

8 Conclusion **60**

Bibliography **61**

List of Figures

2.1 Syntax-tree representation of the expression $\phi(x_1, x_2) = 3x_1 + \sin(x_2/5)$. Internal nodes represent mathematical operators, while leaf nodes represent variables or constants. 7

6.1 Mean range-normalized RMSE by framework and problem using raw inputs. Cell colors represent the base-10 logarithm of NRMSE, while annotations show the untransformed values. 36
6.2 Mean range-normalized RMSE by framework and problem using domain-normalized inputs. Cell colors represent the base-10 logarithm of NRMSE, while annotations show the untransformed values. 37
6.3 Mean coefficient of determination by framework and problem using raw inputs. The color scale is clipped to $[-1, 1]$, while annotations report the untruncated values. 38
6.4 Mean coefficient of determination by framework and problem using domain-normalized inputs. The color scale is clipped to $[-1, 1]$, while annotations report the untruncated values. 39
6.5 Effect of domain normalization on mean range-normalized RMSE. The diagonal represents equal error under both input-scaling conditions. 44
6.6 Distribution of repetition-level range-normalized RMSE by framework using raw inputs. Points represent successful trials across all problems and boxes summarize their distributions. 46
6.7 Distribution of repetition-level range-normalized RMSE by framework using domain-normalized inputs. Points represent successful trials across all problems, boxes summarize their distributions and red annotations report failed trials. 47
6.8 Mean simplified expression-tree node count by framework and problem using raw inputs. An asterisk indicates that at least one expression in the cell required the unsimplified complexity fallback and was excluded from the displayed simplified mean. 49
6.9 Mean simplified expression-tree node count by framework and problem using domain-normalized inputs. An asterisk indicates that at least one expression in the cell required the unsimplified complexity fallback and was excluded from the displayed simplified mean. 50
6.10 Mean model-fitting time by framework and problem using raw inputs. Cell colors represent the base-10 logarithm of time, while annotations report seconds. 52

6.11 Mean model-fitting time by framework and problem using domain-normalized inputs. Cell colors represent the base-10 logarithm of time, while annotations report seconds and are based on successful trials only. 53

List of Tables

5.1 Problems and their roles in the experimental matrix. 24
5.2 Principal framework configurations used in the experiments. 29
5.3 Coverage of the completed experimental matrix. 31

6.1 Trial coverage by problem. 34
6.2 Symbolic-analysis coverage by framework. "Simplified" denotes completion of symbolic simplification, while "Fallback" denotes use of the parsed unsimplified expression. 35
6.3 Overall predictive summary across the 30 problem–scaling combinations. Medians are calculated from problem-level means and wins count the lowest mean NRMSE in each combination. 40
6.4 Lowest mean NRMSE for each problem and input-scaling condition. . 40
6.5 Median of the framework-level mean NRMSE values by problem type and scaling condition. 42
6.6 Effect of domain normalization. The ratio is calculated per problem from the normalized and raw mean NRMSE and then summarized by its median. Values below one favor normalization. 43
6.7 Median problem-level sample standard deviation of NRMSE across repetitions. 45
6.8 Median of the problem-level mean simplified expression-tree node counts across both scaling conditions. Only trials for which simplification completed are included. 48
6.9 Symbolic simplification outcomes for parsed expressions. 51
6.10 Median of problem-level mean model-fitting times across both scaling conditions. 52
6.11 Median problem-level mean prediction and expression-extraction times. Prediction time is the median full-test prediction duration divided by the number of reference-test observations. 54
6.12 Consolidated framework comparison. Predictive, timing and complexity values are medians of problem-level means across both scaling conditions. Simplified node counts exclude fallback expressions. . . . 55

1 Introduction

Scientific and engineering research mostly relies on numerical simulations and physical experiments to investigate complex systems, optimize technical designs and evaluate control strategies. High-fidelity simulations may require expensive numerical solvers, while physical experiments may be time consuming and costly. These costs become a practical bottleneck when a system must be evaluated repeatedly, for example during optimization, uncertainty quantification, sensitivity analysis, or parameter exploration [2].

A surrogate model is trained on observations obtained from simulations, physical measurements, or both and is then used to provide inexpensive predictions for new inputs. This approach is widely used to manage computational complexity in engineering design and simulation-based analysis, where the cost of generating training data must be balanced against predictive accuracy and the computational savings achieved during repeated evaluation [2]. Surrogate models are particularly useful in domains such as physics, mechanical engineering, materials science and energy systems, where obtaining direct simulation results or experimental measurements can be expensive.

Modern machine learning methods are common choices for surrogate modeling because they can approximate complex nonlinear relationships. Neural networks, ensemble models, Gaussian processes and other flexible approaches achieve strong predictive performance [2]. However, this flexibility can make the resulting surrogate difficult to inspect, explain, or compare with known scientific relationships. This lack of transparency may be acceptable when a surrogate is used only for prediction. However, when the model is intended to support scientific understanding, engineering decisions, or safety-relevant applications, predictive accuracy alone may be insufficient and the structure and behavior of the learned model must also be considered.

1.1 The Need for Interpretable Models

Interpretability becomes important when a model is intended to support scientific understanding rather than prediction alone. In scientific and engineering applications, an interpretable surrogate can help researchers inspect which variables appear in the learned relationship, examine their nonlinear interactions and compare the

model structure with established domain knowledge. These forms of inspection are difficult when the surrogate is a black box since a low prediction error on testing data does not by itself demonstrate that a model has learned a scientifically meaningful or domain-consistent relationship.

The distinction between interpretable models and post-hoc explanations is important. Rudin argues that in high-stakes settings, one should prefer models that are interpretable by design instead of first training a black-box model and then trying to explain it afterward [17]. This argument is also relevant for scientific surrogate modeling. If the learned model is meant to support reasoning about a physical or engineering system, the transparency of the model itself is important.

Interpretability is not a single property. A model may be considered interpretable because it is simple, because it uses familiar mathematical operations or because its variables have clear roles. In surrogate modeling, interpretability also must be balanced against accuracy. A very simple model may be easy to understand but too inaccurate to be useful, while a highly accurate model may be too complex to provide valuable insight. This trade-off motivates benchmarking the different frameworks according to both predictive accuracy and model complexity [13, 9].

1.2 Symbolic Regression as a Candidate Approach

Symbolic Regression (SR) is a machine learning approach that searches for explicit mathematical expressions fitting a given dataset. Instead of assuming a fixed model form, such as a linear model or a predefined polynomial basis, SR explores combinations of variables, constants and mathematical operators. The result is not only a predictor but also an equation that can be read, evaluated, simplified and compared with domain knowledge [14, 10].

This makes SR a promising candidate for interpretable surrogate modeling. A symbolic expression can often be much cheaper to evaluate than the original simulation and more transparent than the black-box models. SR has therefore received considerable attention in scientific discovery, including physics, materials science and dynamical systems [3, 12, 22, 4].

Several well-known examples illustrate the scientific motivation for SR. AI Feynman uses physics-inspired strategies to recover equations from the Feynman Lectures on Physics, showing how prior structural ideas such as symmetry and separability can support symbolic equation discovery [21]. Sparse Identification of Nonlinear Dynamics (SINDy) similarly pursues interpretable governing equations from data, although it uses sparse regression over a predefined library of candidate terms rather than general symbolic search [5]. These works show the broader appeal of data-driven equation discovery for scientific modeling.

At the same time, SR is not automatically superior to other surrogate modeling ap-

proaches. The search space of possible expressions is large and different frameworks use different strategies to explore it. Evolutionary algorithms, genetic programming variants and neural or reinforcement-learning-based approaches differ in their assumptions, computational cost, ease of use and ability to discover compact expressions [10, 16]. The quality of the final model also depends on operator choices, complexity penalties, training budgets and implementation details.

1.3 Research Question and Contributions

The central research question of this thesis is:

> *How suitable are Symbolic Regression frameworks for interpretable surrogate modeling, and how do they compare with respect to predictive performance, computational cost, equation complexity and practical usability?*

To answer this question, this thesis conducts a systematic study of six open-source SR frameworks: gplearn [20], Operon [6], PySR [7], GeneticEngine [11], ITEA [8] and EQL [18]. The selected frameworks represent different approaches to symbolic model discovery, including tree-based genetic programming, efficient evolutionary search, grammar-guided genetic programming, interaction transformation based evolutionary search and neural equation learning. The frameworks are evaluated on fifteen analytical, simulator-generated, experimental and measured surrogate-modeling problems using fixed training and test datasets and documented algorithm-specific search budgets. The comparison considers predictive accuracy, computational efficiency, expression complexity, stability across repeated trials, sensitivity to input scaling, practical usability and reproducibility.

The main contributions of this thesis are:

- a structured overview of Symbolic Regression as an approach for interpretable surrogate modeling;
- a benchmark setup for comparing the selected SR frameworks on datasets from different application domains;
- an evaluation protocol covering predictive accuracy, runtime, equation complexity, stability across repeated fitting trials and qualitative practical usability;
- an interpretability-oriented comparison of the discovered symbolic expressions;
- displaying strengths, limitations and challenges of the current SR frameworks for surrogate modeling.

The remainder of this thesis is organized as follows. Chapter 2 introduces the background on surrogate modeling, Symbolic Regression, method families and interpretability. Chapter 3 discusses related work, including existing reviews, benchmark

studies and applications. Chapter 4 describes the methodology, including framework and dataset selection, evaluation metrics, reproducibility setup and interpretability. Chapter 5 presents the experimental setup. Chapter 6 reports the results. Chapter 7 discusses the findings and their limitations. Chapter 8 concludes the thesis and outlines directions for future work.

2 Background

This chapter introduces the theoretical background of the thesis. It discusses surrogate modeling, the role of interpretable models, the foundations and challenges of Symbolic Regression and the frameworks selected for the benchmark.

2.1 Surrogate Modeling

Many scientific and engineering workflows rely on simulation models that provide detailed representations of physical systems but are computationally expensive to evaluate. Finite element analysis and computational fluid dynamics are prominent examples. Their computational cost becomes a practical limitation when numerous evaluations are required for tasks such as design optimization, uncertainty quantification, sensitivity analysis, or exploration of a parameter space [2].

A surrogate model approximates the input output relationship of the computationally expensive simulation or physical process. It is constructed from a finite set of observations and is intended to provide predictions at a substantially lower evaluation cost than the original process [2]. If the original model is denoted by

$$y = f(\mathbf{x}), \tag{2.1}$$

where $\mathbf{x} \in \mathbb{R}^d$ is an input vector and $y \in \mathbb{R}$ is the corresponding output, a surrogate model approximates this relationship with a function $\hat{f}$ such that

$$\hat{y} = \hat{f}(\mathbf{x}) \approx f(\mathbf{x}). \tag{2.2}$$

The main practical advantage of a surrogate is that evaluating $\hat{f}$ is generally less computationally expensive than evaluating the original model f. This makes repeated model evaluations feasible, but computational efficiency alone does not determine whether a surrogate is useful. Its predictive accuracy on relevant unseen data, the amount of data required for its construction and the computational cost of fitting and evaluating it must also be considered [2].

A wide range of statistical and machine-learning methods can be employed as surrogate models, including polynomial response surfaces, Gaussian processes, artificial

neural networks, support vector regression, boosted trees and random forests [2]. These methods can approximate complex nonlinear relationships without requiring a complete analytical description of the underlying process. However, flexible predictive models may provide limited insight into the learned input output relationship [14].

2.2 Symbolic Regression

Symbolic Regression (SR) is a supervised learning approach that searches for mathematical expressions fitting a given dataset. In contrast to ordinary regression methods, SR does not assume a fixed functional form in advance. For example, a linear regression model assumes that the target can be represented as a weighted sum of input variables. A polynomial regression model assumes a predefined set of polynomial terms. SR instead searches over both the structure of the expression and its numerical parameters [3, 13].

Symbolic regression (SR) searches for a mathematical expression that describes the relationship between input variables and a target variable directly from data [14]. Consider a supervised dataset

$$D = \{(\mathbf{x}_i, y_i)\}_{i=1}^{N}, \tag{2.3}$$

where D denotes the complete dataset, N is the number of observations and $i \in \{1, \ldots, N\}$ indexes an individual observation. The vector $\mathbf{x}_i \in \mathbb{R}^d$ contains the values of the d input variables for the i-th observation, while $y_i \in \mathbb{R}$ is its corresponding target value.

Symbolic Regression can be divided into Explicit Symbolic Regression (ESR) and Implicit Symbolic Regression (ISR). ESR searches for a function that expresses a designated target directly in terms of the input variables, such as $y = \phi(\mathbf{x}; \boldsymbol{\theta})$. ISR instead searches for a relation of the form $F(\mathbf{x}, y; \boldsymbol{\theta}) = 0$, without requiring one variable to be isolated as the target. This thesis considers ESR because all benchmark problems define a continuous target that must be predicted from a given set of input variables [10].

The objective of ESR in this thesis is to find both a symbolic expression structure ϕ and numerical constants $\boldsymbol{\theta}$ such that the prediction $\phi(\mathbf{x}_i; \boldsymbol{\theta})$ approximates y_i. For example, one possible measure of prediction error is the mean squared error (MSE),

$$\mathcal{L}_{\text{MSE}}(\phi, \boldsymbol{\theta}) = \frac{1}{N} \sum_{i=1}^{N} \left(y_i - \phi(\mathbf{x}_i; \boldsymbol{\theta})\right)^2 . \tag{2.4}$$

where $y_i - \phi(\mathbf{x}_i; \boldsymbol{\theta})$ denotes the prediction error for the i-th observation.

However, minimizing prediction error alone can produce unnecessarily large expressions. Because the result of SR is intended to remain interpretable, expression complexity must also be considered. Complexity may, for example, be measured by the number of nodes or operators in the expression tree. SR is therefore commonly treated as a multi objective problem involving a trade-off between predictive accuracy and expression complexity [7, 13].

Candidate expressions are commonly represented as syntax trees. In such a tree, internal nodes are mathematical operators such as $+$, $-$, $\times$, division, sin, cos, log, or exp, while leaf nodes are variables or constants. For example, the expression

$$\phi(x_1, x_2) = 3x_1 + \sin(x_2/5) \tag{2.5}$$

can be represented as a tree combining multiplication, division, addition, two constants, two variables and a sine operator.




Figure 2.1: Syntax-tree representation of the expression $\phi(x_1, x_2) = 3x_1 + \sin(x_2/5)$. Internal nodes represent mathematical operators, while leaf nodes represent variables or constants.

This representation makes it possible to modify expressions by changing subtrees, replacing operators, or adjusting constants.

The search space of SR is very large. Even a small set of variables and operators can generate many possible expressions and the number of possible expressions grows quickly with expression size. This is one reason why SR is computationally difficult and why many frameworks use different search strategies [10]. Another challenge is the treatment of constants. In scientific equations, real-valued constants are often essential, but searching simultaneously over expression structure and continuous constants is much harder than fitting coefficients in a fixed model form [7].

Despite these challenges, SR is useful for scientific modeling because its outputs can be interpreted directly. A discovered equation can be evaluated cheaply, simplified symbolically, compared with existing theory, inspected for asymptotic behavior and checked for physically implausible terms. This distinguishes SR from many

black-box methods, where interpretability is usually added after training through explanation methods rather than being part of the model itself [14].

2.3 Main Symbolic Regression Method Families

Recent surveys group SR methods into several broad families. The most relevant distinction for this thesis is between deterministic methods, genetic programming methods and neural methods [10]. These families differ in how they explore the expression space and handle constants.

The distinction between Explicit and Implicit Symbolic Regression is separate from the classification by method family. ESR and ISR describe the form of the relationship being sought, whereas deterministic, genetic-programming-based and neural methods describe how the expression space is searched. These two classifications are therefore conceptually independent, a search strategy can in principle be designed for either an explicit or an implicit formulation, although individual implementations generally specialize in one. All frameworks evaluated in this thesis perform ESR because they construct an explicit prediction of a designated target variable from the given inputs.

Deterministic methods use systematic search, enumeration, sparse regression, mixed-integer optimization, or related strategies to explore candidate expressions. Their main advantage is that they can be more stable and reproducible than purely stochastic methods, because the search process is less dependent on random initialization. Some deterministic approaches can also provide stronger guarantees within a restricted search space. The limitation is that the number of possible expressions grows rapidly with the number of variables, operators and expression depth. As a result, deterministic methods may become computationally expensive for high-dimensional or complex problems [10].

Genetic Programming (GP) methods are historically the most established family of SR algorithms. GP treats expressions as individuals in a population and evolves them over many generations. Candidate expressions are evaluated according to a fitness function, selected, recombined, mutated and simplified. This family is flexible because it can search over many different expression structures without requiring a fixed basis. It also naturally supports multi-objective optimization, where accuracy and complexity are optimized together [3, 13].

Neural-network-based SR methods use differentiable architectures or learned search strategies to construct mathematical expressions. The Equation Learner (EQL) evaluated in this thesis represents expressions using a shallow neural network whose units implement mathematical operations such as identity, multiplication and trigonometric functions [18]. Its numerical parameters are optimized through gradient-based training, while sparsity regularization encourages the removal of unnecessary con-

nections and allows the trained network to be converted into an explicit equation. EQL therefore performs ESR through a neural and differentiable model structure rather than through population-based evolution. Limitations of this approach include sensitivity to input scaling, optimization settings and the set of mathematical operations built into the architecture.

The variety of method families is important for this thesis because there is no single best SR approach. A framework that performs well on one type of problem may behave differently on datasets with noise, high-dimensional inputs, or differently scaled variables. The comparison therefore treats the selected frameworks as explicit symbolic regression tools that share the same prediction objective but rely on different representations and search strategies.

2.4 The Accuracy Complexity Trade-Off

The central evaluation problem in SR is the trade-off between predictive accuracy and expression complexity. If only accuracy is optimized, SR can produce long expressions that fit the training data well but are difficult to interpret and prone to overfitting. If only simplicity is optimized, the resulting expression may be readable but too inaccurate to serve as a useful surrogate. A meaningful SR model should therefore achieve an appropriate balance between these objectives.

Complexity can be measured in different ways. A common syntactic measure is the number of nodes, operators, variables and constants in an expression. Other measures consider expression depth, operator types, semantic behavior, nonlinearity, or the effective difficulty of understanding the formula [13, 10]. There is no perfect complexity metric. A short equation can still be difficult to interpret if it contains unfamiliar or unstable operations, while a slightly longer equation may be more meaningful if it matches known domain structure.

Many SR frameworks return not only one expression but a set of candidate expressions along a Pareto front. A Pareto front contains models for which no other model is both more accurate and less complex. This is useful because the final choice of model depends on the application. For a deployment-focused surrogate, a slightly more complex expression may be acceptable if it improves predictions significantly. For scientific insight, a simpler expression may be preferable if it captures the dominant relation and remains physically plausible.

In this thesis, the accuracy complexity trade-off is treated as a core evaluation dimension. Predictive metrics such as mean squared error or coefficient of determination describe how well a model fits the data, while complexity metrics describe how complex the resulting expression is. Considering both dimensions is essential because a symbolic surrogate is only useful if it is accurate enough to approximate the underlying process and simple enough to support interpretation.

2.5 Interpretability in Scientific Modeling

Interpretability is a major motivation for applying SR to surrogate modeling. In scientific contexts, models are often expected to do more than predict. They should help explain a underlying system, reveal relationships between variables and support reasoning about behavior in new conditions. A symbolic expression is attractive because the full mapping from inputs to outputs is visible in mathematical form.

The distinction between interpretability and post-hoc explainability is important. A black-box model may be explained after training using feature importance scores, saliency methods, local approximations, or other explanation techniques. These methods can be useful, but they do not make the original model transparent. An interpretable model, by contrast, exposes its structure directly. SR belongs to this second category, as it can produce sufficiently compact and meaningful expressions [14].

SR can support scientific discovery when the resulting expression reveals a relation that was not explicitly provided to the model. Reviews of SR in physical sciences emphasize this potential. SR can generate analytical equations from data and thereby connect data-driven modeling with the traditional scientific practice of formulating laws and empirical relations [3, 14]. At the same time, interpretability should not be assumed automatically. A symbolic expression may be mathematically explicit but still too complex, unstable, or domain-inconsistent to be useful.

This thesis treats interpretability as an evaluation criterion rather than as a guaranteed outcome. The discovered expressions will be compared in terms of their size, structure, operator usage and practical readability. This allows SR frameworks to be evaluated not only by whether they predict accurately, but also by whether they produce surrogate models that can plausibly support scientific understanding.

3 Related Work

The recent growth of Symbolic Regression (SR) has led to several survey papers that organize the field and summarize its main technical directions. Makke and Chawla provide a broad review of SR as a method for interpretable scientific discovery, emphasizing the ability of SR to infer compact mathematical expressions directly from data [14]. Their review discusses the historical development of SR, its relation to genetic programming, the emergence of deep-learning-based approaches and applications in scientific domains. This perspective is closely aligned with the motivation of this thesis, because surrogate modeling in science and engineering often requires models that are not only accurate but also interpretable.

Angelis et al. focuses specifically on SR in the physical sciences [3]. Their review positions SR as a response to the limitations of black-box machine learning models in physics-based computation. They discuss SR as a data-driven method that can generate analytical equations and thereby support interpretation, generalization and the discovery or verification of physical relations.

Dong and Zhong provide a more recent and comprehensive survey of advances in SR [10]. They organize SR methods into deterministic, genetic-programming-based and neural-network-based families and they also summarize benchmark datasets, evaluation metrics, software tools and open research challenges. Their survey is useful for understanding the current methodological landscape and for motivating the framework selection in this thesis. In particular, the distinction between GP-based and neural SR approaches is relevant because the evaluated frameworks represent different search and implementation strategies.

These reviews show that SR is no longer limited to genetic programming. Current SR research includes evolutionary algorithms, deterministic search, sparse regression, reinforcement learning, transformer-based approaches and hybrid methods. At the same time, the reviews also point to persistent challenges. For example, high computational cost, sensitivity to benchmark design, difficulty in evaluating interpretability and inconsistent behavior across datasets.

3.1 Benchmark Studies

Benchmarking is a central issue in SR research because methods are often evaluated on different datasets, with different computational budgets and with different def-

initions of success. Early SR papers frequently used small synthetic benchmarks, which made results difficult to compare across studies. Orzechowski, La Cava and Moore addressed this issue by evaluating recent SR methods against standard machine learning regressors on a large set of regression problems [15]. Their study compared four GP-based SR methods with several scikit-learn regression methods on 94 real-world datasets. The results showed that SR methods can be competitive with strong machine learning baselines, but also that runtime remains as a limitation.

La Cava et al. extended this line of work with SRBench, a larger and more systematic benchmark for symbolic regression [13]. SRBench compares 14 SR methods and 7 machine learning methods across 252 regression problems, including real-world datasets, ground-truth symbolic equations, physics equations and systems of ordinary differential equations. Importantly, SRBench evaluates not only predictive accuracy but also expression complexity and symbolic solution recovery. The benchmark therefore provides a basis for comparing SR methods in terms of both predictive performance and expression complexity.

The SRBench results also highlight that no single method is universally optimal. Some frameworks perform strongly on black-box regression tasks, while others are better at recovering exact equations under controlled conditions. Operon, for example, is reported as one of the strongest methods on real-world black-box regression problems and as part of the best accuracy-simplicity trade-offs [13]. These findings motivate a more focused comparison of selected frameworks in the surrogate modeling context, where practical usability and interpretability are important.

More recent work has extended and criticized existing benchmark practices. SRBench++ argues that expression size alone is an insufficient proxy for interpretability and introduces domain-expert interpretation into the benchmarking process [9]. It also evaluates SR algorithms on more specific task properties, such as feature selection, robustness, extrapolation and local minima. This is important because a symbolic expression can be short but still scientifically unhelpful, or slightly longer but more meaningful to a domain expert.

Aldeia et al. present a call for the next generation of SR benchmarks, arguing that SRBench should evolve as a living benchmark [1]. Their work expands the set of evaluated methods, refines evaluation metrics and considers trade-offs between accuracy, complexity and energy consumption. The study emphasizes standardization of hyperparameter tuning, execution constraints, computational resources and benchmark maintenance. These issues are directly relevant for this thesis because a fair comparison of SR frameworks requires a reproducible protocol.

Overall, benchmark studies show that SR evaluation is more complex than ordinary regression benchmarking. Accuracy, model complexity, solution recovery, runtime, robustness and interpretability all matter. The present thesis builds on these insights but uses a narrower experimental scope. Instead of ranking many SR methods across

hundreds of datasets, it compares a selected set of open-source frameworks under a reproducible surrogate modeling protocol.

3.2 Selected Frameworks

This thesis evaluates six open-source Symbolic Regression frameworks: gplearn, Operon, PySR, GeneticEngine, ITEA and EQL. They were selected to represent different approaches to symbolic model construction, including conventional tree-based genetic programming, performance-oriented evolutionary search, grammar-guided genetic programming, interaction transformation expressions and neural equation learning. The associated publications describe the algorithms and software architectures, while the exact versions and configurations used in this thesis are specified separately in the experimental methodology.

gplearn

Gplearn is a Python implementation of conventional tree-based genetic programming with an interface modeled after scikit-learn [20]. Candidate expressions are represented as programs and evolved using tournament selection, crossover and several forms of mutation, while a parsimony coefficient can be used to discourage unnecessarily large expressions. Unlike the other selected frameworks, gplearn does not have a dedicated peer-reviewed framework publication. However, it is included and characterized as a Koza-style symbolic-regression implementation in the SRBench comparison [13]. Its comparatively direct implementation and familiar estimator interface make it a useful reference point for evaluating more specialized SR approaches.

Operon

Operon is an efficient C++ genetic programming framework designed specifically for Symbolic Regression [6]. It represents expression trees as contiguous linear sequences, which improves memory locality and enables efficient evaluation and manipulation of candidate models. Its modular evolutionary design is organized around offspring generators and supports automatic differentiation and gradient-based optimization of numerical constants. Operon emphasizes runtime performance, memory efficiency and extensibility, making it relevant for examining how an optimized genetic programming implementation performs within the benchmark.

PySR

PySR is an open-source library for scientific Symbolic Regression that provides a Python interface to the Julia backend SymbolicRegression.jl [7]. Its search procedure uses multiple evolving populations and an evolve simplify optimize loop in which candidate expressions are evolved, simplified and refined through numerical constant optimization. PySR also supports user defined operators, losses, complexity measures and expression export to several scientific-computing formats. These capabilities make it a flexible framework to search for symbolic models under application specific mathematical constraints.

GeneticEngine

GeneticEngine is a Python framework for grammar-guided genetic programming in which the search space can be defined using Python data types rather than a separate textual grammar [11]. The framework combines ideas from grammar-guided and strongly typed genetic programming, allowing the structures and constraints of valid candidate programs to be expressed through the host language's type system. The publication emphasizes the ergonomics and expressive power of this representation and demonstrates this through an open source Python implementation.

ITEA

The Interaction Transformation Evolutionary Algorithm (ITEA) searches within a restricted representation in which models are formed as linear combinations of transformed interactions between input variables [8]. Each interaction is defined through powers of the input variables and a selected transformation function, while the corresponding linear coefficients are fitted numerically. Rather than using conventional subtree crossover, ITEA evolves a population through mutation operations that add, remove, or modify terms, interactions and transformations. This structured representation distinguishes ITEA from general expression-tree methods and provides direct control over the maximum number of terms in a model.

EQL

Equation Learning (EQL) represents mathematical expressions through a differentiable neural network whose units implement elementary operations such as identity, trigonometric functions and multiplication [18]. Alternating linear transformations and operation-specific units allow the network to construct nonlinear analytical relationships, while sparsity regularization encourages a small number of active connections and therefore more concise expressions. The architecture is optimized using gradient-based methods rather than an evolutionary population, making EQL

methodologically distinct from the other frameworks in the benchmark. The evaluated adapter implements the Equation Learner approach described in the associated literature.

The selected frameworks cover several parts of the contemporary SR landscape. gplearn, Operon, PySR and GeneticEngine use different forms of genetic or evolutionary search, ITEA evolves expressions within the more restricted interaction transformation representation and EQL constructs equations through a differentiable neural architecture.

4 Methodology

This chapter describes the methodology used to design and conduct the benchmark. It presents the framework and dataset selection criteria, the common experimental protocol, the evaluation metrics and the measures taken to ensure reproducibility.

4.1 Framework Selection Criteria

The purpose of this benchmark is not to identify a universally best Symbolic Regression algorithm, but to compare representative frameworks under conditions relevant to surrogate modeling. Framework selection was guided by five criteria:

- the method is described in a scientific publication or has detailed software documentation;
- an open-source implementation is publicly available;
- the implementation returns an explicit mathematical expression rather than predictions alone;
- the framework can be integrated into the common SRBench-derived evaluation pipeline;
- the framework contributes a relevant algorithmic or representational approach to the comparison.

Practical installability, compatibility with the evaluation interface and reproducible execution were also considered because technical failures and unavailable model expressions affect the usefulness of a framework in practice. This reflects recommendations that SR benchmarks should consider reproducibility, complexity and practical execution in addition to predictive accuracy [9, 1].

Based on these criteria, six frameworks were included: gplearn, Operon, PySR, GeneticEngine, ITEA and EQL. Together, they provide a range of evolutionary, representation-based and gradient-based approaches to Symbolic Regression. Their exact configurations and execution environments are described in Chapter 5.

4.2 Dataset Selection Criteria

The benchmark problems were selected to represent scientific and engineering surrogate modeling tasks while remaining feasible for repeated Symbolic Regression searches. Each problem is required to have numerical input variables, a continuous target, clearly documented feature meanings and domains and a reproducible data source or generating function. The available data also had to support disjoint training and test sets without categorical encoding, missing-value imputation, or extensive feature engineering.

The selection combines six analytical problems with nine external datasets. Cantilever, Borehole, Piston, Wing Weight, OTL Circuit and Robot Arm provide controlled relationships of different structural forms. Combined Cycle Power Plant, Naval Propulsion, Gas Turbine NOx Emissions, Concrete Compressive Strength, Energy Efficiency, Airfoil Self-Noise, Yacht Hydrodynamics, Electrical Grid Stability and Lattice Physics add simulator-generated, measured, or experimental relationships from several scientific and engineering domains. All fifteen problems are evaluated using the same predictive, computational, stability and expression-structure criteria.

The final set of fifteen problems covers several scientific and engineering domains, between three and 39 input variables, different physical scales and relationships of varying structural difficulty. The analytical problems include multiplication, division, integer and fractional powers, logarithms, square roots and trigonometric terms, while the external datasets introduce measurement variation, simulator responses, higher-dimensional inputs and relationships for which the benchmark does not assume a privileged symbolic form. This combination allows the frameworks to be assessed across controlled and application-oriented surrogate-modeling tasks. The exact problem definitions, sample sizes, data sources and train–test construction procedures are presented in Chapter 5.

4.3 Benchmark Protocol

All experiments use a common evaluation pipeline derived from SRBench [13, 19]. Each problem has a fixed training table and a separate test table that are generated or selected before the algorithm repetitions are executed. Dataset construction uses documented problem specific seeds, whereas the repetition seed controls the symbolic regression algorithm where supported. Consequently, every framework and repetition receives identical observations, preventing variation in dataset sampling from being confused with variation in algorithm behavior. SHA-256 hashes of the uncompressed training and test tables are stored in each result to make this invariant auditable.

Every algorithm problem combination is evaluated under two input-scaling conditions. In the `raw` condition, the stored inputs are supplied to the estimator in their original physical units. In the `domain_minmax` condition, each input x_j with documented lower and upper bounds l_j and u_j is mapped to $[-1, 1]$ according to

$$z_j = 2\frac{x_j - l_j}{u_j - l_j} - 1. \tag{4.1}$$

The transformation uses fixed problem-domain bounds rather than statistics estimated from the training data, ensuring that it is identical across frameworks and repetitions and does not introduce test-data leakage. Target values are not scaled and remain in their original units under both conditions. Expressions learned from normalized inputs are transformed back to the original physical variables during symbolic post processing.

The final repetition protocol uses the predefined labels 2, 3, 5, 7, 11, 13, 17, 19, 23 and 29. These labels are passed to each estimator that exposes a supported random-seed parameter. The ITEA implementation does not expose such a parameter, so its ten executions are reported as uncontrolled repetitions rather than seed-controlled trials. With six algorithms, fifteen problems, two input-scaling conditions and ten repetitions, the complete benchmark contains 1800 expected trials.

Each trial fits one model using the fixed training target and evaluates it exclusively on the corresponding held-out reference-test set. A successful result, an explicit execution failure and an absent trial are treated as three separate states. Failure records retain the algorithm, problem, scaling condition, repetition label and process exit status, while the summary tables report successful, failed and missing trials separately. Failed or missing runs are therefore not silently excluded from the reported experiment coverage.

Each framework uses one explicitly documented configuration across the benchmark, no hyperparameter optimization is performed using the final test results. The configured search effort is expressed through algorithm-specific controls, such as population sizes, generations, evaluation limits, iterations, or time limits. These settings were selected to make repeated execution feasible and do not impose equal computational budgets across frameworks. Runtime comparisons therefore describe the evaluated configurations and must not be interpreted as equal compute comparisons or estimates of the frameworks best attainable performance.

Shared execution controls restrict benchmark containers to one thread. After fitting each model predicts the complete test set five times to obtain a more reliable estimate of prediction time. Model fitting, prediction and expression extraction are timed within the running algorithm environment. Container startup, image retrieval, dataset generation, result serialization and symbolic post-processing are excluded from the reported algorithm runtime.

Symbolic parsing, transformation to physical coordinates, simplification and structural measurement are performed as separate post-processing steps. Each stage has an independent timeout and writes a versioned analysis record without modifying the original trial result. Separating expression analysis from model execution ensures that a parsing or simplification failure does not invalidate an otherwise successful training and prediction trial.

4.4 Evaluation Metrics

This section defines the metrics used to compare the benchmarked frameworks. The evaluation considers predictive performance, computational efficiency and expression complexity to capture both the quality and practical characteristics of the resulting symbolic models.

4.4.1 Predictive Performance

Predictive performance is evaluated exclusively on the held-out reference-test set. For target values y_i, predictions $\hat{y}_i$, the test-set mean $\bar{y}$ and n test observations, the benchmark reports mean absolute error (MAE), root mean squared error (RMSE) and the coefficient of determination (R^2):

$$\mathrm{MAE} = \frac{1}{n}\sum_{i=1}^{n}\left|y_i - \hat{y}_i\right|, \tag{4.2}$$

$$\mathrm{RMSE} = \sqrt{\frac{1}{n}\sum_{i=1}^{n}\left(y_i - \hat{y}_i\right)^2}, \tag{4.3}$$

$$R^2 = 1 - \frac{\sum_{i=1}^{n}\left(y_i - \hat{y}_i\right)^2}{\sum_{i=1}^{n}\left(y_i - \bar{y}\right)^2}. \tag{4.4}$$

MAE measures the average absolute prediction error, whereas RMSE assigns greater weight to large errors. Both remain in the target's original unit because target values are not scaled. The coefficient of determination measures performance relative to prediction by the test-set mean and may be negative when a model performs worse than that reference. Because the target ranges differ substantially between problems, raw MAE and RMSE values are interpreted within each problem rather than ranked directly across the complete dataset collection.

To provide a dimensionless error measure, the benchmark additionally reports range-normalized RMSE:

$$\mathrm{NRMSE}_{\mathrm{range}} = \frac{\mathrm{RMSE}}{\max_i(y_i) - \min_i(y_i)}. \tag{4.5}$$

The normalization uses the range of the reference-test target and allows prediction errors to be interpreted relative to the observed target variation. It does not modify the target values supplied during model fitting or prediction. The maximum absolute prediction error is also retained in each individual trial record as an additional indicator of the largest observed test-set deviation.

4.4.2 Computational Efficiency

Computational efficiency is evaluated using wall-clock measurements. The benchmark records the duration of the complete estimator fitting call and the first prediction over the reference-test set. Prediction of the full test set is repeated five times, from which the mean, median and sample standard deviation are calculated. The median duration is also divided by the number of test observations and reported in microseconds per sample. Expression extraction is timed separately, while symbolic post-processing, container startup, image retrieval, dataset generation and result serialization are excluded from the algorithm runtime.

4.4.3 Expression Complexity

Every returned expression is parsed with SymPy to obtain framework-independent structural measures. These include expression-tree node count, tree depth, operator count and operator set, constant count and the number and identity of variables used. The same measures are calculated after symbolic simplification where possible. The adapter-specific model-size value is retained for reference but is not used as the primary cross-framework complexity measure because its definition differs between adapters.

4.4.4 Practical Usability

Practical usability is evaluated qualitatively rather than reduced to a single numerical score. The assessment considers whether a framework can be executed in a documented environment, integrated through the common estimator interface, supplied with a controllable repetition seed, used to return both predictions and an explicit expression and processed by the shared symbolic-analysis pipeline. Trial completion, expression availability, parsing coverage, dependency or API incompatibilities and the need for adapter-specific compatibility handling provide observable evidence for this assessment.

This definition concerns the use of each framework within the benchmark workflow and does not attempt to measure general software quality or the effort required for every possible installation environment. Setup observations, pinned container requirements, unsupported seed controls, execution failures and compatibility workarounds are therefore reported descriptively alongside the quantitative predictive, timing, stability and complexity results. No framework is assigned a composite usability rank because the importance of these factors depends on the intended application and reproducibility requirements.

4.5 Reproducibility Setup

The benchmark is organized around separate components for dataset preparation, framework adapters, trial evaluation, symbolic analysis and result aggregation. Versioned JSON files under `configs/` define the problem set, repetition labels, input-scaling conditions, shared execution controls and algorithm-specific parameters. Runner scripts under `scripts/` execute individual trials or the complete experiment matrix. The resolved configuration, its cryptographic hash and the parameters accepted by the estimator are recorded with each trial result.

Algorithm environments are isolated using the published SRBench container images. The image references are pinned by immutable SHA-256 digests in `containers/images.lock`, preventing a later image update from silently changing the execution environment. The host virtual environment is used for dataset preparation, experiment coordination, symbolic post-processing, aggregation and automated tests. Shared execution controls restrict the algorithm containers to one thread, while supported estimators receive the configured repetition seed.

Dataset origin is recorded independently of the algorithm runs. Analytical datasets are generated from documented equations, domains and fixed generation seeds. External datasets retain their source URLs, identifiers, selection procedures and source-file hashes. Every trial additionally records hashes of the exact training and test tables it received, making it possible to verify that all frameworks were evaluated on identical observations.

Trial results are stored under `results/<problem>/<benchmark>/<input-scaling>/<algorithm>/` as JSON files indexed by repetition label. Symbolic parsing, coordinate transformation, simplification and structural measurement write separate analysis sidecars so that post-processing does not modify the original trial record. Aggregate CSV files are generated from these stored artefacts and report successful, failed and missing trials explicitly.

4.6 Interpretability Evaluation

The interpretability evaluation is restricted to properties of the returned symbolic representation that can be measured consistently across all frameworks. It therefore treats expression availability, parseability, structural complexity and simplification behavior as observable indicators of inspectability. These indicators complement predictive performance but do not establish by themselves that an expression is understandable to a particular reader or scientifically meaningful.

4.6.1 Structural Measures

After conversion to a SymPy expression tree, the benchmark records the total node count, tree depth, operator count and operator set, constant count and the number and identity of variables used. Node count includes operator, variable and numerical-constant nodes. Tree depth is the longest number of edges from the expression root to a leaf, with an isolated variable or constant having depth zero. Operator count records the number of non-leaf nodes, while the operator set identifies the distinct operation types present in the tree. Constants are numerical atomic nodes and variables are the free symbols occurring in the expression.

These measures are calculated both for the parsed expression and, when simplification succeeds, for its simplified form. The framework-specific model-size value is retained in the trial record for reference but is not used for the primary comparison because the adapters define model size differently. The cross-framework analysis instead uses the common SymPy-based measures, with simplified node count serving as the principal summary of syntactic expression size.

4.6.2 Parsing and Simplification Policy

The original expression string returned by each adapter remains unchanged in the trial result. A separate post-processing stage translates the prefix notation used by gplearn and the infix notation used by the other frameworks into SymPy. Expressions learned with domain-normalized inputs are then transformed into the original physical input variables before their primary structural measures are calculated. Parsing success and any parsing error are recorded explicitly and a parsing failure leaves the predictive result valid but prevents framework-independent structural measurement.

For each parsed expression, the post-processing procedure attempts cancellation, factorization, factorization after cancellation and general SymPy simplification within a shared bounded simplification stage. If all candidate operations complete, the candidate with the smallest node count is selected, with textual length used to break ties. If any operation exceeds the configured time or memory limit, the complete

simplification stage is treated as unsuccessful and the parsed unsimplified expression and its structural measures are retained as a documented fallback. Simplified and fallback expressions are counted separately and are not combined in the primary simplified-complexity averages.

4.6.3 Interpretive Scope

Smaller and shallower expressions with fewer operations may be easier to inspect, but syntactic complexity is only a proxy for interpretability. The recorded statistics do not measure whether an equation is physically plausible, dimensionally consistent, familiar to a domain expert, or useful for scientific reasoning. The evaluation reported in this thesis does not compare learned expressions with the analytical equations used to generate the controlled datasets. Interpretability is therefore discussed through the observed representation and its structural statistics, together with predictive accuracy, rather than through a claim that the underlying relationship was rediscovered.

5 Experiments

This chapter describes the realization of the benchmark protocol introduced in the methodology chapter. It defines the experimental matrix, documents how the individual datasets were constructed, records the configurations used for the six symbolic regression frameworks and explains the execution and symbolic post-processing procedures.

5.1 Experimental Matrix and Task Roles

The experimental matrix combines fifteen regression problems, six symbolic regression frameworks, two input-scaling conditions and ten repetitions. This produces

$$15 \times 6 \times 2 \times 10 = 1800 \tag{5.1}$$

distinct trial coordinates.

The benchmark problems were selected to fulfill complementary experimental roles rather than to form a homogeneous dataset collection. Six analytical problems permit controlled sampling from relationships with different mathematical structures. The remaining nine problems are based on measured, experimental, or simulator-generated data and represent applied surrogate-modeling tasks from energy, propulsion, materials, building simulation, aeroacoustics, hydrodynamics, electrical-grid control and reactor physics.

Table 5.1: Problems and their roles in the experimental matrix.

Problem	Data type	Inputs	Train/test	Experimental role
Cantilever	Analytical	5	400/4000	Rational power-law relationship
Borehole	Analytical	8	400/4000	Higher-dimensional rational relationship
Piston	Analytical	7	400/4000	Nonlinear relationship containing a nested square root
Combined Cycle Power Plant	Measured	4	400/4000	Low-dimensional industrial energy dataset

Problem	Data type	Inputs	Train/test	Experimental role
Naval Propulsion	Simulator-generated	3	400/4000	Propulsion-system surrogate with correlated operating variables
Wing Weight	Analytical	10	400/4000	Higher-dimensional expression with fractional powers and a trigonometric term
Gas Turbine NOx	Measured	9	400/4000	Industrial-emissions prediction with a chronological train–test separation
Concrete Strength	Experimental	8	400/592	Material-property prediction with replicated experimental observations
Energy Efficiency	Simulator-generated	8	400/368	Building heating-load prediction over simulated designs
Airfoil Self-Noise	Experimental	5	400/1103	Aeroacoustic prediction from wind-tunnel measurements
OTL Circuit	Analytical	6	400/4000	Nonlinear electronic-circuit response with rational interactions
Robot Arm	Analytical	8	400/4000	Trigonometric kinematic relationship with cumulative joint angles
Yacht Hydrodynamics	Experimental	6	210/98	Resistance prediction for hull forms excluded from training
Electrical Grid Stability	Simulator-generated	11	400/4000	Stability prediction for a decentralized electrical grid
Lattice Physics	Simulator-generated	39	400/4000	Higher-dimensional reactor-physics surrogate for k_{inf}

The analytical tasks emphasize controlled approximation of relationships with known structural characteristics, whereas the external datasets emphasize predictive performance on simulator-generated, experimental and measured surrogate-modeling problems. All problems are evaluated using the same predictive, computational, stability and expression-structure measures.

5.2 Dataset Construction

This section describes how the fixed training and reference-test datasets were constructed for the fifteen benchmark problems. It first presents the procedure shared across all datasets, followed by the problem-specific generation, sampling and preprocessing decisions for the analytical and external datasets.

5.2.1 Common Construction Procedure

All training and reference-test tables are constructed before the symbolic regression repetitions are executed. Dataset construction uses fixed problem-specific seeds that are independent of the framework repetition labels. The resulting tables are therefore identical for all frameworks and repetitions within a problem and input-scaling condition. SHA-256 hashes of the uncompressed tables are recorded in each trial result so that this property can be verified.

5.2.2 Analytical Datasets

The Cantilever problem is generated from its analytical rational power-law equation using five input variables. A single random generator is used to draw the 400 training observations followed by the 4000 reference-test observations.

The Borehole problem contains eight input variables and is generated from the standard analytical borehole-flow equation. The training and reference-test designs are independently generated using scrambled Latin hypercube sampling. The equation contains several nonlinear interactions, including logarithmic and rational terms, making it a more structurally demanding approximation task than the Cantilever problem.

The Piston problem contains seven inputs and represents the cycle time of a simulated piston system. Scrambled Latin hypercube designs are used for the training and reference-test tables. The generating expression contains multiple intermediate interactions and a nested square root, allowing the benchmark to examine whether the frameworks can approximate a comparatively deep analytical structure.

The Wing Weight problem contains ten inputs and is generated from an analytical aircraft-wing weight equation. Independent scrambled Latin hypercube samples produce the training and reference-test tables. The equation combines products, fractional powers and a cosine term, thereby extending the analytical task collection beyond rational and square-root expressions.

The OTL Circuit problem contains six inputs and predicts the midpoint voltage of an output-transformerless circuit. Independently seeded scrambled Latin hypercube designs provide 400 training and 4000 reference-test observations over the

documented component ranges. Its analytical expression combines rational terms and interactions between resistances and current gain.

The Robot Arm problem contains four joint angles and four segment lengths and predicts the planar distance between the arm endpoint and the origin. Independently seeded scrambled Latin hypercube designs provide 400 training and 4000 reference-test observations. The analytical relationship combines cumulative joint angles, trigonometric functions, sums, products and a square root.

5.2.3 External Datasets

The Combined Cycle Power Plant dataset is obtained from the UCI Machine Learning Repository and contains 9568 observations with four input variables. A fixed permutation is applied to the complete dataset. The first 400 permuted observations form the training set and the following 4000 observations form the reference-test set.

The Naval Propulsion problem is based on the UCI Condition Based Maintenance of Naval Propulsion Plants dataset. The source data contains a full factorial simulator design with 11934 observations. Three operating variables are used to predict the selected propulsion-system target.

The Gas Turbine NOx problem is constructed from five annual UCI gas-turbine emissions files containing 36733 observations in total. Nine ambient and process variables are used to predict nitrogen-oxide emissions, while the year indicator and carbon-monoxide target are excluded.

The Concrete Strength problem is obtained from the UCI Concrete Compressive Strength dataset. Observations with identical values for all eight input variables are aggregated into distinct experimental designs and their target values are combined, producing 992 unique designs.

The Energy Efficiency problem is obtained from the UCI Energy Efficiency dataset and contains 768 simulated building designs with eight input variables. Heating load is used as the target, while cooling load is excluded. A fixed permutation assigns the first 400 designs to the training set and the remaining 368 designs to the reference-test set.

The Airfoil Self-Noise problem is obtained from the UCI Airfoil Self-Noise dataset and contains 1503 wind-tunnel observations with five input variables. Scaled sound-pressure level is used as the target. A fixed permutation assigns 400 observations to the training set and the remaining 1103 observations to the reference-test set.

The Yacht Hydrodynamics problem is obtained from the UCI Yacht Hydrodynamics dataset and contains 308 observations for 22 hull forms evaluated at 14 Froude numbers. Six inputs are used to predict residuary resistance per unit displacement weight. To prevent operating points from the same hull from appearing in both

subsets, a fixed permutation assigns 15 complete hull forms, corresponding to 210 observations, to training and the remaining seven hull forms, corresponding to 98 observations, to the reference-test set.

The Electrical Grid Stability problem is obtained from the UCI Electrical Grid Stability Simulated Data dataset. Eleven reaction-time, power and price-elasticity variables are used to predict the maximum real part of the characteristic-equation root. The deterministically dependent producer-power variable and the categorical stability label are excluded. A fixed permutation assigns 400 of the 10000 simulated observations to training and the following 4000 observations to the reference-test set.

The Lattice Physics problem is obtained from the UCI Lattice-physics PWR Fuel Assembly Neutronics Simulation Results dataset. The 39 fuel-pin enrichment variables are used to predict the infinite multiplication factor k_{inf}, while the pin-power peaking-factor target is excluded. A fixed permutation assigns 400 of the 24000 MCNP6 simulation records to training and the following 4000 records to the reference-test set.

5.2.4 Input Normalization

For the domain-normalized condition, each raw input x_j is transformed using the documented lower and upper bounds l_j and u_j of its problem domain:

$$z_j = 2\frac{x_j - l_j}{u_j - l_j} - 1. \tag{5.2}$$

These bounds are fixed by the dataset specification and are not estimated from either the training or reference-test observations. The transformation is therefore identical across frameworks and repetitions and does not introduce test-data leakage. Target values are not scaled.

5.3 Framework Configurations

All frameworks are executed with fixed configurations that are shared across problems, scaling conditions and repetition labels. The configurations were selected before the final experiment matrix was executed and no problem-specific hyperparameter optimization was performed. Table 5.2 summarizes the principal search controls.

Table 5.2: Principal framework configurations used in the experiments.

Framework	Search approach	Principal configuration
gplearn	Tree-based genetic programming	Population size 500 and 100 generations
Operon	Efficient tree-based genetic programming	Population size 1000, 1000 generations and a maximum of 1,000,000 evaluations
PySR	Multi-population evolutionary search	20 iterations, 500 cycles per iteration, population size 100, three populations and a 60-second timeout
GeneticEngine	Grammar-guided genetic programming	Population size 200, 100 generations and a 60-second timer
ITEA	Interaction–transformation evolutionary search	Population size 1000 and 500 generations
EQL	Differentiable equation-learning network	10,000 training iterations

The gplearn, PySR and GeneticEngine settings include project-level budget overrides introduced to keep the complete matrix computationally feasible. The Operon, ITEA and EQL settings follow the parameter values exposed by their SRBench adapters. PySR is configured for deterministic serial execution, while the shared execution controls restrict all algorithm containers to one processing thread where supported.

The configurations do not represent equal wall-clock or equal-function-evaluation budgets because the frameworks expose different search controls and perform different internal operations. Runtime comparisons therefore describe the cost of the evaluated configurations rather than a hardware-normalized competition under exactly equivalent search effort.

5.4 Execution Procedure and Environments

The experiment matrix is executed using the benchmark runner scripts, which select one problem, framework, input-scaling condition and repetition label for each trial. The runner loads the fixed training and reference-test tables, applies the selected input representation, invokes the framework adapter, evaluates the returned estimator, extracts its symbolic expression and writes the complete trial record as JSON. Failed fitting, prediction, or expression-extraction operations are recorded explicitly.

Each algorithm is executed in its published SRBench container environment. Dataset preparation, experiment coordination, result validation, symbolic post-processing and aggregation are performed in the project's host virtual environment.

Shared execution controls restrict algorithm containers to one thread to reduce uncontrolled parallelism between frameworks. The configured repetition label is passed to every estimator that exposes a compatible seed parameter. ITEA does not provide a controllable estimator seed through the employed adapter and its repetitions are consequently marked as uncontrolled rather than being presented as deterministically reproducible seed runs.

5.5 Repetitions and Trial Coverage

Each framework problem scaling combination is assigned the ten repetition labels

$$\{2, 3, 5, 7, 11, 13, 17, 19, 23, 29\}. \tag{5.3}$$

These labels control the framework seed where supported, they do not alter the already constructed training and reference-test tables. Repetitions therefore measure variation in the symbolic regression procedure rather than variation caused by resampling the datasets.

5.5.1 Compatible Result Resolution

The benchmark suites were extended incrementally, version 7 introduced Gas Turbine NOx, version 8 added Concrete Strength, version 9 added Energy Efficiency, version 10 added Airfoil Self-Noise and version 11 added OTL Circuit, Robot Arm, Yacht Hydrodynamics, Electrical Grid Stability and Lattice Physics. Later suites also contain selected reruns of earlier coordinates, but repeating every previously completed trial after each dataset addition would duplicate substantial computation without changing the protocol. The final reporting process therefore resolves each problem–scaling–framework–repetition coordinate independently instead of treating one suite directory as an indivisible result set. The resolved matrix consequently combines selected records from compatible versions 7 through 11.

A candidate result is eligible only when its configuration has the same schema version, repetition protocol, execution controls, repetition labels, input-scaling conditions and effective algorithm parameters as the final version-11 configuration. The candidate must also contain the relevant problem and use exactly the same problem-specific dataset-construction specification. Among eligible candidates, the record from the highest suite version is selected, if both a success and a failure record exist for the same coordinate within that suite, the most recently written result is used.

The resolver writes the selected status, suite and source path to an auditable manifest. A successful result's symbolic-analysis sidecar is accepted only when its stored SHA-256 source hash matches the selected trial file, preventing stale post-processing data from being combined with a newer trial.

5.5.2 Completed Trial Matrix

All 1800 coordinates of the planned matrix are represented by either a successful trial record or an explicit failure record. Table 5.3 reports the resulting coverage by problem. No planned coordinate is missing.

Table 5.3: Coverage of the completed experimental matrix.

Problem	Resolved suite(s)	Planned	Successful	Failed
Cantilever	`v8`	120	120	0
Borehole	`v8`	120	120	0
Piston	`v8`	120	120	0
Combined Cycle Power Plant	`v8`	120	119	1
Naval Propulsion	`v8`	120	120	0
Wing Weight	`v8`	120	120	0
Gas Turbine NOx	`v7`, `v8`, `v10`	120	120	0
Concrete Strength	`v8`	120	120	0
Energy Efficiency	`v9`	120	120	0
Airfoil Self-Noise	`v10`	120	120	0
OTL Circuit	`v11`	120	119	1
Robot Arm	`v11`	120	120	0
Yacht Hydrodynamics	`v11`	120	120	0
Electrical Grid Stability	`v11`	120	120	0
Lattice Physics	`v11`	120	120	0
Total	–	1800	1798	2

5.6 Symbolic Post-Processing

Symbolic post-processing is performed after framework execution and writes a separate analysis sidecar. This separation preserves the original expression and metrics returned by the framework while allowing the symbolic analysis procedure to be

repeated or improved without fitting the model again. Each sidecar records a hash of its source trial.

Expressions are translated into SymPy using parsers adapted to the expression formats returned by the frameworks. This includes conversion of the prefix-style function notation used by gplearn and the infix expressions returned by the other adapters. Parsing, coordinate transformation and simplification are treated as separate stages. A failure or timeout in one symbolic stage is recorded explicitly and does not invalidate the predictive results of the corresponding trial.

For trials trained on normalized inputs, the symbolic variables z_j are replaced by the inverse of Equation 5.2,

$$z_j = \frac{2x_j - (u_j + l_j)}{u_j - l_j}, \tag{5.4}$$

to express the learned model in terms of the original physical variables. Candidate expressions are then processed within a bounded simplification stage using operations such as cancellation, factorization and general SymPy simplification. If the complete candidate-generation sequence succeeds, the smallest produced candidate is retained as the principal simplified expression. If any candidate operation exceeds the time or memory limit, the parsed unsimplified expression is retained as a fallback. The original parsed expression remains available in the sidecar in either case.

Framework-independent structural measures are computed before and after simplification. These measures include expression-tree node count, tree depth, operator count and operator set, constant count and the number and identity of variables used. Complexity values associated with transformed expressions describe the equation in the original input coordinates, whereas the untransformed values document the structure directly returned by the estimator.

6 Results

This chapter presents the results of the completed benchmark. It first reports trial and symbolic-analysis coverage before comparing the frameworks in terms of predictive performance, sensitivity to input scaling, stability across repetitions, expression complexity and computational efficiency.

6.1 Trial and Analysis Coverage

Before comparing the frameworks, it is necessary to establish which trials completed successfully and which fitted expressions could be processed by the symbolic-analysis pipeline. This section reports both forms of coverage so that all subsequent summaries can be interpreted in relation to the available results.

6.1.1 Trial Completion and Failures

The complete experimental matrix comprised fifteen problems, six symbolic regression frameworks, two input-scaling conditions and ten repetition labels, resulting in 1800 planned trials. Because the problem collection was expanded incrementally, the reported matrix resolves each problem–scaling–framework–repetition coordinate to its newest result from a suite compatible with the final protocol. This procedure incorporates later reruns without replacing coordinates that were not rerun in the newer suite. Of the resolved trials, 1798 completed successfully and two failed, corresponding to an overall completion rate of 99.9%. Table 6.1 shows that 13 problems completed all 120 trials, while one failure occurred for Combined Cycle Power Plant (CCPP) and one for OTL Circuit.

Table 6.1: Trial coverage by problem.

Problem	Planned	Successful	Failed
Cantilever	120	120	0
Borehole	120	120	0
Piston	120	120	0
CCPP	120	119	1
Naval Propulsion	120	120	0
Wing Weight	120	120	0
Gas Turbine NOx	120	120	0
Concrete Strength	120	120	0
Energy Efficiency	120	120	0
Airfoil Self-Noise	120	120	0
OTL Circuit	120	119	1
Robot Arm	120	120	0
Yacht Hydrodynamics	120	120	0
Electrical Grid Stability	120	120	0
Lattice Physics	120	120	0
Total	1800	1798	2

The two unresolved failures were Operon on domain-normalized CCPP at repetition 7 and PySR on domain-normalized OTL Circuit at repetition 11. Inspection of the saved PySR candidate showed that a square-root argument became negative for three reference-test observations, producing non-finite predictions that were correctly rejected by metric calculation. All six frameworks completed their remaining assigned trials, including all 300 GeneticEngine trials after later compatible reruns replaced earlier output-shape failures. Both failed trials were retained as failures and excluded from numerical means rather than replaced or imputed.

6.1.2 Symbolic-Analysis Coverage

Symbolic post-processing was attempted for every successful trial. As shown in Table 6.2, analysis sidecars were produced for all 1798 successful runs and 1797 expressions could be parsed and assigned framework-independent complexity measures. The single parsing failure occurred for a deeply nested gplearn expression on the raw-input Wing Weight problem, which exceeded the nesting limit of the underlying parser. The bounded simplification procedure completed for 1591 expressions. Of the remaining 206 parsed expressions, 195 exceeded the 60-second simplification

limit and 11 encountered the configured 2 GB memory limit. In these cases, the analysis retained the unsimplified expression and its structural measures as an explicit fallback. Of the 206 fallbacks, 145 occurred with domain-normalized inputs and 61 with raw inputs.

Table 6.2: Symbolic-analysis coverage by framework. "Simplified" denotes completion of symbolic simplification, while "Fallback" denotes use of the parsed unsimplified expression.

Framework	Successful	Analysed	Parsed	Simplified	Fallback
gplearn	300	300	299	214	85
Operon	299	299	299	255	44
PySR	299	299	299	291	8
GeneticEngine	300	300	300	300	0
ITEA	300	300	300	274	26
EQL	300	300	300	257	43
Total	1798	1798	1797	1591	206

6.2 Predictive Performance

Predictive performance is examined at three levels. The framework-wide comparison provides an overall summary, the problem-level results show where individual methods performed best, and the final comparison distinguishes between analytical problems with known equations and empirical problems without a known ground-truth expression.

6.2.1 Overall Framework Performance

Figures 6.1 and 6.2 compare the mean range-normalized RMSE (NRMSE) of every framework–problem combination under raw and domain-normalized inputs. Lower values indicate better predictive performance. The corresponding R^2 values are shown in Figures 6.3 and 6.4, where values closer to one indicate a better fit and negative values indicate performance below prediction by the reference-test mean. Each cell is calculated from the successful repetitions available for that configuration.



Figure 6.1: Mean range-normalized RMSE by framework and problem using raw inputs. Cell colors represent the base-10 logarithm of NRMSE, while annotations show the untransformed values.




Figure 6.2: Mean range-normalized RMSE by framework and problem using domain-normalized inputs. Cell colors represent the base-10 logarithm of NRMSE, while annotations show the untransformed values.




Figure 6.3: Mean coefficient of determination by framework and problem using raw inputs. The color scale is clipped to $[-1, 1]$, while annotations report the untruncated values.




Figure 6.4: Mean coefficient of determination by framework and problem using domain-normalized inputs. The color scale is clipped to $[-1, 1]$, while annotations report the untruncated values.

Across the 30 problem–scaling combinations, Operon achieved the lowest mean NRMSE in 21 cases. ITEA was best in five cases, while PySR and EQL were each best in two. gplearn and GeneticEngine did not obtain the lowest mean NRMSE in any combination. When the 30 problem-level means are summarized by their median, Operon obtained the lowest NRMSE at 0.0455 and the highest median R^2 at 0.9660. ITEA and PySR formed the next group, with median NRMSE values of 0.0722 and 0.0804, respectively.

Table 6.3: Overall predictive summary across the 30 problem–scaling combinations. Medians are calculated from problem-level means and wins count the lowest mean NRMSE in each combination.

Framework	Median NRMSE	Median R^2	NRMSE wins
gplearn	0.1296	0.4231	0
Operon	0.0455	0.9660	21
PySR	0.0804	0.7979	2
GeneticEngine	0.1313	0.3896	0
ITEA	0.0722	0.8564	5
EQL	0.1622	-0.0058	2

6.2.2 Performance by Problem

Table 6.4 reports the strongest framework for each problem and scaling condition. Operon led 21 configurations, including both conditions on OTL Circuit, Yacht Hydrodynamics and Electrical Grid Stability and the normalized Robot Arm and Lattice Physics conditions. ITEA led raw Robot Arm, raw Lattice Physics, CCPP and Airfoil Self-Noise. EQL remained strongest on normalized Borehole and Wing Weight, while PySR obtained the best result on Gas Turbine NOx under both scaling conditions.

Table 6.4: Lowest mean NRMSE for each problem and input-scaling condition.

Problem	Scaling	Framework	Mean NRMSE
Cantilever	Raw	Operon	3.70×10^{-8}
Cantilever	Domain-normalized	Operon	0.0101
Borehole	Raw	Operon	0.0009
Borehole	Domain-normalized	EQL	0.0072
Piston	Raw	Operon	0.0198
Piston	Domain-normalized	Operon	0.0199
CCPP	Raw	ITEA	0.0604
CCPP	Domain-normalized	ITEA	0.0648
Naval Propulsion	Raw	Operon	0.0172
Naval Propulsion	Domain-normalized	Operon	0.0170
Wing Weight	Raw	Operon	0.0120
Wing Weight	Domain-normalized	EQL	0.0099
Gas Turbine NOx	Raw	PySR	0.1536

Problem	Scaling	Framework	Mean NRMSE
Gas Turbine NOx	Domain-normalized	PySR	0.1563
Concrete Strength	Raw	Operon	0.0936
Concrete Strength	Domain-normalized	Operon	0.0900
Energy Efficiency	Raw	Operon	0.0591
Energy Efficiency	Domain-normalized	Operon	0.0319
Airfoil Self-Noise	Raw	ITEA	0.1142
Airfoil Self-Noise	Domain-normalized	Operon	0.1120
OTL Circuit	Raw	Operon	0.0054
OTL Circuit	Domain-normalized	Operon	0.0077
Robot Arm	Raw	ITEA	0.1450
Robot Arm	Domain-normalized	Operon	0.1185
Yacht Hydrodynamics	Raw	Operon	0.0193
Yacht Hydrodynamics	Domain-normalized	Operon	0.0253
Electrical Grid Stability	Raw	Operon	0.1039
Electrical Grid Stability	Domain-normalized	Operon	0.1028
Lattice Physics	Raw	ITEA	0.0286
Lattice Physics	Domain-normalized	Operon	0.0645

The problems added in suite v11 broadened the observed difficulty range. OTL Circuit was predicted accurately by both Operon and ITEA and Yacht Hydrodynamics achieved a best mean R^2 of 0.9938 despite its hull-disjoint split. Electrical Grid Stability was moderately difficult, with Operon reaching $R^2 = 0.7410$, while Robot Arm remained difficult for every framework and reached only $R^2 = 0.4559$ in its strongest condition. Lattice Physics was strongly method- and scaling-dependent: raw-input ITEA reached $R^2 = 0.9536$, whereas most other framework configurations remained close to mean prediction. Gas Turbine NOx remained the most consistently difficult problem, as even its best framework produced negative mean R^2 in both conditions (-0.4349 for raw inputs and -0.4763 for normalized inputs).

6.2.3 Analytical and Empirical Problems

The six analytical problems and nine external datasets serve different evaluation roles. Table 6.5 summarizes their mean-NRMSE distributions across frameworks. The median result on analytical problems was similar under both scaling conditions, whereas the external-problem median increased under domain normalization. These aggregate values hide large differences between individual tasks, the analytical collection includes both the accurately approximated Cantilever and OTL

Circuit problems and the difficult Robot Arm relationship, while the external collection ranges from Yacht Hydrodynamics and Energy Efficiency to the substantially harder Gas Turbine NOx problem.

Table 6.5: Median of the framework-level mean NRMSE values by problem type and scaling condition.

Problem type	Raw inputs	Domain-normalized inputs
Analytical problems	0.0777	0.0763
External datasets	0.1189	0.1318

6.3 Effects of Input Scaling and Repetition Variability

In addition to average predictive performance, the benchmark evaluates whether the results change when the inputs are domain-normalized and how strongly they vary across repeated trials. This analysis reveals whether a framework's observed performance is consistent across preprocessing conditions and repetitions.

6.3.1 Effect of Domain Normalization

The effect of domain normalization was framework-dependent rather than uniformly beneficial. Table 6.6 compares each framework's normalized-input mean NRMSE with its raw-input result on the same problem. EQL improved on all fifteen problems and showed the largest median reduction, with a normalized-to-raw NRMSE ratio of 0.289. PySR improved on ten problems and Operon on eight, while Operon's median ratio remained close to one. gplearn improved on five problems, whereas GeneticEngine and ITEA improved on four each. The strongest newly observed interaction occurred for Lattice Physics, where ITEA's mean R^2 decreased from 0.9536 with raw inputs to 0.0070 after normalization.

Table 6.6: Effect of domain normalization. The ratio is calculated per problem from the normalized and raw mean NRMSE and then summarized by its median. Values below one favor normalization.

Framework	Problems improved (of 15)	Median NRMSE ratio
gplearn	5	1.047
Operon	8	0.991
PySR	10	0.871
GeneticEngine	4	1.160
ITEA	4	1.408
EQL	15	0.289

Figure 6.5 displays the paired raw and normalized results for each framework and problem. Points below the diagonal indicate an improvement after normalization. The figure highlights that EQL's aggregate improvement was driven in part by avoiding very large raw-input errors, whereas the other frameworks showed smaller and less consistent shifts in either direction.




Figure 6.5: Effect of domain normalization on mean range-normalized RMSE. The diagonal represents equal error under both input-scaling conditions.

6.3.2 Stability Across Repetitions

Repetition variability was evaluated using the sample standard deviation of NRMSE within each framework–problem–scaling configuration. Table 6.7 summarizes these values by taking their median across problems. Operon and PySR showed comparatively small dispersion under both scaling conditions. gplearn and GeneticEngine were more variable, particularly with normalized inputs. EQL was highly unstable with raw inputs because individual repetitions produced very large prediction errors, while normalization reduced its median standard deviation substantially.

Table 6.7: Median problem-level sample standard deviation of NRMSE across repetitions.

Framework	Raw inputs	Domain-normalized inputs
gplearn	0.0297	0.0314
Operon	0.0036	0.0040
PySR	0.0088	0.0073
GeneticEngine	0.0133	0.0236
ITEA	0.0003	< 0.0001
EQL	0.4188	0.0045

ITEA produced nearly identical results across repetitions. This observation should not be interpreted as evidence that a controllable random seed made the method reproducible, because the evaluated adapter does not expose a supported repetition-seed parameter. Instead, it indicates that the evaluated configuration returned almost unchanged results when invoked repeatedly on the same fixed tables. Figures 6.6 and 6.7 show the full distributions of repetition-level NRMSE values and make both narrow distributions and isolated failures or extreme errors visible. Separate vertical ranges are used so that the substantially narrower normalized-input distribution remains legible.




Figure 6.6: Distribution of repetition-level range-normalized RMSE by framework using raw inputs. Points represent successful trials across all problems and boxes summarize their distributions.




Figure 6.7: Distribution of repetition-level range-normalized RMSE by framework using domain-normalized inputs. Points represent successful trials across all problems, boxes summarize their distributions and red annotations report failed trials.

6.4 Symbolic Model Properties

The returned equations are compared not only through their predictions but also through properties of their symbolic representations. This section examines expression-tree complexity and reports how frequently the common symbolic simplification procedure completed or required a fallback to the unsimplified expression.

6.4.1 Expression Complexity

Expression complexity varied substantially between frameworks. Table 6.8 reports the median, across the 30 problem–scaling combinations, of each combination's mean simplified node count. On this measure, PySR returned the smallest parsed expressions, followed by ITEA and GeneticEngine. EQL occupied the middle of the aggregate ordering, while gplearn and Operon returned the largest median expressions. These comparisons describe syntactic expression size and do not by themselves measure semantic clarity or scientific usefulness.

Table 6.8: Median of the problem-level mean simplified expression-tree node counts across both scaling conditions. Only trials for which simplification completed are included.

Framework	Median simplified node count
gplearn	64.70
Operon	66.35
PySR	12.11
GeneticEngine	25.65
ITEA	18.63
EQL	49.60

Figures 6.8 and 6.9 show that expression size is also dependent on the problem and scaling condition, so the aggregate ordering did not hold uniformly in every cell. Complexity must therefore be considered alongside prediction error at the framework–problem level rather than interpreted only through one framework-wide average.



Figure 6.8: Mean simplified expression-tree node count by framework and problem using raw inputs. An asterisk indicates that at least one expression in the cell required the unsimplified complexity fallback and was excluded from the displayed simplified mean.




Figure 6.9: Mean simplified expression-tree node count by framework and problem using domain-normalized inputs. An asterisk indicates that at least one expression in the cell required the unsimplified complexity fallback and was excluded from the displayed simplified mean.

6.4.2 Symbolic Simplification and Fallbacks

The simplification completion rate differed significantly between frameworks. GeneticEngine completed simplification for all 300 parsed expressions and PySR did so for 291 of 299. gplearn required the unsimplified fallback for 85 of its 299 parsed expressions, the largest number among the frameworks. Operon required 44 fallbacks, EQL 43 and ITEA 26. Because fallback expressions can be structurally larger than their simplified counterparts, the primary simplified-complexity comparison excludes them rather than treating the two forms as directly equivalent.

Table 6.9: Symbolic simplification outcomes for parsed expressions.

Framework	Parsed	Simplified	Fallback rate
gplearn	299	214	28.4%
Operon	299	255	14.7%
PySR	299	291	2.7%
GeneticEngine	300	300	0.0%
ITEA	300	274	8.7%
EQL	300	257	14.3%

Because simplification failures occurred unevenly across frameworks and problems, the simplified-node summaries are conditional on successful simplification. They therefore describe the successfully simplified subset of each framework's expressions rather than its complete symbolic output.

These fallback counts reflect the benchmark's bounded post-processing procedure rather than failures of model fitting. Separating the original trial record from its analysis sidecar preserved the fitted equation and predictive results even when parsing or simplification was incomplete.

6.5 Computational Efficiency

Computational efficiency is reported separately for model fitting and for the subsequent use of the fitted model. This distinction is relevant for surrogate modeling because training is performed once per trial, whereas prediction may be repeated many times after an expression has been obtained.

6.5.1 Model-Fitting Time

Model-fitting times describe the evaluated configurations under the common one-thread execution controls, they are not the result of equal wall-clock search budgets. Operon had the lowest median problem-level mean fit time at 3.88 seconds, followed by ITEA at 5.83 seconds. EQL required 24.49 seconds, gplearn 33.59 seconds, GeneticEngine 60.25 seconds and PySR 89.77 seconds. PySR's fit times were comparatively consistent with the configured fixed search duration, while the other methods showed stronger problem-dependent variation.

Table 6.10: Median of problem-level mean model-fitting times across both scaling conditions.

Framework	Fit time (s)
Operon	3.88
ITEA	5.83
EQL	24.49
gplearn	33.59
GeneticEngine	60.25
PySR	89.77

Figures 6.10 and 6.11 display the problem-level mean fit times separately for raw and normalized inputs. This placement makes it possible to distinguish framework-wide timing differences from problem-specific increases and from the reduced number of successful repetitions in failed configurations.




Figure 6.10: Mean model-fitting time by framework and problem using raw inputs. Cell colors represent the base-10 logarithm of time, while annotations report seconds.




Figure 6.11: Mean model-fitting time by framework and problem using domain-normalized inputs. Cell colors represent the base-10 logarithm of time, while annotations report seconds and are based on successful trials only.

6.5.2 Prediction and Expression-Extraction Time

Prediction was fast for all fitted symbolic models relative to model fitting. Table 6.11 reports medians of the problem-level mean measurements for each scaling condition. Operon and GeneticEngine had the lowest prediction time per observation, while EQL had the highest. Expression extraction was negligible for gplearn, Operon, GeneticEngine and ITEA, remained below approximately 0.011 seconds for PySR and required approximately 0.10 seconds for EQL.

Table 6.11: Median problem-level mean prediction and expression-extraction times. Prediction time is the median full-test prediction duration divided by the number of reference-test observations.

Framework	Scaling	Prediction (μs/sample)	Extraction (s)
gplearn	Raw	0.437	0.000232
gplearn	Domain-normalized	0.613	0.000232
Operon	Raw	0.026	0.000065
Operon	Domain-normalized	0.028	0.000064
PySR	Raw	0.717	0.008851
PySR	Domain-normalized	0.880	0.010697
GeneticEngine	Raw	0.039	0.000025
GeneticEngine	Domain-normalized	0.045	0.000025
ITEA	Raw	0.220	0.000055
ITEA	Domain-normalized	0.234	0.000052
EQL	Raw	1.918	0.086836
EQL	Domain-normalized	1.901	0.085235

Even the largest median prediction time remained below two microseconds per reference-test observation. The fitted expressions were therefore inexpensive to evaluate once training had completed, although the measurements exclude calling-process and container-startup overhead and should be interpreted as in-process prediction costs.

6.6 Consolidated Framework Comparison

Table 6.12 combines the main framework-level outcomes. Operon provided the strongest overall predictive performance and the shortest model-fitting time, but its expressions were larger than those returned by PySR, ITEA and GeneticEngine. PySR produced the smallest expressions at the cost of the longest fitting time and one failed trial. ITEA combined the second-lowest median NRMSE with short fitting times and relatively compact expressions. gplearn completed every trial but was less accurate and returned expressions almost as large as Operon's in the aggregate. GeneticEngine returned compact expressions and completed all trials after its later compatible reruns were incorporated. EQL benefited most consistently from domain normalization and won two normalized analytical configurations, but its aggregate raw-input performance and variability were poor.

Table 6.12: Consolidated framework comparison. Predictive, timing and complexity values are medians of problem-level means across both scaling conditions. Simplified node counts exclude fallback expressions.

Framework	NRMSE	R^2	Fit time (s)	Nodes	Failed
gplearn	0.1296	0.4231	33.59	64.70	0
Operon	0.0455	0.9660	3.88	66.35	1
PySR	0.0804	0.7979	89.77	12.11	1
GeneticEngine	0.1313	0.3896	60.25	25.65	0
ITEA	0.0722	0.8564	5.83	18.63	0
EQL	0.1622	-0.0058	24.49	49.60	0

The results do not identify one framework as best under every evaluation dimension. Operon dominated the predictive and fitting-time summaries, PySR minimized syntactic expression size, ITEA offered a strong balance of accuracy, speed and compactness and EQL demonstrated the clearest dependence on input scaling. These observed trade-offs, together with the variation in symbolic-analysis coverage and the two unresolved execution failures, form the basis of the interpretation in the following chapter.

7 Discussion

This chapter interprets the benchmark results in relation to the research question and the use of Symbolic Regression for surrogate modeling. Rather than supporting one universal ranking, the results reveal trade-offs between predictive accuracy, expression size, computational effort, stability, preprocessing requirements and practical reliability.

7.1 Interpretation of Framework Trade-Offs

Operon provided the strongest combination of predictive accuracy and fitting speed, leading 21 of the 30 problem–scaling combinations and recording the shortest median fitting time. Its median simplified expression size of 66.35 nodes was nevertheless larger than those of PySR, ITEA and GeneticEngine, so its advantage concerns prediction and computational efficiency more clearly than compactness. Operon also produced one of the two failed trials, although one failure among 300 assigned runs does not change its otherwise high execution coverage. PySR showed the opposite profile. It produced expressions with a median size of approximately 12 nodes but had the longest fitting time and weaker median predictive performance. Its normalized OTL Circuit failure demonstrates that an expression valid on the training observations can become numerically invalid at held-out points. These contrasting outcomes show why predictive accuracy, expression size and numerical validity must be reported separately.

ITEA offered the most balanced profile after Operon, combining the second-lowest median NRMSE with short fitting times and compact expressions. It led both CCPP conditions as well as raw Airfoil Self-Noise, Robot Arm and Lattice Physics. However, its strong Lattice Physics result collapsed after normalization, showing that this aggregate balance does not hold uniformly. Its low repetition variability must also be interpreted cautiously because the adapter exposes no seed parameter. Repeated executions indicate stable behavior under the evaluated implementation but do not establish seed-controlled reproducibility.

The remaining frameworks showed clearer limitations. gplearn remained a dependable conventional genetic-programming baseline and completed every trial, but it produced relatively large expressions and did not lead any condition. GeneticEngine returned compact models and completed all rerun trials after its scalar-output is-

sue was handled, but its predictive results were weaker than those of the leading methods. EQL performed well on several normalized problems, including Borehole and Wing Weight, but produced severe raw-input errors and high variability. It therefore provides the clearest example of preprocessing-dependent suitability.

Input scaling was therefore not uniformly beneficial. Normalization improved EQL on every problem and PySR on ten, but improved gplearn on five and GeneticEngine and ITEA on only four each. Operon's median error remained almost unchanged. For EQL, scaling prevented several extreme raw-input outcomes, whereas for ITEA it removed the strong raw-input Lattice Physics result. Scaling should consequently be treated as part of a framework configuration rather than as a neutral preprocessing choice.

Problem characteristics were equally important. OTL Circuit and Yacht Hydrodynamics were modeled comparatively well, Electrical Grid Stability was moderately difficult and Robot Arm remained difficult despite noise-free targets. Gas Turbine NOx produced negative mean R^2 even for the strongest method, while Lattice Physics sharply favored one framework and scaling condition. The analytical collection therefore did not consist only of easy equation-recovery examples, and the external datasets did not form one uniform difficulty class. This variation supports findings from broader SR benchmarks that no method is uniformly optimal across problem classes [13, 10].

Runtime comparisons must remain limited to the evaluated configurations because the benchmark did not impose equal wall-clock or function-evaluation budgets. PySR and GeneticEngine used practical time limits, whereas the other frameworks used adapter-specific iteration or evaluation controls. The measured times therefore describe the selected configurations rather than each framework's maximum attainable performance, and they should not be interpreted as an equal-compute competition. They also exclude container startup and post-processing, which were measured outside the fitting call. Once fitted, however, all returned expressions were inexpensive to evaluate, demonstrating a common advantage of symbolic surrogates during repeated deployment.

7.2 Suitability for Interpretable Surrogate Modeling

The benchmark supports SR as a useful but conditional approach to interpretable surrogate modeling. Almost every successful trial returned an expression that could be parsed, transformed into physical coordinates and assigned common structural measures. Explicitness should nevertheless not be equated with interpretability. Median simplified size ranged from approximately 12 nodes for PySR to 66 for Operon, while individual models were considerably larger. Node count measures structural compactness but not whether variables have physically plausible roles, constants correspond to meaningful quantities, or a domain expert can understand the expression.

It also treats all operation types uniformly, even though nested functions such as sine, logarithm, or exponential terms may be harder to interpret than several additions or multiplications. Moreover, 206 expressions did not complete the bounded simplification procedure. Because these fallbacks occurred unevenly across frameworks, the primary simplified-complexity comparison describes only the successfully simplified subsets and may not represent each framework's complete output.

Structural statistics must also be interpreted together with predictive adequacy. The negative R^2 results on Gas Turbine NOx and near-constant EQL results on Electrical Grid Stability and Lattice Physics show that a compact or visible expression is not useful merely because it is symbolic. Conversely, the stronger results on Yacht Hydrodynamics, Energy Efficiency, CCPP, Naval Propulsion, Concrete Strength and Airfoil Self-Noise demonstrate that SR can produce workable approximations for several engineering datasets with modest training sizes. Whether these expressions are scientifically informative still requires domain-specific assessment beyond the structural measures used here.

Framework choice should therefore follow the intended use. Operon is the strongest candidate when predictive accuracy and fitting speed are important and larger expressions are acceptable. PySR is preferable when compact output outweighs fitting cost, while ITEA offers a favorable compromise but lacks controlled estimator seeds in the evaluated adapter. EQL may be suitable for compatible structures when normalized inputs and careful stability checks are used. gplearn remains a transparent baseline and GeneticEngine offers compact grammar-guided output, although neither matched the leading predictive results under the selected settings.

Practical suitability also depends on software integration. The benchmark relied on pinned containers, adapter-specific compatibility handling, failure records and separate symbolic post-processing. A valid GeneticEngine constant initially appeared as a failed trial because of its output shape. The invalid PySR OTL expression likewise illustrated the need for validation over the complete test domain. Differences in seed control and expression export further affected how consistently the frameworks could be evaluated. Although 1798 of 1800 trials completed successfully, reproducibility still requires preservation of configurations, environments, data hashes, expressions and post-processing decisions. Current SR frameworks can therefore provide inexpensive and inspectable surrogates, but they are not an automatic route to simple, stable, physically plausible, or scientifically correct equations.

7.3 Research Gaps and Future Benchmarking Needs

The conclusions remain limited to fifteen problems, one fixed train–test design per problem and the evaluated framework configurations. Although the collection spans analytical, simulator-generated, experimental and measured data with three to 39 inputs, it cannot represent the full diversity of surrogate applications. The results

should therefore be interpreted as evidence about these tasks rather than population-wide framework rankings. Additional datasets and repeated train–test designs would show whether the observed ordering persists across sampling choices and broader application domains.

The protocol evaluates interpolation on held-out observations but not controlled extrapolation, corrupted measurements, recursive simulation, or physical constraints such as dimensional consistency and conservation. These properties become important when a surrogate replaces a simulator in optimization, control, or repeated dynamical prediction. Future tracks should vary sample size and noise level, distinguish interpolation from extrapolation and include rollout or constraint-aware evaluations where the problem supports them.

Using one fixed configuration per framework supports reproducibility but does not show the effect of problem-specific operators, complexity penalties, or larger search budgets. The selected expression from each run also represents only one point in the framework's possible accuracy–complexity trade-off. Future comparisons could combine a common wall-clock track with framework-recommended configurations, retain complete accuracy–complexity Pareto fronts and report memory or energy use [9, 1]. This would distinguish performance under a shared resource constraint from performance under settings tailored to each method and allow different applications to select models according to their own complexity requirements.

The absence of non-symbolic baselines also limits conclusions about the predictive cost of explicitness. Polynomial regression, Gaussian processes, tree ensembles and compact neural networks evaluated on the same data splits would show when symbolic models are competitive with established surrogates. Such a comparison should include prediction cost, uncertainty and model-inspection properties rather than predictive error alone.

Finally, syntactic measures do not capture human understanding. Expert assessment of dimensional validity, physical plausibility, recognizable interactions and explanation effort would better distinguish compact expressions from meaningful ones. More consistent framework interfaces for seed control, protected operators, expression export, complexity definitions and failure diagnostics would likewise reduce adapter-specific work. Common, versioned schemas for results and analysis records would make evolving benchmarks easier to audit and reproduce. Standardized infrastructure is therefore important both for broader interpretability studies and for reliable practical adoption.

8 Conclusion

This thesis compared gplearn, Operon, PySR, GeneticEngine, ITEA and EQL on fifteen analytical, simulator-generated, experimental and measured surrogate-modeling problems. Raw and domain-normalized inputs were evaluated over ten repetitions, producing 1800 planned trial coordinates, of which 1798 completed successfully. Fixed train–test tables, pinned execution environments and a common evaluation and post-processing pipeline supported a consistent comparison of predictive performance, computational efficiency, stability and expression structure.

Operon achieved the strongest overall predictive result under the evaluated configurations, leading 21 of the 30 problem–scaling combinations, obtaining the lowest median NRMSE of 0.0455 and requiring the shortest median fitting time of 3.88 seconds. ITEA offered a strong balance of accuracy, runtime and compactness, while PySR produced the smallest expressions but required the longest fitting time. gplearn provided a reliable conventional baseline, GeneticEngine returned comparatively compact models with weaker predictive performance and EQL showed the clearest dependence on input normalization.

The experiments demonstrated that framework suitability depends strongly on the problem and preprocessing condition. Domain normalization benefited EQL consistently but was not uniformly advantageous for the evolutionary methods. OTL Circuit and Yacht Hydrodynamics showed comparatively low prediction errors. Robot Arm and Gas Turbine NOx remained difficult. Predictive accuracy and expression complexity also formed separate evaluation dimensions. The most accurate framework did not produce the smallest expressions and an explicit equation does not mean that it is, physically plausible, or scientifically meaningful.

The research question can therefore be answered conditionally. Symbolic Regression is suitable for constructing inexpensive and inspectable surrogate models when an application benefits from an explicit mathematical representation, but no evaluated framework was preferable under every objective. Accuracy, complexity, stability, computational cost and domain plausibility must be assessed together and the conclusions remain limited to the evaluated problems and configurations. Future work should extend the benchmark with additional noise, extrapolation and physical-constraint experiments, non-symbolic surrogate baselines and expert evaluation of whether the returned expressions are meaningful rather than merely compact.

Bibliography

[1] Aldeia, G. S. I., Zhang, H., Bomarito, G., Cranmer, M., Fonseca, A., Burlacu, B., La Cava, W. G. and de França, F. O. [2025], Call for action: Towards the next generation of symbolic regression benchmark, *in* 'Proceedings of the Genetic and Evolutionary Computation Conference Companion', Association for Computing Machinery, New York, NY, USA, pp. 1–10.
URL: *https://doi.org/10.1145/3712255.3734309*

[2] Alizadeh, R., Allen, J. K. and Mistree, F. [2020], 'Managing computational complexity using surrogate models: A critical review', *Research in Engineering Design* **31**(3), 275–298.
URL: *https://doi.org/10.1007/s00163-020-00336-7*

[3] Angelis, D., Sofos, F. and Karakasidis, T. E. [2023], 'Artificial intelligence in physical sciences: Symbolic regression trends and perspectives', *Archives of Computational Methods in Engineering* **30**(6), 3845–3865.
URL: *https://doi.org/10.1007/s11831-023-09922-z*

[4] Brum, B. R., Lober, L., Previdelli, I. and Rodrigues, F. A. [2026], 'Discovering equations from data: Symbolic regression in dynamical systems', *Journal of Physics: Complexity* **7**(1), 012001.
URL: *https://doi.org/10.1088/2632-072X/ae3eed*

[5] Brunton, S. L., Proctor, J. L. and Kutz, J. N. [2016], 'Discovering governing equations from data by sparse identification of nonlinear dynamical systems', *Proceedings of the National Academy of Sciences* **113**(15), 3932–3937.
URL: *https://doi.org/10.1073/pnas.1517384113*

[6] Burlacu, B., Kronberger, G. and Kommenda, M. [2020], Operon C++: An efficient genetic programming framework for symbolic regression, *in* 'Proceedings of the Genetic and Evolutionary Computation Conference Companion', Association for Computing Machinery, New York, NY, USA, pp. 1562–1570.
URL: *https://doi.org/10.1145/3377929.3398099*

[7] Cranmer, M. [2023], 'Interpretable machine learning for science with PySR and SymbolicRegression.jl'.
URL: *https://arxiv.org/abs/2305.01582*

[8] de França, F. O. and Aldeia, G. S. I. [2021], 'Interaction–transformation evolutionary algorithm for symbolic regression', *Evolutionary Computation*

29(3), 367–390.
URL: *https://doi.org/10.1162/evco_a_00285*

[9] de França, F. O., Virgolin, M., Kommenda, M., Majumder, M. S., Cranmer, M., Espada, G., Ingelse, L., Fonseca, A., Landajuela, M., Petersen, B. et al. [2025], 'SRBench++: Principled benchmarking of symbolic regression with domain-expert interpretation', *IEEE Transactions on Evolutionary Computation* **29**(4), 1127–1134.
URL: *https://doi.org/10.1109/TEVC.2024.3423681*

[10] Dong, J. and Zhong, J. [2025], 'Recent advances in symbolic regression', *ACM Computing Surveys* **57**(11), 1–37.
URL: *https://doi.org/10.1145/3735634*

[11] Espada, G., Ingelse, L., Canelas, P., Barbosa, P. and Fonseca, A. [2022], Data types as a more ergonomic frontend for grammar-guided genetic programming, *in* 'Proceedings of the 21st ACM SIGPLAN International Conference on Generative Programming: Concepts and Experiences', GPCE 2022, Association for Computing Machinery, pp. 86–94.
URL: *https://doi.org/10.1145/3564719.3568697*

[12] Guo, J. and Yin, W.-J. [2024], 'Harnessing data using symbolic regression methods for discovering novel paradigms in physics', *Science China Physics, Mechanics & Astronomy* **67**(6), 267301.
URL: *https://doi.org/10.1007/s11433-023-2346-2*

[13] La Cava, W. G., Orzechowski, P., Burlacu, B., de França, F. O., Virgolin, M., Jin, Y., Kommenda, M. and Moore, J. H. [2021], Contemporary symbolic regression methods and their relative performance, *in* 'Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks', Vol. 1.
URL: *https://openreview.net/forum?id=xVQMrDLyGst*

[14] Makke, N. and Chawla, S. [2024], 'Interpretable scientific discovery with symbolic regression: A review', *Artificial Intelligence Review* **57**(2).
URL: *https://doi.org/10.1007/s10462-023-10622-0*

[15] Orzechowski, P., La Cava, W. and Moore, J. H. [2018], Where are we now? a large benchmark study of recent symbolic regression methods, *in* 'Proceedings of the Genetic and Evolutionary Computation Conference', Association for Computing Machinery, New York, NY, USA, pp. 1183–1190.
URL: *https://doi.org/10.1145/3205455.3205539*

[16] Petersen, B. K., Landajuela Larma, M., Mundhenk, T. N., Santiago, C. P., Kim, S. K. and Kim, J. T. [2021], Deep symbolic regression: Recovering mathematical expressions from data via risk-seeking policy gradients, *in* 'International Conference on Learning Representations'.
URL: *https://arxiv.org/abs/1912.04871*

[17] Rudin, C. [2019], 'Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead', *Nature Machine Intelligence* **1**(5), 206–215.
URL: *https://doi.org/10.1038/s42256-019-0048-x*

[18] Sahoo, S. S., Lampert, C. H. and Martius, G. [2018], Learning equations for extrapolation and control, *in* 'Proceedings of the 35th International Conference on Machine Learning', Vol. 80 of *Proceedings of Machine Learning Research*, PMLR, pp. 4442–4450.
URL: *https://proceedings.mlr.press/v80/sahoo18a.html*

[19] SRBench contributors [n.d.], 'SRBench: A living benchmark framework for symbolic regression', GitHub repository. Revision ac1059bae0f641cf9e4dfd5c91add5d4e01dbcb5, accessed 21 August 2026.
URL: *https://github.com/cavalab/srbench*

[20] Stephens, T. [2026], 'gplearn: Genetic programming in python', Software documentation. Accessed 20 August 2026.
URL: *https://gplearn.readthedocs.io/en/stable/*

[21] Udrescu, S.-M. and Tegmark, M. [2020], 'AI Feynman: A physics-inspired method for symbolic regression', *Science Advances* **6**(16), eaay2631.
URL: *https://doi.org/10.1126/sciadv.aay2631*

[22] Wang, G., Wang, E., Li, Z., Zhou, J. and Sun, Z. [2024], 'Exploring the mathematic equations behind the materials science data using interpretable symbolic regression', *Interdisciplinary Materials* **3**(4), 637–657.
URL: *https://doi.org/10.1002/idm2.12180*