

Correlated random effects: iidkd

This model is available for dimensions $k = 2$, to 10. We describe in detail the case for $k = 3$ as other ones are similar. This model do the same as models `iid2d`, `iid3d`, `iid4d`, `iid5d`, but uses a more efficient parameterisation.

Parametrization

The $(k = 3)$ -dimensional Normal-Wishard model is used if one want to define three vectors of “random effects”, u and v and w , say, for which (u_i, v_i, w_i) are iid bivariate Normals

$$\begin{pmatrix} u_i \\ v_i \\ w_i \end{pmatrix} \sim \mathcal{N}(\mathbf{0}, \mathbf{W}^{-1})$$

where the covariance matrix \mathbf{W}^{-1} is parameterised as $\mathbf{W} = \mathbf{L}\mathbf{L}^T$, where

$$\mathbf{L} = \begin{pmatrix} \exp(\theta_1) & & \\ \theta_4 & \exp(\theta_2) & \\ \theta_5 & \theta_6 & \exp(\theta_3) \end{pmatrix} \quad (1)$$

and $\theta_1, \theta_2, \theta_3, \theta_4, \theta_5, \theta_6$ can take any value. The number of hyperparameters are $k(k+1)/2$, which is 3, 6, 10, 15, 21, 28, 36, 45, 55, for $k = 2, 3, 4, 5, 6, 7, 8, 9, 10$.

For these models the precision matrix \mathbf{W} is Wishart distributed

$$\mathbf{W} \sim \text{Wishart}_k(r, \mathbf{R}^{-1}),$$

with density

$$\pi(\mathbf{W}) = c^{-1} |\mathbf{W}|^{(r-(k+1))/2} \exp \left\{ -\frac{1}{2} \text{Trace}(\mathbf{W}\mathbf{R}) \right\}, \quad r > k+1$$

and

$$c = 2^{(rk)/2} |\mathbf{R}|^{-r/2} \pi^{(k(k-1))/4} \prod_{j=1}^k \Gamma((r+1-j)/2).$$

Then,

$$\text{E}(\mathbf{W}) = r\mathbf{R}^{-1}, \quad \text{and} \quad \text{E}(\mathbf{W}^{-1}) = \mathbf{R}/(r - (k+1)).$$

Hyperparameters

The hyperparameters are $\theta_1, \theta_2, \theta_3, \theta_4, \theta_5, \theta_6$.

The prior-parameters are

$$(r, R_1, R_2, R_3, R_4, R_5, R_6)$$

where

$$\mathbf{R} = \begin{pmatrix} R_1 & R_4 & R_5 \\ R_4 & R_2 & R_6 \\ R_5 & R_6 & R_3 \end{pmatrix}$$

The `inla` function reports posterior distribution for the hyperparameters $\{\theta_i\}$, and the conversion into interpretable quantities can be done using simulation as described below.

The prior for θ is **fixed** to be `wishartkd`, and number of prior parameters required are $1 + k(k+1)/2$. By default the prior-parameters are

$$(r = 100, \underbrace{1, \dots, 1}_{k \text{ times}}, 0, \dots, 0)$$

Specification

The model `iidkd` is specified as

```
y ~ f(i, model="iidkd", order=3, n = <length>) + ...
```

where $\text{order} = k = 3$, and the `iidkd` model is represented internally as one vector of length n ,

$$(u_1, u_2, \dots, u_m, v_1, v_2, \dots, v_m, w_1, w_2, \dots, w_m)$$

where $n = 3m$, and n is the (required) argument in `f()`.

For this model the argument `constr=TRUE` is interpreted as 3 sum-to-zero constraints

$$\sum u_i = 0, \quad \sum v_i = 0 \quad \text{and} \quad \sum w_i = 0.$$

Hyperparameter spesification and default values

(**Note:** The value “2468.8642” is just a code for “replace this by the default value”. As the default value depends on `order`, the was the easy way out for the moment.)

doc Gaussian random effect in dim=k with Wishart prior

hyper

theta1

hyperid 29101

name theta1

short.name theta1

initial 2468.8642

fixed FALSE

prior wishartkd

param 100 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642
2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642
2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642
2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642
2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642
2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642 2468.8642

to.theta function(x) x

from.theta function(x) x

theta2

hyperid 29102

name theta2

short.name theta2

initial 2468.8642

fixed FALSE

prior none

param

to.theta function(x) x

from.theta function(x) x

theta3

```

hyperid 29103
name theta3
short.name theta3
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta4
hyperid 29104
name theta4
short.name theta4
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta5
hyperid 29105
name theta5
short.name theta5
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta6
hyperid 29106
name theta6
short.name theta6
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta7
hyperid 29107
name theta7
short.name theta7
initial 2468.8642

```

```

    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta8
    hyperid 29108
    name theta8
    short.name theta8
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta9
    hyperid 29109
    name theta9
    short.name theta9
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta10
    hyperid 29110
    name theta10
    short.name theta10
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta11
    hyperid 29111
    name theta11
    short.name theta11
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x

```

```

    from.theta function(x) x
theta12
    hyperid 29112
    name theta12
    short.name theta12
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta13
    hyperid 29113
    name theta13
    short.name theta13
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta14
    hyperid 29114
    name theta14
    short.name theta14
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta15
    hyperid 29115
    name theta15
    short.name theta15
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta16
    hyperid 29116
    name theta16

```

```

    short.name theta16
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta17
    hyperid 29117
    name theta17
    short.name theta17
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta18
    hyperid 29118
    name theta18
    short.name theta18
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta19
    hyperid 29119
    name theta19
    short.name theta19
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta20
    hyperid 29120
    name theta20
    short.name theta20
    initial 2468.8642
    fixed FALSE
    prior none

```

```

    param
    to.theta function(x) x
    from.theta function(x) x
theta21
    hyperid 29121
    name theta21
    short.name theta21
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta22
    hyperid 29122
    name theta22
    short.name theta22
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta23
    hyperid 29123
    name theta23
    short.name theta23
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta24
    hyperid 29124
    name theta24
    short.name theta24
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta25

```

```

hyperid 29125
name theta25
short.name theta25
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta26
hyperid 29126
name theta26
short.name theta26
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta27
hyperid 29127
name theta27
short.name theta27
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta28
hyperid 29128
name theta28
short.name theta28
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta29
hyperid 29129
name theta29
short.name theta29
initial 2468.8642

```



```

    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta30
    hyperid 29130
    name theta30
    short.name theta30
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta31
    hyperid 29131
    name theta31
    short.name theta31
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta32
    hyperid 29132
    name theta32
    short.name theta32
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta33
    hyperid 29133
    name theta33
    short.name theta33
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x

```

```

    from.theta function(x) x
theta34
    hyperid 29134
    name theta34
    short.name theta34
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta35
    hyperid 29135
    name theta35
    short.name theta35
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta36
    hyperid 29136
    name theta36
    short.name theta36
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta37
    hyperid 29137
    name theta37
    short.name theta37
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta38
    hyperid 29138
    name theta38

```

```

    short.name theta38
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta39
    hyperid 29139
    name theta39
    short.name theta39
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta40
    hyperid 29140
    name theta40
    short.name theta40
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta41
    hyperid 29141
    name theta41
    short.name theta41
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta42
    hyperid 29142
    name theta42
    short.name theta42
    initial 2468.8642
    fixed FALSE
    prior none

```

```

    param
    to.theta function(x) x
    from.theta function(x) x
theta43
    hyperid 29143
    name theta43
    short.name theta43
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta44
    hyperid 29144
    name theta44
    short.name theta44
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta45
    hyperid 29145
    name theta45
    short.name theta45
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta46
    hyperid 29146
    name theta46
    short.name theta46
    initial 2468.8642
    fixed FALSE
    prior none
    param
    to.theta function(x) x
    from.theta function(x) x
theta47

```

```

hyperid 29147
name theta47
short.name theta47
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta48
hyperid 29148
name theta48
short.name theta48
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta49
hyperid 29149
name theta49
short.name theta49
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta50
hyperid 29150
name theta50
short.name theta50
initial 2468.8642
fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta51
hyperid 29151
name theta51
short.name theta51
initial 2468.8642

```

```

fixed FALSE
prior none
param
to.theta function(x) x
from.theta function(x) x
theta52
  hyperid 29152
  name theta52
  short.name theta52
  initial 2468.8642
  fixed FALSE
  prior none
  param
  to.theta function(x) x
  from.theta function(x) x
theta53
  hyperid 29153
  name theta53
  short.name theta53
  initial 2468.8642
  fixed FALSE
  prior none
  param
  to.theta function(x) x
  from.theta function(x) x
theta54
  hyperid 29154
  name theta54
  short.name theta54
  initial 2468.8642
  fixed FALSE
  prior none
  param
  to.theta function(x) x
  from.theta function(x) x
theta55
  hyperid 29155
  name theta55
  short.name theta55
  initial 2468.8642
  fixed FALSE
  prior none
  param
  to.theta function(x) x

```

```

    from.theta function(x) x
constr FALSE
nrow.ncol FALSE
augmented TRUE
aug.factor 1
aug.constr 1 2 3 4 5 6 7 8 9 10
n.div.by -1
n.required TRUE
set.default.values TRUE
status experimental
pdf iidkd

```

Example

Just simulate some data and estimate the parameters back. This is for `order=4`.

```

n <- 300
m <- 4
N <- m*n
rho <- 0.8

Sigma <- matrix(NA, m, m)
diag(Sigma) <- (1/(1:m))^2
for(i in 1:m) {
  if (i+1 <= m) {
    for (j in (i+1):m) {
      Sigma[i, j] <- Sigma[j, i] <- rho * sqrt(Sigma[i, i]*Sigma[j, j])
    }
  }
}

library(mvtnorm)
yy <- rmvnorm(n, sigma = Sigma)
y <- c()
for(i in 1:m) {
  y <- c(y, yy[, i])
}

r <- inla(y ~ f(i, model = "iidkd", order = m, n=N,
  ## set parameters using 'theta1'.
  ## these are the default parameters.
  hyper = list(theta1 = list(
    param = c(100, rep(1, m), rep(0, m*(m-1)/2))))) ,
  data = data.frame(i = 1:N, y),
  ## fix precision as we have exact observations
  control.family = list(hyper = list(
    prec = list(initial = 15, fixed = TRUE))),
  verbose = TRUE)

```

```

## this is how the internal parameters are defined
L <- t(chol(solve(Sigma)))
diag(L) <- log(diag(L))
LL <- t(chol(solve(cov(yy))))
diag(LL) <- log(diag(LL))

## compare the estimated (internal) parameters with MLE and the truth
round(dig = 3, cbind(true = c(diag(L), L[lower.tri(L)]),
                             mle = c(diag(LL), LL[lower.tri(LL)]),
                             inla = r$mode$theta))

## this is how to compute stdev and correlations from the internal parametes.
## these ones are more interpretable. one have to know where the parameters
## are in the list though, but here it is easy...

convert.internal <- function(theta, dim, offset = 0)
{
  ntheta.off.diag <- dim*(dim-1)/2L
  L <- matrix(0, dim, dim)
  diag(L) <- exp(theta[offset + 1:dim])
  L[lower.tri(L)] <- theta[offset + dim + 1:ntheta.off.diag]
  S <- solve(L %*% t(L))
  iSigma <- 1/sqrt(diag(S))
  Cor <- diag(iSigma) %*% S %*% diag(iSigma)
  return(c(sqrt(diag(S)), Cor[lower.tri(Cor)]))
}

xx <- inla.hyperpar.sample(10000, r)
qq <- rowMeans(apply(xx, 1, convert.internal, dim = m))
iSigma <- 1/sqrt(diag(Sigma))
Cor <- diag(iSigma) %*% Sigma %*% diag(iSigma)
round(dig = 3, cbind(inla = c(qq),
                     true = c(sqrt(diag(Sigma)), Cor[lower.tri(Cor)])))

```