

Total No. of Questions : 4]

SEAT No. :

PF207

[Total No. of Pages : 1

APR-26/SE/Insem-253

**S.E. (Electronics/E&TC/Electronics & Computer) /
(Electronics Engg. (VLSI Design & Technology)) (Insem)
PRINCIPLES OF COMMUNICATION SYSTEMS
(2019 Pattern) (Semester - IV) (204193)**

Time : 1 Hour]

[Max. Marks : 30

Instructions to the candidates.

- 1) Answer Q.1 or Q.2 and Q.3 or Q.4.
- 2) Neat diagrams must be drawn wherever necessary.
- 3) Figures to the right indicate full marks.
- 4) Assume suitable data if necessary.

- Q1)** a) Differentiate between baseband signal and band pass signal. [5]
b) Obtain the Fourier Transform of rectangular pulse with time duration T and amplitude A. [5]
c) What is modulation? Explain the need of modulation in communication systems. [5]

OR

- Q2)** a) Explain the regenerative repeaters and the use of regenerative repeaters. [5]
b) State the following properties of Fourier transform
i) Frequency Shifting
ii) Time Shifting [5]
c) Classify the different types of signal used in communication system. [5]

- Q3)** a) A 12 kW carrier wave is amplitude modulated at 80% depth of modulation by a sinusoidal modulating signal. Calculate the sideband power, total power and the transmission efficiency of the AM wave. [5]
b) Draw the block diagram of low level AM transmitter. [5]
c) Explain the generation of DSB-SC using nonlinear device. [5]

OR

- Q4)** a) A modulating signal $20 \sin(2\pi \times 10^3 t)$ is used to modulate a carrier signal $40 \sin(2\pi \times 10^4 t)$ calculate: [5]
i) Modulation Index
ii) Efficiency
iii) Sideband frequencies and their amplitudes
iv) Bandwidth of AM wave
v) Draw the frequency spectrum
b) Draw the spectrum of DSBFC, DSBSC and SSB. [5]
c) Draw & Explain the block diagram of AM super heterodyne receiver. [5]