

Oracle Instant Client Downloads for Linux x86-64 (64-bit)

Oracle Instant Client enables development and deployment of applications that connect to Oracle AI Database, either on-premise or in the cloud.



Overview

The Instant Client libraries provide the necessary network connectivity and advanced data features to make full use of Oracle AI Database. The libraries support popular languages and environments including Python, Node.js, Go, PHP and Ruby, as well as providing access for Oracle Call Interface (OCI), Oracle C++ Call Interface (OCCI), JDBC OCI, ODBC and Pro*C applications. Tools included in Instant Client include SQL*Plus, SQL*Loader and Oracle Data Pump that provide quick and convenient data access.

For more information, see the [Instant Client Home Page](#). For information on the tools and libraries provided for the Pro*C and Pro*COBOL precompilers, see the [Precompiler Downloads page](#).

Client-server version interoperability is detailed in [Doc ID 207303.1](#). For example, Oracle Call Interface 19.3 can connect to Oracle Database 11.2 or later. Some tools may have other restrictions.



Instant Client RPMs are also available from yum.oracle.com for [Oracle Linux 10](#), [Oracle Linux 9](#) and [Oracle Linux 8](#). Older RPM packages are available for [Oracle Linux 9](#), [Oracle Linux 8](#), [Oracle Linux 7](#) and [Oracle Linux 6](#). More information is on the [Instant Client for Oracle Linux](#) page.

Permanent links to the latest packages are: [Basic \(.zip\)](#), [Basic \(.rpm\)](#), [Basic Light \(.zip\)](#), [Basic Light \(.rpm\)](#), [SQL*Plus \(.zip\)](#), [SQL*Plus \(.rpm\)](#), [Tools \(.zip\)](#), [Tools \(.rpm\)](#), [SDK \(.zip\)](#), [SDK \(.rpm\)](#), [JDBC Supplement \(.zip\)](#), [JDBC Supplement \(.rpm\)](#), [ODBC \(.zip\)](#), [ODBC \(.rpm\)](#)

Note:

We strongly recommend that customers install the latest supported Oracle Instant Client for their Oracle Database release. For example, customers should install Oracle Instant Client 19c or 23ai (23.26.x.x) to benefit from the latest features, security updates, and performance improvements. Older versions will be removed in the near future. Customers who require an older version may request it through Oracle Support.

Select the required Oracle Instant Client version from the choices below:

Version 23.26.3.0.0

Downloads - Version 23.26 (Requires glibc 2.28)

Download	Details
 Basic Package (ZIP)	instantclient-basic-linux.x64-23.26.3.0.0.zip 136,114,689 bytes (checksum = 992902072) SHA256 fce485361332927f8328ea4b68d98968c6b0ea124e62470de8c9d0cef880130e All files required to run OCI, OCCI, and JDBC-OCI applications





Download	Details
 Basic Package (OL10 RPM)	oracle-instantclient-basic-23.26.3.0.0-1.el10.x86_64.rpm 83,867,558 bytes (checksum = 3602500546) SHA256 58dd5d03593ccf081d6a216f184f2fa4e360962deabc267b48610094d76f6eb5 • All files required to run OCI, OCCI, and JDBC-OCI applications
 Basic Package (OL9 RPM)	oracle-instantclient-basic-23.26.3.0.0-1.el9.x86_64.rpm 83,893,356 bytes (checksum = 1614690970) SHA256 acaec44d589a736e29e4fd60c57116fa1d72ac57971acc14476ef01c63bcdfa2 • All files required to run OCI, OCCI, and JDBC-OCI applications
 Basic Package (OL8 RPM)	oracle-instantclient-basic-23.26.3.0.0-1.el8.x86_64.rpm 88,314,292 bytes (checksum = 1731424998) SHA256 6b0755e6be000cea31ad3e4d2a237faaf00db59b74ec20efdfef47d4112f5fe25 • All files required to run OCI, OCCI, and JDBC-OCI applications



Download	Details
 Basic Light Package (ZIP)	instantclient-basiclite-linux.x64-23.26.3.0.0.zip 76,301,906 bytes (checksum = 1397065925) SHA256 88c2b59d473f0d34615556dbee51cb90cce61a9104b4c1c772d13c344fba19c9 • Smaller version of the Basic package, with only English error messages and Unicode, ASCII, and Western European character set support
 Basic Light Package (OL10 RPM)	oracle-instantclient-basiclite-23.26.3.0.0-1.el10.x86_64.rpm 44,518,536 bytes (checksum = 3663809305) SHA256 e3fe4f5151e2e22f0bbc855d68e45a6d78eaa103aedccd8535a29dfa9eef2d6b • Smaller version of the Basic package, with only English error messages and Unicode, ASCII, and Western European character set support
 Basic Light Package (OL9 RPM)	oracle-instantclient-basiclite-23.26.3.0.0-1.el9.x86_64.rpm 44,530,484 bytes (checksum = 2873550540) SHA256 be36312ff493393c962c291e40c9a8fc2dc44d796beb7db4f8bb5e995f85a169 • Smaller version of the Basic package, with only English error messages and Unicode, ASCII, and Western European character set support
 Basic Light Package (OL8 RPM)	oracle-instantclient-basiclite-23.26.3.0.0-1.el8.x86_64.rpm 46,013,712 bytes (checksum = 3451964728) SHA256 708651929a7bca01860e2cbd3e08f4363f04d9ad8f00e3722064c3821d183db5



Download	Details
	• Smaller version of the Basic package, with only English error messages and Unicode, ASCII, and Western European character set support
  SQL*Plus Package (ZIP) 	instantclient-sqlplus-linux.x64-23.26.3.0.0.zip 5,731,358 bytes (checksum = 1854727341) SHA256 6570d7939856767cddb549b51e1423d6a5f53143c57c30c015669706f65a632a • The SQL*Plus command line tool for SQL and PL/SQL queries
  SQL*Plus Package (OL10 RPM) 	oracle-instantclient-sqlplus-23.26.3.0.0-1.el10.x86_64.rpm 4,116,835 bytes (checksum = 2457193264) SHA256 98daf9621e126ee8c6445ce298f489527b3b3e8110eccf7e539885c13de8fa7a • The SQL*Plus command line tool for SQL and PL/SQL queries
  SQL*Plus Package (OL9 RPM) 	oracle-instantclient-sqlplus-23.26.3.0.0-1.el9.x86_64.rpm 4,117,104 bytes (checksum = 37979211) SHA256 7c5fb25f37b5dc01486f13dd94815122c39ae8c82f640526ffd6f37aa168499d • The SQL*Plus command line tool for SQL and PL/SQL queries
  SQL*Plus Package (OL8 RPM) 	oracle-instantclient-sqlplus-23.26.3.0.0-1.el8.x86_64.rpm 4,974,956 bytes (checksum = 1828535870) SHA256 b71e763398247951e3a8f193b24deae709f5144cfe5baa132d069ddf6738b5b8



Download	Details
	The SQL*Plus command line tool for SQL and PL/SQL queries
 Tools Package (ZIP)	instantclient-tools-linux.x64-23.26.3.0.0.zip 1,445,752 bytes (checksum = 2882732731) SHA256 680b6e6f3b7ae13972d4c3959b3dc4f3bd075a0bed51e5d5b21915d5535f350b Includes Data Pump, SQL*Loader and Workload Replay Client
 Tools Package (OL10 RPM)	oracle-instantclient-tools-23.26.3.0.0-1.el10.x86_64.rpm 1,096,537 bytes (checksum = 2080995197) SHA256 377dba650319251fdbff65202a9bbc9e2ac373939f9f3a45540f5cd8f4c72fcc Includes Data Pump, SQL*Loader and Workload Replay Client
 Tools Package (OL9 RPM)	oracle-instantclient-tools-23.26.3.0.0-1.el9.x86_64.rpm 1,096,805 bytes (checksum = 298839553) SHA256 8e5bf21a848a8572d66a9323f8ab55d89e926f7f7354ae3c53bcfe740e98910d Includes Data Pump, SQL*Loader and Workload Replay Client
 Tools Package (OL8 RPM)	oracle-instantclient-tools-23.26.3.0.0-1.el8.x86_64.rpm 1,107,536 bytes (checksum = 3371950603) SHA256 4e2e671eb0397af993ade19af2517b8674913c912fe51379f8967d692ff7ba16



Download	Details
	Includes Data Pump, SQL*Loader and Workload Replay Client
  SDK Package (ZIP) 	instantclient-sdk-linux.x64-23.26.3.0.0.zip 1,090,744 bytes (checksum = 3618157579) SHA256 7ac13587ba8a734ae7cc06cf42753bbfdb69839daf87bd5935a49c83decccf Additional header files and an example makefile for developing Oracle applications with Instant Client
  SDK Package (OL10 RPM) 	oracle-instantclient-devel-23.26.3.0.0-1.el10.x86_64.rpm 700,295 bytes (checksum = 1617325049) SHA256 e45e306b6c25e9e3dbfa3d157166b94f79cd6dfdc3a950e9eb3dbf88aef95dd4 Additional header files and an example makefile for developing Oracle applications with Instant Client
  SDK Package (OL9 RPM) 	oracle-instantclient-devel-23.26.3.0.0-1.el9.x86_64.rpm 700,296 bytes (checksum = 1147835892) SHA256 c5a5eb0be85f1bf95bde3446f4945b3878bcb5d0f716ddcf16da1ee0183b509f Additional header files and an example makefile for developing Oracle applications with Instant Client
  SDK Package (OL8 RPM) 	oracle-instantclient-devel-23.26.3.0.0-1.el8.x86_64.rpm 737,100 bytes (checksum = 2267499234)



Download	Details
	SHA256 aab35ee1f990be463ee7f45bfd23996eae13e0270c218b89db130e9a3a5f589b Additional header files and an example makefile for developing Oracle applications with Instant Client
  JDBC Supplement Package (ZIP) 	instantclient-jdbc-linux.x64-23.26.3.0.0.zip 1,612,442 bytes (checksum = 1945397437) SHA256 8e57710546eb03c864882b5f4620ac42ef793c1e72abdcaa277791d2433eac Additional support for Internationalization under JDBC
  JDBC Supplement Package (OL10 RPM) 	oracle-instantclient-jdbc-23.26.3.0.0-1.el10.x86_64.rpm 1,568,052 bytes (checksum = 1980679654) SHA256 b686fdc4c65dfd8ba962eab157022253ba23a0a4cb88599e8586fe1bed621bb1 Additional support for Internationalization under JDBC
  JDBC Supplement Package (OL9 RPM) 	oracle-instantclient-jdbc-23.26.3.0.0-1.el9.x86_64.rpm 1,567,990 bytes (checksum = 283845780) SHA256 6a31fbc878653bd84112585fcf5617099b91c3444f3e4f0335aa81a15ea33ea1 Additional support for Internationalization under JDBC
  JDBC Supplement Package (OL8 RPM) 	oracle-instantclient-jdbc-23.26.3.0.0-1.el8.x86_64.rpm 1,558,132 bytes (checksum = 4179845559)



Download	Details
	SHA256 32f62045940ce92450112a308f7e4611ff8b9c579d2d83db4dd1312c22d45585 • Additional support for Internationalization under JDBC
 ODBC Package (ZIP)	instantclient-odbc-linux.x64-23.26.3.0.0.zip 819,458 bytes (checksum = 3668825146) SHA256 263cfc77bbabb96484720edf17e83afb96c917d96f053ae762186f0abce6f40c • Additional libraries for enabling ODBC applications
 ODBC Package (OL10 RPM)	oracle-instantclient-odbc-23.26.3.0.0-1.el10.x86_64.rpm 268,534 bytes (checksum = 1839785146) SHA256 61496a24bf1e1a06822122bb12428f9657a367059aeae04957bd309a1d89f4fe • Additional libraries for enabling ODBC applications
 ODBC Package (OL9 RPM)	oracle-instantclient-odbc-23.26.3.0.0-1.el9.x86_64.rpm 268,666 bytes (checksum = 3566382190) SHA256 858fa0e15b3d000aa32e2fb8165ccd889f9cb11681933806958e3992dce10f40 • Additional libraries for enabling ODBC applications
 ODBC Package (OL8 RPM)	oracle-instantclient-odbc-23.26.3.0.0-1.el8.x86_64.rpm 263,212 bytes (checksum = 2234709319)



Download

Details

SHA256 04cc2677b561a47345ffbbdcf9a0bab023cd02efca3b9b2d561930ef09dfa057

- Additional libraries for enabling ODBC applications

Installation Instructions

Instant Client Installation for Linux x86-64 (64-bit)

- For general Instant Client information, see the [Home Page](#).
- ODBC users should follow the [ODBC Installation Instructions](#).
- The "Database Client Installation Guide for Linux" chapter on Installing Oracle Instant Client is [here](#).
- Instant Client RPMs are also available without click-through from [yum.oracle.com](#) for [Oracle Linux 10](#), [Oracle Linux 9](#) and [Oracle Linux 8](#). Older RPM packages are available for [Oracle Linux 9](#), [Oracle Linux 8](#), [Oracle Linux 7](#) and [Oracle Linux 6](#).

Installation of ZIP files:

1. Download the desired Instant Client ZIP files. All installations require a Basic or Basic Light package.
2. Unzip the packages into a single directory, like `/opt/oracle/instantclient_19_3`, that is accessible to your application. For example:

```
cd /opt/oracle
```

```
unzip instantclient-basic-linux.x64-19.3.0.0.0dbru.zip
```

The various packages install into subdirectories of

```
/usr/lib/oracle
```

```
/usr/include/oracle
```

```
/usr/share/oracle
```



3. Prior to version 18.3, create the appropriate links for the version of Instant Client. For example:

```
cd /opt/oracle/instantclient_12_2
ln -s libclntsh.so.12.1 libclntsh.so
ln -s libocci.so.12.1 libocci.so
```

Install the operating system libaio package. This is called `libaio1` on some Linux distributions. On Oracle Linux 8 prior to Instant Client 21 you also need the `libnsl` package. For example, on Oracle Linux, run: `sudo yum install libaio`

4. If Instant Client is the only Oracle Software installed on this system then update the runtime link path, for example:

```
sudo sh -c "echo /opt/oracle/instantclient_19_3 > \ /etc/ld.so.conf.d/oracle-instantclient.conf"
sudo ldconfig
```

Alternatively, set the `LD_LIBRARY_PATH` environment variable prior to running applications. For example:

```
export LD_LIBRARY_PATH=/opt/oracle/instantclient_19_3:$LD_LIBRARY_PATH
```

The variable can optionally be added to configuration files such as `~/.bash_profile` and to application configuration files such as `/etc/sysconfig/httpd`.

5. If you intend to co-locate optional Oracle configuration files such as `tnsnames.ora`, `sqlnet.ora`, `ldap.ora`, or `oraaccess.xml` with Instant Client, put them in the `network/admin` subdirectory. This needs to be created for 12.2 and earlier, for example:

```
mkdir -p /opt/oracle/instantclient_12_2/network/admin.
```

This is the default Oracle configuration directory for applications linked with this Instant Client. Alternatively, Oracle configuration files can be put in another, accessible directory. Then set the environment variable `TNS_ADMIN` to that directory name.

6. To use binaries such as `sqlplus` from the SQL*Plus package, unzip the package to the same directory as the Basic or the Basic Light package and then update your `PATH` environment variable, for example: `export PATH=/opt/oracle/instantclient_19_3:$PATH`

7. Start your application.

Installation of RPM files

1. Download the desired Instant Client RPM packages. All installations require a Basic or Basic Light RPM.

2. Install the packages with `yum`. For example:

```
sudo yum install oracle-instantclient19.3-basic-19.3.0.0.0-1.x86_64.rpm
```

Note that from 19.3, by default only one version of the Instant Client RPM libraries can be installed at a time.

3. Prior to 19.3, if Instant Client is the only Oracle Software installed on this system then update the runtime link path, for example:

```
sudo sh -c "echo /usr/lib/oracle/18.3/client64/lib > \ /etc/ld.so.conf.d/oracle-instantclient.conf" sudo ldconfi
```

For Instant Client 19.3 RPM packages, these commands are automatically run.



An alternative to using `ldconfig` for older versions, is to set the `LD_LIBRARY_PATH` environment variable in each shell prior to running applications. For example:

```
export LD_LIBRARY_PATH=/usr/lib/oracle/18.3/client64/lib:$LD_LIBRARY_PATH
```

The variable can optionally be added to configuration files such as `~/.bash_profile` and to application configuration files such as `/etc/sysconfig/httpd`.

4. If you intend to co-locate optional Oracle configuration files such as `tnsnames.ora`, `sqlnet.ora`, `ldap.ora`, or `oraaccess.xml` with Instant Client, put them in the `network/admin` subdirectory. This needs to be created for 12.2 and earlier, for example:

```
sudo mkdir -p /usr/lib/oracle/12.2/client64/lib/network/admin
```

This is the default Oracle configuration directory for applications linked with this Instant Client.

Alternatively, Oracle configuration files can be put in another, accessible directory. Then set the environment variable `TNS_ADMIN` to that directory name.

5. To use binaries from the tools package, use `yum` to install the package and then update your `PATH` environment variable, for example:

```
export PATH=/usr/lib/oracle/19.3/client64/bin:$PATH
```

6. Start your application.

