

Oracle Database Free

Description

Oracle AI Database 26ai Free Container Image Documentation

Oracle AI Database 26ai Free is the free edition of the industry-leading database. The Oracle AI Database 26ai Free Container Image contains Oracle AI Database 26ai Free based on an Oracle Linux 8 base image.

Two flavors of the image are supported:

1. The `Full` image: supports all the database features provided by Oracle AI Database 26ai Free.
2. The `Lite` image: smaller image size with a stripped-down installation of the database.

The `Lite` image has a smaller storage footprint than the `Full` image (~80% image size reduction) and a substantial improvement in image pull time. This image is useful in CI/CD scenarios and for simpler use cases where advanced database features are not required.

For more information on Oracle AI Database 26ai Free, see: <https://oracle.com/database/free>

Using the Full image

Starting an Oracle AI Database 26ai Free container

Short URL for Repo

```
https://container-registry.oracle.com/ords/ocr/ba/database/free
```

Other Open Source Licenses

The container image you have selected and all of the software that it contains is licensed under the Oracle Free Use Terms and Conditions which is provided in the container image. Your use of the container is subject to the terms of [Oracle Free Use Terms and Conditions license](#).

Pull Command for Latest

```
docker pull
```

container, run the following command where, `<oracle-db>` can be any custom name for the container:

```
podman run -d --name <oracle-db> container-registry.oracle.com/database/free:latest
```

When the container is started, a random password is generated for the SYS, SYSTEM and PDBADMIN users. This is termed the default password.

Note:

- Throughout this document, words enclosed within angle brackets `<it>`; `>` indicate variables in code lines.
- To change the default password, see: *"Changing the Default Password for SYS User"*
- To learn about advanced use cases, see: *"Custom Configurations"*
- This document uses `podman` as the prescribed container runtime, but using contemporary commands is also anticipated to work.
- The Oracle Enterprise Manager Database Express (OEM DB Express) is no longer supported with Oracle AI Database 26ai Free. Please use [SQL Developer](#) instead.

The Oracle AI Database is ready to use when the `STATUS` field shows `(healthy)` in the `podman ps` output.

Custom Configurations

To facilitate custom configurations, the Oracle AI Database container provides configuration parameters that you can use when starting the container. For example, this is the detailed `podman run` command supporting all custom configurations:

```
podman run --name <container name=""> \  
-P | -p <host port="">:1521 \  
-e ORACLE_PWD=<your database="" passwords=""> \  
-e ORACLE_CHARACTERSET=<your character="" set=""> \  
-e ENABLE_ARCHIVELOG=true \  
-e ENABLE_FORCE_LOGGING=true \  
-v [<host mount="" point="">:]/opt/oracle/oradata \  
container-registry.oracle.com/database/free:latest
```

Parameters:

- | | |
|----------|--|
| --name: | The name of the container (default: auto generated) |
| -P -p: | The port mapping of the host port to the container port. |

```
-e ORACLE_CHARACTERSET:
    The character set to use when creating the database (default: AL32UTF8)
-e ENABLE_ARCHIVELOG:
    To enable archive log mode when creating the database (default: true)
-e ENABLE_FORCE_LOGGING:
    To enable force logging mode when creating the database (default: true)
-v /opt/oracle/oradata
    The data volume to use for the database.
    Has to be writable by the Unix "oracle" (uid: 54321) user inside the container.
    If omitted the database will not be persisted over container recreation.
-v /opt/oracle/scripts/startup
    Optional: A volume with custom scripts to be run after database startup.
    For further details see the "Running scripts after setup and on startup" section.
-v /opt/oracle/scripts/setup
    Optional: A volume with custom scripts to be run after database setup.
    For further details see the "Running scripts after setup and on startup" section.
```

The supported configuration options are:

- **ORACLE_CHARACTERSET:**

This parameter modifies the character set of the database. This parameter is optional, and the default value is set to AL32UTF8. Please note that, this parameter will set the character set only when a new database is created i.e. a host system directory is mounted using -v option while running the image (Please refer to *Mounting Podman volume/host directory for database persistence* section).

- **ORACLE_PWD:**

This parameter modifies the password for the SYS, SYSTEM and PDBADMIN users. This parameter is optional, and the default value is randomly generated. Note: Using this option exposes the password as a container environment variable. Hence using Podman secrets as described below is recommended.

- **Podman Secrets Support:**

This option is supported only when **the Podman runtime is being used** to run the Oracle AI Database 26ai Free container image. Podman secrets is a secure mechanism of passing strings of text to the container, such as ssh-keys, or passwords. To specify the password for SYS, SYSTEM and PDBADMIN users securely, create a secret named `oracle_pwd` and a secret named `oracle_pwd_priv_key` for the key to encrypt the password. The commands are as follows:

- Generate the private and public key files

```
openssl genrsa -out key.pem
```

```
openssl rsa -in key.pem -out key.pub -pubout
```

- Create a text file with the unencrypted password
Seed password and saving the /opt/.secrets/pwdfile.txt

```
vi /opt/.secrets/pwdfile.txt
```

- Encrypt the password file using the private key generated above

```
openssl pkeyutl -in /opt/.secrets/pwdfile.txt -out /opt/.secrets/pwdfile.enc -pubin -inkey  
/opt/.secrets/key.pub -encrypt
```

```
rm -rf /opt/.secrets/pwdfile.txt
```

- Create podman secrets for the encrypted passwords and the public key generated above

```
podman secret create oracle_pwd /opt/.secrets/pwdfile.enc
```

```
podman secret create oracle_pwd_priv_key /opt/.secrets/key.pub
```

- Pass the podman secrets to the container

Pass the above created podman secrets `oracle_pwd` and `oracle_pwd_priv_key` to the container with the `--secret` option

```
podman run --name <container_name> --secret=oracle_pwd --secret=oracle_pwd_priv_key  
container-registry.oracle.com/database/free:latest
```

- **Mounting Podman volume/host directory for database persistence:**

To obtain database persistence, either a named Podman volume or a host system directory can be mounted at the location `/opt/oracle/oradata` inside the container. The difference between these two options are as follows:

1. If a **Podman volume** is mounted on the `/opt/oracle/oradata` location, then the volume is prepopulated with the data files already present in the image. In this case, the startup will be very fast, similar to starting the image without mount. These data files exist in the image to enable quick startup of the database.

To use a podman volume for the data volume, run the following:

```
container-registry.oracle.com/database/free:latest
```

2. If a **host system directory** is mounted on the `/opt/oracle/oradata` location, two things can happen :

- If the datafiles are present in the host system directory which is being mounted, then these files will overwrite the files present at `/opt/oracle/oradata` and the database startup will be very fast.
- If host system directory doesn't contain the datafiles the data files present at `/opt/oracle/oradata` will be overwritten , and **a new database setup will begin**. It takes a significant amount of time (approximately 10 minutes) to set up a fresh database.

To use a directory on the host system for the data volume, run the following:

```
$ podman run -d --name \  
-v /opt/oracle/oradata \  
container-registry.oracle.com/database/free:latest
```

Note: Cleaning up a mounted host directory can be done by changing into the directory location and executing `rm -rf * .*`

- **ENABLE_ARCHIVELOG and/or ENABLE_FORCE_LOGGING:**

These options are enabled by default in the prebuilt database image. To disable these options, execute the relevant SQL commands using SQLPlus from within the database container.

Changing the Default Password for SYS User

On the first startup of the container, a random password is generated for the database if a password is not provided by using the **-e option**, as described in the *"Custom Configurations"* section.

To change the password for these accounts, use the `podman exec` command, to run the `setPassword.sh` script that is found in the container. Note that the container must be running before you run the script.

For example:

```
podman exec <oracle-db> ./setPassword.sh <your_password>
```

Database Alert Logs

```
podman logs <oracle-db>
```

Connecting to the Oracle AI Database Free Container

After the Oracle AI Database indicates that the container has started, and the `STATUS` field shows (healthy), client applications can connect to the database.

Connecting from Within the Container

You can connect to the Oracle AI Database by running a SQL*Plus command from within the container using one of the following commands:

```
podman exec -it <oracle-db> sqlplus sys/<your_password>@FREE as sysdba
```

```
podman exec -it <oracle-db> sqlplus system/<your_password>@FREE
```

```
podman exec -it <oracle-db> sqlplus pdbadmin/<your_password>@FREEPDB1
```

Connecting from Outside the Container

By default, Oracle AI Database exposes port 1521 for Oracle client connections, using Oracle's SQL*Net protocol. SQL*Plus or any Oracle AI Database client software can be used to connect to the database from outside of the container.

To connect from outside of the container, start the container with the `-P` option, as described in the detailed Podman run command in the "Custom Configurations" section.

Discover the mapped port by running the following command:

```
podman port <oracle-db>
```

To connect from outside of the container using SQL*Plus, run the following commands:

```
# To connect to the database at the CDB$ROOT Level as sysdba:  
sqlplus sys/<your password="">@//localhost:<port mapped="" to="" 1521="">/FREE as sysdba
```

```
# To connect to the default Pluggable Database (PDB) within the FREE Database:  
sqlplus pdbname/<your password="">@//localhost:<port mapped="" to="" 1521="">/FREEPDB1
```

Reusing the Existing Database

If the database is started using a host system directory mounted at an `/opt/oracle/oradata` location inside the container, as explained in the Custom Configuration section under “*Mounting Podman volume/host directory for database persistence*”, then the data files remain persistent even after the container is destroyed. Another container with the same data files can be started by reusing the host system directory.

To reuse this directory on the host system for the data volume, run the following commands:

```
podman run -d --name <oracle-db> -v \  
    <writable_host_directory_path>:/opt/oracle/oradata \  
    container-registry.oracle.com/database/free:latest
```

Running Scripts After Setup and On Startup

The Container images can be configured to run scripts after setup and on startup. Currently, `.sh` and `.sql` extensions are supported. For post-setup scripts, mount the volume `/opt/oracle/scripts/setup` to include scripts in this directory. For post-startup scripts, mount the volume `/opt/oracle/scripts/startup` to include scripts in this directory.

After the database is set up or started, the scripts in those folders are run against the database in the container. SQL scripts are run as SYSDBA, and shell scripts are run as the current user. To ensure proper order for running scripts, Oracle recommends that you prefix your scripts with a number. For example: `01_users.sql`, `02_permissions.sql`, and so on.

Note: The setup scripts will not run in Free and Free Lite image as both comes with a pre-built database. If host mount point (empty directory) is provided, then a new database setup will start and setup scripts will run.

The following example mounts the local directory `/home/oracle/myScripts` to `/opt/oracle/scripts/startup`, which is then searched for custom startup scripts:

```
container-registry.oracle.com/database/free:latest
```

Oracle True Cache

Oracle True Cache is an in-memory, consistent, and automatically managed cache for Oracle AI Database.

Setting Up Network for Communication Between Primary Database and True Cache Container

- Oracle AI Database Free True Cache container (True Cache container) and the Oracle AI Database Free Primary Database container (Primary Database container) must be on the same podman network to communicate with each other.

Set up a podman network for inter-container communication using the following command which creates a bridge connection enabling communication between containers on the same host.

```
podman network create tc_net
```

Fetch the default subnet assigned to the preceding network by running the following command:

```
podman inspect tc_net | grep -iw 'subnet'
```

Pick any two IP addresses from the preceding subnet and assign one for the Primary Database container (say, PRI_DB_FREE_IP) and the other for the True Cache container (say, TRU_CC_FREE_IP).

For communication across hosts, create a macvlan or ipvlan connection per [documentation](#). \ Specify the preceding podman network using the `--net` option to the podman run command of both the Primary Database container and the True Cache container as shown in following sections.

Running Oracle AI Database Free True Cache in a Container

- Launch the Oracle AI Database Free Primary Database container using the `podman run` command as follows:

```
podman run -td --name pri-db-free \
--hostname pri-db-free \
```



```
-p :1521 \
-secret=oracle_pwd \
-secret=oracle_pwd_priv_key \
-add-host="tru-cc-free:" \
-e ENABLE_ARCHIVELOG=true \
-e ENABLE_FORCE_LOGGING=true \
-v [:]/opt/oracle/oradata \
container-registry.oracle.com/database/free:latest
```

Ensure that your Primary Database container is up and running and in a healthy state.

- Launch the Oracle AI Database Free True Cache container using the `podman run` command as follows:

```
podman run -td --name tru-cc-free \
--hostname tru-cc-free \
--net=tc_net \
--ip \
-p :1521 \
-secret=oracle_pwd \
-secret=oracle_pwd_priv_key \
-add-host="pri-db-free:" \
-e TRUE_CACHE=true \
-e PRIMARY_DB_CONN_STR=:1521/FREE \
-e
PDB_TC_SVCS="FREEDB1:sales1:sales1_tc;FREEDB1:sales2:sales2_tc;FREEDB1:sales3:sales3_tc;FREEDB1:sales4:sales4_tc" \
-v [:]/opt/oracle/oradata \
container-registry.oracle.com/database/free:latest
```

Note: In above command, the list of Primary and True Cache services are mentioned using the string

"FREEDB1:sales1:sales1_tc;FREEDB1:sales2:sales2_tc;FREEDB1:sales3:sales3_tc;FREEDB1:sales4:sales4_tc". The string consists of multiple entries in the format "::<" and these entries are separated by ";".

Using the Lite image

Starting an Oracle AI Database 26ai Free Lite Container

the container, run the following command where, <oracle-db> is the name of the container:

```
$ podman run -d --name <oracle-db> container-registry.oracle.com/database/free:latest-lite
```

When the container is started, a random password is generated for the SYS, SYSTEM, and PDBADMIN users. This is termed as the default password.

The Oracle AI Database is ready to use when the STATUS field shows (healthy) in the podman ps output.

Custom Configurations

To facilitate custom configurations, the Oracle AI Database container provides configuration parameters that you can use when starting the container. For example, this is the detailed podman run command supporting all custom configurations:

```
podman run --name <container name=""> \
-p <host port="">:1521 -p \
-e ORACLE_PDB=<your pdb="" name=""> \
-e ORACLE_PWD=<your database="" passwords=""> \
-v [<host mount="" point="">:]/opt/oracle/oradata \
container-registry.oracle.com/database/free:latest-lite
```

Parameters:

- name: The name of the container (default: auto generated).
- p: The port mapping of the host port to the container port.
The following ports is exposed: 1521 (Oracle Listener).
- e ORACLE_PDB: The Oracle AI Database PDB name that should be used (default: FREEPDB1).
- e ORACLE_PWD: The Oracle AI Database SYS, SYSTEM and PDB_ADMIN password (default: auto generated).
- v /opt/oracle/oradata
The data volume to use for the database.
Has to be writable by the Unix "oracle" (uid: 54321) user inside the container.
If omitted the database will not be persisted over container recreation.
- v /opt/oracle/scripts/startup
Optional: A volume with custom scripts to be run after database startup.
For further details see the "Running scripts after setup and on startup" section.

Invoking APIs to any of these features may result in errors:

- Oracle True Cache
- Oracle XML DB
- Oracle Database Multilingual Engine (MLE)
- Oracle Secure Backup (OSB)
- Oracle Memory Speed (OMS)
- Oracle SQL access to Kafka
- Oracle File Mapping (ORAMAP)
- Online Analytical Processing (OLAP)
- Oracle DBNest
- Oracle Database File System (DBFS)
- Oracle Heterogeneous Services
- Oracle Internet Directory
- Oracle External Job Scheduler
- Non-Volatile Memory (NVM) support
- Oracle Data Pump
- Oracle Summary Advisor
- Oracle Notifications service (ONS)
- Oracle Embedded R Execution
- Oracle I/O Numbers
- PL/SQL Server Pages (PSP)
- PL/SQL Hierarchical Profiler
- PLSQL Native Compilation
- Oracle Text - Knowledge Base Extension Compiler
- Oracle Text - Lexical Compiler
- Oracle Text Lexers - Only BASIC_LEXER Type is supported

Availability/Scalability Features

- Oracle Sharding
- Oracle Recovery Manager (RMAN)

Diagnostic Features

- Autonomous Health Framework (AHF)
- Automatic Diagnostic Repository
- Oracle Trace File Analyzer

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <https://www.oracle.com/corporate/accessibility/>.

Oracle AI Database 26ai Free Container Image Documentation

Copyright © 2005, 2022, 2025 Oracle and/or its affiliates.

Oracle Free Use Terms and Conditions

Definitions

"Oracle" refers to Oracle America, Inc. "You" and "Your" refers to (a) a company or organization (each an "Entity") accessing the Programs, if use of the Programs will be on behalf of such Entity; or (b) an individual accessing the Programs, if use of the Programs will not be on behalf of an Entity.

"Program(s)" refers to Oracle software provided by Oracle pursuant to the following terms and any updates, error corrections, and/or Program Documentation provided by Oracle. "Program Documentation" refers to Program user manuals and Program installation manuals, if any. If available, Program Documentation may be delivered with the Programs and/or may be accessed from www.oracle.com/documentation. "Separate Terms" refers to separate license terms that are specified in the Program Documentation, readmes or notice files and that apply to Separately Licensed Technology. "Separately Licensed Technology" refers to Oracle or third party technology that is licensed under Separate Terms and not under the terms of this license.

Separately Licensed Technology

Oracle may provide certain notices to You in Program Documentation, readmes or notice files in connection with Oracle or third party technology provided as or with the Programs. If specified in the Program Documentation, readmes or notice files, such technology will be licensed to You under Separate Terms.

Your rights to use Separately Licensed Technology under Separate Terms are not restricted in any way by the terms herein. For clarity, notwithstanding the existence of a notice, third party technology that is not Separately Licensed Technology shall be deemed part of the Programs licensed to You under the terms of this license.

Source Code for Open Source Software

the applicable source code from <https://oss.oracle.com/sources/> or <https://www.oracle.com/goto/opensourcecode>.

If the source code for such software was not provided to You with the binary, You can also receive a copy of the source code on physical media by submitting a written request pursuant to the instructions in the "Written Offer for Source Code" section of the latter website.

The following license terms apply to those Programs that are not provided to You under Separate Terms.

License Rights and Restrictions

Oracle grants to You, as a recipient of this Program, a nonexclusive, nontransferable, limited license to, subject to the conditions stated herein, (a) internally use the unmodified Programs for the purposes of developing, testing, prototyping and demonstrating your applications, and running the Programs for your own internal business operations; and (b) redistribute unmodified Programs and Programs Documentation, under the terms of this License, provided that You do not charge Your end users any additional fees for the use of the Programs. You may make copies of the Programs to the extent reasonably necessary for exercising the license rights granted herein and for backup purposes. You are granted the right to use the Programs to provide third party training in the use of the Programs and associated Separately Licensed Technology only if there is express authorization of such use by Oracle on the Program's download page or in the Program Documentation.

Your license is contingent on Your compliance with the following conditions:

- * You include a copy of this license with any distribution by You of the Programs;
- * You do not remove markings or notices of either Oracle's or a licensor's proprietary rights from the Programs or Program Documentation;
- * You comply with all U.S. and applicable export control and economic sanctions laws and regulations that govern Your use of the Programs (including technical data);
- * You do not cause or permit reverse engineering, disassembly or decompilation of the Programs (except as allowed by law) by You nor allow an associated party to do so.

For clarity, any source code that may be included in the distribution with the Programs is provided solely for reference purposes and may not be modified, unless such source code is under Separate Terms permitting modification.

Ownership

The Programs' installation and/or auto-update processes, if any, may transmit a limited amount of data to Oracle or its service provider about those processes to help Oracle understand and optimize them. Oracle does not associate the data with personally identifiable information. Refer to Oracle's Privacy Policy at www.oracle.com/privacy.

Disclaimer of Warranties; Limitation of Liability

THE PROGRAMS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND. ORACLE FURTHER DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW WILL ORACLE BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Last updated: 10 October, 2025

🔍 Search Tag Name

Tags

Download Mirror

Default



Tag	OS/Architecture	Size	Pull Command	Last Updated	Image ID
latest-lite	linux/arm64	786.81 MB	docker pull container-registry.oracle.com/database/free:latest-lite	2 months ago	eb56b0029432

23.26.2.0-lite-arm64	linux/arm64	786.81 MB	docker pull container-registry.oracle.com/database/free:23.26.2.0-lite-arm64	2 months ago	eb56b0029432
23.26.2.0-lite	linux/arm64	786.81 MB	docker pull container-registry.oracle.com/database/free:23.26.2.0-lite	2 months ago	eb56b0029432
latest	linux/arm64	3.25 GB	docker pull container-registry.oracle.com/database/free:latest	2 months ago	e380148ec436
23.26.2.0-arm64	linux/arm64	3.25 GB	docker pull container-registry.oracle.com/database/free:23.26.2.0-arm64	2 months ago	e380148ec436
23.26.2.0	linux/arm64	3.25 GB	docker pull container-registry.oracle.com/database/free:23.26.2.0	2 months ago	e380148ec436
latest-lite	linux/amd64	848.22 MB	docker pull container-registry.oracle.com/database/free:latest-lite	3 months ago	9251985d10da
23.26.2.0-lite-amd64	linux/amd64	848.22 MB	docker pull container-registry.oracle.com/database/free:23.26.2.0-lite-amd64	3 months ago	9251985d10da
23.26.2.0-lite	linux/amd64	848.22 MB	docker pull container-registry.oracle.com/database/free:23.26.2.0-lite	3 months ago	9251985d10da
latest	linux/amd64	3.38 GB	docker pull container-registry.oracle.com/database/free:latest	3 months ago	8dfd189f9fd7
23.26.2.0-amd64	linux/amd64	3.38 GB	docker pull container-registry.oracle.com/database/free:23.26.2.0-amd64	3 months ago	8dfd189f9fd7
23.26.2.0	linux/amd64	3.38 GB	docker pull container-registry.oracle.com/database/free:23.26.2.0	3 months ago	8dfd189f9fd7
23.26.1.0-arm64	linux/arm64	3.48 GB	docker pull container-registry.oracle.com/database/free:23.26.1.0-arm64	6 months ago	b129f74fa818
23.26.1.0	linux/arm64	3.48 GB	docker pull container-registry.oracle.com/database/free:23.26.1.0	6 months ago	b129f74fa818
23.26.1.0-lite-arm64	linux/arm64	776.24 MB	docker pull container-registry.oracle.com/database/free:23.26.1.0-lite-arm64	6 months ago	961db65ca528

row(s) 1 - 15 of 36 ▼

Next ►