

Tuples

Chapter 10

Tuples are like lists

- Tuples are another kind of sequence that functions much like a list - they have elements which are indexed starting at 0

```
>>> x = ('Glenn', 'Sally', 'Joseph')
>>> print x[2]
Joseph
>>> y = ( 1, 9, 2 )
>>> print y
(1, 9, 2)
>>> print max(y)
9
```

```
>>> for iter in y:
...     print iter
...
1
9
2
>>>
```

but... Tuples are “immutable”

- Unlike a list, once you create a tuple, you cannot alter its contents - similar to a string

```
>>> x = [9, 8, 7]
>>> x[2] = 6
>>> print x
>>> [9, 8, 6]
>>>
```

```
>>> y = 'ABC'
>>> y[2] = 'D'
Traceback: 'str'
object does
not support item
Assignment
>>>
```

```
>>> z = (5, 4, 3)
>>> z[2] = 0
Traceback: 'tuple'
object does
not support item
Assignment
>>>
```

Things not to do with tuples

```
>>> x = (3, 2, 1)
```

```
>>> x.sort()
```

```
Traceback:
```

```
AttributeError: 'tuple' object has no attribute 'sort'
```

```
>>> x.append(5)
```

```
Traceback:
```

```
AttributeError: 'tuple' object has no attribute 'append'
```

```
>>> x.reverse()
```

```
Traceback:
```

```
AttributeError: 'tuple' object has no attribute 'reverse'
```

```
>>>
```

A Tale of Two Sequences

```
>>> l = list()
>>> dir(l)
['append', 'count', 'extend', 'index', 'insert', 'pop',
 'remove', 'reverse', 'sort']
```

```
>>> t = tuple()
>>> dir(t)
['count', 'index']
```

Tuples are more efficient

- Since Python does not have to build tuple structures to be modifiable, they are simpler and more efficient in terms of memory use and performance than lists
- So in our program when we are making “temporary variables” we prefer tuples over lists

Tuples and Assignment

- We can also put a **tuple** on the **left-hand side** of an assignment statement
- We can even omit the parentheses

```
>>> (x, y) = (4, 'fred')
>>> print y
fred
>>> (a, b) = (99, 98)
>>> print a
99
```

Tuples and Dictionaries

- The `items()` method in dictionaries returns a list of (key, value) tuples

```
>>> d = dict()
>>> d['csev'] = 2
>>> d['cwen'] = 4
>>> for (k,v) in d.items():
...     print k, v
...
csev 2
cwen 4
>>> tups = d.items()
>>> print tups
[('csev', 2), ('cwen', 4)]
```


Tuples are Comparable

- The comparison operators work with tuples and other sequences. If the first item is equal, Python goes on to the next element, and so on, until it finds elements that differ.

```
>>> (0, 1, 2) < (5, 1, 2)
```

```
True
```

```
>>> (0, 1, 2000000) < (0, 3, 4)
```

```
True
```

```
>>> ( 'Jones', 'Sally' ) < ( 'Jones', 'Sam' )
```

```
True
```

```
>>> ( 'Jones', 'Sally' ) > ( 'Adams', 'Sam' )
```

```
True
```

Sorting Lists of Tuples

- We can take advantage of the ability to sort a list of **tuples** to get a sorted version of a dictionary
- First we sort the dictionary by the key using the **items()** method

```
>>> d = {'a':10, 'b':1, 'c':22}
>>> t = d.items()
>>> t
[('a', 10), ('c', 22), ('b', 1)]
>>> t.sort()
>>> t
[('a', 10), ('b', 1), ('c', 22)]
```

Using sorted()

We can do this even more directly using the built-in function `sorted` that takes a sequence as a parameter and returns a sorted sequence

```
>>> d = {'a':10, 'b':1, 'c':22}
>>> d.items()
[('a', 10), ('c', 22), ('b', 1)]
>>> t = sorted(d.items())
>>> t
[('a', 10), ('b', 1), ('c', 22)]
>>> for k, v in sorted(d.items()):
...     print k, v
...
a 10
b 1
c 22
```

Sort by values instead of key

- If we could construct a list of **tuples** of the form **(value, key)** we could **sort** by value
- We do this with a **for** loop that creates a list of tuples

```
>>> c = {'a':10, 'b':1, 'c':22}
>>> tmp = list()
>>> for k, v in c.items():
...     tmp.append( (v, k) )
...
>>> print tmp
[(10, 'a'), (22, 'c'), (1, 'b')]
>>> tmp.sort(reverse=True)
>>> print tmp
[(22, 'c'), (10, 'a'), (1, 'b')]
```

```
fhand = open('romeo.txt')
counts = dict()
for line in fhand:
    words = line.split()
    for word in words:
        counts[word] = counts.get(word, 0 ) + 1

lst = list()
for key, val in counts.items():
    lst.append( (val, key) )

lst.sort(reverse=True)

for val, key in lst[:10] :
    print key, val
```

The top 10 most
common words

Even Shorter Version

```
>>> c = {'a':10, 'b':1, 'c':22}
```

```
>>> print sorted( [ (v,k) for k,v in c.items() ] )
```

```
[(1, 'b'), (10, 'a'), (22, 'c')]
```

List comprehension creates a dynamic list. In this case, we make a list of reversed tuples and then sort it.

<http://wiki.python.org/moin/HowTo/Sorting>

Summary

- Tuple syntax
- Immutability
- Comparability
- Sorting
- Tuples in assignment statements
- Sorting dictionaries by either key or value



Acknowledgements / Contributions



These slides are Copyright 2010- Charles R. Severance (www.dr-chuck.com) of the University of Michigan School of Information and open.umich.edu and made available under a Creative Commons Attribution 4.0 License. Please maintain this last slide in all copies of the document to comply with the attribution requirements of the license. If you make a change, feel free to add your name and organization to the list of contributors on this page as you republish the materials.

Initial Development: Charles Severance, University of Michigan School of Information

... Insert new Contributors and Translators here

...