



For the LTC4361 (per datasheet page 5):  
 $R_{SENSE} = (0.05V) / I_{SENSE}$

5V Current Limit:  
 Max Power = 0.5W (good for experiment safety)  
 Max Current (at 5V) =  $0.5W / 5V = 0.1A$   
 $R_{SENSE} = 0.05V / I_{MAX} = 0.05V / 0.1A = 0.5 \text{ ohms}$




(Auto-Retry on overcurrent [-2 model])



3V3 Current Limit:  
 Max Power = 2W (a little over the 1.75W max)  
 Max Current (at 3V3) =  $2W / 3V3 = 0.61A$   
 $R_{SENSE} = 0.05V / I_{MAX} = 0.05V / 0.61A = 0.081 \text{ ohms}$


0.075 ohms => 0.66A => 2.2W



Step-Up Converter  
 0.1S7B\_0512S3UP (5V -> 12V) [max 84 mA]

C206 should be 4kVDC  
 Vishay HGZ102MBP  
 TDK CD45-E2GA102M-GKA  
 (Plugin Suppression)

TODO switch to one of these if we can order one





Sheet: /PowerSheet/  
 File: PowerSheet.kicad\_sch

Title:

Size: USLetter Date:  
 KiCad E.D.A. kicad 7.0.5

Rev:  
 Id: 2/10






Sheet: /MicrocontrollerSheet/  
File: MicrocontrollerSheet.kicad\_sch

# Title:

Size: USLetter Date:  
KiCad E.D.A. kicad 7.0.5

Rev:  
Id: 4/10




Sheet: /RF\_System/  
File: RF\_System.kicad\_sch

# **Title:**

Size: USLetter    Date:  
KiCad E.D.A.    kicad 7.0.5

**Rev:**  
Id: 5/10






Sheet: /PINDiodeExperiment2/  
File: PINDiodeExperiment.kicad\_sch

**Title:**

Size: USLetter	Date:	Rev:
KiCad E.D.A. kicad 7.0.5		Id: 7/10




Sheet: /PINDiodeExperiment3/  
File: PINDiodeExperiment.kicad\_sch

**Title:**

Size: USLetter	Date:	Rev:
KiCad E.D.A. kicad 7.0.5		Id: 8/10





Sheet: /PINDiodeExperiment4/  
File: PINDiodeExperiment.kicad\_sch

**Title:**

Size: USLetter	Date:	Rev:
KiCad E.D.A. kicad 7.0.5		Id: 9/10

