

1 · JavaScript

saída:

```
false
9007199254740992
```

quando: nunca

2 · Python

saída:

```
4 6
```

quando: nunca

3 · Go

saída: 0

quando: nunca

4 · Java

saída:

```
Main.java:6: error: <identifier> expected
System.out.println(v[0]);
                  ^
Main.java:6: error: ']' expected
System.out.println(v[0]);
                  ^
Main.java:8: error: <identifier> expected
System.out.println(v[3]);
                  ^
Main.java:8: error: ']' expected
System.out.println(v[3]);
                  ^
4 errors
```

quando: execução

5 · Rust

saída:

```
error[E0382]: borrow of moved value: `s`
  --> HelloWorld.rs:6:19
   |
   |
2  |     let s = String::from("oi");
   |         - move occurs because `s` has type `String`, which does not implement the `Copy` trait
3  |
4  | let t = s;
   |         - value moved here
5  |
6  | println!("{}", s, t);
   |               ^ value borrowed here after move
   |
help: consider cloning the value if the performance cost is acceptable
   |
4  | let t = s.clone();
   |         +++++++
```

error: aborting due to 1 previous error

For more information about this error, try `rustc --explain E0382`.

quando: compilação

6 · C

saída: 1065353216

quando: nunca