

Thickness: **1.6MM**      Finished Outer Copper: **10Z**      Inner Copper: **10Z**      Inner layer Residual copper ratio: **70%**

|  |  |  |  | Layer | Material                | Thickness (mm) | Thickness after lamination(mm) |
|--|--|--|--|-------|-------------------------|----------------|--------------------------------|
|  |  |  |  | L1-CU | Outer Base Copper 0.5OZ | 0.0175         | 0.0175 (Plating to 10Z)        |
|  |  |  |  | PP    | 2116 RC58% DK:4.45      | 0.1300         | 0.1195                         |
|  |  |  |  | L2-CU | Inner Copper 10Z        | 0.0350         | 0.5 (Core with Cu)             |
|  |  |  |  | CORE  | Core DK:4.6             | 0.4300         |                                |
|  |  |  |  | L3-CU | Inner Copper 10Z        | 0.0350         |                                |
|  |  |  |  | PP    | 7628 RC46% DK:4.74      | 0.1960         | 0.1750                         |
|  |  |  |  | L4-CU | Inner Copper 10Z        | 0.0350         | 0.5 (Core with Cu)             |
|  |  |  |  | CORE  | Core DK:4.6             | 0.4300         |                                |
|  |  |  |  | L5-CU | Inner Copper 10Z        | 0.0350         |                                |
|  |  |  |  | PP    | 2116 RC58% DK:4.45      | 0.1300         | 0.1195                         |
|  |  |  |  | L6-CU | Outer Base Copper 0.5OZ | 0.0175         | 0.0175 (Plating to 10Z)        |

L1-CU

PP

L2-CU

CORE

L3-CU

PP

L4-CU

CORE

L5-CU

PP

L6-CU