

### 蓝牙天线设计指南

Latest Version: 1.0

2016-04-26



1	目 录	2
2	版本历史	3
3	RF布局	4
	· RF布线	
	5 常用天线设计及选型	
	<b>5.1</b> 陶瓷天线	6
	5.2 板载PCB天线	6
6	5 天线匹配	8
	<b>吉 明</b>	




# 2 版本历史

日期	版本号	注释	作者
2016-04-26	V1.0	建立初始版本	han
2016-05-25	V1.1	语句及错字更正	ChenZhiPing




# 3 RF 布局

- (1) 在 PCB 设计时优先考虑蓝牙 RF 布局及布线。
- (2)为保证良好的天线性能,原则上天线周围 1cm 内不能有金属物体,金属物体包括: USB 接口、按键、焊接线等。蓝牙耳机空间小,但是也需要遵守天线远离金属物体的原则,在 PCB 设计时需要考虑这点,否则即使天线匹配好效果可能还是不理想。
  - (3) 天线位置预留足够的净空区域。如图(1)中d1约为2mm。
  - (4) 天线边上 GND 要完整,且每小于 100mil 的间隔就要有一个过孔,如图 (1) 所示。天线地要远离高频电路的地,如天线参考地避免靠近晶振 GND。



图(1)天线参考地

(**5**) 匹配网络元件应尽量靠近天线放置,并且元件需紧靠,如图(2)所示。





图(2) 匹配网络位置

# 4 RF 布线

- (**1**) **RF** 走线要在表层,避免走线上打过孔,走线正下方要有完整的地作为 参考,参考地不能被分割。
- (2) RF 走线尽量走直线,且越短越好,拐弯时不能采用直角,需要采用弧线,减少损耗。
- (3) RF 走线的阻抗需要控制为 50R,阻抗可以通过调整线宽、PCB 板厚、铜厚来达到 50R,这部分需求须与 PCB 生产工程师沟通。
- (4) RF 走线周围需要有完整的地,且每小于 **100mil** 的间隔要有地过孔,保证地的一致性,如图(**3**)所示。




图 (3) RF 走线两边有 GND 过孔

# 5 常用天线设计及选型

天线设计及选型需要根据 PCB 的净空区、成本、及 RF 性能要求来综合考虑。对于天线净空区域很小的 PCB 应优先考虑使用陶瓷天线,对于有足够净空区域来布局板载天线的可以使用板载天线以节约成本。



### **5.1** 陶瓷天线

- (**1**)陶瓷天线的选型需要考虑到天线的增益,一般来讲,面积越大增益和效率越好。反之,天线越小增益及效率越差,越容易受外围影响。综合体现出来的效果是方向性及距离差。
- (**2**)使用陶瓷天线设计时应根据规格书要求来设计。图(**4**)是某一陶瓷天线的设计要求,其要求在陶瓷天线后还要走一段线,这些地方都需要注意。





图 (4) 某陶瓷天线设计规格

### 5.2 板载 PCB 天线

(**1**) 蛇形天线,天线的参考规格如下图所示,注意天线参考地需完整,该天线可使用在有足够净空区的 **PCB** 上。





图(5)蛇形天线






图 (6) 倒 F 天线

对于空间有限的 PCB,可以对天线做变形处理,但要尽量满足 **1/4** 波长的要求,长度为 **32mm**。如图(**6**)所示。如果天线长度不够,RF 性能会变差。变形后的天线增益及方向性需要实测样机调试,通过不断调整达到最好增益及效率。








### 图 (6) 蛇形天线变形

图(7)倒F天线变形

# 6 天线匹配

天线匹配的目的是使天线的特征阻抗接近50欧姆,减小插入损耗。

天线匹配可通过调整匹配网络的参数,例如改变匹配网络中的电感和电容值,使 **S11** 驻波比 **VSWR** 小于 **2**,**S11** 回波损耗小于-**10dB**。天线匹配需要考虑 **PCB** 外围器件、机壳对天线的影响,入耳式耳机还需要考虑人体对天线谐振点的影响。天线匹配需要在产品的真实使用环境中调试,这样调试的结果才有实际的应用意义。



图(8) 匹配网络






图 (9) 天线 S11 参数

**S11** 参数需要使用网络分析仪去调试。如果没有设备就只能通过改变匹配网络参数,然后实际测试通讯距离来衡量匹配程度。良好的天线匹配可以提高通讯距离。



### 7 声 明

#### **Disclaimer**

Information given in this document is provided just as a reference or example for the purpose of using Actions' products, and cannot be treated as a part of any quotation or contract for sale.

Actions products may contain design defects or errors known as anomalies or errata which may cause the products' functions to deviate from published specifications. Designers must not rely on the instructions of Actions' products marked "reserved" or "undefined". Actions reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them.

ACTIONS DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, INCLUDING WITHOUT LIMITATION ANY AND ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, ACCURACY, SECURITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY AND THE LIKE TO THE INFORMATON OF THIS DOCUMENT AND ACTIONS PRODUCTS.

IN NO EVENT SHALL ACTIONS BE LIABLE FOR ANY DIRECT, INCIDENTAL, INDIRECT, SPECIAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES WHATSOEVER, INCLUDING, WITHOUT LIMITATION FOR LOST OF DATA, PROFITS, SAVINGS OR REVENUES OF ANY KIND ARISING FROM USING THE INFORMATON OF THIS DOCUMENT AND ACTIONS PRODUCTS. REGARDLESS OF THE FORM OF ACTION, WHETHER BASED ON CONTRACT; TORT; NEGLIGENCE OF ACTIONS OR OTHERS; STRICT LIABILITY; OR OTHERWISE; WHETHER OR NOT ANY REMEDY OF BUYER IS HELD TO HAVE FAILED OF ITS ESSENTIAL PURPOSE, AND WHETHER ACTIONS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR NOT.

Actions' products are not designed, intended, authorized or warranted for use in any life support or other application where product failure could cause or contribute to personal injury or severe property damage. Any and all such uses without prior written approval of an Officer of Actions and further testing and/or modification will be fully at the risk of the customer.

#### Ways of obtaining information

Copies of this document and/or other Actions product literature, as well as the Terms and Conditions of Sale Agreement, may be obtained by visiting Actions' website at: <a href="http://www.actions-semi.com">http://www.actions-semi.com</a> or from an authorized Actions representative.

#### **Trademarks**



The word "Actions" and the logo are the trademarks of Actions Semiconductor Co., Ltd, and Actions (Zhuhai) Technology Co., Limited is authorized to use them. Word "炷芷" is the trademark of Actions (Zhuhai) Technology Co., Limited. Names and brands of other companies and their products that may from time to time descriptively appear in this document are the trademarks of their respective holders, no affiliation, authorization, or endorsement by such persons are claimed or implied except as may be expressly stated therein.

### **Rights Reserved**

The provision of this document shall not be deemed to grant buyers any right in and to patent, copyright, trademark, trade secret, know how, and any other intellectual property of Actions or others.

#### Miscellaneous

Information contained or described herein relates only to the Actions products and as of the release date of this publication, abrogates and supersedes all previously published data and specifications relating to such products provided by Actions or by any other person purporting to distribute such information.

Actions reserves the rights to make changes to information described herein at any time without notice. Please contact your Actions sales representatives to obtain the latest information before placing your product order.

### **Additional Support**

Additional products and company information can be obtained by visiting the Actions website at: <a href="http://www.actions-semi.com">http://www.actions-semi.com</a>

### 支持:

如欲获得公司及产品的其它信息,欢迎访问我公司的网站: http://www.actions-semi.com



### 炬芯 (珠海) 科技有限公司

地址: 珠海市唐家湾镇高新区科技四路 1号 1#厂房一层 C区

电话: +86-756-3392353 传真: +86-756-3392251

邮政编码: 519085

网址: http://www.actions-semi.com

电子邮件 (业务): mp-sales@actions-semi.com

(技术支持): mp-cs@actions-semi.com