ATS2823 Bluetooth Module SPEC

Latest Version: 1.1

2015-10-26

Declaration

Disclaimer

Information given in this document is provided just as a reference or example for the purpose of using Actions' products, and cannot be treated as a part of any quotation or contract for sale.

Actions products may contain design defects or errors known as anomalies or errata which may cause the products' functions to deviate from published specifications. Designers must not rely on the instructions of Actions' products marked "reserved" or "undefined". Actions reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them.

ACTIONS DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, INCLUDING WITHOUT LIMITATION ANY AND ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, ACCURACY, SECURITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY AND THE LIKE TO THE INFORMATON OF THIS DOCUMENT AND ACTIONS PRODUCTS.

IN NO EVENT SHALL ACTIONS BE LIABLE FOR ANY DIRECT, INCIDENTAL, INDIRECT, SPECIAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES WHATSOEVER, INCLUDING, WITHOUT LIMITATION FOR LOST OF DATA, PROFITS, SAVINGS OR REVENUES OF ANY KIND ARISING FROM USING THE INFORMATON OF THIS DOCUMENT AND ACTIONS PRODUCTS. REGARDLESS OF THE FORM OF ACTION, WHETHER BASED ON CONTRACT; TORT; NEGLIGENCE OF ACTIONS OR OTHERS; STRICT LIABILITY; OR OTHERWISE; WHETHER OR NOT ANY REMEDY OF BUYER IS HELD TO HAVE FAILED OF ITS ESSENTIAL PURPOSE, AND WHETHER ACTIONS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR NOT.

Actions' products are not designed, intended, authorized or warranted for use in any life support or other application where product failure could cause or contribute to personal injury or severe property damage. Any and all such uses without prior written approval of an Officer of Actions and further testing and/or modification will be fully at the risk of the customer.

Ways of obtaining information

Copies of this document and/or other Actions product literature, as well as the Terms and Conditions of Sale Agreement, may be obtained by visiting Actions' website at: http://www.actions-semi.com or from an authorized Actions representative.

Trademarks

The word "Actions" and the logo are the trademarks of Actions Semiconductor Co., Ltd, and Actions (Zhuhai) Technology Co., Limited is authorized to use them. Word "炬芯" is the trademark of Actions (Zhuhai) Technology Co., Limited. Names and brands of other companies and their products that may from time to time descriptively appear in this document are the trademarks of their respective holders, no affiliation, authorization, or endorsement by such persons are claimed or implied except as may be expressly stated therein.

Rights Reserved

The provision of this document shall not be deemed to grant buyers any right in and to patent, copyright, trademark, trade secret, know how, and any other intellectual property of Actions or others.

Miscellaneous

Information contained or described herein relates only to the Actions products and as of the release date of this publication, abrogates and supersedes all previously published data and specifications relating to such products provided by Actions or by any other person purporting to distribute such information.

Actions reserves the rights to make changes to information described herein at any time without notice. Please contact your Actions sales representatives to obtain the latest information before placing your product order.

Additional Support

Additional products and company information can be obtained by visiting the Actions website at: http://www.actions-semi.com

List of Contents

Features

- 104 MHz MIPS32 Processor and 180 MHz DSP
- Internal ROM and serial flash memory interface supporting randomizer
- Internal RAM for data and program
- Built-in high performance stereo 24 bit DAC & ADC
- Supports Digital microphones, single-ended Analog microphones and full difference microphone
- Built-in stereo PA for headphone and differential audio output for speaker PA
- Bluetooth V4.2 compatible with Bluetooth V4.1/V4.1 BLE, V3.0, V2.1 systems
- Bluetooth fast AGC control to improve receiving dynamic range
- Supports AFH to dynamically detect channel quality to improve Bluetooth transmission quality
- Support SD/MMC/eMMC card interface for upgrade software
- SPI Nor Flash interface
- Audio Interfaces: SPDIF TX
- Serial Interfaces: UART, SPI
- Infrared Remote controller supported
- Integrated PMU supports multiple low energy States
- Integrated Linear battery charger up to 600mA charging current
- PCB Dimension: 15.9mm (L) × 13.7mm (W) × 0.8mm (H)

ATS2823 Bluetooth Module

Bluetooth Audio Solution

Low Power Solution for Portable&Wireless Audio Applications Speaker and Headphone

MIPS + DSP Dual-core Single-chip Bluetooth V4.2

Revision V1.0



ATS2823 provides wireless and local high quality music and support wireless calls with low power and BOM, making it competitive at high-end Bluetooth audio products market. Above all, ATS2823 delivers a true “ALL-IN-ONE” solution; it is the ideal choice for Single-chip wireless and audio application

Applications

- Stereo headsets and headphones
- Portable stereo speakers and speakerphones
- Bluetooth car audio unit
- Bluetooth sound bar

More Information please visit:
http://www.actions-semi.com

Application Diagram



Specifications

Operating Frequency Band	2.4GHz ~ 2.48GHz unlicensed ISM band
Bluetooth Specification	V2.1+EDR/V3.0/V4.0/ V4.1/V4.1 BLE/V4.2
Bluetooth Protocol	A2DP,AVRCP,HFP,SPP BAS,DIS,FMP,HRP,HRS,HTP,HTS,IAS,LLS
Output Power Class	Class 2
Operating Voltage	Core :1.2V, IO:3.3V, BAT:3.4V~4.2V
Operating temperate range	-10 ℃ ~ +70 ℃
External Interface	UART,SPI,IR, DMIC, SPDIF TX

Electrical Characteristics

Absolute Maximum Ratings				
Parameter	**Symbol**	**Min**	**Max**	**Unit**
Temperature	Storage temperature (Tstg)	-55	+150	°C
ESD Stress voltage	VESD (Human body model)	2000	-	V
Supply Voltage	DC5V	-0.3	9.0	V
	BAT	-0.3	5.0	V
	VCC/AVCC/BTVCC	-0.3	3.6	V
	VDD	-0.3	1.32	V
Input Voltage	3.3V IO	-0.3	3.6	V
	1.2V IO	-0.3	1.32	V

Recommended Power Supply				
Supply Voltage	**Min**	**Typ**	**Max**	**Unit**
BAT (Li)	3.4	3.8	4.3	V
DC5V	4.5	5.0	7.0	V
VCC/AVCC/BTVCC	2.8	3.1	3.4	V
VD15	1.0	1.5	1.7	V
VDD/RTCVDD	1.08	1.2	1.32	V
VD12	0.8	1.05	1.5	V

Regulators Maximum Output Current		
Block Name	**Output Voltage**	**Load Capacity**
VCC	2.7V ~ 3.4V	300mA
VDD	0.8V ~ 1.32V	100mA
VD15	1.0V ~ 1.7V	170mA
BTVCC	2.8V ~ 3.5V	100mA
AVCC	VCC – 0.15V	50mA@98%

Note: The output voltages are precisely within ±2%, providing large currents with a significantly small dropout voltage within ±5%.

AUDIO Features

Test Condition: Power BAT=3.8V, Analog audio output AOUTL/R, Load = 10K ohm,
BW=20Hz ~ 20 KHz, A-Weight. Test equipment: AP2700.

Audio Codec	DAC/ADC Sampling rate	Max : 48K Typical : 44.1K Min : 8K
Audio performance DAC (0Hz/1KHz,A weight)	Output Level	Max : 960mVrms Typical : 940 mVrms
	Ground Noise	Max : 10 uV Typical : 7 uV
	DAC SNR	Max : 101dB Typical : 98dB
	DAC THD+N	Min: -87dB Typical : -85 dB
	Dynamic Range	Max : 101 dB Typical : 98dB
	Crosstalk	Min : -100 dB Typical : -96dB
	Frequency Response	20Hz ~20KHz
Audio performance ADC (0Hz/1KHz,A weight)	Input Level THD+N <1%	Max : 980mVrms Min : --
	Ground Noise	Max : 40 uVrms Typical : 30 uVrms
	ADC SNR	Max : 90 dB Typical : 87 dB
	ADC THD+N	Min : -82dB Typical : -80 dB
	Dynamic Range	Max : 85 dB Typical : 82dB
	Crosstalk	Min : -85 dB Typical : -82dB
	Frequency Response	20Hz ~20KHz

DAC/ADC audio output performance chart:

Line in Input Mode:



Line in Input player: 1KHz Sin wave FFT 20Hz ~ 20 KHz



Line in Input player: 0KHz FFT 20Hz ~ 20 KHz



Line in Input Player: Frequency Response 20Hz ~ 20 KHz



Line in Input player: THD+N Distortion 20Hz ~ 20 KHz

Bluetooth Player Music Mode:



Bluetooth A2DP Player: 1KHz Sin wave FFT 20Hz ~ 20 KHz



Bluetooth A2DP Player: 0Hz FFT 20Hz ~ 20 KHz



Bluetooth A2DP Player: Frequency Response 20Hz ~ 20 KHz



Bluetooth A2DP Player: THD+N Distortion 20Hz ~ 20 KHz

RF Characteristics

Test conditions:

1. BAT=3.8V, VCC=3.1V, VDD=1.2V, Tamb=25℃.
2. BLE ON, SPP OFF, Scan time:1.28S, DAE OFF, No Load.

BT Protocols	A2DP/AVRCP/HFP /SPP	A2DP1.3
		AVRCP1.6
		HFP1.7
		SPP1.2
Power Consumption	A2DP	Typical : 21mA
	HFP	Typical : 26mA
	Sniff	Typical : 0.6mA
	Standby	Typical : 38uA
Distance	A2DP	Max:50M Typical : 20M
	HFP	Max : 20M Typical : 10M

Basic Data Rate of Transmitter					
Core Supply Voltage = 1.05V @ Tamb=25℃					
Parameter	**Condition**	**Min.**	**Typ.**	**Max.**	**Unit**

Maximum RF Transmit Power			2	4	dBm
RF Power Control Range		2	3	8	dB
20dB Bandwidth for Modulated Carrier			930	990	KHz
Adjacent Channel Transmit	+2 MHz	-47	-52		dBm
	-2 MHz	-51	-52		dBm
	+3 MHz	-40	-58		dBm
	-3 MHz	-56	-57		dBm
Frequency Deviation	Δf1avg Maximum	140	170	175	KHz
	Δf2max Maximum	100%	100%		
	Δf1avg/Δf2avg	0.89	0.9	0.91	
Initial Carrier Frequency Tolerance		3	5	6	KHz
Frequency Drift	HD1 Packet	-9	-8	8	KHz
	HD3 Packet	-8	-9	-10	KHz
	HD5 Packet	-10	-7	-6	KHz
Frequency Drift Rate		3	4	5	KHz/50us
Harmonic Content			-50		dBm

Enhanced Data Rate of Transmitter

Core Supply Voltage =1. 05V @ Tamb=25℃

Parameter	Condition	Min.	Typ.	Max.	Unit
Relative Transmit Power			-0.4		dB
π/4 DQPSK max carrier frequency stability $\|\omega_0\|$		-10		10	KHz
π/4 DQPSK max carrier frequency stability $\|\omega_i\|$		-75		75	KHz
π/4 DQPSK max carrier frequency stability $\|\omega_0+\omega_i\|$		-75		75	KHz
8DPSK max carrier frequency stability$\|\omega_0\|$		-10		10	KHz
8DPSK max carrier frequency stability$\|\omega_i\|$		-75		75	KHz
8DPSK max carrier frequency stability$\|\omega_0+\omega_i\|$		-75		75	KHz
π/4 DQPSK Modulation Accuracy	RMS DEVIN		7	20	%
	99% DEVM	99	100		%

	Peak DEVM		18	35	%
8DPSK Modulation Accuracy	RMS DEVIN		6	13	%
	99% DEVM	99	100		%
	Peak DEVM		18	25	%
In-band spurious emissions	F > F0 + 3MHz			-40	dBm
	F < F0 - 3MHz			-40	dBm
	F = F0 + 3MHz			-40	dBm
	F = F0 - 3MHz			-40	dBm
	F = F0 + 2MHz			-20	dBm
	F = F0 - 2MHz			-20	dBm
	F = F0 + 1MHz			-26	dB
	F = F0 - 1MHz			-26	dB
EDR Differential Phase Encoding		99	100		%

Basic Data Rate of Receiver

Core Supply Voltage =1. 05V@ Tamb=25℃

Parameter	Condition	Min.	Typ.	Max.	Unit
Sensitivity at 0.1% BER	2.404GHz		-90		dBm
	2.441GHz		-90		dBm
	2.480GHz		-90		dBm
Maximum Input Power at 0.1% BER		-20			dBm
Co-Channel Interface				11	dB
Adjacent Channel Selectivity C/I	$F = F_0 + 1MHz$			0	dB
	$F = F_0 - 1MHz$			0	dB
	$F = F_0 + 2MHz$			-20	dB
	$F = F_0 - 2MHz$			-20	dB
	$F = F_0 + 3MHz$			-40	dB
	$F = F_{image}$			-9	dB
Maximum Level of Intermediation Interface		-39			dBm
Blocking @ Pin = -67dBm with 0.1% BER	30-2000 MHz	-10	-8		dBm
	2000-2400 MHz	-27	-25		dBm
	2500-3000 MHz	-27	-25		dBm
	3000-12750 MHz	-10	-8		dBm

Enhanced Data Rate of Receiver						
Core Supply Voltage = 1. 05V @ Tamb=25℃						
Parameter	**Condition**		**Min.**	**Typ.**	**Max.**	**Unit**
Sensitivity at 0.01% BER	π/4 DQPSK			-88		dBm
	8DPSK			-82		dBm
Maximum Input Power at 0.1% BER	π/4 DQPSK		-20			dBm
	8DPSK		-20			dBm
Co-Channel Interference	π/4 DQPSK			13		dB
	8DPSK			21		dB
Adjacent Channel Selectivity C/I	$F = F_0 + 1MHz$	π/4 DQPSK		0		dB
		8DPSK		5		dB
	$F = F_0 - 1MHz$	π/4 DQPSK		0		dB
		8DPSK		5		dB
	$F = F_0 + 2MHz$	π/4 DQPSK		-30		dB
		8DPSK		-25		dB
	$F = F_0 - 2MHz$	π/4 DQPSK		-20		dB
		8DPSK		-13		dB
	$F = F_0 + 3MHz$	π/4 DQPSK		-40		dB
		8DPSK		-33		dB
	$F = F_{image}$	π/4 DQPSK		-7		dB
		8DPSK		0		dB

PMU Characteristics

PMU	Charging current	Max : 600mA Typical : 500mA
	Charger input voltage	Max : 7.0V Typical : 5V Min : 4.5V
Power Consumption	Test conditions: 3. BAT=3.8V, VCC=3.1V, VDD=1.2V, Tamb=25℃. 4. BLE ON, SPP OFF, Scan time:1.28S, DAE OFF, No Load.	
	Standby	38 uA (type)
	Card music play	13 mA (type)
	Line in music play	10.4 mA (type)
	Bluetooth music play	20.6mA (type)

	Bluetooth hands free	26.4 mA (type)

Charge Flow Chart and Settings：



Charge Flow Chart

Note：

1. Charging process is divided into 3 stages: the pre charge process, the constant current process and the constant voltage process.
2. The pre charge current (**IPC**) is 0.1 times the constant current charge current (**ICC**). Or **IPC = 0.1 × ICC** (mA); Disable this function by set [CHG_CTL.bit14] =0, default is disable.
3. When the starting charge voltage to **3.0V** (**VTV**), the pre charging process is over, and the charging process is entered into the constant current charging process.
4. Set the constant current charging current **ICC**, constant current charge continues to the battery voltage to **VCV**, switch to the constant voltage charging process. **ICC** current can be set with 8 levels of parameters: 000:25mA, 001:50mA, 010:100mA, 011:200mA, 100:300mA, 101:400mA, 110:500mA, 111:600mA.
5. **VCV** voltage can be set with 8 levels of parameters: 000:4.2V, 001:4.23V, 010:4.26V, 011:4.29V, 100:4.32V, 101:4.35V, 110:4.38V, 111:4.41V.
6. After the end of the charge, the Li-BAT voltage is generally **VEV**= 4.18V±0.05V.

Module Pin definitions



2Layer: L × W × H = 17.0mm × 13.7mm × 0.8mm

Pin Configurations

PIN NO.	NAME	TYPE	FUNCTION
1	AGND	Power ground	Analog ground
2	MICINR	Analog input	MIC right channel input
3	MICINL	Analog input	MIC left channel input
4	VRO	Analog output	Virtual Ground for PA
5	AOUTL	Analog output	Left channel of PA
6	AOUTR	Analog output	Right channel of PA
7	VRO_S	Analog input	VRO Sense for PA

8	AGND	Power ground	Analog ground
9	GND	Power ground	Ground
10	VCC	Power output	3.3V power supply
11	GPIOA21	Bi-directional	General Purpose Input Output: A21
12	GPIOA23	Bi-directional	General Purpose Input Output: A23
13	GPIOA22	Bi-directional	General Purpose Input Output: A22
14	GPIOA16	Bi-directional	General Purpose Input Output: A16
15	SPI_MOSI	Bi-directional	SPI data
16	SPI_CLK	Bi-directional	SPI clock
17	SPI_SS	Bi-directional	SPI chip enable
18	GPIOB11	Bi-directional	General Purpose Input Output: B11
19	GND	Power ground	Ground
20	BT_ANT	Bi-directional	Bluetooth antenna junction
21	RTCVDD	Power output	power for RTC Module, typical voltage:1.2V
22	ONOFF	Input	Power on/off
23	BAT	Power input	Battery input, typical voltage range:3.4V~4.2V
24	GND	Power ground	Ground
25	DC5V	Power input	Charge power input ,typical voltage range:4.5V~7.0V
26	GND	Power ground	Ground
27	GND	Power ground	Ground
28	AUX0R	Analog input	AUX0 right channel input
29	AUX0L	Analog input	AUX0 left channel input
30	AVCC	Power output	Power for Analog module, typical voltage:2.95V

Module Package Information



Module Dimension (Top VIEW)



Module Dimension (Bottom VIEW)



Recommended PCB layout footprint

Document History

Revision	Date	History
V1.0	2015/06/09	First release
V1.1	2015/10/26	Update PMU and Audio 。

Contact Information

Actions (Zhuhai) Technology Co.,Limited

http://www.actions-semi.com
Address:
No. 1 / C, Ke Ji Si Road, Hi-Tech Zone, Tangjia, Zhuhai
Post Code: 519085
Fax: +86-756-3392251
Tel: +86-756-3392353
Business Email:
mmp-sales@actions-semi.com
Technical Service Email:
mmp-cs@actions-semi.com