

CERTIFICATE OF QUALITY

Order No. : 33149902 Country of origin : QATAR

Manufacturer : Qatar Petrochemical Company (QAPCO) Q.S.C.

Packing : 25 KG NET PER BAG

Standards Adopted : ASTM

Item Description : LDPE - Low Density Polyethylene Lotrene FE3000 - 25.5 MT

						Sales Specification			
Grade	Lot Number	Qty. M/t	Test	Result	Min	Max	Qapco	ASTM	
FE3000	2108QC001	25.500	Melt Flow Index (2.16kg /190°C) g / 10 min	0.3300	0.2600	0.3400	QM-PE-001	ASTM D-1238	
			Density (at 23°C) g/cm ³	0.9230	0.9220	0.9260	QM-PE-006	ASTM D-792	

These test results were obtained on representative samples from the batch. Should you wish to confirm these figures, it is very necessary to calibrate your instruments using certified valid reference standards.

We certify that this product has been manufactured, tested and inspected by Qatar Petrochemical Company (QAPCO) Q.S.C.. and is conforming to Manufacturer's specifications of the grade(s) set forth herein above. QAPCO LOTRENE grades should not be stored for more than three months nor be exposed to direct sunlight and / or heating during storage, since, this may adversely affect the properties of the product.

Fumigation Treatment

ISPM : Heat treatment

Duration & temperature : 4 hours at a temperature of 57 C

We hereby certify that pallets used for this shipment have been treated in accordance

with ISPM-15 regulation of the IPPC.

This is a computer generated document and does not require a signature & stamp

TOTAL PETROCHEMICALS FRANCE (Qatar Branch Office)

Alfardan Office Tower, 2nd Floor 61 Al Funduq Street, West Bay, P.O. Box 5177, Doha-Qatar

Tel.:+974 4420 8360 C.R. No.29251