

# ZONOIDS

Alberto Parravicini

Université libre de Bruxelles

April 19, 2017

# A super short summary:

- **Some interesting facts**
- **Zonoids & K-Sets**
- **Zonoids & K-Levels**
- **Applications**

## DEFINITIONS & PROPERTIES

---

# Definition

You might recall...

Given a set of points

$$S = \{p_1, p_2, \dots, p_n\} \subset \mathbb{R}^d$$

→ **Convex Hull:**


$$CH(S) = \left\{ \sum_{i=1}^n \lambda_i p_i : 0 \leq \lambda_i \leq 1, \sum_{i=1}^n \lambda_i = 1 \right\}$$

Let's impose a constraint on  $\lambda_i$ , i.e.

$$\lambda_i \leq \frac{1}{k} \quad \forall k \in [1, n]$$

→  $Z_k(S) = \left\{ \sum_{i=1}^n \lambda_i p_i : 0 \leq \lambda_i \leq \frac{1}{k}, \sum_{i=1}^n \lambda_i = 1 \right\}$

# What does it look like?



A place-holder zonoid, for  $k = 3$ . Look at the demo instead!

# Cool facts!

- For  $k = 1$ , we get the convex hull.
- For  $k = n$ , we find the mean point of  $S$  (as  $\lambda_i = \frac{1}{n} \forall i$ ).
- $\forall k$ ,  $Z_k(S)$  is a **convex** polygon.
- If  $k_1 > k_2$ , then  $Z_{k_1} \subseteq Z_{k_2}$ .

# Zonoid depth

The **zonoid depth** of  $x$  with respect to  $S$  is the **max** value of  $k$  s.t.  $x \in Z_k(S)$ .


$$D(x, S) = \begin{cases} \max\{k \mid x \in Z_k(S)\}, & \text{if } x \in CH(S) \\ 0, & \text{otherwise} \end{cases}$$

→ **Affine invariant:**

$$D(Ax + Ab, AS + Ab) = D(x, S), \quad \forall A : \mathbb{R}^{d \times d}, b \in \mathbb{R}^d$$

→ **Zero at infinity:**  $\lim_{\|x\| \rightarrow \infty} D(x, S) = 0$ .

# What does it look like?



Zonoid depth = 5. Look at the demo instead!



# K-SETS & ZONOIDS

---

# K-Sets, definition

- How can we draw a zonoid?
- Exploit **K-Sets**!
- **K-Set**: subset of  $S$  of size  $k$  that can be separated from the other points in  $S$  with a straight line.

# K-Sets & Zonoids

- Obtain a vertex of the  $k$ -zonoid by giving  $\lambda = \frac{1}{k}$  to the  $k$  extreme points in a direction.
- Equal to taking the mean of a certain  $k$ -set!
- Repeat for all  $k$ -sets and find all the vertices.
- Formally, the  $k$ -zonoid vertex  $x$  in a direction  $p$  is:

$$\arg \max_x \{p \cdot x \mid x \in Z_k(S)\} = \left( \sum_{i=1}^k \frac{1}{k} s_i^p \right)$$


## K-LEVELS & ZONOIDS

---

# K-Levels

- The **k-level** of a set of lines  $L$  is the the set of points on one line of  $L$  and strictly **above**  $k - 1$  lines.
- **Reflex vertices**: points on the  $k$ -level found at the intersection of 2 lines, and above  $k - 2$  lines.
- **Point-line duality**: the dual of  $p = (p_1, p_2)$  is the line  $p^* = \{(x, y) : y = p_1x - p_2\}$ . The dual of a line  $l = \{(x, y) : y = ax + b\}$  is the point  $l^* = (a, -b)$ .

# K-Level, visually



$k$ -level of a set of lines, for  $k = 3$

# K-Levels & Zonoids, 1


- **Reflex vertices** are above or equal  $k$  lines.
- In the primal plane, a reflex vertex becomes a line above  $k$  points.
- These  $k$  points are a  $k$ -set in the primal plane!

## K-Levels & Zonoids, 2

- For each reflex vertex of the  $k$ -level, trace a downward vertical ray.
- Intersect the ray with the lines below the reflex vertex.
- Compute the mean point of the intersections, find an *envelope*.
- It will be a line of the zonoid boundary, in the primal plane!
- Repeat for the  $n - k$ -level, with an upward ray.



# K-Level & Zonoids, visually



3-zonoid computed from the k-levels.


# Zonoid point inclusion

- How can we check if a point is inside the  $k$ -zonoid?
- Look at the *envelopes* of the zonoid in the dual plane.
- The point is included if its dual line intersects the envelopes.

It works as *duality* is **order-preserving**:

If a primal point is outside, it is above (below) 2 edges of the zonoid. In the dual, the dual line will be above the duals of those 2 edges, i.e. points on the 2 envelopes.

# K-Level & Zonoids, visually



The point is inside the zonoid, the dual line doesn't intersect the envelopes

**THANK YOU!**

# References |

- [1] C. Bradford Barber, David P. Dobkin, and Huhdanpaa Hannu.  
The quickhull algorithm for convex hulls.  
1995.
- [2] T. M. Chan.  
Optimal output-sensitive convex hull algorithms in two and three dimensions.  
Discrete & Computational Geometry, 16(4):361–368, 1996.
- [3] Donald R. Chand and Sham S. Kapur.
- [4] Ioannis Z. Emiris and John F. Canny.  
An efficient approach to removing geometric degeneracies.  
Technical report, 1991.
- [5] Christer Ericson.  
Real-Time Collision Detection.  
CRC Press, Inc., Boca Raton, FL, USA, 2004.
- [6] A. Goshtasby and G. C. Stockman.  
Point pattern matching using convex hull edges.  
IEEE Transactions on Systems, Man, and Cybernetics, SMC-15(5), 1985.

# References ||

- [7] David G. Kirkpatrick and Raimund Seidel.  
The ultimate planar convex hull algorithm ?  
Technical report, 1983.
- [8] Joseph O'Rourke.  
Computational Geometry in C.  
Cambridge University Press, 2nd edition, 1998.
- [9] F. P. Preparata and S. J. Hong.  
Convex hulls of finite sets of points in two and three dimensions.  
Commun. ACM, 20(2):87–93, February 1977.
- [10] Franco P. Preparata and Michael I. Shamos.  
Computational Geometry: An Introduction.  
Springer-Verlag New York, Inc., 1985.
- [11] Franco P. Preparata and Michael I. Shamos.  
Computational Geometry: An Introduction.  
Springer-Verlag New York, Inc., 1985.

**Beamer theme:** *Presento*, by Ratul Saha. *The research system in Germany*, by Hazem Alsaied