Text completions

WORKING WITH THE OPENAL API

James Chapman
Curriculum Manager, DataCamp



Recap...

Text completions for Q&A

```
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt="How many days are in October?"
)
print(response["choices"][0]["text"])
```

October has 31 days.

What is a text completion?

• Text most likely to complete the prompt

```
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt="Life is like a box of chocolates."
)
print(response["choices"][0]["text"])
```

You never know what you're going to get.

• Response is **non-deterministic** (inherently random)

¹ Quote from Forrest Gump (1994)



Controlling response randomness

- temperature : control on determinism
- Ranges from 0 (highly deterministic) to 2 (very random)

```
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt="Life is like a box of chocolates.",
  temperature=2
)
print(response["choices"][0]["text"])
```

You never know what bitter constraints to any fate journey of Enlightenment you instead be forced...

Content transformation

- Changing text based on an instruction
 - Find and replace
 - Summarization
 - Copyediting

```
prompt = """
Update name to Maarten, pronouns to he/him, and job title to Senior Content Developer:

Joanne is a Content Developer at DataCamp. Her favorite programming language is R,
which she uses for her statistical analyses.
"""
```

Content transformation

```
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt=prompt
)
print(response["choices"][0]["text"])
```

Maarten is a Senior Content Developer at DataCamp. His favorite programming language is R, which he uses for his statistical analyses.

Content generation

```
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt="Create a tagline for a new hot dog stand."
)
print(response["choices"][0]["text"])
```

```
"Frankly, we've got the BEST dogs in town!"
```

Controlling response length

Default max_tokens

```
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt="Write a haiku about AI."
)
print(response["choices"][0]["text"])
```

```
AI so powerful
Computers that think and learn
Superseding
```

$max_tokens = 30$

```
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt="Write a haiku about AI.",
  max_tokens=30
)
print(response["choices"][0]["text"])
```

```
A machine mind thinks
Logic dictates its choices
Mankind ponders anew
```

Understanding tokens

How can the OpenAl API deliver business value?

In English:

- 1 token ~ 4 characters
- 100 tokens ~ 75 words

Example: 150 words → max_tokens=200

Returning to cost

- Increasing max_tokens increases cost
- Usage costs dependent on amount of generated text
 - Models are priced by cost/1K tokens
 - Input and output tokens can be priced differently
- Scoping feature cost often starts with a rough calculation:

$$\frac{\mathrm{Cost}}{\mathrm{Time}} = \mathrm{Avg.} \ \mathrm{Tokens} \ \mathrm{Generated} \times \mathrm{Model} \ \mathrm{Cost} \times 1000 \times \frac{\mathrm{Expected} \ \mathrm{no.} \ \mathrm{of} \ \mathrm{requests}}{\mathrm{Time}}$$

¹ https://openai.com/pricing



Let's practice!

WORKING WITH THE OPENAL API



Text completions for classification tasks

WORKING WITH THE OPENAL API


James Chapman
Curriculum Manager, DataCamp



Classification tasks

- Task that involves assigning a label to information
 - Identifying the language from text
 - Categorization
 - Classifying sentiment

- Completion endpoint can perform these tasks, providing:
 - Model has sufficient knowledge
 - Prompt contains sufficient context



Categorizing animals

```
Mammals: Zebra, Polar Bear, Dog
Fish: Salmon
Reptiles: Crocodile
```

Specifying groups

```
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt="Classify the following animals into animals with fur and without: zebra,
  crocodile, dolphin, polar bear, salmon, dog.",
  max_tokens=50
)
print(response["choices"][0]["text"])
```

```
Animals with fur: Dog, Polar Bear, Zebra
Animals without fur: Crocodile, Dolphin, Salmon
```

Classifying sentiment

```
prompt = """Classify sentiment in the following statements:
1. The service was very slow
2. The steak was awfully tasty!
3. Meal was decent, but I've had better.
4. My food was delayed, but drinks were good.
11 11 11
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt=prompt,
  max_tokens=50
print(response["choices"][0]["text"])
```

Classifying sentiment

- 1. The service was very slow
- 2. The steak was awfully tasty!
- 3. Meal was decent, but I've had better.
- 4. My food was delayed, but drinks were good.
 - 1. Negative
 - 2. Positive
 - 3. Neutral
 - 4. Mixed

Classifying sentiment

```
prompt = """Classify sentiment as 1-5 (bad-good) in the following statements:
1. The service was very slow
2. The steak was awfully tasty!
3. Meal was decent, but I've had better.
4. My food was delayed, but drinks were good.
"""
```

```
    1. 1
    2. 5
    3. 3
    4. 2
```

Zero-shot vs. one-shot vs. few-shot prompting

• Zero-shot prompting: no examples provided

In-context learning:

- One-shot prompting: one example provided
- Few-shot prompting: a handful of examples provided

One-shot prompting

```
prompt = """Classify sentiment in the following statements:
The service was very slow // Disgruntled
Meal was decent, but I've had better. //
11 11 11
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt=prompt
print(response["choices"][0]["text"])
```

Neutral



Few-shot prompting

```
prompt = """Classify sentiment in the following statements:
The service was very slow // Disgruntled
The steak was awfully tasty! // Delighted
Good experience overall. // Satisfied
Meal was decent, but I've had better. //
11 11 11
response = openai.Completion.create(
 model="gpt-3.5-turbo-instruct",
 prompt=prompt
print(response["choices"][0]["text"])
```

Mildly dissatisfied



Let's practice!

WORKING WITH THE OPENAL API



Chat completions with GPT


WORKING WITH THE OPENAL API

James Chapman
Curriculum Manager, DataCamp




The Chat Completions endpoint

- Multi-turn conversations
 - Also performs well on single-turn
- Better customizability of response through the use of roles
- Cost benefit: gpt-3.5-turbo is 10x cheaper than gpt-3.5-turbo-instruct



Roles

- System: controls assistant's behavior
- User: instruct the assistant
- Assistant: response to user instruction
 - Can also be written by the user to provide examples



Request setup

Completions

```
response = openai.Completion.create(
  model="gpt-3.5-turbo-instruct",
  prompt="____"
)
```

ChatCompletion

```
response = openai.ChatCompletion.create(
  model="gpt-3.5-turbo",
  messages=____
)
```

Prompt setup

Making a request

The response

```
"choices": [
   "finish_reason": "stop",
    "index": 0,
    "message": {
      "content": "Mutable objects are objects whose values can be changed after they have been created, whereas immutable objects are objects
      whose values cannot be changed after they have been created. Examples of mutable objects include lists, dictionaries, and sets, while
      examples of immutable objects include integers, floating-point numbers, and strings.",
      "role": "assistant"
"created": 1685096884,
"id": "chatcmpl-7K0xwXKBkLQ17EKRGqmiC9HHJbh6s",
"model": "gpt-3.5-turbo-0301",
"object": "chat.completion",
"usage": {
  "completion_tokens": 62,
  "prompt_tokens": 35,
  "total_tokens": 97
```

Extracting the text

```
print(response["choices"])
```

```
[<OpenAIObject at 0x7fd82c617310> JSON: {
    "finish_reason": "stop",
    "index": 0,
    "message": {
        "content": "Mutable objects are objects whose values can be changed after they have been created,
        whereas immutable objects are objects whose values cannot be changed after they have been created.
        Examples of mutable objects include lists, dictionaries, and sets, while examples of immutable objects
        include integers, floating-point numbers, and strings.",
        "role": "assistant"
    }
}
```

Extracting the text

print(response["choices"][0])

```
"finish_reason": "stop",
"index": 0,
"message": {
 "content": "Mutable objects are objects whose values can be changed after they have been
 created, whereas immutable objects are objects whose values cannot be changed after they
 have been created. Examples of mutable objects include lists, dictionaries, and sets,
 while examples of immutable objects include integers, floating-point numbers, and
 strings.",
 "role": "assistant"
```

Extracting the text

print(response["choices"][0]["message"]["content"])

Mutable objects are objects whose values can be changed after they have been created, whereas immutable objects are objects whose values cannot be changed after they have been created. Examples of mutable objects include lists, dictionaries, and sets, while examples of immutable objects include integers, floating-point numbers, and strings.



Let's practice!

WORKING WITH THE OPENAL API



Multi-turn chat completions with GPT

WORKING WITH THE OPENAL API

James Chapman
Curriculum Manager, DataCamp




Chat completions for single-turn tasks

- System: controls assistant's behavior
- User: instruct the assistant
- Assistant: response to user instruction

Providing examples

- Steer model in the right direction
- Nothing surfaced to the end-user
- Example: Data Science Tutor Application
 - Provide examples of data science questions and answers



Providing examples

```
response = openai.ChatCompletion.create(
  model="gpt-3.5-turbo",
  messages=[{"role": "system",
             "content": "You are a data science tutor who speaks concisely."},
            {"role": "user",
             "content": "How do you define a Python list?"},
            {"role": "assistant",
             "content": "Lists are defined by enclosing a comma-separated sequence of
                         objects inside square brackets [ ]."},
            {"role": "user",
             "content": "What is the difference between mutable and immutable objects?"}]
```

The response


```
print(response["choices"][0]["message"]["content"])
```

Mutable objects are objects whose values can change after they are created. Examples of mutable objects in Python include lists, sets and dictionaries. Immutable objects are objects whose values cannot change after they are created. Examples of immutable objects in Python include strings, numbers and tuples.



Storing responses

- Create conversation history
- Create back-and-forth conversations



Coding a conversation

```
messages = [{"role": "system",
             "content": "You are a data science tutor who provides short, simple explanations."}]
user_qs = ["Why is Python so popular?", "Summarize this in one sentence."]
for q in user_qs:
    print("User: ", q)
    user_dict = {"role": "user", "content": q}
    messages.append(user_dict)
    response = openai.ChatCompletion.create(
        model="qpt-3.5-turbo",
        messages=messages
    assistant_dict = dict(response["choices"][0]["message"])
    messages.append(assistant_dict)
    print("Assistant: ", response["choices"][0]["message"]["content"], "\n")
```

Conversation with an Al

User: Why is Python so popular?

Assistant: Python is popular for many reasons, including its simplicity, versatility, and wide range of available libraries. It has a relatively easy-to-learn syntax that makes it accessible to beginners and experts alike. It can be used for a variety of tasks, such as data analysis, web development, scientific computing, and machine learning. Additionally, Python has an active community of developers who contribute to its development and share their knowledge through online resources and forums.

User: Summarize this in one sentence.

Assistant: Python is popular due to its simplicity, versatility, wide range of libraries, and active community of developers.

Let's practice!

WORKING WITH THE OPENAL API

