Advanced Computer Architecture: The "Smooth" Challenge

Romain Brault¹, Alexandre Camus², Giorgos Flourentzos³

Abstract

Coding is a question of how to compute things, but also how to compute them the fastest. These are often two questions that can't be resolved at once. Although coding a program that gives the expected result is an obstacle, another problem arises when performance is to be maximized. Once this is done, optimizing the written code might take a lot of time, depending on whether the hardware on which it is running, is taken into account. Here, given a correct program, the aim was to optimize it, given a chosen architecture. This consisted of understanding the code, then optimizing it sequentially and finally trying to improve it by parallelizing through vectorization or offloading the calculation to an accelerator (GPU).

Contents

1	Introduction	1
1.1	Context and Objectives	1
1.2	Software Considerations	1
1.3	Hardware Considerations	2
2	The Sequential Issue	2
2.1	Algorithm	2
2.2	Code Style	3
2.3	Data's Representation	3
3	CPU Parallelization	3
3.1	Analysis	3
3.2	Optimization	3
4	Results	3
4.1	Sequential Improvements	3
4.2	Parallelization Performance	4

1. Introduction

1.1 Context and Objectives

Simulation in computer science is usually computationally intensive. Although an algorithm can be theoretically efficient¹, a naive implementation, without any hardware consideration reveal to be slower than expected.

This paper start with a basic implementation of a curve smoothing algorithm where the curve – a mesh – is represented by a graph. This paper present a various methods to reduce the computation time of the smoothing algorithm on a specific machine, according to the

hardware specification. The list of optimizations presented is non exhaustive, however the considered approach reduced the computation time by approximately 1300% on the given architecture.

The method used to achieved this speed-up is the following:

- first optimize on one CPU core,
- then parallelize over one node (here a single computer).
- eventually used hardware accelerator such as GPU.

1.2 Software Considerations

The hardware considered is one of the Imperial College computing laboratory. All these computer are equipped with an Intel CPU, thus the best performances were obtained using the Intel Compiler². However the Imperial College computer do not have the latest version of the Intel Compiler installed on, providing some optimizations and and the use of the new C++ standard (C++11). To obtained the maximum throughput additional library, not installed on Imperial College computer, such as blitz++, were used. A solution to have the best of the latest compiler version, library flexibility and the performances of the Imperial College computers is to cross-compile the code.

Cross-compiling is the action of creating executable code for a platform other than the one on which the compiler is running. This is challenging because the compiler usually tune the code to be as fast as possible on the machine where the code is compiled lowering the

¹With a low complexity.

²The speed-up gained by switching from g++ (GNU) to icpc (Intel) is presented section ??.

performances on the target machine. Additionally, extra care must be payed to the portability of the code.

The code was compiled on a Linux-Fedora 18 64bits station and is to run on a Linux-Ubuntu 12.04 64bits station.

1.3 Hardware Considerations

Table 1 and 2 show respectively the hardware characteristics of the compiling machine and the running machine. The compiling machine is much slower than the running machine but is able to generate code optimized for the running machine.

Model Name	Intel Core i7-QM720
Clock Speed	1.6 GHz
Max Turbo Frequency	2.8 GHz
Cache line size and alignment	64 B
CPU cores	4
CPU Threads	8
Integrated GPU	No
Memory Channels	2
Max Memory Bandwith	21 GB/s
Flags	fpu, sse, sse2, sse3, ssse3, sse4_1, sse4_2

Table 1. CPU Specifications for the compiling station.

Model Name	Intel Core i7-2600
Clock Speed	3.4 GHz
Max Turbo Frequency	3.8 GHz
Cache line size and alignment	64 B
CPU cores	4
CPU Threads	8
Integrated GPU	Intel HD Graphics 2000
Memory Channels	2
Max Memory Bandwith	21 GB/s
Flags	fpu, sse, sse2, sse3, ssse3, sse4_1, sse4_2, avx

Table 2. CPU Specifications for the running station.

To summarize, the figure 1 and 2 gives a quick overview of the hardware topology.




Figure 1. Topology of the running station.




Figure 2. Topology of the compiling station.

2. The Sequential Issue

After running for the first time the program, it appears that the method mesh_quality() is the most called and so is the most expensive in computation time. Hence its code has been considered as a potential source of optimization.

Reading the code, some sequential issues were found. There are three kinds of problems: the algorithms chosen, the coding style and the data's representation.

2.1 Algorithm

The method used to solve an equations' system was correct but two general to be efficient. The program needs only to solve systems of two equations in two unknowns. The Cramer's rule based on determinants is far more efficient.

The use of the method pow() seems a little too heavy in the method element_quality(). As the number of multiplication is known, the use of simple multiplications is more efficient here, e.g. x*x*x.

2.2 Code Style

Few changes in the style of the code might help the compiler. Some of these changes have been done to speed up the program.

First of all, the code has been slightly rewritten in order to be more oriented object than before. Basically all the attributes of the Mesh class have been set to private and the smooth function is now a method of this class. This did not really increase the performance. But this was for a better readability. It might also help the compiler to improve its compiled code as it is used to read object oriented code.

Inline functions do often help the compiler to optimize the translated assembly language. That is why functions like isSurfaceNode() or isCornerNode() or element_quality() or svd_solve_2x2().

In loops changes have been made to avoid recomputation of the invariant (e.g. calling .size() in a loop). Instead, this invariant is now stored in a local variable.

2.3 Data's Representation

The data structure used is fine and one of the most efficient to represent a graph. However, the C++ structures used seem to be a little too big in this case. So instead of using vectors of sets, the program is now using vectors of vectors. This increases a little the global performance.

Similarly, the number of node does not exceed 10⁵ which is less than the maximum integer represented thanks to the uint32_t. This type is faster to manipulate than the classic int type. Hence uint32_t has been preferred.

In the element_quality() method, the call of an element in a matrix during its multiplication, is very expensive in memory access. So instead of calling the element at each step of the loop, it is better to use an intermediate variable that is assigned into the matrix element at the end.

Finally the vectors normals and ENList are not anymore vectors. The Blitz library³ provides useful arrays' types with a speed comparable to Fortran implementations. After testing it on the different vectors in the program, it appears that the type Array of this library was more efficient for vectors that are linearly accessed. normals and ENList have this property. So they are now implemented thanks to Array type.

3. CPU Parallelization

3.1 Analysis

Parallelization can't be done easily. The program needs to be slightly modified in order to cut the graph in groups of independent nodes. Independent nodes are nodes that can be inspected at the same time while running the program. To group nodes in such groups the graph must be colored. Then each color represents nodes that can be inspected at the same time because they are not adjacent.

But the coloring algorithm might be very expensive in computation time. This depends on the number of colors used and if this number is specified or not. In this very case, the goal of such an algorithm is to minimize the colors used in order to maximize parallel computations. Hence a powerful algorithm is needed.

3.2 Optimization

A first try was realized with a very complex algorithm that colors a graph with minimum of colors needed. But the simple fact of coloring the graph was itself longer than the original program (hundreds of minutes). This confirmed that the graph is complex and parallelizing the program will surely reduce the run time.

So the coloring algorithm finally chosen was very basic. It just tries to color the graph without minimizing the number of colors used. It succeeds in coloring the graphs with 4 or 5 colors. Algorithms 1 and 2 are its implementation in pseudocode.

```
input : the graph G
output : C the array containing the colors
creating C, the output of size: number of node;
intializing each element of C to -1;
for i \leq number of node do
 | C[i] \leftarrow get\_colors(G[i]);
end
return C;
```

Algorithm 1: The coloring Algorithm

Then each color represents a set of nodes that are computable in parallel. Actually this is simply done by adding a for loop on the colors before the loop that inspects all the nodes of the graph. The color of each node is compared to the current color. If they are different the node is skipped. The parallelization is then simply done on the loop that inspects all the nodes.

4. Results

4.1 Sequential Improvements

³http://blitz.sourceforge.net/

Algorithm 2: The get_colors Algorithm

4.2 Parallelization Performance