

SON implementation on Spark in python

Carli Alberto VR473845

Fraccaroli Leonardo VR???????

Contents

1	Introduction	1
2	SON	3
2.1	SON Algorithm	3
2.2	Our Implementation	3
2.2.1	First Map	3
2.2.2	First Reduce	3
2.2.3	Second Map	4
2.2.4	Second Reduce	4
3	apriori	5
4	benchmark	5
4.1	Datasets	6
4.2	Results	6
5	Conclusions	6

1 Introduction

Finding frequent itemsets is frequently done in data mining domains to understand which items frequently appear together. The definition of "items" is beyond the scope of this work. Suffice to say that we treated them as binary variables, listed in a basket only when their value is True. In our project a basket is a list of items that appear together.

This is an analysis that can be performed on almost any dataset, but is especially suited for domains like e-commerce. It is an interesting challenge to try and take the system to the extreme where the dataset is so large that it does not fit on any single machine's memory and it is more convenient to distribute analysis to multiple compute units.

We tried to imagine ourselves into a big e-commerce company that stores transaction data on a distributed database and wants to periodically analyse data to understand which items are usually bought together.

The data is simply a list of items bought at any one time; as the distributed database we used MongoDB and thus we needed a version of parallel apriori.

We tried to parallelize apriori by using Spark on python and using the SON algorithm as proposed in chapter 6.4.4 of the Mining Massive Datasets book.

2 SON

In this section we will dissect our implementation of SON through Spark on python, describing all the steps of computation and their result.

2.1 SON Algorithm

The algorithm as described in the book involves two phases of mapreduce as follows:

1. The map basically executes apriori on a batch of baskets, extracting all frequent itemsets. The required frequency (support) is reduced by a factor equal to the number of number of batches the data is partitioned in. The reducer is an identity reducer and simply combine all the frequent itemsets from every basket in a single list. These are candidate frequent itemsets.
2. The map function takes a batch of the data and counts every occurrence of every itemset in the candidates list. The reducer adds up the counts from every batch and finally filters out the infrequent ones using the original support.

The result of this is the list of frequent itemsets without false positives.

2.2 Our Implementation

Our implementation expects a *pyspark* RDD

2.2.1 First Map

The input data is in the form of a list of lists, where every internal list holds a set of strings, which are the items (fig: 1a).

Apriori algorithm is applied to every batch, which returns a list of frequent itemsets (fig: 1b). This is done with the *mapPartitions* function of *pyspark*:

```
.mapPartitions(lambda x: apriori(list(x), chunk_support))
```

We will discuss our implementation of apriori, in details, in section 3. We chose not to keep only the largest set because we saw that there may be cases where the larger set is not globally supported, but the smaller ones are.

Then every itemset is "emitted" with a 1, to facilitate the reduce phase:

```
.map(lambda x: (x, 1))
```

2.2.2 First Reduce

Now the result of the previous step is grouped by key (fig: 1c) and the list of counts discarded entirely:

```
.groupByKey()  
.map(lambda x: x[0])
```

[illegible]

At this point our candidate frequent itemsets are still partitioned. We need to distribute the whole list to every batch of data. In order to do so we coalesced the candidates RDD into one single partition, group it together and multiply it with every partition of the original data:

The result is, for every partition, a list containing two lists; the first one is a list of itemsets and the second one is the batch of data (fig: 2a). Then, for every itemset in the first list, we count in how many baskets is present¹:

```
.mapPartitions(lambda x : count_frequencies(list(x)[0]))
```

2.2.4 Second Reduce

```
.reduceByKey(lambda x, y: x + y)
.filter(lambda x: x[1] / data_size >= support)
```

¹count_frequencies is a function we developed that does exactly that: count the occurrences of the elements in the first list in the second list.

(a) Cartesian product result

(b) Counts of itemsets for every batch

(c) Sum of counts across partitions

mented a gridsearch to test many parameters. We also added a logging feature to our project to better follow executions and ease debug. We compared our implementation, both based on DB and in memory, to a method *FreqItems* provided by *pyspark.sql*. This function uses a modified version of FP-Tree to be more parallelizeable. This function proved itself to be absurdly fast, at the expense of false positives. Both a ‘simple’ dataset and a ‘harder’ one were used to compare performances.

4.1 Datasets

4.2 Results

These tests were performed on an 8 core *i5 – 8250U@1.6GHz*, with 16 GB DDR4 memory @2400MHz

5 Conclusions

After the benchmarks it is clear that apriori is blazingly fast and the only reasons one should instead use SON is when data doesn’t fit in memory or many compute units are available.